



CS Model – Compact Superior Washer / Disinfector

MANUFACTURER

Stanbridge Limited

Unit 78, Powder Mill Lane, Questor
Dartford, Kent, DA1 1JA, United Kingdom
Tel: +44 (0)1689 806500
Website: www.stanbridge.co.uk

PRODUCT DESCRIPTION

The **CS Model – Compact Superior Washer / Disinfector** is a compact washer disinfector designed for use in healthcare sluice and dirty utility environments. The unit provides automated washing and high-temperature thermal disinfection of bedpans, urine bottles, commode pots and approved healthcare utensils, supporting effective infection control through hands-free operation and controlled disinfection cycles.

The CS Compact Superior range is available in multiple model variants, including **CS1** and **CS2**, to suit differing capacity and operational requirements.

Model Variants

- CS1 Compact Superior Washer / Disinfector
- CS2 Compact Superior Washer / Disinfector
- CS3 Compact Superior Washer/ Disinfector

Specifications apply to CS1 and CS2 models unless otherwise stated.

Dimensions & Weight

Model	Height (mm)	Width (mm)	Depth (mm)	Net Weight (approx. kg)
CS1	915	435	655	67
CS2	915	435	655	68
CS3	1100	600	720	78

UTILITIES

Water Supply

- Supply: Cold water only
- Connection: ¾" BSP male parallel
- Minimum Pressure: 0.2 Bar (2.9 psi)
- Maximum Pressure: 10 Bar (145.04 psi)
- Typical Consumption: Approx. 17.5 litres per cycle
- Overflow: 1 × 21 mm bore, visible, compliant with BS EN 15883-1 (UK requirements)

Stanbridge Limited Unit 78, Powder Mill Road, Questor Park, Dartford, Kent DA1 1JA

Telephone: +44 (0) 1689 806500

Email: admin@stanbridge.co.uk www.stanbridge.co.uk

Registered in England and Wales No. 570388 Registered Office: as above

VAT No. 335 8708 35





Electrical Supply

- Electrical Supply: 230V / 50Hz / 16A, single phase
- Mains Fuse: 16A
- Control Fuse: 5A
- Steam Generator Heater: 3 kW
- Pump Rating: 0.53 kW

Performance

- Thermal Disinfection: $\geq 80^{\circ}\text{C}$ for 70 seconds
- Maximum Operating Temperature: Approx. 85°C
- Estimated Cycle Time: 6–12 minutes (cycle dependent)
- Number of Wash Cycles: 2 (Bottle Wash and Pan Wash)

Chamber & Loading

- Top loading/Front-loading stainless-steel chamber (dependent on model)
- Fixed utensil carrier (model dependent)
- Hands-free lid operation via foot pedal or auto sensors

Compliance & Standards

- WRAS Approved – Approval No. **240102706**
- Internal break tank with Type AB air gap
- Designed in accordance with BS EN 15883-1 (UK requirements)

Options & Accessories

Additional models, utensil carriers and optional accessories are available within the CS Compact Superior range.

Notes

- Specifications are subject to change without notification
- Cycle times are indicative and may vary depending on installation conditions and ambient room temperature