

LIGHTING COLLECTION 2025-26



PERFORMANCE
in LIGHTING

powered by
GEWISS

PERFORMANCE
iN LIGHTING | powered by
GEWISS

Light is our language

Every environment is born twice: first with its shape, then with its light. Light is the invisible element that shapes space, modulating its geometries and activating its functions and perceptions. It is what makes environments more welcoming, efficient, safe, and inspiring.

For over forty years, PERFORMANCE iN LIGHTING | powered by GEWISS has taken on these challenges, speaking the language of light—a language made of intensity and nuances, but also of luminous efficiency, optical precision, and harmonious architectural integration.

For us, illuminating means interpreting space, respecting it, and transforming it into a coherent system, balanced between form and function. Every luminaire signed PERFORMANCE iN LIGHTING | powered by GEWISS is the result of meticulous design, combining photometric research, technical reliability, and aesthetic care.

From architectural to industrial lighting, from infrastructures to public and sports spaces, our goal remains unchanged: to design lighting solutions that improve the quality of built spaces in terms of performance, safety, durability, and visual comfort.

Made iN

With over 2,200 employees, the GEWISS Group is positioned as an international entity, with manufacturing sites, commercial branches, agencies, and distributors in over 100 countries worldwide.

The headquarters are located in Cenate Sotto (BG), while production facilities are situated in Italy, Germany, France, Portugal, Belgium, and the United States.

All products under the GEWISS and PERFORMANCE iN LIGHTING brands are conceived, designed, engineered, and tested in the Group's facilities, using only components from certified brands.



Warranty

Focus on quality, safety and durability are the essential objectives of the GEWISS Group.

All products are covered by a 5-year warranty, provided that they are installed, maintained and used according to the instructions and information contained in the catalogue or on the web.

Consumable materials, such as lamps, starters, and electronic ignitors and reactors, emergency-units and batteries which are compliant with warranty regulations issued by the European Directive on the subject, are not included in the warranty.

To consult the full text of our warranty, please go to the website www.performanceinlighting.com



Clear conditions

In order to always provide customers with clear, complete information, PERFORMANCE iN LIGHTING has decided to provide the data pertaining to its LED luminaires in the following ways:

- Nominal lumen indicate the luminous flux produced by the LED source according to indications by the manufacturer of the LEDs used in the luminaire. Sometimes this is an average value derived from the range indicated by the producer.
- Real lumen indicate the luminous flux output of the luminaire. The real flux is therefore lower than the nominal flux because it depends on the luminaire's thermal regime and the use of reflectors, diffusers, screens or lenses to direct the light.
- Wattage drawn indicated in the table includes not only absorption by the LED light source, but also driver's loss from other electronic components of the luminaire. We then indicate the total amount of energy actually consumed by the luminaire as a whole.

With this information, PERFORMANCE iN LIGHTING aims to help creating more clarity in this sector, the LED luminaire industry, where it is sometimes difficult to interpret information and compare products.

Professional lighting solutions

Discover the perfect lighting products for your business: three paths of light, endless possibilities. Choosing the right lighting for your business is essential to enhance both the aesthetics and functionality of your space. Explore the three main categories of lighting solutions available: DISCOVER, BOOST, and ELEVATE.

Each category is designed to meet specific needs and is defined by five key elements to help you find the ideal choice. Thanks to this segmentation, you can easily compare options based on their distinctive features, ensuring an investment that contributes to an efficient and pleasant work environment.



DISCOVER

Start your journey with reliable and straightforward lighting solutions that provide crucial performance.

Use

Designed for straightforward lighting scenarios, ideal for first time installations and easy replacements.

Range

Focused and user friendly, making quality of light accessible to all.

Performance

Built to deliver consistent illumination with minimal maintenance.

Potential

Equipped with fundamental features that support plain future enhancements.

Standards

Complies with all necessary standards to ensure safety and reliability.



BOOST

Bring your spaces to life with enhanced lighting that highlights and transforms.

Use

Tailored for challenging environments where every detail matters, enhancing visibility and ambiance.

Range

Extensive and diverse, offering robust solutions for dynamic settings.

Performance

Exceptional longevity and performance, designed to withstand intensive use.

Potential

Ready for the future with adaptable technologies that cater to evolving needs.

Standards

Complete with high standard certifications, ensuring superior quality and safety.



ELEVATE

High end lighting solutions offering peak performance and innovation for specialized requirements.

Use

Crafted for the most challenging and demanding areas, this range sets the standard in lighting innovation.

Range

A complete suite of high specification solutions designed to inspire and transform any space.

Performance

Delivers unparalleled performance and durability, crafted for longevity in the most challenging conditions.


Potential

Incorporates cutting edge technologies and customizable features for maximum adaptability.

Standards

Holds the highest level of industry certifications, representing the zenith of lighting standards.

Linear system



2
SL764+ PL

6
SL764+ RE

8
SL764+ RF

10
SL764+ SM

14
SL787+ PL

16
SL787+ RE

Free standing



17
SL730+ SL

22
SMALL LINE SL

25
SL720SL L LED

25
SL720SL XL LED

25
SL720SL L TWIN LED


28
SL764+ SL

30
SL713SL LED

32
SL740SL L LED

32
SL740SL XL LED

Wall and ceiling surface



34
ELIA CL

36
FL ROUND+ 333 SM

40
FL ROUND+ 555 SM

44
FL ROUND+ 777 SM

48
FL SQUARE 300 SM

48
FL SQUARE 600 SM

50
FLEXILED SM

52
SL629AB

54
SL630AB

56
SL713AB ROUND LED S

56
SL713AB ROUND LED M

56
SL713AB ROUND LED L

60
SL720+ SM

64
RONDA+ LED 1X

64
RONDA+ LED 2X

66
WL900 RECT

66
WL1200 RECT

66
WL1500 RECT

68
WL220 ROUND

68
WL270 ROUND


68
WL400 ROUND

70
WL210 SQUARE

70
WL260 SQUARE

70
WL390 SQUARE

Ceiling recessed



72
ELIA PL M1 1200

74
ELIA PL M2 600

76
ELIA PL M3 625

78
FL ROUND+ 333 RE

82
FL ROUND+ 555 RE

85
FL ROUND+ 777 RE

88
FL SQUARE 300 RE

89
FLEXILED IL

92
FLEXILED RE

94
PLATO 1200

96
PLATO 600

99
PLATO 625

102
AMIGO 36




104
ELIA 600




106
ELIA 625



108
ELIA PL BACKLIT
M1 1200




110
ELIA PL BACKLIT
M2 600




112
ELIA PL BACKLIT
M3 625



114
ELIA PL IP65 M1
1200



116
ELIA PL IP65 M2
600



118
ELIA PL IP65 M3 625



120
VISIO [16] M1 1200



122
VISIO [16] M2 600



124
VISIO [16] M3 625

Suspended



126
IN-TENSE PL



130
LIQUID PL



132
MERCURY PL



134
SMALL LINE PL



138
FL ROUND+ 333 PL



142
FL ROUND+ 555 PL



146
FL ROUND+ 777 PL



150
FL SQUARE PL



152
FLEXILED PL



154
SL629 PL



156
SL629 PL CM



158
SL713PL ROUND
LED S



158
SL713PL ROUND
LED M



158
SL713PL ROUND
LED L



162
SL713+ PL



165
SL720+ PL

Downlight and spotlight



168
DL ROUND MIDI



168
DL ROUND MAXI



171
DL SQUARE MIDI



171
DL SQUARE MAXI



174
DLSB100 LED




174
DLSB150 LED




174
DLSB185 LED




174
DLSB220 LED




178
EB431 LED



178
EB432 LED




178
EB433 LED




178
EB434 LED



178
EB435 LED




186
ELIA AL S2




186
ELIA AL M2



188
ELIA DL




190
MANGO+ MAXI




192
MANGO+ MIDI

Tracklight



194
AS425 LED



197
AS427 LED



200
AS615



202
OTR TRACKS RAILS
STANDARD



202
OTR TRACKS RAILS
RECESSED

Trunking system



219
TRY

High bay and low bay




228
SMART [4]




242
SMART [4] SPECIAL
VERSIONS



247
UNIQO



252
UNIQO REUSE




256
ELIA HL



260
LAMA+



264
LAMA+ MINI



266
A+



268
GYM+

Waterproof



272
SMART [3] PLUS



284
SMART [3]



288
SMART [3]E



290
LM4



292
ACRO PRO




294
ACRO+



298
ACRO BASIC





300
NORMA+



300
NORMA+ CL

Bulkhead






350
SUPERDELTA
TONDO



352
SUPERDELTA
OVALE



352
SUPERDELTA
OVALE 33



354
TONDA ES

Posts / garden co-ords




318
NIKKO+21



318
NIKKO+21/G



318
NIKKO+27




318
NIKKO+27/G



321
NIKKO+45



321
NIKKO+45 G



304
BLIZ RING



304
BLIZ GUARD



327
CHIP TONDO 25




327
CHIP TONDO GRILL



350
SUPERDELTA
TONDO




352
SUPERDELTA
OVALE



352
SUPERDELTA
OVALE

Exterior ceiling



356
MIMIK 10 CEILING

356
MIMIK 10 CEILING
TECH

358
MIMIK 20 CEILING

360
MASK+ ROUND

362
QUASAR 10 CEILING

363
QUASAR 30
CEILING

Exterior wall



364
MIMIK 10

368
MIMIK 20

372
MIMIK 30

374
MIMIK 50

377
AMON WALL

378
MASK+

379
MASK+ MINI



380
QUASAR 10

382
QUASAR 20

384
QUASAR 30

386
QUASAR 60

388
SHIELD+ 1

390
SHIELD+ 2

392
ELIA OL



394
ORION H

396
ORION V

398
POLO+ 2

399
POLO+ 3

Garden post



400
MIMIK 10 POST
300

400
MIMIK 10 POST
600

400
MIMIK 10 POST
1000

404
INSERT+ ZERO
POST

405
INSERT+ 1 V POST

406
INSERT+ 2 V POST

407
ORION POST 260



408
ELIA BL

410
PADO BASIC

410
PADO 600

410
PADO 900

410
PADO 1200

414
Q-LIGHT

Steplight



416
CRICKET+ 10
WALL


418
INSERT+ ZERO

420
INSERT+ ZERO CLIP

422
INSERT+ ZERO
GLASS

424
INSERT+ ZERO SM

426
INSERT+ ZERO SM
GLASS



428
INSERT+ 1

428
INSERT+ 2

431
INSERT+ 1
MARINE

432
INSERT+ 1 V

432
INSERT+ 2 V

434
INSERT+ 1 V GLASS



436
INSERT+ 1 V SM


438
INSERT+ 1 V SM
GLASS

440
INSERT+ 3














































Architectural floodlight



Inground



Professional floodlight

						
504 LASER+ 10	504 LASER+ 20	504 LASER+ 30	511 LASER+ 10 EXTREME RM	514 LASER+ 10 EXTREME	514 LASER+ 20 EXTREME	514 LASER+ 30 EXTREME
						
520 SMART [PRO] 2.0 1M	524 SMART [PRO] 2.0 2M	529 SMART [PRO] 2.0 2+2M	533 SMART [PRO] 2.0 3X2M	536 SPATIUM PRO 1M	538 SPATIUM PRO 2M	540 SPATIUM PRO 3M
						
542 SQUARE PRO	547 SQUARE PRO GLASS	550 STADIUM PRO 1M	555 STADIUM PRO 2M	559 STADIUM PRO 3M		
						
562 GUELL ZERO KIT	562 GUELL ZERO	564 GUELL 1+	567 GUELL 2+	571 GUELL 25+	574 GUELL 3	576 GUELL 4
						
578 SMART IPROIE 1M	580 SMART IPROIE 2M	583 SMART IPROIE 4M	586 WIN PRO 20	588 WIN PRO 30	594 WIN PRO 40	596 WIN PRO L3
						
598 ELIA FL S3	600 ELIA FL M3	602 ELIA FL L3	604 ELIA FL XL3	606 ELIA FL MINI XS1	608 ELIA FL MINI XS2	610 ELIA FL MINI XS3
						
612 SPIDER+ 10 KIT	612 SPIDER+ 10	614 SPIDER+ 20	616 SPIDER+ 30	618 SPIDER+ POST		

Streetlight




620 KREOS 624 ROAD [5] MINI 630 ROAD [5] MEDIUM 640 KYRO+ 2 640 KYRO+ 1 646 STREET [O3]



648 THEOS GLASS 648 THEOS GLASS MINI 656 THEOS LUM GLASS 660 LYRA+

Bollard and column



662 INDEX+ 46 662 INDEX+ 86 664 KHA TECH 5 664 KHA TECH 9 666 KHA 5 666 KHA 9

668 KHA SLIM 93 668 KHA SLIM 220 670 KHA CITY 12 670 KHA CITY 26 674 KHA CITY MARINE 12 674 KHA CITY MARINE 26

676 AMON MINI 678 AMON MAXI

Urban light



680 URBAN [O3] 682 HEDO+ FT 686 SPILLO MINI POST 686 SPILLO MINI 688 SPILLO 690 HEDO+

Discover more

Seven light collections

Through a careful qualitative analysis of the lighting solutions, this catalog presents a wide range of fixtures across seven light collections.



How to read product sheets

All informations presented in this catalogue may be subject to modifications. The company reserves the right to make any changes if necessary without prior notice. Partial or complete reproduction of this catalogue is prohibited.

Scan the QR-code for the latest information




Website

www.performanceinlighting.com



WEBSITE



New

LIGHT-PERFORMER®

www.light-performer.com




LIGHT-PERFORMER®



New

Downloads

Design instruments



PHOTOMETRIC DATA



AUTODESK® REVIT



AUTODESK® 3DS MAX



DIALUX



OXYTECH LITESTAR



SKETCHUP



DXF




RELUX®

Colours


Natural Metals



BR-10/
Natural brass/
Glossy




INOX/
Stainless steel/
Glossy




INOX/
Stainless steel/
Matt

Anodized | Metals



GR-EV1/
Anodised grey/
Matt

Painting | Metals / Technopolymer



IVORY-10/
Ivory/
Textured



AN-96/
Anthracite gray/
Textured



BK-81/
Black/
Textured




RB-10
Rust/
Textured




BK-RAL9005/
Black RAL9005/
Glossy

Technopolymer



GR-94/
Metallic grey/
Textured




GR-RAL7035/
Grey RAL7035/
Matt



WH-87/
White/
Glossy



WH-87/
White/
Textured



GR-RAL7035/
Grey RAL7035/

Painting | Metals



SL-10/
Silver/
Matt



BK-RAL9005/
Black RAL9005/
Textured




BK-RAL9005/
Black RAL9005/
Glossy




WH-RAL9003/
White RAL9003/
Glossy



WH-RAL9010/
White RAL9010/
Glossy



WH-RAL9010/
White RAL9010/
Textured




GR-20/
Metallic grey/
Glossy



GR-RAL9006/
Grey RAL9006/
Textured



WH-RAL9016/
White RAL9016/
Glossy



WH-RAL916/
White RAL9016/
Textured



BK-RAL 9017/
Black RAL9017/



















Graphite grey/
Graphite grey/
















BlueGreen/
BlueGreen/

Pictograms















International protection marking

 IP 20	Protection against solid objects greater than 12 mm. No protection against water.	 IP 43	Protection against solid objects greater than 1,0 mm. Protection against spraying water.	 IP 54	Dust-protected. Protection against splashing water.	 IP 66	Total dust protection and total protection against hard splashing water.
 IP 23	Protection against entry of solid objects $\varnothing \geq 12$ mm and against rain.	 IP 44	Protection against solid objects greater than 1,0 mm. Protection against splashing water.	 IP 55	Dust-protected. Protection against water jets.	 IP 67	Dust-tight. Protection against the effects of temporary immersion.
 IP 40	Protection against solid objects greater than 1,0 mm. No protection against water.	 IP 45	Protection against solid objects greater than 1,0 mm. Protection against water jets.	 IP 64	Dust-tight. Protection against splashing water.	 IP 68	Fully dust protected. Protected against the effects of permanent immersion.
 IP 41	Protection against solid objects greater than 1,0 mm. Protection against vertically falling water drops.	 IP 50	Dust-protected. No protection against water.	 IP 65	Dust-tight. Protection against water jets.	 IK 10	Mechanical resistance to impacts of the diffuser




Mechanical characteristics

 WATER DRAIN	Water drain		Easing maintenance		Through wiring connection		Quick installation
	Side cable entry		Adjustable louvre		Glow wire resistance		Water stop
	Continuous mounted luminaire		Devices with limited surface temperature		Heavy use conditions		Loop through
	Suitable for sea front installation						
























Listings

	CE certified		RCM certified		Drive-over luminaire		Full cut-off
	ENEC certified		Cool touch		DIN EN 12464-1 conform		ULR (Upward Light Ratio) nominal value, device not inclined.
	EAC certified		Walk-over luminaire		DIN 18032-3 conform		3° CIE flow code corresponding to 3 π / 2 sr (75.5°).
	ATEX certified		UKCA certified				

Protection degree class


 CLASS I	Class I luminaire. Luminaire with security earthing.	 CLASS II	Class II luminaire. Reinforced or double insulated luminaire without earth protection.	 CLASS III	Class III luminaire. SELV (Safety Extra Low-Voltage) luminaire which can only be fed by an extra low voltage supply (i.e. less than 50 Volts). Class III luminaires may not be earthed.
---	---	--	---	---	--


Electronic features

	Double switch		Dimmable 1-10V		Power levels selectable during installation		Fuse
	Dawn-dusk switch		Dimmable DALI		SMART! light monitor		Hot restrike
	Constant light / presence control		DMX dimming function		Human Centric Lighting		Emergency luminaire 1 h
	High frequency motion sensor		Dynamic white		Automatic derating		Emergency luminaire 2 h
	Infrared motion sensor		RGBW		Pilot wire command derating		Emergency luminaire 3 h
	Colour rendering index Ra ≥ 90		Colour temperature selectable during installation		Surge protection up to 10 kV		

Light Controls



 **HCL - Human centric lighting**

 **Tunable white**

By continuously changing brightness and light temperature natural daylight has a big influence on the human biorhythm. Lighting fixtures with HCL (human centric lighting) change their light throughout the day bringing a small piece of nature indoors via artificial light. Control is done by freely configurable software varying the indirect light of the floor lamps reg. level of illumination intensity and light colour (2700 K up to 6200 K) according to the time of day. The direct share as workplace illumination is kept constant at 4000K, individual dimming is possible. Another technical version of floor lamps is Tunable White (TW). These allow changing individually the direct light between 2700 K and 6200 K via tactile switch while the direct light constantly remains at a colour temperature of 4000K. Both indirect and direct light can be dimmed by a switch.



 **DimSMART!® - Wireless dimming and controlling**

dimSMART! offers a simple system for wireless dimming and controlling of luminaires. Control is done via a smartphone (iOS or Android). You can download (free access) an easy and user friendly app with many functions. The user can set scenes and configure groups of luminaires according to their requirements. dimSMART! uses Bluetooth for communication therefore, WLAN-net or DALI wiring is not necessary, which makes dimSMART! perfectly suitable for existing installations.




SMART - light control system 868 mhz

The system is based on a 868 MHz wireless platform and includes luminaires that are fitted with a highly intelligent device for complete management of light, a complete sensory range to detect the person and lighting levels, and dedicated control stations.

SMART allows to create systems that dynamically interact with the surrounding environment by modulating the flow level of luminaires based on natural light variations or on the specific need by detecting staff in the work place. The entire system is wireless controlled and needs no additional control line.

System flexibility is highest with a dedicated management software that allows to program the luminaires as required at any time, even after installation.

To create or design systems with SMART, contact the Company.




Automatic power reduction

Luminaires are also available with automatic power reduction and with high-output electronic ballast already programmed to reduce the luminous flux by 50%. The power supply recognises the virtual night mid-point (e.g. midpoint of the switch-on time) and reduces the flux for a total of 8 hours, of which 2 hours before and 6 hours after.



Automatic power reduction with pilot command

Luminaire provided with dual-tap ballasts and switch device controlled from additional command line (pilot command). By intervening on the device, the pilot command switches the power supply of the lamp from 100% to the reduced power value. In case of a power failure, when the installation is set at reduced power, the switch device always guarantees the re-switch of the lamp at 100% until stabilization is achieved, in order not to damage the lamp, and then goes back to the reduced power.



Identifying and classifying our optics





The Group's luminaires offer different types of optics depending on project requirements.

The optic can be identified as the set of equipment designed to direct the light generated by a light source in a particular direction, thus determining the luminous emission of the luminaire itself.



The diagram below identifies the data that will be contained in subsequent pages, regarding the opening angle of the beam.

IMAX = maximum luminous intensity, i.e. the maximum intensity of the emitted light beam.



Depending on this luminous emission, the optics are classified in the following categories:

- S | Symmetric optics
- A | Asymmetric optics
- C | Circular optics
- ELL | Elliptical optics
- R | Grazing reflector optics
- SR | Road optics
- Z | Optics for pedestrian crossings



Symmetric optics

Symmetric optics are the ones with symmetric emission in relation to planes α and β .

The symmetry between the two planes may be either identical (in this case we are dealing with optics with square light distribution) or different (optics with rectangular light distribution).

Example

Symmetric optic code: S/xx

where:

S = Symmetric

xx = the abbreviated name of the opening angle

For example: S/I - S/M - S/W - S/EW

By convention, we consider the beam opening of plane α . Multiple optics within the same range of opening will be distinguished by inserting the numerical value of the beam opening at the end.

For example: S/W50 - S/W60

Symmetrical optics for series of luminaires with double light emission



This classification identifies the light emission typology of the luminaires inside those series that contain models with direct, indirect and / or combined light emission.

Symmetric optic name		
Mandatory indications	Additional indications	
Type of optic	Type of opening	Opening angle plane α
S	I	$0^\circ \div 20^\circ$
	M	$21^\circ \div 45^\circ$
	W	$46^\circ \div 75^\circ$
	EW	over 75°

Mandatory indications	Additional indications
Type of opening	Description
S1 S2	Includes all symmetrical optics from Narrow to Wide for Power LED
SN SM SW	Includes all symmetrical optics from Narrow to Wide for COB
ARRAY	Free distribution
MEDIUM	Medium beam diffuser
OPAL MICRO	Wide beam diffusers
SYMM	Symmetrical optic

Name of symmetrical optics for luminaires with double light emission			
Type of optic	Acronyms	Typology of light emission	
S	S/A	Direct symmetrical light	
	S/B	Mainly symmetrical direct light	
	S/C	Evenly direct - indirect symmetrical light	
	S/D	Mainly symmetrical indirect light	
	S/E	Indirect symmetrical light	

Identifying and classifying our optics



Asymmetric optics

Asymmetric optics generally have asymmetric light distribution on plane α with a point of maximum concentration. The axis passing through the point of maximum concentration and the point marked by the axis of the lamp is called the I_{max} axis. The light distribution on plane β , on the other hand, may be symmetric or asymmetric. An asymmetric optic may be symmetric in relation to one plane only.

Example

Asymmetric optic code: Ayy/xx

where:

A = Asymmetric

yy = numeric value of the I_{max} angle.

The I_{max} angle is the angle between axis A and the I_{max} axis.

xx = the abbreviated name of the opening angle

For example: Ayy/I – Ayy/M – Ayy/W – Ayy/EW.

By convention, the beam opening of plane α is considered.

For example:

A30/M = Asymmetric axis with I_{max} 30° and Medium opening

A45/I = Asymmetric axis with I_{max} 45° and Intensive opening

In the presence of multiple asymmetric optics with the same I_{max} value and same beam opening range, it will be necessary to distinguish them by adding the numeric value of the beam opening at the end.

For example: A45/M25 - A45/M40

Asymmetric optic name

Mandatory indications		Additional indications	
Type of optic	I_{max} angle	Type of opening	Opening angle plane α
A	Numeric value of the I_{max} angle	I	0° ÷ 20°
		M	21° ÷ 45°
		W	46° ÷ 75°
		EW	over 75°
Mandatory indications		Additional indications	
Type of opening	Description		
A1 A2 A3	Includes all asymmetrical optics from Narrow to Wide for Power LED		
ASW ALW	Includes all asymmetrical optics from Narrow to Wide for COB		
ASYMM	Asymmetrical optic		

Circular optics

For circular optics, those optics are identified as optics that generate a luminous emission with a symmetry of revolution about the A axis as circular optics.

The opening angle of the beam is generally constant in all planes.

The reflectors generating these optics generally have a circular opening.

Example

Circular optic code: C/xx

where:

C = Circular

xx = the abbreviated name of the opening angle


For example: C/I - C/M - C/IW - C/MW -C/EW

Multiple optics within the same range of opening will be distinguished by inserting the numerical value of the beam opening at the end.

For example: C/IW46 - C/IW50

Circular optic name

Mandatory indications		Additional indications
Type of optic	Type of opening	Opening angle α
C	I	0° ÷ 20°
	M	21° ÷ 45°
	IW	46° ÷ 60°
	MW	61° ÷ 75°
	EW	over 75°
Mandatory indications		Additional indications
Type of opening	Opening angle α	
C1	30° ÷ 45°	
C2	25° ÷ 30°	
C3	20° ÷ 25°	
C4	15° ÷ 20°	
C5	10° ÷ 15°	
C6	0° ÷ 10°	



Elliptical optics

Elliptical optics are circular but differ from roto-symmetrical circular optics because the opening of the light beam on planes α and β is symmetric, but differs greatly between the two. The light distribution is highly elliptical.

Example

Elliptical optic code: E α x β


where:

E = Elliptical

α = Opening of the light beam on plane α expressed in degrees

β = Opening of the light beam on plane β expressed in degrees

For example: E 10°x45°




Grazing reflector optics


Grazing reflector optics stand out for their luminous emission that is typically parallel (grazing) to the installation surface (wall or ground).

These optics are primarily used for architectural lighting with the purpose of designing patterns of light and they rarely have a functional use.

A fundamental characteristic is the value of the α angle that identifies the value of the light beam aperture measured on the installation surface.



Identifying and classifying our optics



Road optics

Road optics are identified as the optics that have a very broad beam spread on the β plane (usually greater than 120°), with the point of maximum emission on one of the adjacent planes to the latter, up to a maximum of 45° .

Road lighting based on L/H ratio that can be found in road lighting systems, where:

- L: distance between the optical axes of the luminaire and the part of the area furthest from it with its own requirements.
- H: height of installation of the luminaire.

Example

Acronym of the road optics based on the L/H ratio: R/xxx

where:


R = road

xxx = L/H value (e.g. 100 = 1.00)


For example: R/075, R/100

Name of the road optics based on the L/H ratio:

Type of optic	Acronyms	Description
SR	075	Optic for L/H up to 0.75 ($0,5 \leq L/H \leq 0,875$)
	100	Optic for L/H of 1 ($0,875 \leq L/H \leq 1,125$)
	125	Optic for L/H of 1.25 ($1,125 \leq L/H \leq 1,375$)
	150	Optic for L/H of 1.5 ($1,375 \leq L/H \leq 1,625$)



Mandatory indications	Additional indications
Acronyms	Description
HUGE	Optics for wide road geometries
WIDE	Optics for medium road geometries
ST1	Optics for medium-wide road geometries
CYCLE	Optics for pedestrian crossings



Optics for pedestrian crossings

For optics for pedestrian crossings are identified those optics for lighting in the direction of their flow. They feature asymmetrical emission both on the α plane and on the β plane.


Example

Acronym of optics for pedestrian crossings: Z/R

where:

Z = zebra (pedestrian crossing)

R = right (for countries where driving is on the right)









Two-way traffic

One-way traffic

Road lighting - EN 13201-2 2015

This part of the European standard defines the performance requirements specified in the form of lighting categories for road lighting designed to satisfy the visual needs of road users and considers environmental aspects of road lighting.

Class		Requirements					Recommended optic					
	Motor traffic Roads with predominantly motor traffic. The lighting magnitude considered is average horizontal illuminance.		L (cd/m^2) (\geq)	U_o (\geq)	U_l (\geq)	fT_1 (%) (\leq)	R_g (\geq)	SR/075	SR/100	SR/125	SR/150	Z/R
		M1	2,00	0,40	0,70	10	0,35	-	-	-	-	-
		M2	1,50	0,40	0,70	10	0,35	-	✓	-	-	-
		M3	1,00	0,40	0,60	15	0,30	✓	✓	✓	✓	-
		M4	0,75	0,40	0,60	15	0,30	✓	✓	✓	✓	-
		M5	0,50	0,35	0,40	15	0,30	✓	✓	✓	✓	-
		M6	0,30	0,35	0,40	20	0,30	✓	✓	✓	✓	-
	Motor traffic Conflict areas (crossroads and roundabouts) and residential streets. The lighting magnitude considered is average horizontal illuminance.		\bar{E} (lx) (\geq)	U_o (\geq)	fT_1 (%) (\leq)		SR/075	SR/100	SR/125	SR/150	Z/R	
		C0	50	0,40	15		-	✓	✓	✓	-	
		C1	30	0,40	15		-	✓	✓	✓	-	
		C2	20,0	0,40	15		-	✓	✓	✓	-	
		C3	15,0	0,40	20		✓	✓	✓	-	-	
		C4	10,0	0,40	20		✓	✓	-	-	-	
C5	7,50	0,40	20		✓	✓	-	-	-			
	Pedestrian areas Pedestrian and/or cycling areas, residential streets, emergency lanes, car parks and pavements. The lighting magnitude considered is average horizontal illuminance.		\bar{E} (lx) (\geq)	E_{min} (lx) (\geq)	fT_1 (%) (\leq)		SR/075	SR/100	SR/125	SR/150	Z/R	
		P1	15,0	3,00	20		✓	✓	✓	✓	-	
		P2	10,0	2,00	25		✓	✓	✓	✓	-	
		P3	7,50	1,50	25		✓	✓	-	-	-	
		P4	5,00	1,00	30		✓	✓	-	-	-	
		P5	3,00	0,60	30		✓	-	-	-	-	
		P6	2,00	0,40	35		✓	-	-	-	-	
P7	-	-	-		✓	-	-	-	-			
	Pedestrian areas Pedestrian and/or cycling areas, residential streets, emergency lanes, car parks and pavements. The lighting magnitude considered is average hemispherical illuminance.		E_{HS} (lx) (\geq)	U_o (\geq)			SR/075	SR/100	SR/125	SR/150	Z/R	
		HS1	5,00	0,15			✓	✓	✓	✓	-	
		HS2	2,50	0,15			✓	✓	-	-	-	
		HS3	1,50	0,15			✓	-	-	-	-	
HS4	-	-			✓	-	-	-	-			
	Additional categories Additional category in pedestrian areas in which face recognition is required for security reasons. The lighting magnitude considered is specific minimum semi-cylindrical illuminance.		$E_{\text{SC,min}}$ (lx) (\geq)				SR/075	SR/100	SR/125	SR/150	Z/R	
		SC1	10,0				✓	✓	✓	✓	-	
		SC2	7,50				✓	✓	✓	✓	-	
		SC3	5,00				✓	✓	✓	✓	-	
		SC4	3,00				✓	✓	✓	✓	-	
		SC5	2,00				✓	✓	✓	✓	-	
		SC6	1,50				✓	✓	-	-	-	
		SC7	1,00				✓	-	-	-	-	
		SC8	0,75				✓	-	-	-	-	
SC9	0,50				✓	-	-	-	-			
	Additional categories Additional category in areas where attention must be paid to vertical elements, such as pedestrian crossings and conflict areas. The lighting magnitude considered is specific minimum vertical illuminance.		$E_{\text{V,min}}$ (lx) (\geq)				SR/075	SR/100	SR/125	SR/150	Z/R	
		EV1	50				-	-	-	-	✓	
		EV2	30				-	-	-	-	✓	
		EV3	10,0				-	-	✓	✓	✓	
		EV4	7,50				-	-	✓	✓	✓	
		EV5	5,00				-	-	✓	✓	✓	
EV6	0,50				-	-	✓	✓	✓			

Corrosion



ISO 9223: 2012 has established a classification system for atmospheric corrosion of various environments for alloys and metals. It defines the corrosion classes of atmospheric, on the corrosion rate detected in environments for one year on standardised specimens. The norm provides dose-response functions for estimating the corrosivity class, calculated based on normalised metals' annual loss from corrosion. It makes it possible to estimate maximum corrosion class based on the local environment situation knowledge. These consist of the combined effect of temperature and humidity and pollution from sulfur dioxide and salinity.

Corrosivity category for typical external environments


The reference standard does not consider other elements, such as wind speed, sand abrasion, accidental breakage of the protective layer, maintenance frequency, and exposure level. The classifications in the areas shown do not identify solutions or test methods for their suitability.

Corrosivity Category	Corrosivity	Typical environments
C1	Very low	Dry or cold zone, atmospheric environment with very low pollution and humidity time, e.g., certain deserts, Central Arctic / Antarctica.
C2	Low	Low-temperature zone, low pollution atmospheric environment (SO_2^* < 5 $\mu\text{g} / \text{m}^3$), rural areas, and small towns. Dry or cold location, atmospheric setting with a short humidity time, e.g., deserts, subarctic areas.
C3	Medium	The temperate zone, atmospheric environment with medium pollution (SO_2^* : from 5 $\mu\text{g} / \text{m}^3$ to 30 $\mu\text{g} / \text{m}^3$) or some chlorides, e.g., urban areas, coastal areas with low chloride deposition. Subtropical and tropical zone, quiet pollution atmosphere.
C4	High	Temperate zone, highly polluted atmospheric environment (SO_2^* : 30 $\mu\text{g} / \text{m}^3$ to 90 $\mu\text{g} / \text{m}^3$) or substantial effect of chlorides, e.g., polluted urban areas, industrial areas, coastal areas without saltwater splash or exposure to the strong impact of antifreeze salts-subtropical and tropical zone, medium pollution atmosphere.
C5	Very high	Temperate and subtropical zone, atmospheric environment with very high pollution (SO_2^* : from 90 $\mu\text{g} / \text{m}^3$ to 250 $\mu\text{g} / \text{m}^3$) and significant effect of chlorides, e.g., industrial areas, generic coastal areas, sheltered locations on the coast.
CX	Extreme	Subtropical and tropical zone (very high humidity period), atmospheric environment with very high SO_2^* pollution (above 250 $\mu\text{g} / \text{m}^3$) including accompanying and production factors and the strong effect of chlorides, e.g., extreme industrial areas, coastal and offshore locations, and occasional contact with salt spray. Category CX is to be considered for extreme situations where the corrosion rates exceed the upper limits in category C5. Indeed, CX refers to specific marine and marine/industrial environments, such as bridges.

* SO_2^* : Sulphur dioxide – (not sodium chloride)

Note: without prejudice – die-cast aluminium chemically pre-treated polyester powder coated products offer some protection, it is not a total protection against a marine environment

The fittings located in or near coastal locations may suffer oxidation caused by the atmospheric conditions; this may affect the finish and appearance of the luminaire, but not necessarily its electrical integrity. However, the electrical integrity and safety of the fitting are paramount, which a suitably qualified persons should also check as part of the maintenance cycle. It is usually recommended that a regular maintenance regime be undertaken in coastal locations. The fittings are frequently hosed down with clean water and a liquid-based surfactant, which should be used to clean down the salty regularly deposits. As third parties are involved and responsible for undertaking actions outside our remit, we wish to clarify that we cannot be held accountable for acts of nature and offer this advice as best practice only.



Standards

The company tests its products and processes using the ISO 9227: 2017 test standard and use this regulatory reference to provide measurable results for the qualification of materials, treatments, and processes. We adopt a pre-treatment process to produce the highest quality paint finish capable of guaranteeing excellent adhesion of the paint and the best protection against corrosion using chemicals specifically dedicated to aluminium. There are three active cleaning and conversion stages, including thorough rinsing. Furthermore, the complete luminaire is tested in atmospheric sodium chloride (5 g/l) cabinet. The surface of the luminaire is scratched horizontally and vertically to the metal. We check the corrosion behaviour on the complete product:

- The quality of the paint
- The sensibility of the design
- The behaviour of stainless-steel screws and the aluminium quality

Before introducing to the market, following ISO 9227, any new product is subjected to a salt spray test to validate its resistance to corrosion.

The company in addition to applying ISO 9227: 2017, also uses UNI EN 12944 to verify its processes for an exposure time of 1440 hours at a constant temperature of $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$ ($U > 60\%$ - NaCl 5%). All our painted products pass this type of test.


However, no environmental factors classification is detailed in ISO 9223: 2012. Tests are conducted according to ISO 9227, and the results are subsequently classified to conform to ISO 9223. The company keeps the test documentation and self-declares the C5 (or CX) declaration.

HRT - Beyond the standards

The reference standard ISO 9223: 2012 specifies but does not define the classification of the test method to verify the products to be used in these areas. In any case, corrosion is not a problem in our painted products.

The High Resistant Treatment (HRT) painting process, exclusive to the company, is based on decades of experience within the sector. It is a further evolution for particularly aggressive contexts that improve protection and duration. Consult the factory for "sea-front coastal locations" schemes, to define the most suitable solution for your project with our specialised technicians.

Quality, tests, certifications



The company is oriented towards constant improvement and striving for the delicate balance between form and function. These aspects become luminaires and solutions that balance remarkable lighting performance with timeless aesthetics.

Performance, beauty, ease of installation and durability are objectives established at the initial product concept and intellectually carried through every design phase, paying particular attention to even the smallest construction detail.

All products are entirely designed in Italy, Germany and Belgium.

The group's technical offices for product development, design, 3D modelling, thermal simulation and study of fluid dynamics, and optics development all use the latest generation of professional software.

Management software is also used in which all the technical information is reported. These tools make it possible to optimize some phases of the general project management process, improving the broad productivity indices of the company.

The R&D department is equipped with modern 3D printers that can quickly produce a prototype of the designed part, reducing product development times.

Through continuous training, highly competent staff, and instrumentation supplied in its laboratories, the company can now independently perform almost all of the tests required by national and international regulations.

All lighting fixtures manufactured must comply with the strictest safety, quality, and durability regulations. To this end, the company has invested in internal laboratories that operate according to the international standard ISO 17025.

The laboratories are accredited with CTF STAGE 2 (Customers' Testing Facilities - Stage 2) certifications issued by IMQ and VDE.

They produce and certify the technical documentation necessary for the issue of the European ENEC certification.

The same laboratories are WTDP (Witness Test Data Program), qualified to conduct tests according to American standards (UL) to obtain product certification.

Within the laboratories, temperatures, electrical resistance, electrical insulation, mechanical resistance, protection against the entry of solids and liquids, electromagnetic compatibility and photometric distribution are checked to obtain a safe and efficient product.

Today, the Group has laboratories for electrical safety tests, photometric chambers with proprietary photogoniometers, integrating spheres, measuring optical flicker and stroboscopic effect, climatic chamber, salt spray test chamber and laboratories for electromagnetic compatibility tests.

The constant commitment to improving product quality and service has led the company to be certified by a quality system that complies with the ISO 9001-2015 standard for the whole production cycle, from design and production activities to logistics and marketing of its products.



All products which are subject to European Directive 2014/35/EU bear the mark CE.



The internal laboratory operates following the UNI EN ISO 17025:2005 standard, which allows PERFORMANCE IN LIGHTING to conduct all of the safety tests for its products. This guarantees the compliance of all products with the current European and extra-European standards.



The ENEC certified lighting fixtures are approved by a third-party certification body and comply with the European electrical safety standards. Companies that offer ENEC products apply a quality system in compliance with UNI EN ISO 9001.



The RCM Mark "Regulatory Compliance Mark", certifies that each individual electrical and electronic product complies with the mandatory safety requirements in Australia and New Zealand such as the electrical safety and electromagnetic compatibility.



The VDE mark documents the safety and conformity to standards of an electrical product with regard to electrical, mechanical, thermal, toxic and other hazards. It is awarded exclusively by the VDE test and certification institute (VDE-PZI). A manufacturer may only provide its products with the VDE mark after checking and issuing of a corresponding certificate.



The EAC mark certifies the conformity of the products with the regulations of the Eurasian customs' area; the mark allows the access to the marketplace of Russia, Belarus, Armenia, Kazakhstan, Kyrgyzstan.

Testing laboratory



All testing activities are supervised once a year by the Official Certification Bodies (IMQ S.p.A. and UL).

The laboratories are recognized by IMQ and VDE according to the CTFs STAGE 2 (Customers' Testing Facilities) procedures that release the ENEC label in compliance with the following standards:

IEC/EN 60598-1
Luminaires

IEC/EN 60598-2-1
Luminaires - Part 2-1: Particular requirements – Specification for fixed general purpose luminaires

IEC/EN 60598-2-2
Luminaires - Part 2-2: Particular requirements – Recessed luminaires

IEC/EN 60598-2-3
Luminaires - Part 2-3: Particular requirements – Luminaires for road and street lighting

IEC/EN 60598-2-4
Luminaires - Part 2-4: Particular requirements – Portable general purpose luminaires

IEC/EN 60598-2-5
Luminaires - Part 2-5: Floodlights

IEC/EN 60598-2-7
Luminaires - Part 2-7: Particular requirements – Portable luminaires for garden use

IEC/EN 60598-2-13
Luminaires - Part 2-13: Particular requirements - Ground recessed luminaires

IEC/EN 6598-2-18
Luminaires - Part 2-18: Particular requirements – Luminaries for swimming pools and similar applications

IEC/EN 62031
LED modules for general lighting - Safety specifications



Furthermore, the laboratories are recognized by UL according to the WTDP (Witness Test Data Program) for the release of the UL label in compliance with the following standards:

UL 1598
Luminaires

CSA C22.2 NO 250.0-08
Luminaires

UL 8750
Standard for Light Emitting Diode (LED) Equipment for Use in Lighting Products

CSA C22.2 NO 250.13-12
Light Emitting Diode (LED) Equipment for Lighting Applications

Within the laboratories, there is also an outfitted room (with the best EMI Receivers) for electromagnetic compatibility measurements and to ensure that the products are in compliance with the most important industry standards such as:

CISPR 15
Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

EN 55015
European Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

Quality, tests, certifications



Photometric laboratory

Considerable investments have also been made in photometric laboratories, which are recognized by UL and operate in accordance with the UNI EN 13032 standard.

This certification is synonymous with reliability and quality, as laboratories are subjected to inter-laboratory inspections and comparisons by the certifying body.

This result is that the company has the knowledge to supply the customer with highly reliable data, which translates theoretical projects into field results. The photometric laboratories are climate controlled to 25°C and are equipped with photogoniometers of various types (T2 and Type C), spectroradiometers, integrating spheres and Data Logger Multimeters with which it is possible to measure luminous flux and electrical parameters, temperature and all the colorimetry characteristics (CRI - CCT - Chromatic coordinates), as described in the reference standards listed below. Data measurements and processing are collected in compliance with the following standards:

UNI EN 13032-1

Light and Lighting – Measurement and presentation of photometric data of lamps and luminaires Part 1: Measurement and file format.

UNI EN 13032-4

Light and lighting. Measurement and presentation of photometric data of lamps and luminaires. Part 4: LED lamps, modules and luminaires.

IES LM-79-08

Approved method for the Electrical and Photometric Measurements of Solid-State Lighting Products.

To illuminate with led – photo-biological risk

With the coming onto the market of high power LED technology, usable both as common and signaling lighting, a confused marketing of poorly performing and unsafe products from a photo-biological viewpoint has taken place.

Therefore the Group chose to use high power LED from leading brands only.

On an international level a new standard has been fixed: EN62471 (IEC62471). This standard deals in a transversal way with the photo-biological risks of lighting sources and especially of LED devices and products using specific types of discharge lamps and LED light sources. A classification of GROUPS OF PHOTO-BIOLOGICAL RISKS under which luminaires may fall has been drawn.

The Groups of risks are defined as follows:

Group of Risk Nil:

The luminaires do not pose any photo-biological risks.

Group of Risk 1:

The luminaires do not cause photo-biological damage for the risk is cancelled by the common behavioral reaction of a person to the exposure to a light source.

Group of Risk 2:

The luminaires cannot cause photo-biological damage for the risk is cancelled by instinctive reaction of looking away from a very bright and strong light or from a thermal suffering.

Group of Risk 3:

The luminaires may cause photo-biological damage; risk is high even for a short or instant exposure. It is strongly advised to not use the luminaires for general lighting.

Production checks

PRODUCTION CHECKS

All products are subject to a vast number of accurate checks directly in the production line. Checks are done with control instruments that are checked and managed by the quality system procedure jointly with the indications reported on the “Minimum Values for Electrical Tests” List of the IEC/EN 60598-1 – Luminaires standard. This ensures the reliability and the compliance with security and performance of the product the Client expects.

Training of technical department

By constantly attending upgrade courses proposed by the industry associations and different certifying bodies, a fundamental importance is given to the specific training of the technical department. The company attends the meetings of the industry association (ASSIL) and is present in the 34D and 34A subcommittee of CEI (Italian Electro-technical Committee).



Environment

The concept of limited natural resources is given much consideration by the Group during product development.

The design choices, the entire production cycle up to packaging, transport, and all stages of the life of the fixtures placed on the market, including their recycling, aim to reduce potential environmental impacts.

The Group uses components and materials to save energy and respect the environment.

Intelligent control technologies are used, such as sensors that detect daylight and movement, software and electronic components for controlling products and their sources to obtain significant energy savings.

Furthermore, specially designed high-performance reflectors or lenses allow for optimal distribution of light where it is needed, avoiding waste and loss.

The combination of efficient ballasts, optoelectronic light sources, intelligent sensors and highly complex reflectors results in durable, energy-efficient products with respect for the environment.



Ecodesign

New European directives on ecodesign and energy labelling of light sources for more sustainable lighting.

The European Community has set essential objectives that will lead to significant energy savings by 2030 and an increasingly diminished environmental impact by introducing the new UE 2019/2020 SRL (Ecodesign) and UE 2019/2015 ELR (Energy Labelling) regulations.

SRL REGULATION (Single Light Regulation UE 2019/2020 Ecodesign)

The Group designs and develops its lighting fixtures following the regulations, focusing on the environment and energy sustainability.

All the information required by the regulation is available on the free access website and product instruction sheets.

ELR REGULATION (Energy Labelling Regulation UE 2019/2015)

The company guarantees the registration of the light fixtures of its design and development in the EPREL database following the regulations.



RoHS compliant

The company is registered as a manufacturer with the German waste electrical equipment register EAR, in implementation of European Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE), under the following number: WEEE-Reg. No. DE 27756601. All electric and electronic equipment brought into circulation by the company is marked with the "crossed-out dustbin" symbol with a bar denoting the limit date for putting into circulation.

To our knowledge, our products contain no substances in concentrations or applications the putting into circulation of which in products is forbidden in accordance with the applicable requirements of Directive 2002/95/EC (RoHS). An environmental officer constantly examines further improvements, and constant staff training courses round off the complete catalogue of measures.



Partner CasaClima

Our company has always been focused on important issues such as environmental protection, energy saving and the well-being of people. The design and development of our products are inspired by these themes every day.

A new collaboration starts with Agenzia CasaClima, an independent public certification body in South Tyrol (I), which managed to create its own certification protocol not only for residential construction, but also in the field of public lighting, wineries, schools, factories and much more. Over the years, it has become a protocol national, also known in Austria and Germany. PERFORMANCE IN LIGHTING becomes the partner in the field of artificial lighting, providing training and consultancy regarding energy savings, smart lighting management, regulations, well-being and visual comfort.



Interseroh recycling

The Group has concluded a contract with INTERSEROH for the proper recording, sorting and recycling of transport packaging. This ensures that packaging at our clients' premises is recorded by INTERSEROH partners, the packaging material is recycled and all requirements of the packaging directive are fulfilled.





Founding member of ECOLIGHT

The company is a member of the ECOLIGHT consortium for the recycling of lighting fixtures. ECOLIGHT brings together over 1,700 companies and ensures the management and disposal of WEEE, exhausted batteries and accumulators, and end-of-life photovoltaic modules.

Structure of the Group

The holding is composed by various manufacturing companies and many branches all over the world.
It is a unique industrial framework, its brands are distributed in more than one hundred countries throughout the world.






SL764+ PL



Headquarters BCD travel - Utrecht - Netherlands




Scan the QR-code for the latest information

- GR-EV1 / Anodised grey / Matt
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:

- Extruded aluminium profile housing, anodised (EV1) or polyester powder coat, die-cast aluminium end caps, polyester powder coat
- The luminaire is available with different light engines:
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Black grid for maximum luminaire efficiency, glare reduction and a high uniformity
 - VDU application suitable acc. to EN 12464-1
 - Light distribution direct or direct/ indirect
 - Streamlined, simple design with flush end caps
 - High-quality workmanship of profile connections for a perfect look
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Through-wiring designed
 - Simple and convenient lighting installation
 - Interchangeable lighting inserts
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy
 - Continuous mounted options and many other configurations are available at www.light-performer.com



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL764+ PL OP

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12	I	✓	-	80	4000	2150	1860	■	1412	3109600	✓
12	I	✓	-	80	3000	2040	1770	■	1412	3109599	✓
10	I	✓	-	80	4000	1720	1490	■	1132	3109598	✓
10	I	✓	-	80	3000	1630	1410	■	1132	3109597	✓



SL764+ PL LV S/C

IP30 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
51	I	✓	✓	90	4000	7470	6280	■	1412	3112563	✓
51	I	✓	✓	90	3000	7080	5960	■	1412	3112562	✓
51	I	✓	✓	90	4000	7470	6280	□	1412	3113763	✓
51	I	✓	✓	90	3000	7080	5960	□	1412	3113762	✓
51	I	✓	✓	80	4000	8540	7180	■	1412	3112565	✓
51	I	✓	✓	80	3000	8280	6970	■	1412	3112564	✓
41	I	✓	✓	90	4000	5980	5030	■	1132	3112559	✓
41	I	✓	✓	90	3000	5660	4770	■	1132	3112558	✓
41	I	✓	✓	90	4000	5980	5030	□	1132	3113761	✓
41	I	✓	✓	90	3000	5660	4770	□	1132	3113760	✓
41	I	✓	✓	80	4000	6830	5750	■	1132	3112561	✓
41	I	✓	✓	80	3000	6630	5570	■	1132	3112560	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz

51	I	✓	✓	90	4000	7470	6280	■	1412	3112571	✓
51	I	✓	✓	90	3000	7080	5960	■	1412	3112570	✓
51	I	✓	✓	90	4000	7470	6280	□	1412	3113767	✓
51	I	✓	✓	90	3000	7080	5960	□	1412	3113766	✓
51	I	✓	✓	80	4000	8540	7180	■	1412	3112573	✓
51	I	✓	✓	80	3000	8280	6970	■	1412	3112572	✓
41	I	✓	✓	90	4000	5980	5030	■	1132	3112567	✓
41	I	✓	✓	90	3000	5660	4770	■	1132	3112566	✓
41	I	✓	✓	90	4000	5980	5030	□	1132	3113765	✓
41	I	✓	✓	90	3000	5660	4770	□	1132	3113764	✓
41	I	✓	✓	80	4000	6830	5750	■	1132	3112569	✓
41	I	✓	✓	80	3000	6630	5570	■	1132	3112568	✓

SL764+ PL MP

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
41	I	✓	-	90	4000	6980	5650	■	1412	3115844	✓
41	I	✓	-	90	3000	6480	5240	■	1412	3115843	✓
41	I	✓	-	90	4000	6980	5650	□	1412	3115846	✓
41	I	✓	-	90	3000	6480	5240	□	1412	3115845	✓
32	I	✓	-	90	4000	5510	4460	■	1132	3115836	✓
32	I	✓	-	90	3000	5120	4140	■	1132	3115835	✓
32	I	✓	-	90	4000	5510	4460	□	1132	3115838	✓
32	I	✓	-	90	3000	5120	4140	□	1132	3115837	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
41	I	✓	-	90	4000	6980	5650	■	1412	3115848	✓
41	I	✓	-	90	3000	6480	5240	■	1412	3115847	✓
41	I	✓	-	90	4000	6980	5650	□	1412	3115850	✓
41	I	✓	-	90	3000	6480	5240	□	1412	3115849	✓
32	I	✓	-	90	4000	5510	4460	■	1132	3115840	✓
32	I	✓	-	90	3000	5120	4140	■	1132	3115839	✓
32	I	✓	-	90	4000	5510	4460	□	1132	3115842	✓
32	I	✓	-	90	3000	5120	4140	□	1132	3115841	✓



SL764+ PL MP S/D

IP40 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	-------------	------

Power LED 220-240 V 50/60 Hz

89	I	✓	✓	80	4000	14170	12430	■	2532	3117900	✓
89	I	✓	✓	80	3000	13460	11810	■	2532	3117892	✓
89	I	✓	✓	80	4000	14170	12430	■	2532	3117916	✓
89	I	✓	✓	80	3000	13460	11810	■	2532	3117908	✓
69	I	✓	✓	80	4000	11620	9670	■	1972	3117899	✓
69	I	✓	✓	80	3000	11040	9180	■	1972	3117891	✓
69	I	✓	✓	80	4000	11620	9670	■	1972	3117915	✓
69	I	✓	✓	80	3000	11040	9180	■	1972	3117907	✓
59	I	✓	✓	80	4000	9960	8280	■	1692	3117898	✓
59	I	✓	✓	80	3000	9460	7870	■	1692	3117890	✓
59	I	✓	✓	80	4000	9960	8280	■	1692	3117914	✓
59	I	✓	✓	80	3000	9460	7870	■	1692	3117906	✓
39	I	✓	✓	80	4000	6640	5520	■	1132	3117897	✓
39	I	✓	✓	80	3000	6310	5250	■	1132	3117889	✓
39	I	✓	✓	80	4000	6640	5520	■	1132	3117913	✓
39	I	✓	✓	80	3000	6310	5250	■	1132	3117905	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz

89	I	✓	✓	80	4000	14170	12430	■	2532	3117904	✓
89	I	✓	✓	80	3000	13460	11810	■	2532	3117896	✓
89	I	✓	✓	80	4000	14170	12430	■	2532	3117920	✓
89	I	✓	✓	80	3000	13460	11810	■	2532	3117912	✓
88	I	✓	✓	80	4000	-	14140	■	2532	3115655	✓
69	I	✓	✓	80	4000	11620	9670	■	1972	3117903	✓
69	I	✓	✓	80	3000	11040	9180	■	1972	3117895	✓
69	I	✓	✓	80	4000	11620	9670	■	1972	3117919	✓
69	I	✓	✓	80	3000	11040	9180	■	1972	3117911	✓
67	I	✓	✓	80	4000	-	10660	■	1972	3115649	✓
59	I	✓	✓	80	4000	9960	8280	■	1692	3117902	✓
59	I	✓	✓	80	3000	9460	7870	■	1692	3117894	✓
59	I	✓	✓	80	4000	9960	8280	■	1692	3117918	✓
59	I	✓	✓	80	3000	9460	7870	■	1692	3117910	✓
48	I	✓	✓	80	4000	-	7560	■	1412	3115643	✓
39	I	✓	✓	80	4000	6640	5520	■	1132	3117901	✓
39	I	✓	✓	80	3000	6310	5250	■	1132	3117893	✓
39	I	✓	✓	80	4000	6640	5520	■	1132	3117917	✓
39	I	✓	✓	80	3000	6310	5250	■	1132	3117909	✓



De Romein Group - Veendam - Netherlands

SL764+ RE



Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

Series of recessed LED luminaires, comprising:


- Extruded aluminium profile housing, die-cast aluminium end caps, powder-coated
- Opal PMMA diffuser for optimal light distribution and uniformity
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Includes recessed mounting kit
- Continuous mounted options and many other configurations are available at www.light-performer.com



ABI BV offices - Haarlem - Netherlands



SL764+ PL



SL764+ RF



SL764+ RE OP




CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL764+ RE OP

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12	I	✓	-	80	4000	2150	1860	□	1412	3109604	✓
12	I	✓	-	80	3000	2040	1770	□	1412	3109603	✓
10	I	✓	-	80	4000	1720	1490	□	1132	3109602	✓
10	I	✓	-	80	3000	1630	1410	□	1132	3109601	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
SL764+ RE				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585





3122586



3122587

SL764+ RF



- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Scan the QR-code for the latest information

Ceiling surface mounted LED luminaire, comprising:


- Extruded aluminium profile housing, die-cast aluminium end caps, powder-coated
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Black grid for maximum luminaire efficiency, glare reduction and a high uniformity
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Includes recessed mounting kit
- Continuous mounted options and many other configurations are available at www.light-performer.com




SL764+ PL



SL764+ RE



SL764+ RF



SL764+ RF



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL764+ RF LV

IP30 - IK05 - 650 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	I	✓	✓	90	4000	4670	3870	■	1428	3112579	✓
32	I	✓	✓	90	3000	4430	3670	■	1428	3112578	✓
32	I	✓	✓	90	4000	4670	3870	□	1428	3113771	✓
32	I	✓	✓	90	3000	4430	3670	□	1428	3113770	✓
32	I	✓	✓	80	4000	5340	4430	■	1428	3112581	✓
32	I	✓	✓	80	3000	5180	4290	■	1428	3112580	✓
25	I	✓	✓	90	4000	3740	3100	■	1148	3112575	✓
25	I	✓	✓	90	3000	3540	2940	■	1148	3112574	✓
25	I	✓	✓	90	4000	3740	3100	□	1148	3113769	✓
25	I	✓	✓	90	3000	3540	2940	□	1148	3113768	✓
25	I	✓	✓	80	4000	4270	3540	■	1148	3112577	✓
25	I	✓	✓	80	3000	4140	3440	■	1148	3112576	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
32	I	✓	✓	90	4000	4670	3870	■	1428	3112587	✓
32	I	✓	✓	90	3000	4430	3670	■	1428	3112586	✓
32	I	✓	✓	90	4000	4670	3870	□	1428	3113775	✓
32	I	✓	✓	90	3000	4430	3670	□	1428	3113774	✓
32	I	✓	✓	80	4000	5340	4430	■	1428	3112589	✓
32	I	✓	✓	80	3000	5180	4290	■	1428	3112588	✓
25	I	✓	✓	90	4000	3740	3100	■	1148	3112583	✓
25	I	✓	✓	90	3000	3540	2940	■	1148	3112582	✓
25	I	✓	✓	90	4000	3740	3100	□	1148	3113773	✓
25	I	✓	✓	90	3000	3540	2940	□	1148	3113772	✓
25	I	✓	✓	80	4000	4270	3540	■	1148	3112585	✓
25	I	✓	✓	80	3000	4140	3440	■	1148	3112584	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
SL764+ RF			
External Casambi module	■	3122585	✓
Single wireless wall switch	□	3122586	✓
Double wireless wall switch	□	3122587	✓



3122585



3122586




3122587

SL764+ SM



Mediatheque Les 7 lieux - Bayeux - France




Scan the QR-code for the latest information

- GR-EV1 / Anodised grey / Matt
- BK-RAL9005 / Black RAL9005 / Textured

LED surface-mount luminaire for indoor, comprising:

- Extruded aluminium profile housing, anodised (EV1) or polyester powder coat, die-cast aluminium end caps, polyester powder coat
- Opal PMMA diffuser for optimal light distribution and uniformity
- Direct light distribution
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Continuous mounted options and many other configurations are available at www.light-performer.com



SL764+ SM OP

SL764+ SM OP

SL764+ SM OP

SL764+ SM OP



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL764+ SM OP

IP40 - IK05 - 650 °C




LUMINAIRE WATTAGE [W]	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
44	I	✓	-	80	4000	7560	6570	■	2532	3117932	✓
44	I	✓	-	80	3000	7180	6240	■	2532	3117924	✓
44	I	✓	-	80	4000	7560	6570	■	2532	3117948	✓
44	I	✓	-	80	3000	7180	6240	■	2532	3117940	✓
34	I	✓	-	80	4000	5880	5110	■	1972	3117931	✓
34	I	✓	-	80	3000	5590	4850	■	1972	3117923	✓
34	I	✓	-	80	4000	5880	5110	■	1972	3117947	✓
34	I	✓	-	80	3000	5590	4850	■	1972	3117939	✓
29	I	✓	-	80	4000	5040	4380	■	1692	3117930	✓
29	I	✓	-	80	3000	4790	4160	■	1692	3117922	✓
29	I	✓	-	80	4000	5040	4380	■	1692	3117946	✓
29	I	✓	-	80	3000	4790	4160	■	1692	3117938	✓
19	I	✓	-	80	4000	3360	2920	■	1132	3117929	✓
19	I	✓	-	80	3000	3190	2770	■	1132	3117921	✓
19	I	✓	-	80	4000	3360	2920	■	1132	3117945	✓
19	I	✓	-	80	3000	3190	2770	■	1132	3117937	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
44	I	✓	-	80	4000	7560	6570	■	2532	3117936	✓
44	I	✓	-	80	3000	7180	6240	■	2532	3117928	✓
44	I	✓	-	80	4000	7560	6570	■	2532	3117952	✓
44	I	✓	-	80	3000	7180	6240	■	2532	3117944	✓
34	I	✓	-	80	4000	5880	5110	■	1972	3117935	✓
34	I	✓	-	80	3000	5590	4850	■	1972	3117927	✓
34	I	✓	-	80	4000	5880	5110	■	1972	3117951	✓
34	I	✓	-	80	3000	5590	4850	■	1972	3117943	✓
29	I	✓	-	80	4000	5040	4380	■	1692	3117934	✓
29	I	✓	-	80	3000	4790	4160	■	1692	3117926	✓
29	I	✓	-	80	4000	5040	4380	■	1692	3117950	✓
29	I	✓	-	80	3000	4790	4160	■	1692	3117942	✓
19	I	✓	-	80	4000	3360	2920	■	1132	3117933	✓
19	I	✓	-	80	3000	3190	2770	■	1132	3117925	✓
19	I	✓	-	80	4000	3360	2920	■	1132	3117949	✓
19	I	✓	-	80	3000	3190	2770	■	1132	3117941	✓



EAN clinic - Iași - Romania



SL787+ PL



Scan the QR-code for the latest information


■ GR-EV1 / Anodised grey / Matt

Suspended, LED luminaire for indoor, comprising:


- Extruded aluminium housing, anodised (EV1), die-cast aluminium endcaps, polyester powder coat finish
- Opal PMMA diffuser for optimal light distribution and uniformity
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- UGR < 19 for all luminosities
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m), transparent power cable and canopy
- Continuous mounted options and many other configurations are available at www.light-performer.com



Offices Compensorio OLIVETTI - Pozzuoli - Naples - Italy



SL787+ RE



SL787+ PL OP

SL787+ PL OP



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com



SL787+ PL OP

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12	I	✓	-	80	4000	2150	1910	■	1412	3109608	✓
12	I	✓	-	80	3000	2040	1820	■	1412	3109607	✓
10	I	✓	-	80	4000	1720	1530	■	1132	3109606	✓
10	I	✓	-	80	3000	1630	1450	■	1132	3109605	✓



SL787+ RE



Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

Series of recessed LED luminaires, comprising:


- Extruded aluminium profile housing, die-cast aluminium end caps, powder-coated
- Opal PMMA diffuser for optimal light distribution and uniformity
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- UGR < 19 for all luminosities
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Includes recessed mounting kit
- Continuous mounted options and many other configurations are available at www.light-performer.com



Handelskammer innovations campus - Hamburg - Germany



SL787+ PL



SL764+ RF

SL764+ RF



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL787+ RE OP

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12	I	✓	-	80	4000	2150	1910	<input type="checkbox"/>	1412	3109612	✓
12	I	✓	-	80	3000	2040	1820	<input type="checkbox"/>	1412	3109611	✓
10	I	✓	-	80	4000	1720	1530	<input type="checkbox"/>	1132	3109610	✓
10	I	✓	-	80	3000	1630	1450	<input type="checkbox"/>	1132	3109609	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
SL787+ RE				
External Casambi module	<input checked="" type="checkbox"/>	3122585	213,00	✓
Single wireless wall switch	<input type="checkbox"/>	3122586	189,00	✓
Double wireless wall switch	<input type="checkbox"/>	3122587	194,00	✓



3122585



3122586



3122587

SL730+ SL




Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Sustainable, smart free-standing luminaire for office applications with future-proof technology

- Impact-resistant, impression-resistant powder coating
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and $3000\text{cd/m}^2 >65^\circ$)
- Future-proof thanks to simple revisions (replaceable light engine and converter)
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Direct / indirect light distribution with high indirect ratio
- Direct and indirect light can be dimmed and switched separately or together (depending on version)
- Easy charging of mobile devices via integrated USB ports
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- L, XL or table clamp: three versions offer flexible lighting solutions for single, double and multiple workstations
- Inclination of the light can be easily adjusted using a device on the base
- The U-shaped base enables flexible, flush positioning of the luminaire and fits exactly over the floor tank for barrier-free cable routing
- Smart versions available with swarm function, Human Centric Lighting, Bluetooth control, daylight control with motion detector and Tunable White
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Presence sensor with adjustable cut-off ensures targeted light activation and prevents the luminaire from being switched on unnecessarily
- Complete with flexible power cord with plug
- Special colour versions available. Consult factory



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL730+ SL L MP

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W] CLASS ENEC DIV EN 12464-1 CRI KELVIN LIGHTSOURCE LUMEN OUTPUT (lm) LUMINAIRE LUMEN OUTPUT (lm) COLOUR / FINISH PART NUMBER UKCA

Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz

117		-	✓	80	4000	19600	17680	■	3123807	✓
117		-	✓	80	3000	19000	17150	■	3123798	✓
117		-	✓	80	4000	19600	17680	■	3123804	✓
117		-	✓	80	3000	19000	17150	■	3123795	✓
117		-	✓	80	4000	19600	17680	□	3123810	✓
117		-	✓	80	3000	19000	17150	□	3123801	✓
102		-	✓	80	4000	15550	14140	■	3123783	✓
102		-	✓	80	3000	15100	13720	■	3123774	✓
102		-	✓	80	4000	15550	14140	■	3123780	✓
102		-	✓	80	3000	15100	13720	■	3123771	✓
102		-	✓	80	4000	15550	14140	□	3123786	✓
102		-	✓	80	3000	15100	13720	□	3123777	✓

Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz

117		-	✓	80	4000	19600	17680	■	3123808	✓
117		-	✓	80	3000	19000	17150	■	3123799	✓
117		-	✓	80	4000	19600	17680	■	3123805	✓
117		-	✓	80	3000	19000	17150	■	3123796	✓
117		-	✓	80	4000	19600	17680	□	3123811	✓
117		-	✓	80	3000	19000	17150	□	3123802	✓
102		-	✓	80	4000	15550	14140	■	3123784	✓
102		-	✓	80	3000	15100	13720	■	3123775	✓
102		-	✓	80	4000	15550	14140	■	3123781	✓
102		-	✓	80	3000	15100	13720	■	3123772	✓
102		-	✓	80	4000	15550	14140	□	3123787	✓
102		-	✓	80	3000	15100	13720	□	3123778	✓

TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz

114		-	✓	80	tw 2700-6500	18700	16930	■	3123815	✓
114		-	✓	80	tw 2700-6500	18700	16930	■	3123813	✓
114		-	✓	80	tw 2700-6500	18700	16930	□	3123817	✓
92		-	✓	80	tw 2700-6500	14600	13020	■	3123791	✓
92		-	✓	80	tw 2700-6500	14600	13020	■	3123789	✓
92		-	✓	80	tw 2700-6500	14600	13020	□	3123793	✓

Power LED - dimmable DALI with bluetooth control - daylight sensor and PIR detector - 220-240 V 50/60Hz

117		-	✓	80	4000	19600	17680	■	3123806	✓
117		-	✓	80	3000	19000	17150	■	3123797	✓
117		-	✓	80	4000	19600	17680	■	3123803	✓
117		-	✓	80	3000	19000	17150	■	3123794	✓
117		-	✓	80	4000	19600	17680	□	3123809	✓
117		-	✓	80	3000	19000	17150	□	3123800	✓
102		-	✓	80	4000	15550	14140	■	3123782	✓
102		-	✓	80	3000	15100	13720	■	3123773	✓
102		-	✓	80	4000	15550	14140	■	3123779	✓
102		-	✓	80	3000	15100	13720	■	3123770	✓
102		-	✓	80	4000	15550	14140	□	3123785	✓
102		-	✓	80	3000	15100	13720	□	3123776	✓

TunableWhite Power LED - HCL with bluetooth control - 220-240 V 50/60 Hz

114		-	✓	80	tw 2700-6500	18700	16930	■	3123814	✓
114		-	✓	80	tw 2700-6500	18700	16930	■	3123812	✓
114		-	✓	80	tw 2700-6500	18700	16930	□	3123816	✓
92		-	✓	80	tw 2700-6500	14600	13020	■	3123790	✓
92		-	✓	80	tw 2700-6500	14600	13020	■	3123788	✓
92		-	✓	80	tw 2700-6500	14600	13020	□	3123792	✓

SL730+ SL XL MP

IP20 - IK05 - 650 °C




LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
130	I	-	✓	80	4000	22000	20010	■	3123759	✓
130	I	-	✓	80	3000	21340	19410	■	3123750	✓
130	I	-	✓	80	4000	22000	20010	■	3123756	✓
130	I	-	✓	80	3000	21340	19410	■	3123747	✓
130	I	-	✓	80	4000	22000	20010	□	3123762	✓
130	I	-	✓	80	3000	21340	19410	□	3123753	✓
111	I	-	✓	80	4000	18000	16320	■	3123735	✓
111	I	-	✓	80	3000	17460	15830	■	3123726	✓
111	I	-	✓	80	4000	18000	16320	■	3123732	✓
111	I	-	✓	80	3000	17460	15830	■	3123723	✓
111	I	-	✓	80	4000	18000	16320	□	3123738	✓
111	I	-	✓	80	3000	17460	15830	□	3123729	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
130	I	-	✓	80	4000	22000	20010	■	3123760	✓
130	I	-	✓	80	3000	21340	19410	■	3123751	✓
130	I	-	✓	80	4000	22000	20010	■	3123757	✓
130	I	-	✓	80	3000	21340	19410	■	3123748	✓
130	I	-	✓	80	4000	22000	20010	□	3123763	✓
130	I	-	✓	80	3000	21340	19410	□	3123754	✓
111	I	-	✓	80	4000	18000	16320	■	3123736	✓
111	I	-	✓	80	3000	17460	15830	■	3123727	✓
111	I	-	✓	80	4000	18000	16320	■	3123733	✓
111	I	-	✓	80	3000	17460	15830	■	3123724	✓
111	I	-	✓	80	4000	18000	16320	□	3123739	✓
111	I	-	✓	80	3000	17460	15830	□	3123730	✓
TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
137	I	-	✓	80	tw 2700-6500	22600	20430	■	3123767	✓
137	I	-	✓	80	tw 2700-6500	22600	20430	■	3123765	✓
137	I	-	✓	80	tw 2700-6500	22600	20430	□	3123769	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	■	3123743	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	■	3123741	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	□	3123745	✓
Power LED - dimmable DALI with bluetooth control - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
130	I	-	✓	80	4000	22000	20010	■	3123758	✓
130	I	-	✓	80	3000	21340	19410	■	3123749	✓
130	I	-	✓	80	4000	22000	20010	■	3123755	✓
130	I	-	✓	80	3000	21340	19410	■	3123746	✓
130	I	-	✓	80	4000	22000	20010	□	3123761	✓
130	I	-	✓	80	3000	21340	19410	□	3123752	✓
111	I	-	✓	80	4000	18000	16320	■	3123734	✓
111	I	-	✓	80	3000	17460	15830	■	3123725	✓
111	I	-	✓	80	4000	18000	16320	■	3123731	✓
111	I	-	✓	80	3000	17460	15830	■	3123722	✓
111	I	-	✓	80	4000	18000	16320	□	3123737	✓
111	I	-	✓	80	3000	17460	15830	□	3123728	✓
TunableWhite Power LED - HCL with bluetooth control - 220-240 V 50/60 Hz										
137	I	-	✓	80	tw 2700-6500	22600	20430	■	3123766	✓
137	I	-	✓	80	tw 2700-6500	22600	20430	■	3123764	✓
137	I	-	✓	80	tw 2700-6500	22600	20430	□	3123768	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	■	3123742	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	■	3123740	✓
90	I	-	✓	80	tw 2700-6500	15050	13400	□	3123744	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL730+ SL			
Remote control "User" for versions with a sensor function		8118000647	✓
Remote control "Master" for versions with a sensor function		8118000257	✓




8118000647



8118000257

SMALL LINE SL




- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured


Scan the QR-code for the latest information

Free-standing (SL) LED luminaire for indoor, comprising:

- Pole and light plate made of extruded aluminium profile, head piece made of die cast aluminium, sheet steel base, powder-coated
- Slender plates with open spaces give the luminaire a uniquely delicate design
- Practical U-shaped base enables luminaire to be positioned flexibly and flush to a writing desk
- Gear tray with high-shine multifaceted reflectors (metallized with ultra-pure aluminium) for maximum luminaire efficiency and neutral colour rendering
- Direct / indirect light distribution
- Direct and indirect portions individually dimmable using TouchDIM® (for version with sensor: direct and indirect portions dimmable in tandem using TouchDIM®)
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- All versions are also available in black on request, without any price variation
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Sensor device available with task oriented PIR detector and daylight control
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Design by BÜRO SOMMER



SMALL LINE PL



SMALL LINE SL REFLECTOR

SMALL LINE SL REFLECTOR

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
89	I	-	✓	80	4000	14540	10750	■	3115403	✓
89	I	-	✓	80	3000	14110	10430	■	3115402	✓
89	I	-	✓	80	4000	14540	10750	□	8726741888410	✓
89	I	-	✓	80	3000	14110	10430	□	8726741888310	✓
63	I	-	✓	80	4000	10770	7940	□	8726741598410	✓
61	I	-	✓	80	3000	10450	7700	□	8726741598310	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
89	I	-	✓	80	4000	14540	10750	■	3115401	✓
89	I	-	✓	80	3000	14110	10430	■	3115400	✓
89	I	-	✓	80	4000	14540	10750	□	8726741885410	✓
89	I	-	✓	80	3000	14110	10430	□	8726741885310	✓
63	I	-	✓	80	4000	10770	7940	□	8726741595410	✓
61	I	-	✓	80	3000	10450	7700	□	8726741595310	✓



Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
SMALL LINE SL			
Remote control "User" for versions with a sensor function		8118000647	✓
Remote control "Master" for versions with a sensor function		8118000257	✓



8118000647



8118000257



© Copyright Fotodesign And

SL720SL LED




Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Free-standing (SL) LED luminaire for indoor, comprising:

- Steel sheet head, extruded aluminium profile post, steel sheet base, polyester powder coat finish
- Angle of the lamp head adjustable using a set screw
- Practical U-shaped base enables luminaire to be positioned flexibly and flush to a writing desk
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Direct / indirect light distribution
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Direct share of light dimmable; CCT 4000K
- Direct and indirect portions simultaneously dimmable (versions in 4000K with sensor)
- Complete with flexible power cord with plug
- VDU application suitable acc. to EN 12464-1
- Sensor device available with task oriented PIR detector and daylight control
- Light colour and brightness of indirect light share manually adjustable via Tunable White control system
- Light colour and brightness of indirect light share automatically adjustable via HCL (Human Centric Lighting) for wholesome and performance-enhancing management of the biorhythm
- 3000K (CCT) versions available. Consult factory
- The XL version is suitable for simultaneous illumination of two workplaces
- D+ version: The direct light section is increased, dimmable, with CCT 4000K
- The TWIN version is suitable for simultaneous illumination of two workplaces
- TWIN version: switchable/dimmable direct and indirect light section
- TWIN version: individual lighting control system for individual luminaires available. Consult factory
- Special colour versions available. Consult factory



SL720SL L LED MICROPRISMA

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
110	I	-	✓	80	4000	16000	14040	■	8720761118430	✓
110	I	-	✓	80	4000	16000	14040	□	8720761118410	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
110	I	-	✓	80	4000	16000	14040	■	8720761115430	✓
110	I	-	✓	80	4000	16000	14040	□	8720761115410	✓
TunableWhite Power LED - Human Centric Lighting control - 220-240 V 50/60 Hz										
70	I	-	✓	80	tw 2700-6200	11500	10470	■	8720761779930	✓
70	I	-	✓	80	tw 2700-6200	11500	10470	□	8720761779910	✓
TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
70	I	-	✓	80	tw 2700-6200	11500	10470	■	8720761775930	✓
70	I	-	✓	80	tw 2700-6200	11500	10470	□	8720761775910	✓
70	I	-	✓	80	tw 2700-6200	11500	10470	■	8720761778930	✓
70	I	-	✓	80	tw 2700-6200	11500	10470	□	8720761778910	✓



SL720SL L D+ LED MICROPRISMA

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
131	I	-	✓	80	4000	18200	16020	■	3101689	✓
131	I	-	✓	80	4000	18200	16020	□	3101688	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
131	I	-	✓	80	4000	18200	16020	■	3101687	✓
131	I	-	✓	80	4000	18200	16020	□	3101686	✓
TunableWhite Power LED - Human Centric Lighting control - 220-240 V 50/60 Hz										
90	I	-	✓	80	tw 2700-6200	13800	12450	■	3101695	✓
90	I	-	✓	80	tw 2700-6200	13800	12450	□	3101694	✓
TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
90	I	-	✓	80	tw 2700-6200	13800	12450	■	3101691	✓
90	I	-	✓	80	tw 2700-6200	13800	12450	□	3101690	✓
90	I	-	✓	80	tw 2700-6200	13800	12450	■	3101693	✓
90	I	-	✓	80	tw 2700-6200	13800	12450	□	3101692	✓



SL720SL L ECO LED MICROPRISMA

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
72	I	-	✓	80	4000	12700	9180	■	8720761748430	✓
72	I	-	✓	80	4000	12700	9180	□	8720761748410	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
72	I	-	✓	80	4000	12700	9180	■	8720761745430	✓
72	I	-	✓	80	4000	12700	9180	□	8720761745410	✓



SL720SL L TWIN LED MICROPRISMATIC COVER

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
106	I	-	✓	80	4000	17200	15110	■	8720762708430	✓
106	I	-	✓	80	4000	17200	15110	□	8720762708410	✓



SL720SL XL LED MICROPRISMA

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
148	I	-	✓	80	4000	22800	20060	■	8720761168430	✓
148	I	-	✓	80	4000	22800	20060	□	8720761168410	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
148	I	-	✓	80	4000	22800	20060	■	8720761165430	✓
148	I	-	✓	80	4000	22800	20060	□	8720761165410	✓
TunableWhite Power LED - Human Centric Lighting control - 220-240 V 50/60 Hz										
96	I	-	✓	80	tw 2700-6200	15700	14470	■	8720761109930	✓
96	I	-	✓	80	tw 2700-6200	15700	14470	□	8720761109910	✓
TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
96	I	-	✓	80	tw 2700-6200	15700	14470	■	8720761105930	✓
96	I	-	✓	80	tw 2700-6200	15700	14470	□	8720761105910	✓
96	I	-	✓	80	tw 2700-6200	15700	14470	■	8720761108930	✓
96	I	-	✓	80	tw 2700-6200	15700	14470	□	8720761108910	✓

SL720SL XL D+ LED MICROPRISMA


IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
195	I	-	✓	80	4000	26800	23520	■	8720761218430	✓
195	I	-	✓	80	4000	26800	23520	□	8720761218410	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
195	I	-	✓	80	4000	26800	23520	■	8720761215430	✓
195	I	-	✓	80	4000	26800	23520	□	8720761215410	✓
TunableWhite Power LED - Human Centric Lighting control - 220-240 V 50/60 Hz										
141	I	-	✓	80	tw 2700-6200	19300	17930	■	8720761179930	✓
141	I	-	✓	80	tw 2700-6200	19300	17930	□	8720761179910	✓
TunableWhite Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
141	I	-	✓	80	tw 2700-6200	19300	17930	■	8720761175930	✓
141	I	-	✓	80	tw 2700-6200	19300	17930	□	8720761175910	✓
141	I	-	✓	80	tw 2700-6200	19300	17930	■	8720761178930	✓
141	I	-	✓	80	tw 2700-6200	19300	17930	□	8720761178910	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL720SL LED			
Remote control "Master" for versions with a sensor function		8118000257	✓
Remote control "User" for versions with a sensor function		8118000647	✓
SL720 SL TWIN LED			
Remote control "Master"		8740195967	✓



8118000257




8118000647



8740195967

SL764+ SL



■ BK-RAL9005 / Black RAL9005 / Textured


Scan the QR-code for the latest information

Free-standing (SL) LED luminaire for indoor, comprising:


- Steel sheet head, extruded aluminium profile post, steel sheet base, polyester powder coat finish
- Practical U-shaped base enables luminaire to be positioned flexibly and flush to a writing desk
- Black grid for maximum luminaire efficiency, glare reduction and a high uniformity
- Direct / indirect light distribution
- VDU application suitable acc. to EN 12464-1
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Sensor device available with task oriented PIR detector and daylight control
- The sensor's detection range can be finely adjusted via the shutter
- Direct and indirect light section can be switched and dimmed separately via push-buttons
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with flexible power cord with plug
- Special colour versions available. Consult factory



SL764+ PL



SL764+ RF



SL764+
SINGLE

SL764+
DOUBLE

SL764+ SL SINGLE HEAD LV

IP30 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
71	I	-	✓	80	4000	-	9830	■	3115662	✓
71	I	-	✓	80	3000	-	9830	■	3118005	✓



SL764+ SL DOUBLE HEAD LV

IP30 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
141	I	-	✓	80	4000	-	19670	■	3115663	✓
141	I	-	✓	80	3000	-	19670	■	3118006	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL764+ SL			
Remote control "Master"		8740195967	✓



8740195967

SL713SL LED



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Free-standing (SL) LED luminaire for indoor, comprising:

- Luminaire head and tube made of aluminium profile, base made of sheet steel, powder-coated
- Angle of the lamp head adjustable using a set screw
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Direct / indirect light distribution
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Complete with flexible power cord with plug
- Sensor device available with task oriented PIR detector and daylight control
- Special colour versions available. Consult factory




Municipal Building - Castel Goffredo - Mantua - Italy



SL713AB ROUND LED



SL713PL ROUND LED



SL713SL LED

SL713SL LED MICROPRISMATIC COVER

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
94	I	-	-	80	4000	15800	11430	■	3122123	✓
94	I	-	-	80	3000	15330	11090	■	3122105	✓
94	I	-	-	80	4000	15800	11430	■	3122125	✓
94	I	-	-	80	3000	15330	11090	■	3122107	✓
94	I	-	-	80	4000	15800	11430	□	3122121	✓
94	I	-	-	80	3000	15330	11090	□	3122103	✓
72	I	-	✓	80	4000	12700	9180	■	3122122	✓
72	I	-	✓	80	3000	12320	8910	■	3122104	✓
72	I	-	✓	80	4000	12700	9180	■	3122124	✓
72	I	-	✓	80	3000	12320	8910	■	3122106	✓
72	I	-	✓	80	4000	12700	9180	□	3122120	✓
72	I	-	✓	80	3000	12320	8910	□	3122102	✓

Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
94	I	-	-	80	4000	15800	11430	■	3122135	✓
94	I	-	-	80	3000	15330	11090	■	3122117	✓
94	I	-	-	80	4000	15800	11430	■	3122137	✓
94	I	-	-	80	3000	15330	11090	■	3122119	✓
94	I	-	-	80	4000	15800	11430	□	3122133	✓
94	I	-	-	80	3000	15330	11090	□	3122115	✓
72	I	-	✓	80	4000	12700	9180	■	3122134	✓
72	I	-	✓	80	3000	12320	8910	■	3122116	✓
72	I	-	✓	80	4000	12700	9180	■	3122136	✓
72	I	-	✓	80	3000	12320	8910	■	3122118	✓
72	I	-	✓	80	4000	12700	9180	□	3122132	✓
72	I	-	✓	80	3000	12320	8910	□	3122114	✓


Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
94	I	-	-	80	4000	15800	11430	■	3122129	✓
94	I	-	-	80	3000	15330	11090	■	3122111	✓
94	I	-	-	80	4000	15800	11430	■	3122131	✓
94	I	-	-	80	3000	15330	11090	■	3122113	✓
94	I	-	-	80	4000	15800	11430	□	3122127	✓
94	I	-	-	80	3000	15330	11090	□	3122109	✓
72	I	-	✓	80	4000	12700	9180	■	3122128	✓
72	I	-	✓	80	3000	12320	8910	■	3122110	✓
72	I	-	✓	80	4000	12700	9180	■	3122130	✓
72	I	-	✓	80	3000	12320	8910	■	3122112	✓
72	I	-	✓	80	4000	12700	9180	□	3122126	✓
72	I	-	✓	80	3000	12320	8910	□	3122108	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL713SL LED			
Remote control "User" for versions with a sensor function		8118000647	✓
Remote control "Master" for versions with a sensor function		8118000257	✓




8118000647



8118000257

SL740SL LED



- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured


Scan the QR-code for the latest information

Free-standing (SL) LED luminaire for indoor, comprising:

- Steel sheet head, extruded aluminium profile post, steel sheet base, polyester powder coat finish
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Direct / indirect light distribution
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Complete with flexible power cord with plug
- Sensor device available with task oriented PIR detector and daylight control
- The XL version is suitable for simultaneous illumination of two workplaces
- Special colour versions available. Consult factory



TAZ Berlin headquarters - Berlin - Germany



max 18 kg
 SL740SL
 L LED MICROPRISMATIC COVER
 L ECO LED MICROPRISMATIC COVER

max 18 kg
 SL740SL
 XL LED MICROPRISMATIC COVER

SL740SL L LED MICROPRISMATIC COVER

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
79	I	✓	✓	80	4000	13000	11050	■	8740761938431	✓
79	I	✓	✓	80	4000	13000	11050	□	8740761938411	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
79	I	✓	✓	80	4000	13000	11050	■	8740761935431	✓
79	I	✓	✓	80	4000	13000	11050	□	8740761935411	✓

SL740SL L ECO LED MICROPRISMATIC COVER

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
62	I	✓	✓	80	4000	9000	7950	■	8740761608431	✓
62	I	✓	✓	80	4000	9000	7950	□	8740761608411	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
62	I	✓	✓	80	4000	9000	7950	■	8740761605431	✓
62	I	✓	✓	80	4000	9000	7950	□	8740761605411	✓

SL740SL XL LED MICROPRISMATIC COVER

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOR / FINISH	PART NUMBER	UKCA
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz										
119	I	✓	✓	80	4000	19000	15730	■	8740761138431	✓
119	I	✓	✓	80	4000	19000	15730	□	8740761138411	✓
Power LED - dimmable DALI with switch-key - 220-240 V 50/60 Hz										
119	I	✓	✓	80	4000	19000	15730	■	8740761135431	✓
119	I	✓	✓	80	4000	19000	15730	□	8740761135411	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL740SL LED			
Remote control "Master" for versions with a sensor function		8118000257	✓
Remote control "User" for versions with a sensor function		8118000647	✓




8118000257



8118000647

ELIA CL




WH-RAL9016 / White RAL9016 /



Scan the QR-code for the latest information

LED device made from white polycarbonate designed for ceiling or surface mounting, ideal for lighting stairways, bathrooms/rest rooms and service areas, it is quick and easy to install, and features clean, minimalist lines

- Designed in two different sizes and power versions, it features a polycarbonate opal diffusing shell, a colour temperature of 4,000 K (neutral white) and a colour rendering index of more than 80
- It is also available in the Sensor version, with movement detection up to 8m, a radius of up to 120° and duration of 30 seconds, and in the Emergency version, the luminous flux is guaranteed for 3 hours of operation at 10%
- It has been designed to withstand temperature variations from -20°C to + 45°C, and offers protection from water and dust penetration of up to level IP54 and from shocks and impacts of up to level IK08
- Light and easy to handle, ELIA CL is easy to install thanks to the steel bracket on the back of the device for wall mounting, the quick-coupling terminal on the rear of the device for the electrical wiring and the bayonet locking mechanism for attaching the body of the light



ELIA CL
S2 12W



ELIA CL
M2 25W

ELIA CL S2 12W

IP20 - IK08 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
12	II	-	-	80	4000	-	1300	<input type="checkbox"/>	GWF1310GA840	✓
12	II	-	-	80	3000	-	1200	<input type="checkbox"/>	GWF1310GA830	✓
Power LED 220-240 V 50/60 Hz + HF Sensor										
12	II	-	-	80	4000	-	1300	<input type="checkbox"/>	GWF1315GA840	✓
12	II	-	-	80	3000	-	1200	<input type="checkbox"/>	GWF1315GA830	✓




ELIA CL M2 25W

IP20 - IK08 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
25	II	-	-	80	4000	-	2600	<input type="checkbox"/>	GWF1310MA840	✓
25	II	-	-	80	3000	-	2400	<input type="checkbox"/>	GWF1310MA830	✓
Power LED 220-240 V 50/60 Hz + HF Sensor										
25	II	-	-	80	4000	-	2600	<input type="checkbox"/>	GWF1315MA840	✓
25	II	-	-	80	3000	-	2400	<input type="checkbox"/>	GWF1315MA830	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz										
25	II	-	-	80	4000	-	2600	<input type="checkbox"/>	GWF1314MA840	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz + HF Sensor										
25	II	-	-	80	4000	-	2600	<input type="checkbox"/>	GWF1316MA840	✓



FL ROUND+ 333 SM



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Wall and ceiling mounted LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
- Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 ($UGR < 19$ and $< 3000 \text{cd/m}^2 > 65^\circ$)
- Predominantly direct light distribution
- 2 power levels adjustable
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Integrated twist-in system for quick installation and easy maintenance
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through-wiring designed
- Built-in driver




Maison relais kindergarten - Consdorf - Luxembourg



FL ROUND+ 333 / 555 - 777 RE



FL ROUND+ 333 / 555 - 777 PL



max 3,5 kg

FL ROUND+ 333 SM

FL ROUND+ 333 SM MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	---------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

8 25		-	-	80	4000	1300 4000	1060 3160	■	3123884	✓
8 25		-	-	80	3000	1260 3880	1010 3000	■	3123874	✓
8 25		-	-	80	4000	1300 4000	1060 3160	□	3123888	✓
8 25		-	-	80	3000	1260 3880	1010 3000	□	3123878	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

8 25		-	-	80	4000	1300 4000	1060 3160	■	3123882	✓
8 25		-	-	80	3000	1260 3880	1010 3000	■	3123872	✓
8 25		-	-	80	4000	1300 4000	1060 3160	□	3123886	✓
8 25		-	-	80	3000	1260 3880	1010 3000	□	3123876	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

8 25		-	-	80	tw 2700-6500	1250 3900	1010 3070	■	3123891	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3070	□	3123893	✓

FL ROUND+ 333 SM OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	---------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

8 25		-	-	80	4000	1300 4000	1080 3280	■	3123885	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123875	✓
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123881	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123871	✓
8 25		-	-	80	4000	1300 4000	1080 3280	□	3123889	✓
8 25		-	-	80	3000	1260 3880	1030 3110	□	3123879	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

8 25		-	-	80	4000	1300 4000	1080 3280	■	3123883	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123873	✓
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123880	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123870	✓
8 25		-	-	80	4000	1300 4000	1080 3280	□	3123887	✓
8 25		-	-	80	3000	1260 3880	1030 3110	□	3123877	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz


8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	■	3123892	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	■	3123890	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	□	3123894	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 333 SM				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585



3122586




3122587



Maison Relais et Ecole Fondamentale - Consdorf - Luxemburg

FL ROUND+ 555 SM



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Wall and ceiling mounted LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
- Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Integrated twist-in system for quick installation and easy maintenance
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <math><3000\text{cd}/\text{m}^2 >65^\circ</math>)
- In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
- Predominantly direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through-wiring designed
- Built-in driver




Sparkasse EHM offices - Kues - Germany



FL ROUND+ 333 / 555 - 777 RE



FL ROUND+ 333 / 555 - 777 PL



max 5,4 kg

FL ROUND+ 555 SM

FL ROUND+ 555 SM MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6320	■	3124036	✓
49	I	-	-	80	3000	7760	6000	■	3124026	✓
49	I	-	-	80	4000	8000	6320	□	3124040	✓
49	I	-	-	80	3000	7760	6000	□	3124030	✓
21	I	-	✓	80	4000	3800	3030	■	3124011	✓
21	I	-	✓	80	3000	3690	2880	■	3124001	✓
21	I	-	✓	80	4000	3800	3030	□	3124015	✓
21	I	-	✓	80	3000	3690	2880	□	3124005	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6320	■	3124034	✓
49	I	-	-	80	3000	7760	6000	■	3124024	✓
49	I	-	-	80	4000	8000	6320	□	3124038	✓
49	I	-	-	80	3000	7760	6000	□	3124028	✓
21	I	-	✓	80	4000	3800	3030	■	3124009	✓
21	I	-	✓	80	3000	3690	2880	■	3123999	✓
21	I	-	✓	80	4000	3800	3030	□	3124013	✓
21	I	-	✓	80	3000	3690	2880	□	3124003	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
49	I	-	-	80	tw 2700-6500	7600	5980	■	3124043	✓
49	I	-	-	80	tw 2700-6500	7600	5980	□	3124045	✓
21	I	-	✓	80	tw 2700-6500	3600	2820	■	3124018	✓
21	I	-	✓	80	tw 2700-6500	3600	2820	□	3124020	✓

FL ROUND+ 555 SM OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6500	■	3124037	✓
49	I	-	-	80	3000	7760	6170	■	3124027	✓
49	I	-	-	80	4000	8000	6500	■	3124033	✓
49	I	-	-	80	3000	7760	6170	■	3124023	✓
49	I	-	-	80	4000	8000	6500	□	3124041	✓
49	I	-	-	80	3000	7760	6170	□	3124031	✓
21	I	-	-	80	4000	3800	3110	■	3124012	✓
21	I	-	-	80	3000	3690	2950	■	3124002	✓
21	I	-	-	80	4000	3800	3110	■	3124008	✓
21	I	-	-	80	3000	3690	2950	■	3123998	✓
21	I	-	-	80	4000	3800	3110	□	3124016	✓
21	I	-	-	80	3000	3690	2950	□	3124006	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6500	■	3124035	✓
49	I	-	-	80	3000	7760	6170	■	3124025	✓
49	I	-	-	80	4000	8000	6500	■	3124032	✓
49	I	-	-	80	3000	7760	6170	■	3124022	✓
49	I	-	-	80	4000	8000	6500	□	3124039	✓
49	I	-	-	80	3000	7760	6170	□	3124029	✓
21	I	-	-	80	4000	3800	3110	■	3124010	✓
21	I	-	-	80	3000	3690	2950	■	3124000	✓
21	I	-	-	80	4000	3800	3110	■	3124007	✓
21	I	-	-	80	3000	3690	2950	■	3123997	✓
21	I	-	-	80	4000	3800	3110	□	3124014	✓
21	I	-	-	80	3000	3690	2950	□	3124004	✓


TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
49	I	-	-	80	tw 2700-6500	7600	6280	■	3124044	✓
49	I	-	-	80	tw 2700-6500	7600	6280	■	3124042	✓
49	I	-	-	80	tw 2700-6500	7600	6280	□	3124046	✓
21	I	-	-	80	tw 2700-6500	3600	2960	■	3124019	✓
21	I	-	-	80	tw 2700-6500	3600	2960	■	3124017	✓
21	I	-	-	80	tw 2700-6500	3600	2960	□	3124021	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 555 SM				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓




3122585



3122586




3122587



Body shop K. Van Oudenaren - Zaandam - Netherlands

FL ROUND+ 777 SM



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Wall and ceiling mounted LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and $\langle 3000\text{cd}/\text{m}^2 \rangle >65^\circ$)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Predominantly direct light distribution
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Built-in driver




Offices Compensorio OLIVETTI - Pozzuoli - Naples - Italy



FL ROUND+ 333 / 555 - 777 RE



FL ROUND+ 333 / 555 - 777 PL



FL ROUND 777 SM

FL ROUND+ 777 SM MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9390	■	3124186	✓
67	I	-	-	80	3000	11640	8920	■	3124176	✓
67	I	-	-	80	4000	12000	9390	□	3124190	✓
67	I	-	-	80	3000	11640	8920	□	3124180	✓
38	I	-	✓	80	4000	7200	5620	■	3124161	✓
38	I	-	✓	80	3000	6980	5340	■	3124151	✓
38	I	-	✓	80	4000	7200	5620	□	3124165	✓
38	I	-	✓	80	3000	6980	5340	□	3124155	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

67	I	-	-	80	4000	12000	9390	■	3124184	✓
67	I	-	-	80	3000	11640	8920	■	3124174	✓
67	I	-	-	80	4000	12000	9390	□	3124188	✓
67	I	-	-	80	3000	11640	8920	□	3124178	✓
38	I	-	✓	80	4000	7200	5620	■	3124159	✓
38	I	-	✓	80	3000	6980	5340	■	3124149	✓
38	I	-	✓	80	4000	7200	5620	□	3124163	✓
38	I	-	✓	80	3000	6980	5340	□	3124153	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

67	I	-	-	80	tw 2700-6500	11500	8820	■	3124193	✓
67	I	-	-	80	tw 2700-6500	11500	8820	□	3124195	✓
38	I	-	✓	80	tw 2700-6500	6900	5280	■	3124168	✓
38	I	-	✓	80	tw 2700-6500	6900	5280	□	3124170	✓

FL ROUND+ 777 SM OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9040	■	3124187	✓
67	I	-	-	80	3000	11640	8590	■	3124177	✓
67	I	-	-	80	4000	12000	9040	■	3124183	✓
67	I	-	-	80	3000	11640	8590	■	3124173	✓
67	I	-	-	80	4000	12000	9040	□	3124191	✓
67	I	-	-	80	3000	11640	8590	□	3124181	✓
38	I	-	-	80	4000	7200	5450	■	3124162	✓
38	I	-	-	80	3000	6980	5180	■	3124152	✓
38	I	-	-	80	4000	7200	5450	■	3124158	✓
38	I	-	-	80	3000	6980	5180	■	3124148	✓
38	I	-	-	80	4000	7200	5450	□	3124166	✓
38	I	-	-	80	3000	6980	5180	□	3124156	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

67	I	-	-	80	4000	12000	9040	■	3124185	✓
67	I	-	-	80	3000	11640	8590	■	3124175	✓
67	I	-	-	80	4000	12000	9040	■	3124182	✓
67	I	-	-	80	3000	11640	8590	■	3124172	✓
67	I	-	-	80	4000	12000	9040	□	3124189	✓
67	I	-	-	80	3000	11640	8590	□	3124179	✓
38	I	-	-	80	4000	7200	5450	■	3124160	✓
38	I	-	-	80	3000	6980	5180	■	3124150	✓
38	I	-	-	80	4000	7200	5450	■	3124157	✓
38	I	-	-	80	3000	6980	5180	■	3124147	✓
38	I	-	-	80	4000	7200	5450	□	3124164	✓
38	I	-	-	80	3000	6980	5180	□	3124154	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz


67	I	-	-	80	tw 2700-6500	11500	9080	■	3124194	✓
67	I	-	-	80	tw 2700-6500	11500	9080	■	3124192	✓
67	I	-	-	80	tw 2700-6500	11500	9080	□	3124196	✓
38	I	-	-	80	tw 2700-6500	6900	5440	■	3124169	✓
38	I	-	-	80	tw 2700-6500	6900	5440	■	3124167	✓
38	I	-	-	80	tw 2700-6500	6900	5440	□	3124171	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 777 SM				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585



3122586



3122587



Public Utilities Company - Lehrte - Germany

FL SQUARE SM



WH-RAL9016 / White RAL9016 / Textured

Scan the QR-code for the latest information

LED surface-mount luminaire for indoor, comprising:


- Extruded aluminium housing profile, powder-coated
- The luminaire is available with different light engines:
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the diffuser
 - Glare prevention in accordance with DIN EN 12464-1 (for designs with micro prism)
 - Predominantly direct light distribution
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver




Centre for integrative psychiatry - Kiel - Germany





FL SQUARE PL



 max 3,1 kg

FL SQUARE
300 SM OP



 max 5,7 kg

FL SQUARE
600 SM

FL SQUARE 300 SM OP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2430	<input type="checkbox"/>	8300691233400	✓
19	I	-	-	80	3000	2900	2350	<input type="checkbox"/>	8300691233300	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2430	<input type="checkbox"/>	8300691236400	✓
19	I	-	-	80	3000	2900	2350	<input type="checkbox"/>	8300691236300	✓



FL SQUARE 600 SM MP

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
40	I	-	✓	80	4000	5950	4950	<input type="checkbox"/>	8600661403400	✓
40	I	-	✓	80	3000	5660	4840	<input type="checkbox"/>	8600661403300	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
40	I	-	✓	80	4000	5950	4950	<input type="checkbox"/>	8600661406400	✓
40	I	-	✓	80	3000	5660	4840	<input type="checkbox"/>	8600661406300	✓



FL SQUARE 600 SM OP


IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
41	I	-	-	80	4000	6310	5000	<input type="checkbox"/>	8600691403400	✓
40	I	-	-	80	3000	5720	4780	<input type="checkbox"/>	8600691403300	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
41	I	-	-	80	4000	6310	5000	<input type="checkbox"/>	8600691406400	✓
40	I	-	-	80	3000	5720	4780	<input type="checkbox"/>	8600691406300	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FL SQUARE SM			
Casambi module for installation		3122584	✓
Single wireless wall switch	<input type="checkbox"/>	3122586	✓
Double wireless wall switch	<input type="checkbox"/>	3122587	✓




3122586



3122587

FLEXILED SM




Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 / Textured

Indoor surface mounted luminaire, comprising:


- Housing made of form-stable 1.0 mm sheet steel
 - Impact-resistant, impression-resistant powder coating
- The luminaire is available with different light engines:
- Black reflector ensures maximum efficiency and high visual comfort
 - Wallwasher with asymmetrical light distribution ensures optimum panel illumination
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Barrier-free light
 - Glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <math><3000\text{cd}/\text{m}^2 >65^\circ</math>)
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - UGR <19 for all luminosities
 - Reliable and low-maintenance 50,000h L80B10
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - 2 power levels adjustable
 - Through-wiring designed
 - Special colour versions available. Consult factory




FLEXILED SM
LV



FLEXILED SM
LV



FLEXILED SM



FLEXILED SM



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

FLEXILED SM LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21	I	-	✓	80	4000	3750	3230	□	1500	3122037	✓
32	I	-	✓	80	4000	5500	4780	□	1500	3122037	✓
17	I	-	✓	80	4000	3000	2590	□	1200	3122036	✓
26	I	-	✓	80	4000	4400	3830	□	1200	3122036	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
21	I	-	✓	80	4000	3750	3230	□	1500	3122039	✓
32	I	-	✓	80	4000	5500	4780	□	1500	3122039	✓
17	I	-	✓	80	4000	3000	2590	□	1200	3122038	✓
26	I	-	✓	80	4000	4400	3830	□	1200	3122038	✓



FLEXILED SM LV ASYM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
42	I	-	-	80	4000	6150	5260	□	1500	3122045	✓
34	I	-	-	80	4000	4900	4190	□	1200	3122044	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
42	I	-	-	80	4000	6150	5260	□	1500	3122047	✓
34	I	-	-	80	4000	4900	4190	□	1200	3122046	✓



FLEXILED SM MICROPRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2060	□	1500	3122553	✓
24	I	-	-	80	4000	4200	3390	□	1500	3122553	✓
12	I	-	-	80	4000	2130	1670	□	1200	3122552	✓
20	I	-	-	80	4000	3360	2630	□	1200	3122552	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2060	□	1500	3122555	✓
24	I	-	-	80	4000	4200	3390	□	1500	3122555	✓
12	I	-	-	80	4000	2130	1670	□	1200	3122554	✓
20	I	-	-	80	4000	3360	2630	□	1200	3122554	✓



FLEXILED SM OPAL


IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2170	□	1500	3122561	✓
24	I	-	-	80	4000	4200	3560	□	1500	3122561	✓
12	I	-	-	80	4000	2130	1770	□	1200	3122560	✓
20	I	-	-	80	4000	3360	2790	□	1200	3122560	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2170	□	1500	3122563	✓
24	I	-	-	80	4000	4200	3560	□	1500	3122563	✓
12	I	-	-	80	4000	2130	1770	□	1200	3122562	✓
20	I	-	-	80	4000	3360	2790	□	1200	3122562	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FLEXILED SM			
Mounting template	■	3122577	✓
Casambi module for installation		3122584	✓
Single wireless wall switch	■	3122586	✓
Double wireless wall switch	■	3122587	✓
Suspension set	□	3123706	✓
Suspension set - DALI	□	3123707	✓
Suspension set - MICROPRISM / OPAL	□	3124221	✓
Suspension set - MICROPRISM / OPAL - DALI	□	3124222	✓



3122586




3122587



3123706
3123707
3124221
3124222

SL629 AB



Flughafen Office - Hannover - Germany




Scan the QR-code for the latest information


- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

LED surface-mount luminaire for indoor, comprising:

- Steel sheet housing, die-cast aluminium end caps, polyester powder coat finish
- Prismatic diffuser for efficient light distribution, glare reduction and a high level of uniformity
- Direct light distribution
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Light engine can be replaced by means of a slide-in mechanism
- UGR < 19
- VDU application suitable acc. to EN 12464-1
- The dedicated accessory can be used to create continuous line power supply
- Motion sensor available with task-oriented PIR detector and daylight control. Consult factory
- Special colour versions available. Consult factory



SL629 AB PRISM



SL629 AB PRISM

SL629 AB PRISM

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	-------------	------

Power LED 220-240 V 50/60 Hz


69	I	✓	-	80	4000	12000	8070	■	1544	8629661613430	✓
69	I	✓	-	80	3000	11640	7830	■	1544	8629661613330	✓
69	I	-	-	80	4000	12000	8070	■	1544	3119894	✓
69	I	✓	-	80	4000	12000	8070	□	1544	8629661613410	✓
69	I	✓	-	80	3000	11640	7830	□	1544	8629661613310	✓
54	I	-	-	90	4000	8350	5830	□	1244	3112478	✓
54	I	-	-	90	3000	8100	5570	□	1244	3112438	✓
54	I	✓	-	80	4000	8900	5970	■	1244	8629661453430	✓
54	I	✓	-	80	3000	8630	5790	■	1244	8629661453330	✓
54	I	-	-	80	4000	8900	5970	■	1244	3119896	✓
54	I	✓	-	80	4000	8900	5970	□	1244	8629661453410	✓
54	I	✓	-	80	3000	8630	5790	□	1244	8629661453310	✓
31	I	-	✓	90	4000	5700	3910	□	1544	3112436	✓
31	I	-	✓	90	3000	5530	3730	□	1544	3112434	✓
31	I	✓	✓	80	4000	6000	4000	■	1544	8629661403430	✓
31	I	✓	✓	80	3000	5820	3880	■	1544	8629661403330	✓
31	I	-	✓	80	4000	6000	4000	■	1544	3119893	✓
31	I	✓	✓	80	4000	6000	4000	□	1544	8629661403410	✓
31	I	✓	✓	80	3000	5820	3880	□	1544	8629661403310	✓
26	I	-	✓	90	4000	4500	3040	□	1244	3112477	✓
26	I	-	✓	90	3000	4370	2900	□	1244	3112433	✓
26	I	✓	✓	80	4000	4700	3220	■	1244	8629661283430	✓
26	I	✓	✓	80	3000	4560	3120	■	1244	8629661283330	✓
26	I	-	✓	80	4000	4700	3220	■	1244	3119895	✓
26	I	✓	✓	80	4000	4700	3220	□	1244	8629661283410	✓
26	I	✓	✓	80	3000	4560	3120	□	1244	8629661283310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz


69	I	✓	-	80	4000	12000	8070	■	1544	8629661616430	✓
69	I	✓	-	80	3000	11640	7830	■	1544	8629661616330	✓
69	I	✓	-	80	4000	12000	8070	□	1544	8629661616410	✓
69	I	✓	-	80	3000	11640	7830	□	1544	8629661616310	✓
54	I	-	-	90	4000	8350	5830	□	1244	3112479	✓
54	I	-	-	90	3000	8100	5570	□	1244	3112439	✓
54	I	-	-	80	4000	8900	5970	■	1244	8629661456430	✓
54	I	-	-	80	3000	8630	5790	■	1244	8629661456330	✓
54	I	-	-	80	4000	8900	5970	□	1244	8629661456410	✓
54	I	-	-	80	3000	8630	5790	□	1244	8629661456310	✓
31	I	-	✓	90	4000	5700	3910	□	1544	3112437	✓
31	I	-	✓	90	3000	5530	3730	□	1544	3112435	✓
31	I	-	✓	80	4000	6000	4000	■	1544	8629661406430	✓
31	I	-	✓	80	3000	5820	3880	■	1544	8629661406330	✓
31	I	-	✓	80	4000	6000	4000	□	1544	8629661406410	✓
31	I	-	✓	80	3000	5820	3880	□	1544	8629661406310	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
SL629 AB			
Assembly kit continuous line		3117260	✓
Casambi module for installation		3122584	✓
Single wireless wall switch	□	3122586	✓
Double wireless wall switch	□	3122587	✓



3117260



3122586




3122587

SL630 AB



Raabe Nursery School - Saarbrücken - Germany




Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured


LED surface-mount luminaire for indoor, comprising:

- Steel sheet housing, die-cast aluminium end caps, polyester powder coat finish
- Prismatic diffuser for efficient light distribution, glare reduction and a high level of uniformity
- Renovation (retrofit) version with luminaire width of >370 mm to cover the existing holes
- Direct light distribution
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Light engine can be replaced by means of a slide-in mechanism
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Motion sensor available with task-oriented PIR detector and daylight control. Consult factory
- Special colour versions available. Consult factory



SL630 AB PRISM

9,5 kg



SL630 AB PRISM

10 kg

SL630 AB PRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	✓	✓	80	4000	9400	6270	■	1574	8630661613430	✓
49	I	✓	✓	80	3000	9120	6080	■	1574	8630661613330	✓
49	I	✓	✓	80	4000	9400	6270	□	1574	8630661613410	✓
49	I	✓	✓	80	3000	9120	6080	□	1574	8630661613310	✓
40	I	✓	✓	80	4000	7200	4860	■	1274	8630661453430	✓
40	I	✓	✓	80	3000	6980	4710	■	1274	8630661453330	✓
40	I	✓	✓	80	4000	7200	4860	□	1274	8630661453410	✓
40	I	✓	✓	80	3000	6980	4710	□	1274	8630661453310	✓


Power LED - dimmable DALI 220-240 V 50/60 Hz

49	I	-	✓	80	4000	9400	6270	■	1574	8630661616430	✓
49	I	-	✓	80	3000	9120	6080	■	1574	8630661616330	✓
49	I	-	✓	80	4000	9400	6270	□	1574	8630661616410	✓
49	I	-	✓	80	3000	9120	6080	□	1574	8630661616310	✓
40	I	-	✓	80	4000	7200	4860	■	1274	8630661456430	✓
40	I	-	✓	80	3000	6980	4710	■	1274	8630661456330	✓
40	I	-	✓	80	4000	7200	4860	□	1274	8630661456410	✓
40	I	-	✓	80	3000	6980	4710	□	1274	8630661456310	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL630 AB			
Casambi module for installation		3122584	✓
Single wireless wall switch	■	3122586	✓
Double wireless wall switch	■	3122587	✓




3122586



3122587

SL713AB ROUND LED



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Surface-mounted round LED luminaire for indoor, comprising:


- Aluminium profile lightframe, steel sheet canopy, painted
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Predominantly direct light distribution
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- VDU application suitable acc. to EN 12464-1
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Built-in driver
- Through-wiring designed
- Special colour versions available. Consult factory




Public Utilities Company - Lehrte - Germany




SL713PL ROUND LED



SL713AB ROUND LED
MICROPRISMATIC
S



SL713AB ROUND LED
MICROPRISMATIC
M



SL713AB ROUND LED
MICROPRISMATIC
L

SL713AB ROUND LED MICROPRISMATIC S

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8		-	-	80	4000	1500	1140	■	3122355	✓
18.5		-	-	80	3000	3200	2440	■	3122349	✓
8		-	-	80	3000	1460	1110	■	3122349	✓
18.5		-	-	80	4000	3100	2370	■	3122349	✓
8		-	-	80	4000	1500	1140	■	3122353	✓
18.5		-	-	80	3000	3200	2440	■	3122353	✓
8		-	-	80	3000	1460	1110	■	3122347	✓
18.5		-	-	80	4000	3100	2370	■	3122347	✓
8		-	-	80	4000	1500	1140	□	3122357	✓
18.5		-	-	80	3000	3200	2440	□	3122357	✓
8		-	-	80	3000	1460	1110	□	3122351	✓
18.5		-	-	80	4000	3100	2370	□	3122351	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8		-	-	80	4000	1500	1140	■	3122354	✓
18.5		-	-	80	3000	3200	2440	■	3122354	✓
8		-	-	80	3000	1460	1110	■	3122348	✓
18.5		-	-	80	4000	3100	2370	■	3122348	✓
8		-	-	80	4000	1500	1140	■	3122352	✓
18.5		-	-	80	3000	3200	2440	■	3122352	✓
8		-	-	80	3000	1460	1110	■	3122346	✓
18.5		-	-	80	4000	3100	2370	■	3122346	✓
8		-	-	80	4000	1500	1140	□	3122356	✓
18.5		-	-	80	3000	3200	2440	□	3122356	✓
8		-	-	80	3000	1460	1110	□	3122350	✓
18.5		-	-	80	4000	3100	2370	□	3122350	✓

SL713AB ROUND LED MICROPRISMATIC M

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49		-	-	80	4000	8000	6480	■	8713661513434	✓
49		-	-	80	3000	7760	6280	■	8713661513334	✓
49		-	-	80	4000	8000	6480	■	3122399	✓
49		-	-	80	3000	7760	6280	■	3122397	✓
49		-	-	80	4000	8000	6480	□	8713661513414	✓
49		-	-	80	3000	7760	6280	□	8713661513314	✓
26		-	✓	80	4000	4500	3680	■	8713661343434	✓
26		-	✓	80	3000	4370	3570	■	8713661343334	✓
26		-	✓	80	4000	4500	3680	■	3122395	✓
26		-	✓	80	3000	4370	3570	■	3122393	✓
26		-	✓	80	4000	4500	3680	□	8713661343414	✓
26		-	✓	80	3000	4370	3570	□	8713661343314	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
49		-	-	80	4000	8000	6480	■	8713661516434	✓
49		-	-	80	3000	7760	6280	■	8713661516334	✓
49		-	-	80	4000	8000	6480	■	3122398	✓
49		-	-	80	3000	7760	6280	■	3122396	✓
49		-	-	80	4000	8000	6480	□	8713661516414	✓
49		-	-	80	3000	7760	6280	□	8713661516314	✓
26		-	✓	80	4000	4500	3680	■	8713661346434	✓
26		-	✓	80	3000	4370	3570	■	8713661346334	✓
26		-	✓	80	4000	4500	3680	■	3122394	✓
26		-	✓	80	3000	4370	3570	■	3122392	✓
26		-	✓	80	4000	4500	3680	□	8713661346414	✓
26		-	✓	80	3000	4370	3570	□	8713661346314	✓

SL713AB ROUND LED MICROPRISMATIC L

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz


70	I	-	-	80	4000	11000	8800	■	8713661763434	✓
70	I	-	-	80	3000	10670	8530	■	8713661763334	✓
70	I	-	-	80	4000	11000	8800	■	3122316	✓
70	I	-	-	80	3000	10670	8530	■	3122314	✓
70	I	-	-	80	4000	11000	8800	□	8713661763414	✓
70	I	-	-	80	3000	10670	8530	□	8713661763314	✓
46	I	-	-	80	4000	8000	6110	■	8713661483434	✓
46	I	-	✓	80	3000	7760	5930	■	8713661483334	✓
46	I	-	-	80	4000	8000	6110	■	3122312	✓
46	I	-	✓	80	3000	7760	5930	■	3122310	✓
46	I	-	-	80	4000	8000	6110	□	8713661483414	✓
46	I	-	✓	80	3000	7760	5930	□	8713661483314	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz


70	I	-	-	80	4000	11000	8800	■	8713661766434	✓
70	I	-	-	80	3000	10670	8530	■	8713661766334	✓
70	I	-	-	80	4000	11000	8800	■	3122315	✓
70	I	-	-	80	3000	10670	8530	■	3122313	✓
70	I	-	-	80	4000	11000	8800	□	8713661766414	✓
70	I	-	-	80	3000	10670	8530	□	8713661766314	✓
46	I	-	-	80	4000	8000	6110	■	8713661486434	✓
46	I	-	✓	80	3000	7760	5930	■	8713661486334	✓
46	I	-	-	80	4000	8000	6110	■	3122311	✓
46	I	-	✓	80	3000	7760	5930	■	3122309	✓
46	I	-	-	80	4000	8000	6110	□	8713661486414	✓
46	I	-	✓	80	3000	7760	5930	□	8713661486314	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL713AB ROUND LED			
Casambi module for installation		3122584	✓
Single wireless wall switch	■	3122586	✓
Double wireless wall switch	■	3122587	✓



3122586



3122587



De Romein Group - Veendam - Netherlands

SL720+ SM






Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured

LED surface-mount luminaire for indoor, comprising:

- Extruded aluminium housing profile, powder-coated
- Fitted frame made of sheet steel, powder-coated
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- VDU application suitable acc. to EN 12464-1
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician)
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Predominantly direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters
- In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
- In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8)
- Sensor device available with task oriented PIR detector and daylight control
- Complete with steel suspension cable (1.5 m), transparent power cord and canopy
- Through-wiring designed
- Special colour versions available. Consult factory



SL720+ SM MP S/B

SL720+ SM MP S/B

SL720+ SM MP S/B

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
33	I	-	✓	80	4000	5620	4110	■	1538	3115916	✓
33	I	-	✓	80	3000	5330	4130	■	1538	3115915	✓
33	I	-	✓	80	4000	5620	4110	□	1538	3115912	✓
33	I	-	✓	80	3000	5330	4130	□	1538	3115911	✓
26	I	-	✓	80	4000	4340	3200	■	1238	3115914	✓
26	I	-	✓	80	3000	4120	3195	■	1238	3115913	✓
26	I	-	✓	80	4000	4340	3200	□	1238	3115910	✓
26	I	-	✓	80	3000	4120	3195	□	1238	3115909	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
33	I	-	✓	80	4000	5620	4110	■	1538	3114881	✓
33	I	-	✓	80	3000	5330	4130	■	1538	3114880	✓
33	I	-	✓	80	4000	5620	4110	□	1538	3114877	✓
33	I	-	✓	80	3000	5330	4130	□	1538	3114876	✓
26	I	-	✓	80	4000	4340	3200	■	1238	3114879	✓
26	I	-	✓	80	3000	4120	3195	■	1238	3114878	✓
26	I	-	✓	80	4000	4340	3200	□	1238	3114875	✓
26	I	-	✓	80	3000	4120	3195	□	1238	3114874	✓
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz											
33	I	-	✓	80	4000	5620	4110	■	1538	3115908	✓
33	I	-	✓	80	3000	5330	4130	■	1538	3115907	✓
33	I	-	✓	80	4000	5620	4110	□	1538	3115904	✓
33	I	-	✓	80	3000	5330	4130	□	1538	3115903	✓
26	I	-	✓	80	4000	4340	3200	■	1238	3115906	✓
26	I	-	✓	80	3000	4120	3195	■	1238	3115905	✓
26	I	-	✓	80	4000	4340	3200	□	1238	3115902	✓
26	I	-	✓	80	3000	4120	3195	□	1238	3115901	✓
Power LED - dimmable DALI with bluetooth control - 220-240 V 50/60 Hz											
33	I	-	✓	80	4000	5620	4110	■	1538	3114889	✓
33	I	-	✓	80	3000	5330	4130	■	1538	3114888	✓
33	I	-	✓	80	4000	5620	4110	□	1538	3114885	✓
33	I	-	✓	80	3000	5330	4130	□	1538	3114884	✓
26	I	-	✓	80	4000	4340	3200	■	1238	3114887	✓
26	I	-	✓	80	3000	4120	3195	■	1238	3114886	✓
26	I	-	✓	80	4000	4340	3200	□	1238	3114883	✓
26	I	-	✓	80	3000	4120	3195	□	1238	3114882	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz											
33	I	-	✓	80	tw 2700-6500	5400	3690	■	1538	3114893	✓
33	I	-	✓	80	tw 2700-6500	5400	3690	□	1538	3114891	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	■	1238	3114892	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	□	1238	3114890	✓
TunableWhite Power LED - HCL with bluetooth control - 220-240 V 50/60 Hz											
33	I	-	✓	80	tw 2700-6500	5400	3690	■	1538	3114897	✓
33	I	-	✓	80	tw 2700-6500	5400	3690	□	1538	3114895	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	■	1238	3114896	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	□	1238	3114894	✓
TunableWhite Power LED - dimmable DALI DT8 with daylight sensor and PIR detector - 220-240 V 50/60 Hz											
33	I	-	✓	80	tw 2700-6500	5400	3690	■	1538	3115920	✓
33	I	-	✓	80	tw 2700-6500	5400	3690	□	1538	3115918	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	■	1238	3115919	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	□	1238	3115917	✓
TunableWhite Power LED - dimmable DALI DT8 with bluetooth control - 220-240 V 50/60 Hz											
33	I	-	✓	80	tw 2700-6500	5400	3690	■	1538	3114901	✓
33	I	-	✓	80	tw 2700-6500	5400	3690	□	1538	3114899	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	■	1238	3114900	✓
26	I	-	✓	80	tw 2700-6500	4236	2920	□	1238	3114898	✓

TunableWhite Power LED - DALI DT8 with bluetooth control - daylight sensor + PIR detector - 220-240V 50/60Hz


33		-	✓	80	tw	2700-6500	5400	3690	■	1538	3115928	✓
33		-	✓	80	tw	2700-6500	5400	3690	□	1538	3115926	✓
26		-	✓	80	tw	2700-6500	4236	2920	■	1238	3115927	✓
26		-	✓	80	tw	2700-6500	4236	2920	□	1238	3115925	✓

TunableWhite Power LED - HCL with daylight sensor and PIR-detector - 220-240 V 50/60 Hz


33		-	✓	80	tw	2700-6500	5400	3690	■	1538	3115924	✓
33		-	✓	80	tw	2700-6500	5400	3690	□	1538	3115922	✓
26		-	✓	80	tw	2700-6500	4236	2920	■	1238	3115923	✓
26		-	✓	80	tw	2700-6500	4236	2920	□	1238	3115921	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL720+ SM			
Casambi module for installation		3122584	✓
Single wireless wall switch	■	3122586	✓
Double wireless wall switch	■	3122587	✓



3122586



3122587



Haus der Höfe - Bonn - Germany

RONDA+ LED



Scan the QR-code for the latest information


□ WH-87 / White / Textured

Ceiling mounted LED luminaire with satin louvre, suitable for lighting offices, conference rooms and commercial complexes, comprising:

- Polyester powder coat finish steel sheet housing
- Satin aluminium louvre attached by four concealed spring fixings
- Louvre remains attached to the housing during lamp replacement
- Built-in driver



Municipal Building - Castel Goffredo - Mantua - Italy



RONDA+ LED 1X

IP20 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	-	-	80	4000	-	3100	<input type="checkbox"/>	1498	3100085	✓
19	I	-	-	80	4000	-	1900	<input type="checkbox"/>	1198	3100084	✓




RONDA+ LED 2X

IP20 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
60	I	-	-	80	4000	-	6200	<input type="checkbox"/>	1498	3100087	✓
38	I	-	-	80	4000	-	3800	<input type="checkbox"/>	1198	3100086	✓



WL RECT



Scan the QR-code for the latest information


WH-87 / White / Textured


LED surface-mount luminaire for indoor, comprising:

- Technopolymer housing
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Power levels can be set via a switch
- Colour tolerance according to MacAdam ≤ 3 SDCM
- IP54 for horizontal ceiling mounting - IP20 for wall mounting
- Through wiring
- Built-in driver



WL ROUND




 max 0,9 kg

WL
900 OPAL

 max 1,5 kg

WL
1200 OPAL

 max 2,8 kg

WL
1500 OPAL

WL900 OPAL

IP20 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24 31	II	-	80	3000/4000	S/B	2 x 62°/58°	3800 4700	3050 3780	<input type="checkbox"/>	3118547	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

24 31	II	-	80	3000/4000	S/B	2 x 62°/58°	3800 4700	3050 3780	<input type="checkbox"/>	3118559	✓
----------	----	---	----	-----------	-----	-------------	--------------	--------------	--------------------------	----------------	---

WL1200 OPAL

IP20 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28 37	II	-	80	3000/4000	S/B	2 x 62°/58°	4700 5850	3770 4680	<input type="checkbox"/>	3118548	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

28 37	II	-	80	3000/4000	S/B	2 x 62°/58°	4700 5850	3770 4680	<input type="checkbox"/>	3118560	✓
----------	----	---	----	-----------	-----	-------------	--------------	--------------	--------------------------	----------------	---

WL1500 OPAL

IP20 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27.3 35.8 48	II	-	80	3000/4000	S/B	2 x 62°/58°	4500 5650 7200	3610 4510 5760	<input type="checkbox"/>	3118549	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

27 36 48	II	-	80	3000/4000	S/B	2 x 62°/58°	4500 5650 7200	3610 4510 5760	<input type="checkbox"/>	3118561	✓
----------------	----	---	----	-----------	-----	-------------	----------------------	----------------------	--------------------------	----------------	---

WL ROUND



Scan the QR-code for the latest information


■ GR-94 / Metallic grey / Textured

Wall and ceiling mounted LED luminaire for indoor, comprising:

- Technopolymer housing (WL220/WL270)
- Die-cast aluminium housing, powder-coated (WL400)
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Power levels can be set via a switch
- Luminaire efficiency (in lower power ratings) up to 127 lm/W
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through wiring
- Versions with motion detector (HF) available
- Built-in driver




WL SQUARE




max 0,9 kg

WL
220 OPAL



max 1,5 kg

WL
270 OPAL



max 2,8 kg

WL
400 OPAL

WL220 OPAL

IP54 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	II	-	80	3000/4000	S/B	-	1350	1150	■	3105557	✓
14							1900	1660			



WL270 OPAL

IP54 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	II	-	80	3000/4000	S/B	-	1600	1280	■	3105559	✓
17.7							2700	2170			
23							3300	2670			
Power LED 220-240 V 50/60 Hz + HF Sensor											
10	II	-	80	3000/4000	S/B	-	1600	1280	■	3118562	✓
17.7							2700	2170			
23							3300	2670			
Power LED - dimmable DALI 220-240 V 50/60 Hz											
10	II	-	80	3000/4000	S/B	-	1600	1280	■	3118565	✓
17.7							2700	2170			
23							3300	2670			




WL400 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28	II	-	80	3000/4000	S/B	-	4250	3440	■	3105561	✓
37							5200	4210			
Power LED - dimmable DALI 220-240 V 50/60 Hz											
28	II	-	80	3000/4000	S/B	-	4250	3440	■	3118564	✓
37							5200	4210			



WL SQUARE



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

Wall and ceiling mounted LED luminaire for indoor, comprising:

- Technopolymer housing (WL210/WL260)
- Die-cast aluminium housing, powder-coated (WL390)
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Power levels can be set via a switch
- Luminaire efficiency (in lower power ratings) up to 127 lm/W
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through wiring
- Built-in driver




WL RECT




max 0,9 kg

WL 210 OPAL



max 1,6 kg

WL 260 OPAL



max 2,8 kg

WL 390 OPAL

WL210 OPAL

IP54 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.7	II	-	80	3000/4000	S/B	-	1400	1180	■	3105556	✓
15						2000	1700				



WL260 OPAL

IP54 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	II	-	80	3000/4000	S/B	-	1550	1260	■	3105558	✓
17.8							2650	2130			
24							3300	2650			



WL390 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28.7	II	-	80	3000/4000	S/B	-	4350	3490	■	3105560	✓
38							5300	4280			



ELIA PL M1 1200




Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 /

LED low bay for lighting offices

- Available in square or rectangular versions with a frame in white powder-coated die-cast aluminium and two types of PMMA shield, a high-efficiency micro-prism version with a UGR of less than 19 and an opal version with an UGR of 22
- The family of products is available with a colour temperature of 3,000K (warm white) or 4,000K (neutral white), a colour rendering index of more than 80 or more than 90 and a separate electronic power supply supplied as part of a kit, in On/Off or DALI versions
- ELIA PL is easy to install thanks to the reduced weight of the device and the connector for electrical wiring which enables connection to the remote power supply
- ELIA PL can be flush-mounted in false ceilings with standard panels, or alternatively, can be ceiling or suspension-mounted using the accessories provided separately
- External emergency kit with 3h autonomy available (to be ordered separately)



ELIA PL M1 1200

ELIA PL M1 1200 MP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	1195	GWF1610LN940	✓
33	II	✓	✓	90	3000	-	3300	□	1195	GWF1610LN930	✓
33	II	✓	✓	80	4000	-	4300	□	1195	GWF1610LN840	✓
33	II	✓	✓	80	3000	-	4000	□	1195	GWF1610LN830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	1195	GWF1611LN940	✓
33	II	✓	✓	90	3000	-	3300	□	1195	GWF1611LN930	✓
33	II	✓	✓	80	4000	-	4300	□	1195	GWF1611LN840	✓
33	II	✓	✓	80	3000	-	4000	□	1195	GWF1611LN830	✓



ELIA PL M1 1200 OP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	1195	GWF1610LA940	✓
33	II	✓	-	90	3000	-	3300	□	1195	GWF1610LA930	✓
33	II	✓	-	80	4000	-	4300	□	1195	GWF1610LA840	✓
33	II	✓	-	80	3000	-	4000	□	1195	GWF1610LA830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	1195	GWF1611LA940	✓
33	II	✓	-	90	3000	-	3300	□	1195	GWF1611LA930	✓
33	II	✓	-	80	4000	-	4300	□	1195	GWF1611LA840	✓
33	II	✓	-	80	3000	-	4000	□	1195	GWF1611LA830	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL M1 1200			
Suspension kit with 4 cables		GWF1921	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1922	✓
Ceiling box kit 300x1200 mm - white		GWF1913	✓
Assemblable ceiling box kit 300x1200 mm - white		GWF1919	✓
Emergency kit 3h		GWS2992	✓




GWF1921



GWS2992

ELIA PL M2 600



□ WH-RAL9016 / White RAL9016 /


Scan the QR-code for the latest information

LED low bay for lighting offices

- Available in square or rectangular versions with a frame in white powder-coated die-cast aluminium and two types of PMMA shield, a high-efficiency micro-prism version with a UGR of less than 19 and an opal version with an UGR of 22
- The family of products is available with a colour temperature of 3,000K (warm white) or 4,000K (neutral white), a colour rendering index of more than 80 or more than 90 and a separate electronic power supply supplied as part of a kit, in On/Off or DALI versions
- ELIA PL is easy to install thanks to the reduced weight of the device and the connector for electrical wiring which enables connection to the remote power supply
- ELIA PL can be flush-mounted in false ceilings with standard panels, or alternatively, can be ceiling or suspension-mounted using the accessories provided separately
- External emergency kit with 3h autonomy available (to be ordered separately)



Campus Della Salute - Pavia - Italy



ELIA PL M2 600

ELIA PL M2 600 MP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	595	GWF1610MN940	✓
33	II	✓	✓	90	3000	-	3300	□	595	GWF1610MN930	✓
33	II	✓	✓	80	4000	-	4300	□	595	GWF1610MN840	✓
33	II	✓	✓	80	3000	-	4000	□	595	GWF1610MN830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	595	GWF1611MN940	✓
33	II	✓	✓	90	3000	-	3300	□	595	GWF1611MN930	✓
33	II	✓	✓	80	4000	-	4300	□	595	GWF1611MN840	✓
33	II	✓	✓	80	3000	-	4000	□	595	GWF1611MN830	✓



ELIA PL M2 600 OP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	595	GWF1610MA940	✓
33	II	✓	-	90	3000	-	3300	□	595	GWF1610MA930	✓
33	II	✓	-	80	4000	-	4300	□	595	GWF1610MA840	✓
33	II	✓	-	80	3000	-	4000	□	595	GWF1610MA830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	595	GWF1611MA940	✓
33	II	✓	-	90	3000	-	3300	□	595	GWF1611MA930	✓
33	II	✓	-	80	4000	-	4300	□	595	GWF1611MA840	✓
33	II	✓	-	80	3000	-	4000	□	595	GWF1611MA830	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL M2 600			
Suspension kit with 4 cables		GWF1921	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1922	✓
Ceiling box kit 600x600 mm - white		GWF1911	✓
Assemblable ceiling box kit 600x600 mm - white		GWF1917	✓
Emergency kit 3h		GWS2992	✓




GWF1921



GWS2992

ELIA PL M3 625



□ WH-RAL9016 / White RAL9016 /


Scan the QR-code for the latest information

LED low bay for lighting offices

- Available in square or rectangular versions with a frame in white powder-coated die-cast aluminium and two types of PMMA shield, a high-efficiency micro-prism version with a UGR of less than 19 and an opal version with an UGR of 22
- The family of products is available with a colour temperature of 3,000K (warm white) or 4,000K (neutral white), a colour rendering index of more than 80 or more than 90 and a separate electronic power supply supplied as part of a kit, in On/Off or DALI versions
- ELIA PL is easy to install thanks to the reduced weight of the device and the connector for electrical wiring which enables connection to the remote power supply
- ELIA PL can be flush-mounted in false ceilings with standard panels, or alternatively, can be ceiling or suspension-mounted using the accessories provided separately
- External emergency kit with 3h autonomy available (to be ordered separately)



Albinoleffe stadium - Zanica - Italy



ELIA PL M3 625

ELIA PL M3 625 MP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	620	GWF1610NN940	✓
33	II	✓	✓	90	3000	-	3300	□	620	GWF1610NN930	✓
33	II	✓	✓	80	4000	-	4300	□	620	GWF1610NN840	✓
33	II	✓	✓	80	3000	-	4000	□	620	GWF1610NN830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	✓	90	4000	-	3600	□	620	GWF1611NN940	✓
33	II	✓	✓	90	3000	-	3300	□	620	GWF1611NN930	✓
33	II	✓	✓	80	4000	-	4300	□	620	GWF1611NN840	✓
33	II	✓	✓	80	3000	-	4000	□	620	GWF1611NN830	✓



ELIA PL M3 625 OP

IP20 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	620	GWF1610NA940	✓
33	II	✓	-	90	3000	-	3300	□	620	GWF1610NA930	✓
33	II	✓	-	80	4000	-	4300	□	620	GWF1610NA840	✓
33	II	✓	-	80	3000	-	4000	□	620	GWF1610NA830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
33	II	✓	-	90	4000	-	3600	□	620	GWF1611NA940	✓
33	II	✓	-	90	3000	-	3300	□	620	GWF1611NA930	✓
33	II	✓	-	80	4000	-	4300	□	620	GWF1611NA840	✓
33	II	✓	-	80	3000	-	4000	□	620	GWF1611NA830	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL M3 625			
Suspension kit with 4 cables		GWF1921	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1922	✓
Ceiling box kit 620x620 mm - white		GWF1912	✓
Assemblable ceiling box kit 620x620 mm - white		GWF1918	✓
Emergency kit 3h		GWS2992	✓




GWF1921



GWS2992

FL ROUND+ 333 RE



Scan the QR-code for the latest information


- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Recessed round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <math><3000\text{cd}/\text{m}^2 >65^\circ</math>)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Direct light distribution
 - 2 power levels adjustable
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Built-in driver




Public Utilities Company - Lehrte - Germany



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 PL



FL ROUND+ 333 RE

FL ROUND+ 333 RE MP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3123859	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3123849	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3123863	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3123853	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3123857	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3123847	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3123861	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3123851	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	■	3123866	✓
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	□	3123868	✓



FL ROUND+ 333 RE OP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123860	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123850	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123856	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123846	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3123864	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3123854	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123858	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123848	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123855	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123845	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3123862	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3123852	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3123867	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3123865	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	□	3123869	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 333 RE				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓




3122585




3122586



3122587



FL ROUND+ 555 RE



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Recessed round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 ($UGR < 19$ and $< 3000 \text{cd/m}^2 > 65^\circ$)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Direct light distribution
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Built-in driver




Public Utilities Company - Lehrte - Germany



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 PL



310 mm max 5,5 kg

FL ROUND+ 555 RE

FL ROUND+ 555 RE MP

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6070	■	3123986	✓
49	I	-	-	80	3000	7760	5770	■	3123976	✓
49	I	-	-	80	4000	8000	6070	□	3123990	✓
49	I	-	-	80	3000	7760	5770	□	3123980	✓
21	I	-	✓	80	4000	3800	2890	■	3123961	✓
21	I	-	✓	80	3000	3690	2740	■	3123951	✓
21	I	-	✓	80	4000	3800	2890	□	3123965	✓
21	I	-	✓	80	3000	3690	2740	□	3123955	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

49	I	-	-	80	4000	8000	6070	■	3123984	✓
49	I	-	-	80	3000	7760	5770	■	3123974	✓
49	I	-	-	80	4000	8000	6070	□	3123988	✓
49	I	-	-	80	3000	7760	5770	□	3123978	✓
21	I	-	✓	80	4000	3800	2890	■	3123959	✓
21	I	-	✓	80	3000	3690	2740	■	3123949	✓
21	I	-	✓	80	4000	3800	2890	□	3123963	✓
21	I	-	✓	80	3000	3690	2740	□	3123953	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

49	I	-	-	80	tw 2700-6500	7600	5680	■	3123993	✓
49	I	-	-	80	tw 2700-6500	7600	5680	□	3123995	✓
21	I	-	-	80	tw 2700-6500	3600	2680	■	3123968	✓
21	I	-	-	80	tw 2700-6500	3600	2680	□	3123970	✓

FL ROUND+ 555 RE OP

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6250	■	3123987	✓
49	I	-	-	80	3000	7760	5940	■	3123977	✓
49	I	-	-	80	4000	8000	6250	■	3123983	✓
49	I	-	-	80	3000	7760	5940	■	3123973	✓
49	I	-	-	80	4000	8000	6250	□	3123991	✓
49	I	-	-	80	3000	7760	5940	□	3123981	✓
21	I	-	-	80	4000	3800	2970	■	3123962	✓
21	I	-	-	80	3000	3690	2830	■	3123952	✓
21	I	-	-	80	4000	3800	2970	■	3123958	✓
21	I	-	-	80	3000	3690	2830	■	3123948	✓
21	I	-	-	80	4000	3800	2970	□	3123966	✓
21	I	-	-	80	3000	3690	2830	□	3123956	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

49	I	-	-	80	4000	8000	6250	■	3123985	✓
49	I	-	-	80	3000	7760	5940	■	3123975	✓
49	I	-	-	80	4000	8000	6250	■	3123982	✓
49	I	-	-	80	3000	7760	5940	■	3123972	✓
49	I	-	-	80	4000	8000	6250	□	3123989	✓
49	I	-	-	80	3000	7760	5940	□	3123979	✓
21	I	-	-	80	4000	3800	2970	■	3123960	✓
21	I	-	-	80	3000	3690	2830	■	3123950	✓
21	I	-	-	80	4000	3800	2970	■	3123957	✓
21	I	-	-	80	3000	3690	2830	■	3123947	✓
21	I	-	-	80	4000	3800	2970	□	3123964	✓
21	I	-	-	80	3000	3690	2830	□	3123954	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz


49	I	-	-	80	tw 2700-6500	7600	5660	■	3123994	✓
49	I	-	-	80	tw 2700-6500	7600	5660	■	3123992	✓
49	I	-	-	80	tw 2700-6500	7600	5660	□	3123996	✓
21	I	-	-	80	tw 2700-6500	3600	2630	■	3123969	✓
21	I	-	-	80	tw 2700-6500	3600	2630	■	3123967	✓
21	I	-	-	80	tw 2700-6500	3600	2630	□	3123971	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 555 RE				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585




3122586



3122587

FL ROUND+ 777 RE



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Recessed round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and $3000\text{cd}/\text{m}^2 >65^\circ$)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Direct light distribution
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Built-in driver




Ergosign offices - Saarbrücken - Germany



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 PL



FL ROUND+ 777 RE

FL ROUND+ 777 RE MP

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9120	■	3124136	✓
67	I	-	-	80	3000	11640	8670	■	3124126	✓
67	I	-	-	80	4000	12000	9120	□	3124140	✓
67	I	-	-	80	3000	11640	8670	□	3124130	✓
38	I	-	-	80	4000	7200	5450	■	3124111	✓
38	I	-	✓	80	3000	6980	5180	■	3124101	✓
38	I	-	-	80	4000	7200	5450	□	3124115	✓
38	I	-	✓	80	3000	6980	5180	□	3124105	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9120	■	3124134	✓
67	I	-	-	80	3000	11640	8670	■	3124124	✓
67	I	-	-	80	4000	12000	9120	□	3124138	✓
67	I	-	-	80	3000	11640	8670	□	3124128	✓
38	I	-	-	80	4000	7200	5450	■	3124109	✓
38	I	-	✓	80	3000	6980	5180	■	3124099	✓
38	I	-	-	80	4000	7200	5450	□	3124113	✓
38	I	-	✓	80	3000	6980	5180	□	3124103	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
67	I	-	-	80	tw 2700-6500	11500	8540	■	3124143	✓
67	I	-	-	80	tw 2700-6500	11500	8540	□	3124145	✓
38	I	-	-	80	tw 2700-6500	6900	5130	■	3124118	✓
38	I	-	-	80	tw 2700-6500	6900	5130	□	3124120	✓

FL ROUND+ 777 RE OP

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
69	I	-	-	80	4000	12000	8800	■	3124137	✓
69	I	-	-	80	4000	12000	8800	■	3124133	✓
69	I	-	-	80	4000	12000	8800	□	3124141	✓
67	I	-	-	80	3000	11640	8360	■	3124127	✓
67	I	-	-	80	3000	11640	8360	■	3124123	✓
67	I	-	-	80	3000	11640	8360	□	3124131	✓
38	I	-	-	80	4000	7200	5290	■	3124112	✓
38	I	-	-	80	3000	6980	5030	■	3124102	✓
38	I	-	-	80	4000	7200	5290	■	3124108	✓
38	I	-	-	80	3000	6980	5030	■	3124098	✓
38	I	-	-	80	4000	7200	5290	□	3124116	✓
38	I	-	-	80	3000	6980	5030	□	3124106	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
69	I	-	-	80	4000	12000	8800	■	3124135	✓
69	I	-	-	80	4000	12000	8800	■	3124132	✓
69	I	-	-	80	4000	12000	8800	□	3124139	✓
67	I	-	-	80	3000	11640	8360	■	3124125	✓
67	I	-	-	80	3000	11640	8360	■	3124122	✓
67	I	-	-	80	3000	11640	8360	□	3124129	✓
38	I	-	-	80	4000	7200	5290	■	3124110	✓
38	I	-	-	80	3000	6980	5030	■	3124100	✓
38	I	-	-	80	4000	7200	5290	■	3124107	✓
38	I	-	-	80	3000	6980	5030	■	3124097	✓
38	I	-	-	80	4000	7200	5290	□	3124114	✓
38	I	-	-	80	3000	6980	5030	□	3124104	✓


TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
67	I	-	-	80	tw 2700-6500	11500	8210	■	3124144	✓
67	I	-	-	80	tw 2700-6500	11500	8210	■	3124142	✓
67	I	-	-	80	tw 2700-6500	11500	8210	□	3124146	✓
38	I	-	-	80	tw 2700-6500	6900	4900	■	3124119	✓
38	I	-	-	80	tw 2700-6500	6900	4900	■	3124117	✓
38	I	-	-	80	tw 2700-6500	6900	4900	□	3124121	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND* 777 RE				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585





3122586



3122587


FL SQUARE RE



Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

- Recessed, square LED luminaire for indoor, comprising:
- Extruded aluminium housing profile, powder-coated
 - LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the diffuser
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver



max 3,1 kg

FL SQUARE 300 RE OP

FL SQUARE 300 RE OP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIR EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2260	<input type="checkbox"/>	8300591233400	✓
19	I	-	-	80	3000	2900	2200	<input type="checkbox"/>	8300591233300	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2260	<input type="checkbox"/>	8300591236400	✓
19	I	-	-	80	3000	2900	2200	<input type="checkbox"/>	8300591236300	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
FL SQUARE RE			
External Casambi module	<input checked="" type="checkbox"/>	3122585	✓
Single wireless wall switch	<input checked="" type="checkbox"/>	3122586	✓
Double wireless wall switch	<input checked="" type="checkbox"/>	3122587	✓



3122585





3122586



3122587

FLEXILED IL




Scan the QR-code for the latest information


□ WH-RAL9016 / White RAL9016 / Textured

Inlayed for indoor use consisting of:


- Housing made of form-stable 1.0 mm sheet steel
 - Impact-resistant, impression-resistant powder coating
- The luminaire is available with different light engines:
- Barrier-free light
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Wallwasher with asymmetrical light distribution ensures optimum panel illumination
 - Black, white or metallised reflector ensure maximum efficiency and high visual comfort
 - Glare-free light for office applications in accordance with DIN EN 12464-1 ($UGR < 19$ and $< 3000 \text{cd/m}^2 > 65^\circ$)
 - $UGR < 19$ for all luminosities
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Reliable and low-maintenance 50,000h L80B10
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - 2 power levels adjustable
 - Through-wiring designed
 - Configurable via LIGHT-PERFORMER®
 - Special colour versions available. Consult factory




FLEXILED IL LV



FLEXILED IL LV



FLEXILED IL LV



FLEXILED IL LV



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

FLEXILED IL LV BLACK

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21 32	I	-	✓	80	4000	3750 5500	3230 4780	□	1500	3120848	✓
21 32	I	-	✓	80	4000	3750 5500	3230 4780	□	1495	3122382	✓
17 26	I	-	✓	80	4000	3000 4400	2590 3830	□	1200	3120847	✓
17 26	I	-	✓	80	4000	3000 4400	2590 3830	□	1195	3122381	✓
17 26	I	-	✓	80	4000	3000 4400	2590 3830	□	1240	3123272	✓



FLEXILED IL LV SILVER

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21 32	I	-	✓	80	4000	3750 5500	3610 5340	□	1500	3120852	✓
21 32	I	-	✓	80	4000	3750 5500	3610 5340	□	1495	3122439	✓
17 26	I	-	✓	80	4000	3000 4400	2890 4270	□	1200	3120851	✓
17 26	I	-	✓	80	4000	3000 4400	2890 4270	□	1195	3122438	✓
17 26	I	-	✓	80	4000	3000 4400	2890 4270	□	1240	3123273	✓



FLEXILED IL LV WHITE

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21 32	I	-	-	80	4000	3750 5500	3560 5260	□	1500	3120850	✓
21 32	I	-	-	80	4000	3750 5500	3560 5260	□	1495	3122437	✓
17 26	I	-	-	80	4000	3000 4400	2840 4210	□	1240	3123274	✓
17 26	I	-	-	80	4000	3000 4400	2840 4210	□	1200	3120849	✓
17 26	I	-	-	80	4000	3000 4400	2840 4210	□	1195	3122383	✓



FLEXILED IL MICROPRISM

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14 24	I	-	-	80	4000	2560 4200	2060 3390	□	1500	3123269	✓
14 24	I	-	-	80	4000	2560 4200	2060 3390	□	1495	3123281	✓
12 20	I	-	-	80	4000	2130 3360	1670 2630	□	1200	3123268	✓
12 20	I	-	-	80	4000	2130 3360	1670 2630	□	1240	3123275	✓
12 20	I	-	-	80	4000	2130 3360	1670 2630	□	1195	3123280	✓



FLEXILED IL OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14 24	I	-	-	80	4000	2560 4200	2170 3560	□	1500	3123271	✓
14 24	I	-	-	80	4000	2560 4200	2170 3560	□	1495	3123283	✓
12 20	I	-	-	80	4000	2130 3360	1770 2790	□	1200	3123270	✓
12 20	I	-	-	80	4000	2130 3360	1770 2790	□	1240	3123276	✓
12 20	I	-	-	80	4000	2130 3360	1770 2790	□	1195	3123282	✓



FLEXILED IL LV ASYM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
42	I	-	-	80	4000	6150	5260	□	1500	3123267	✓
42	I	-	-	80	4000	6150	5260	□	1495	3123279	✓
34	I	-	-	80	4000	4900	4190	□	1200	3123266	✓
34	I	-	-	80	4000	4900	4190	□	1240	3123277	✓
34	I	-	-	80	4000	4900	4190	□	1195	3123278	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FLEXILED IL				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585



3122586



3122587

FLEXILED RE



Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

Recessed lights, comprising:

- Housing made of form-stable 1.0 mm sheet steel
- Impact-resistant, impression-resistant powder coating
- The luminaire is available with different light engines:
 - Barrier-free light
 - Black, white or metallised reflector ensure maximum efficiency and high visual comfort
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Wallwasher with asymmetrical light distribution ensures optimum panel illumination
 - Glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <math><3000\text{cd}/\text{m}^2 >65^\circ</math>)
 - UGR < 19 for all luminosities
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Reliable and low-maintenance 50,000h L80B10
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - 2 power levels adjustable
 - Incl. pre-assembled installation spring
 - Through-wiring designed
 - Special colour versions available. Consult factory




FLEXILED IL



FLEXILED PL



FLEXILED RE
LV



FLEXILED RE
LV



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

FLEXILED RE LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21	I	-	✓	80	4000	3750	3230	□	1500	3122228	✓
32	I	-	✓	80	4000	5500	4780	□	1500	3122228	✓
17	I	-	✓	80	4000	3000	2590	□	1200	3122225	✓
26	I	-	✓	80	4000	4400	3830	□	1200	3122225	✓



FLEXILED RE LV SILVER

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21	I	-	✓	80	4000	3750	3610	□	1500	3122229	✓
32	I	-	✓	80	4000	5500	5340	□	1500	3122229	✓
17	I	-	✓	80	4000	3000	2890	□	1200	3122226	✓
26	I	-	✓	80	4000	4400	4270	□	1200	3122226	✓



FLEXILED RE LV WHITE

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
21	I	-	-	80	4000	3750	3560	□	1500	3122230	✓
32	I	-	-	80	4000	5500	5260	□	1500	3122230	✓
17	I	-	-	80	4000	3000	2840	□	1200	3122227	✓
26	I	-	-	80	4000	4400	4210	□	1200	3122227	✓



FLEXILED RE MICROPRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2060	□	1500	3123287	✓
24	I	-	-	80	4000	4200	3390	□	1500	3123287	✓
12	I	-	-	80	4000	2130	1670	□	1200	3123286	✓
20	I	-	-	80	4000	3360	2630	□	1200	3123286	✓



FLEXILED RE OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	-	80	4000	2560	2170	□	1500	3123289	✓
24	I	-	-	80	4000	4200	3560	□	1500	3123289	✓
12	I	-	-	80	4000	2130	1770	□	1200	3123288	✓
20	I	-	-	80	4000	3360	2790	□	1200	3123288	✓



FLEXILED RE LV ASYM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
42	I	-	-	80	4000	6150	5260	□	1500	3123285	✓
34	I	-	-	80	4000	4900	4190	□	1200	3123284	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FLEXILED RE				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585




3122586



3122587

PLATO 1200



Scan the QR-code for the latest information


WH-87 / White / Textured

Ultra-flat LED luminaire, includes:


- Extruded aluminium profile, powder-coated mounting frame
- Technopolymer diffuser
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- UGR<19
- Remote ON/OFF driver included

Options:


- Optional fixing clamps for suspended ceiling mounting
- Dimmable DALI
- Dimmable driver 1-10V ballast
- Emergency 3h



PLATO 600



PLATO 625




PLATO 1200

PLATO 1200 MP

IP40 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	II	-	✓	90	4000	4190	3654	□	1195	3116614	✓
32	II	-	✓	90	3000	4020	3307	□	1195	3116613	✓
32	II	-	✓	80	4000	5240	4245	□	1195	3116612	✓
32	II	-	✓	80	3000	4660	3802	□	1195	3116611	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
PLATO 1200			
Driver 36 W DALI		19-02565	✓
Driver 36 W 1-10 V push		19-02566	✓



19-02565



19-02566


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
PLATO 1200			
Kit EM3P		19-02567	✓
Suspension kit		3121971	✓



19-02567

PLATO 600



Scan the QR-code for the latest information

WH-87 / White / Textured

Ultra-flat LED luminaire, includes:


- Extruded aluminium profile, powder-coated mounting frame
- Microprism technopolymer diffuser for efficient light diffusion, reduced glare and high uniformity
- UGR<19
- Remote ON/OFF driver included

Options:


- Optional fixing clamps for suspended ceiling mounting
- Installation kit for ceiling mounting available
- Emergency 3h
- Dimmable driver 1-10V ballast
- Dimmable DALI




Ayal Kaas Company - Westzaan - Netherlands



PLATO 625



PLATO 1200



PLATO 600

PLATO 600 MP

IP40 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIV EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	II	-	✓	90	4000	5110	4026	□	595	3116610	✓
32	II	-	✓	90	3000	4540	3706	□	595	3116609	✓
32	II	-	✓	80	4000	5054	4080	□	595	3116608	✓
32	II	-	✓	80	3000	4718	3848	□	595	3116607	✓



PLATO 600 MULTIPOWER

IP40 - IK06 - 750 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIV EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22						3550	2894				
28	II	-	✓	90	4000	4440	3623	□	595	3117957	✓
33						5180	4230				
38						5840	4766				
22						3190	2604				
28	II	-	✓	90	3000	4010	3269	□	595	3117956	✓
33						4680	3817				
38						5280	4307				
22						3490	2843				
28	II	-	✓	80	4000	4360	3555	□	595	3117955	✓
33						5090	4150				
38						5750	4686				
22						3150	2571				
28	II	-	✓	80	3000	3950	3221	□	595	3117954	✓
33						4620	3767				
38						5210	4252				



PLATO 600 TUNABLE WHITE

IP40 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIV EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz											
33	II	-	✓	80	tw 2700-6500	5880	3857	□	595	3117964	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
PLATO 600			
Driver 36 W DALI		19-02565	✓
Driver 36 W 1-10V push		19-02566	✓



19-02565




19-02566

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
PLATO 600			
Kit EM3P		19-02567	✓
Suspension kit		3121971	✓
Ceiling kit		3116983	✓



19-02567



3116983




3116616



Ayal Kaas Company - Westzaan - Netherlands

PLATO 625



TETRA PAK - Modena - Italy




Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

Inlaid, square LED luminaire for indoors, comprising:


- Extruded aluminium housing profile, powder-coated
- The luminaire is available with different light engines:
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Four power levels can be set via a switch
 - MULTIPOWER version: VDU application suitable acc. to DIN EN 12464-1 (in lowest power rating)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Suitable grid, modular plasterboard and coffered ceilings
 - Built-in driver
 - Protection class IP43 (for light emission surface for installation in closed ceilings)
 - Separate accessory allows the lights to be used as a suspended, surface mounted or recessed luminaires



PLATO 600



PLATO 1200



PLATO 625

PLATO 625 MP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
22						3230	2330				
28		-	✓	90	4000	4000	2890	□	620	3118514	✓
34						4760	3430				
40						5530	3950				
22						3230	2370				
28		-	✓	90	3000	4000	2950	□	620	3118513	✓
34						4760	3500				
40						5530	4030				
22						3800	3060				
28		-	✓	80	4000	4700	3790	□	620	3118512	✓
34						5600	4500				
40						6500	5190				
22						3800	2800				
28		-	✓	80	3000	4700	3470	□	620	3118511	✓
34						5600	4120				
40						6500	4740				
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz											
31		-	✓	80	tw 2700-6500	5600	3860	□	620	3118515	✓

PLATO 625 MP MULTIPOWER

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22						3230	2330				
28		-	✓	90	4000	4000	2890	□	620	3118510	✓
34						4760	3430				
40						5530	3950				
22						3230	2370				
28		-	✓	90	3000	4000	2950	□	620	3118509	✓
34						4760	3500				
40						5530	4030				
22						3800	3060				
28		-	✓	80	4000	4700	3790	□	620	3118508	✓
34						5600	4500				
40						6500	5190				
22						3800	2800				
28		-	✓	80	3000	4700	3470	□	620	3118507	✓
34						5600	4120				
40						6500	4740				

PLATO 625 OP

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23						3230	2470				
29		-	-	90	4000	4000	3050	<input type="checkbox"/>	620	3118505	✓
36						4760	3610				
42						5530	4150				
23						3230	2470				
29		-	-	90	3000	4000	3050	<input type="checkbox"/>	620	3118504	✓
36						4760	3610				
42						5530	4150				
23						3800	2900				
29		-	-	80	4000	4700	3580	<input type="checkbox"/>	620	3117705	✓
36						5600	4250				
42						6500	4880				
23						3800	2900				
29		-	-	80	3000	4700	3580	<input type="checkbox"/>	620	3117704	✓
36						5600	4250				
42						6500	4880				
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz											
32		-	-	80	tw	2700-6500	5500	<input type="checkbox"/>	620	3118506	✓


PLATO 625 OP MULTIPOWER

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23						3230	2470				
29		-	✓	90	4000	4000	3050	<input type="checkbox"/>	620	3118503	✓
36						4760	3610				
42						5530	4150				
23						3230	2470				
29		-	✓	90	3000	4000	3050	<input type="checkbox"/>	620	3118502	✓
36						4760	3610				
42						5530	4150				
23						3800	2900				
29		-	-	80	4000	4700	3580	<input type="checkbox"/>	620	3114723	✓
36						5600	4250				
42						6500	4880				
23						3800	2900				
29		-	-	80	3000	4700	3580	<input type="checkbox"/>	620	3114722	✓
36						5600	4250				
42						6500	4880				

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
PLATO 625			
Ceiling kit	<input type="checkbox"/>	3118552	✓
Mounting frame	<input type="checkbox"/>	86256010	✓
Ceiling rose	<input type="checkbox"/>	890000410	✓
Y-wire suspension (1,5 m)		86252015	✓
Mains supply (3-pole)		8103031800	✓
Mains supply (5-pole)		8105031800	✓
External Casambi module	<input checked="" type="checkbox"/>	3122585	✓
Single wireless wall switch	<input type="checkbox"/>	3122586	✓
Double wireless wall switch	<input type="checkbox"/>	3122587	✓



86256010



890000410




86252015




8103031800
8105031800



3122585




3122586



3122587

AMIGO 36



Scan the QR-code for the latest information


WH-87 / White / Textured

Ultra-flat LED luminaire, includes:

- Galvanized perforated sheet, powder-coated housing
- Optics made up of PMMA optics and white polycarbonate reflectors to optimise light distribution
- UGR<16
- Remote ON/OFF driver included
- Emergency 3h
- Wieland connector GST18i3

Options:

- Dimmable DALI options available. Consult factory
- Installation kit for ceiling mounting available




AMIGO 36

AMIGO 36 S/EW

IP20 - IK05 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	-	✓	90	4000	4392	3091	□	595	3109251	✓
25	II	-	✓	90	3000	4100	2900	□	595	3108208	✓
25	II	-	✓	80	4000	5110	3604	□	595	3108209	✓
25	II	-	✓	80	3000	4680	3383	□	595	3109250	✓



AMIGO 36 WIELAND

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	-	✓	90	4000	4392	3091	□	595	3110032	✓
25	II	-	✓	90	3000	4100	2900	□	595	3110039	✓
25	II	-	✓	80	4000	5110	3604	□	595	3110038	✓
25	II	-	✓	80	3000	4680	3383	□	595	3110031	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
AMIGO 36			
Driver DALI		3109055	✓
Ceiling kit		19-02531	✓
Kit EM3P		3111872	✓



3109055




19-02531



3111872

ELA 600



Scan the QR-code for the latest information


WH-87 / White / Textured

LED recessed luminaire, consisting of:


- Extruded aluminium profile, powder-coated mounting frame
- Prismatic technopolymer diffuser
- UGR<19
- Remote ON/OFF driver included

Options:

- Emergency 3h
- Dimmable DALI options available. Consult factory
- Dimmable 1/10V ballast available. Consult factory



ELA 625




ELA 600 PR

ELA 600 PR

IP40 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	II	-	✓	90	4000	3980	3476	□	595	3116606	✓
32	II	-	✓	90	3000	3870	3181	□	595	3116605	✓
32	II	-	✓	80	4000	4600	3988	□	595	3116604	✓
32	II	-	✓	80	3000	4380	3590	□	595	3116603	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELA 600			
Driver 36 W DALI		19-02565	✓
Driver 36 W 1-10 V push		19-02566	✓



19-02565



19-02566


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELA 600			
Kit EM3P		19-02567	✓



19-02567


ELA 625




Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

- Inlaid, square LED luminaire for indoors, comprising:
- Extruded aluminium housing profile, powder-coated
 - Prismatic diffuser for efficient light distribution, glare reduction and a high uniformity
 - VDU application suitable acc. to EN 12464-1
 - UGR<19
 - Inlaid luminaire suitable for lattice and coffered ceilings
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Electronic converter included







ELA 600




ELA 625 PR




ELA 625 PR

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
33	I	-	✓	80	4000	-	4150		620	3118517	✓
33	I	-	✓	80	3000	-	3720		620	3118516	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
33	I	-	✓	80	4000	-	4150		620	3118519	✓
33	I	-	✓	80	3000	-	3720		620	3118518	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
ELA 625			
External Casambi module		3122585	✓
Single wireless wall switch		3122586	✓
Double wireless wall switch		3122587	✓



3122585




3122586



3122587

ELIA PL BACKLIT M1 1200



Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 /

Modular recessed LED luminaire for indoor lighting applications

- Thanks to its superior energy efficiency, it is the ideal solution for a fast return on investment in the replacement of traditional lighting systems
- It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
- The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80; and with an On/Off or DALI external power supply (included with the product)
- The luminaire is equipped with an opal diffuser with UGR lower than 22
- It is easy to install thanks to its reduced weight and its quick coupling connector for fast electrical wiring
- External emergency kit with 3h autonomy available (to be ordered separately)



Campus Della Salute - Pavia - Italy



ELIA PL BACKLIT M1 1200

ELIA PL BACKLIT M1 1200 OP


IP40 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	1195	GWF1610LT840	✓
25	II	✓	-	80	3000	-	3000	□	1195	GWF1610LT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	1195	GWF1611LT840	✓
25	II	✓	-	80	3000	-	3000	□	1195	GWF1611LT830	✓


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL BACKLIT M1 1200			
Suspension kit with 4 cables		GWF1926	✓
Assemblable ceiling box kit 300x1200 mm - white		GWF1919	✓
Emergency kit 3h		GWS2992	✓



GWS2992

ELIA PL BACKLIT M2 600




Scan the QR-code for the latest information

□ WH-RAL9016 / White RAL9016 /

- Modular recessed LED luminaire for indoor lighting applications
- Thanks to its superior energy efficiency, it is the ideal solution for a fast return on investment in the replacement of traditional lighting systems
 - It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
 - The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80; and with an On/Off or DALI external power supply (included with the product)
 - The luminaire is equipped with an opal diffuser with UGR lower than 22
 - It is easy to install thanks to its reduced weight and its quick coupling connector for fast electrical wiring
 - External emergency kit with 3h autonomy available (to be ordered separately)



Orobia Climbing - Curno - Italy



ELIA PL BACKLIT M2 600

ELIA PL BACKLIT M2 600 OP

IP40 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	595	GWF1610MT840	✓
25	II	✓	-	80	3000	-	3000	□	595	GWF1610MT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	595	GWF1611MT840	✓
25	II	✓	-	80	3000	-	3000	□	595	GWF1611MT830	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL BACKLIT M2 600			
Suspension kit with 4 cables		GWF1926	✓
Assemblable ceiling box kit 600x600 mm - white		GWF1917	✓
Emergency kit 3h		GWS2992	✓



GWS2992

ELIA PL BACKLIT M3 625



Scan the QR-code for the latest information


□ WH-RAL9016 / White RAL9016 /

Modular recessed LED luminaire for indoor lighting applications

- Thanks to its superior energy efficiency, it is the ideal solution for a fast return on investment in the replacement of traditional lighting systems
- It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
- The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80; and with an On/Off or DALI external power supply (included with the product)
- The luminaire is equipped with an opal diffuser with UGR lower than 22
- It is easy to install thanks to its reduced weight and its quick coupling connector for fast electrical wiring
- External emergency kit with 3h autonomy available (to be ordered separately)



Campus Della Salute - Pavia - Italy



ELIA PL BACKLIT M3 625

ELIA PL BACKLIT M3 625 OP

IP40 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	620	GWF1610NT840	✓
25	II	✓	-	80	3000	-	3000	□	620	GWF1610NT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
25	II	✓	-	80	4000	-	3300	□	620	GWF1611NT840	✓
25	II	✓	-	80	3000	-	3000	□	620	GWF1611NT830	✓


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL BACKLIT M3 625			
Suspension kit with 4 cables		GWF1926	✓
Assemblable ceiling box kit 620x620 mm - white		GWF1918	✓
Emergency kit 3h		GWS2992	✓



GWS2992

ELIA PL IP65 M1 1200




Scan the QR-code for the latest information

□ WH-RAL9016 / White RAL9016 /

- Modular recessed LED luminaire for indoor applications which require a high resistance against penetration of water and dust, such as high-humidity ambients
- Available in 3 different sizes (300 x 1200 mm, 600 x 600 mm and 620 x 620 mm), it is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
 - The range allows for great flexibility with its possible combinations of colour temperatures: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80
 - The luminaire is equipped with an opal diffuser with UGR lower than 22 and with an On/Off external power supply which is also IP65-rated (included with the product). Both sides of the luminaire are IP65 rated



GEWISS Stadium - Bergamo - Italy



ELIA PL IP65 M1 1200 OP

ELIA PL IP65 M1 1200 OP

IP65 - IK03 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 200-240 V 50/60 Hz											
36	II	✓	-	80	4000	-	3600	□	1195	GWF1910LA840	✓
36	II	✓	-	80	3000	-	3300	□	1195	GWF1910LA830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL IP65 M1 1200			
Suspension kit with 4 cables		GWF1924	✓
Assemblable ceiling box kit 300x1200 mm - white		GWF1919	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1925	✓
Ceiling box kit 300x1200 mm - white		GWF1932	✓



GWF1921

ELIA PL IP65 M2 600




WH-RAL9016 / White RAL9016 /

Scan the QR-code for the latest information

- Modular recessed LED luminaire for indoor applications which require a high resistance against penetration of water and dust, such as high-humidity ambients
- Available in 3 different sizes (300 x 1200 mm, 600 x 600 mm and 620 x 620 mm), it is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
 - The range allows for great flexibility with its possible combinations of colour temperatures: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80
 - The luminaire is equipped with an opal diffuser with UGR lower than 22 and with an On/Off external power supply which is also IP65-rated (included with the product). Both sides of the luminaire are IP65 rated



Campus Della Salute - Pavia - Italy



ELIA PL IP65 M2 600

ELIA PL IP65 M2 600 OP

IP65 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 200-240 V 50/60 Hz											
36	II	✓	-	80	4000	-	3600	□	595	GWF1910MA840	✓
36	II	✓	-	80	3000	-	3300	□	595	GWF1910MA830	✓


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL IP65 M2 600			
Suspension kit with 4 cables		GWF1924	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1925	✓
Ceiling box kit 600x600 mm - white		GWF1930	✓
Assemblable ceiling box kit 600x600 mm - white		GWF1917	✓



GWF1925

ELIA PL IP65 M3 625




Scan the QR-code for the latest information

□ WH-RAL9016 / White RAL9016 /

- Modular recessed LED luminaire for indoor applications which require a high resistance against penetration of water and dust, such as high-humidity ambients
- Available in 3 different sizes (300 x 1200 mm, 600 x 600 mm and 620 x 620 mm), it is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
 - The range allows for great flexibility with its possible combinations of colour temperatures: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) of 80
 - The luminaire is equipped with an opal diffuser with UGR lower than 22 and with an On/Off external power supply which is also IP65-rated (included with the product). Both sides of the luminaire are IP65 rated



Campus Della Salute - Pavia - Italy



ELIA PL IP65 M3 625

ELIA PL IP65 M3 625 OP

IP65 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 200-240 V 50/60 Hz											
36	II	✓	-	80	4000	-	3600	□	620	GWF1910NA840	✓
36	II	✓	-	80	3000	-	3300	□	620	GWF1910NA830	✓


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA PL IP65 M3 625			
Suspension kit with 4 cables		GWF1924	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1925	✓
Assemblable ceiling box kit 620x620 mm - white		GWF1918	✓
Ceiling box kit 620x620 mm - white		GWF1931	✓



GWF1925

VISIO [16] M1 1200




□ WH-RAL9016 / White RAL9016 /

Scan the QR-code for the latest information

Modular recessed LED luminaire ideal for work and study environments. It was designed to ensure maximum visual comfort, thanks to an advanced low-glare optical system (UGR < 16) and a high colour rendering LED source

- It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
- The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) above 90 for a crisp light; and with an On/Off or DALI external power supply (included with the product)
- The luminaire is easy to install thanks to its quick coupling connector for fast electrical wiring
- External emergency kit with 3h autonomy available (to be ordered separately)



VISIO [16] M1 1200

VISIO [16] M1 1200

IP40 - IK06 - 850 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	1195	GWF1810LL940	✓
35	II	✓	-	90	3000	-	3000	□	1195	GWF1810LL930	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	1195	GWF1811LL940	✓
35	II	✓	-	90	3000	-	3000	□	1195	GWF1811LL930	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
VISIO [16] M1 1200			
Suspension kit with 4 cables		GWF1928	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1929	✓
Ceiling box kit 300x1200 mm - white		GWF1932	✓
Emergency kit 3h		GWS2992	✓




GWF1929



GWS2992

VISIO [16] M2 600




□ WH-RAL9016 / White RAL9016 /

Scan the QR-code for the latest information

Modular recessed LED luminaire ideal for work and study environments. It was designed to ensure maximum visual comfort, thanks to an advanced low-glare optical system (UGR <16) and a high colour rendering LED source

- It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
- The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) above 90 for a crisp light; and with an On/Off or DALI external power supply (included with the product)
- The luminaire is easy to install thanks to its quick coupling connector for fast electrical wiring
- External emergency kit with 3h autonomy available (to be ordered separately)



VISIO [16] M2 600

VISIO [16] M2 600

IP40 - IK06 - 850 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	595	GWF1810ML940	✓
35	II	✓	-	90	3000	-	3000	□	595	GWF1810ML930	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	595	GWF1811ML940	✓
35	II	✓	-	90	3000	-	3000	□	595	GWF1811ML930	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
VISIO [16] M2 600			
Suspension kit with 4 cables		GWF1928	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1929	✓
Ceiling box kit 600x600 mm - white		GWF1930	✓
Emergency kit 3h		GWS2992	✓




GWF1921



GWS2992

VISIO [16] M3 625




□ WH-RAL9016 / White RAL9016 /

Scan the QR-code for the latest information

Modular recessed LED luminaire ideal for work and study environments. It was designed to ensure maximum visual comfort, thanks to an advanced low-glare optical system (UGR < 16) and a high colour rendering LED source

- It is suitable for flush-mounting in modular ceilings and can alternatively be ceiling or suspension-mounted using dedicated accessories (to be ordered separately)
- The range allows for great flexibility with its multiple possible combinations of colour temperatures and control systems: it can be ordered in 3,000 K (warm white) or 4,000 K (neutral white), both with a colour rendering index (CRI) above 90 for a crisp light; and with an On/Off or DALI external power supply (included with the product)
- The luminaire is easy to install thanks to its quick coupling connector for fast electrical wiring
- External emergency kit with 3h autonomy available (to be ordered separately)



VISIO [16] M3 625

VISIO [16] M3 625

IP40 - IK06 - 850 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	620	GWF1810NL940	✓
35	II	✓	-	90	3000	-	3000	□	620	GWF1810NL930	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
35	II	✓	-	90	4000	-	3300	□	620	GWF1811NL940	✓
35	II	✓	-	90	3000	-	3000	□	620	GWF1811NL930	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
VISIO [16] M3 625			
Suspension kit with 4 cables		GWF1928	✓
Safety cable kit		GWF1923	✓
Kit with 4 springs for flush-mounting		GWF1929	✓
Ceiling box kit 620x620 mm - white		GWF1931	✓
Emergency kit 3h		GWS2992	✓



GWF1929



GWS2992

IN-TENSE PL



Private Villa - Verona - Italy



Scan the QR-code for the latest information


- BK-RAL9005 / Black RAL9005 / Glossy
- WH-RAL9003 / White RAL9003 / Glossy

Suspended, LED luminaire for indoor, comprising:

- Tempered, flat glass diffuser with thermoformed technopolymer housing
- Pendant metal tube and suspension cable on one side only, with drop-shaped die-cast coupling
- Die-cast aluminium suspension system and canopy
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover

The luminaire is available with different light engines:

- Partially mirrored, black glass with a black ceramic edge (BLACK DRK) and integrated micro prism for efficient light distribution, glare minimisation, and excellent uniformity
- High transparent glass with a black ceramic edge (BLACK TR) and integrated micro prism diffuser for efficient light distribution, glare minimisation, and excellent uniformity
- High transparent glass with a white ceramic edge (WHITE TR) and integrated micro prism for efficient light distribution, glare minimisation, and excellent uniformity
- Direct/indirect-beam light distribution for an improved room atmosphere and increased visual comfort
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Pendant tube, cable suspension, supply cable and ceiling canopy included
- Motion sensor available with task-oriented PIR detector and daylight control. Consult factory
- Versions with suspension length 500 mm or 1500 mm. Consult factory
- Special colour versions available. Consult factory
- Design by WALTER DE SILVA



Max 13,5 kg


IN-TENSE PL M2

IN-TENSE PL M2 BLACK DRK

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
95	I	-	✓	80	4000	13500	6920	■	8808421943482	✓
95	I	-	✓	80	3000	13100	6710	■	8808421943382	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
95	I	-	✓	80	4000	13500	6920	■	8808421946482	✓
95	I	-	✓	80	3000	13100	6710	■	8808421946382	✓





Partially mirrored, black glass with a black ceramic edge (BLACK DRK) and integrated micro prism for efficient light diffusion, glare minimisation, and excellent uniformity

IN-TENSE PL M2 BLACK TR

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
78	I	-	✓	80	4000	11600	8650	■	8808411723482	✓
78	I	-	✓	80	3000	11250	8390	■	8808411723382	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
78	I	-	✓	80	4000	11600	8650	■	8808411726482	✓
78	I	-	✓	80	3000	11250	8390	■	8808411726382	✓





High transparent glass with a black ceramic edge (BLACK TR) and integrated micro prism diffuser for efficient light diffusion, glare minimisation, and excellent uniformity

IN-TENSE PL M2 WHITE TR

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
78	I	-	✓	80	4000	11600	8650	□	8808411723422	✓
78	I	-	✓	80	3000	11250	8390	□	8808411723322	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
78	I	-	✓	80	4000	11600	8650	□	8808411726422	✓
78	I	-	✓	80	3000	11250	8390	□	8808411726322	✓



High transparent glass with a white ceramic edge (WHITE TR) and integrated micro prism for efficient light diffusion, glare minimisation, and excellent uniformity





Private house - Verona - Italy

LIQUID PL



Vetroin offices - Brescia - Italy



Scan the QR-code for the latest information


- BK-RAL9005 / Black RAL9005 / Glossy
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Glossy
- WH-RAL9016 / White RAL9016 / Textured

Suspended, round LED luminaire for indoor, comprising:

- Die-cast aluminium luminaire body and canopy, powder-coated or with exclusive water lacquering painting process
- Steel suspension tube, polyester powder coat or with exclusive water lacquering
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM

The luminaire is available with different light engines:

- Optical diffuser with integrated high transmittance light guide in black glass (BLACK)
- Optical diffuser with integrated high transmittance light guide in shiny opal white glass (WHITE)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Special colour versions available. Consult factory
- Design by WALTER DE SILVA



LIQUID PL
M2

LIQUID PL
M3

LIQUID PL M2 BLACK

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
55	I	-	✓	80	3000	6200	1140	■	8712211553341	✓
55	I	-	✓	80	3000	6200	1140	■	8712211553381	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
55	I	-	✓	80	3000	6200	1140	■	8712211556341	✓
55	I	-	✓	80	3000	6200	1140	■	8712211556381	✓



LIQUID PL M3 BLACK

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
55	I	-	✓	80	3000	6200	1140	■	8712211553342	✓
55	I	-	✓	80	3000	6200	1140	■	8712211553382	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
55	I	-	✓	80	3000	6200	1140	■	8712211556342	✓
55	I	-	✓	80	3000	6200	1140	■	8712211556382	✓



LIQUID PL M2 WHITE

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
55	I	-	-	80	3000	6200	4130	□	8712211553301	✓
55	I	-	-	80	3000	6200	4130	□	8712211553311	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
55	I	-	-	80	3000	6200	4130	□	8712211556301	✓
55	I	-	-	80	3000	6200	4130	□	8712211556311	✓



LIQUID PL M3 WHITE

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
55	I	-	-	80	3000	6200	4130	□	8712211553302	✓
55	I	-	-	80	3000	6200	4130	□	8712211553312	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
55	I	-	-	80	3000	6200	4130	□	8712211556302	✓
55	I	-	-	80	3000	6200	4130	□	8712211556312	✓



MERCURY PL



- BK-RAL9005 / Black RAL9005 / Glossy
- WH-RAL9003 / White RAL9003 / Glossy


Scan the QR-code for the latest information

Suspended, LED luminaire for indoor, comprising:

- Luminaire head made from glass with moulded designer cover in a wave shape and moulded technopolymer moulded canopy
- Pendant tube made from metal and cable suspension on one side
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover

The luminaire is available with different light engines:

- Partially mirrored, black glass with a black ceramic edge (BLACK DRK) and integrated micro prism for efficient light distribution, glare minimisation, and excellent uniformity
- High transparent glass with a black ceramic edge (BLACK TR) and integrated micro prism diffuser for efficient light distribution, glare minimisation, and excellent uniformity
- High transparent glass with a white ceramic edge (WHITE TR) and integrated micro prism for efficient light distribution, glare minimisation, and excellent uniformity
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Through-wiring designed
- Motion sensor available with task-oriented PIR detector and daylight control. Consult factory
- Versions with suspension length 500 mm or 1500 mm. Consult factory
- Special colour versions available. Consult factory
- Design by WALTER DE SILVA




MERCURY PL M2

MERCURY PL M2 BLACK DRK

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
95	I	-	✓	80	4000	13500	1910	■	8807221723482	✓
95	I	-	✓	80	3000	13100	1850	■	8807221723382	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
95	I	-	✓	80	4000	13500	1910	■	8807221726482	✓
95	I	-	✓	80	3000	13100	1850	■	8807221726382	✓




Partially mirrored, black glass with a black ceramic edge (BLACK DRK) and integrated micro prism for efficient light diffusion, glare minimisation, and excellent uniformity

MERCURY PL M2 BLACK TR

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
34	I	-	✓	80	4000	6300	3710	■	8807211323482	✓
34	I	-	✓	80	3000	6110	3600	■	8807211323382	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
34	I	-	✓	80	4000	6300	3710	■	8807211326482	✓
34	I	-	✓	80	3000	6110	3600	■	8807211326382	✓





High transparent glass with a black ceramic edge (BLACK TR) and integrated micro prism diffuser for efficient light diffusion, glare minimisation, and excellent uniformity

MERCURY PL M2 WHITE TR

IP20 - IK04 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
34	I	-	✓	80	4000	6300	3710	□	8807211323422	✓
34	I	-	✓	80	3000	6110	3600	□	8807211323322	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
34	I	-	✓	80	4000	6300	3710	□	8807211326422	✓
34	I	-	✓	80	3000	6110	3600	□	8807211326322	✓



High transparent glass with a white ceramic edge (WHITE TR) and integrated micro prism for efficient light diffusion, glare minimisation, and excellent uniformity

SMALL LINE PL



Scan the QR-code for the latest information

- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:


- Extruded aluminium housing profile, powder-coated
- Coated die-cast aluminium end caps
- Steel sheet canopy, painted
- Slender plates with open spaces give the luminaire a uniquely delicate design
- Gear tray with high-shine multifaceted reflectors (metallized with ultra-pure aluminium) for maximum luminaire efficiency and neutral colour rendering
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Direct / indirect light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m) and canopy
- The luminaire unit is attached to the cable suspension without tools using clips
- Power is supplied via the cable suspension, no additional supply cable is required
- VDU application suitable acc. to EN 12464-1
- Sensor device available with task oriented PIR detector and daylight control
- Bluetooth sensor component for use with dimSMART! light control
- Through-wiring designed
- Continuous mounted version at www.light-performer.com
- Design by BÜRO SOMMER



ROBRI - Wekerom - Netherlands



SMALL LINE SL



SMALL LINE PL REFLECTOR

SMALL LINE PL REFLECTOR

SMALL LINE PL REFLECTOR


IP20 - IK03 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
83	I	-	✓	80	4000	14430	10910	■	1556	3115691	✓
83	I	-	✓	80	3000	14000	10590	■	1556	3115690	✓
83	I	-	✓	80	4000	14430	10910	□	1556	8726441863410	✓
83	I	-	✓	80	3000	14000	10590	□	1556	8726441863310	✓
69	I	-	✓	80	4000	12210	9250	□	1556	8726441713410	✓
69	I	-	✓	80	3000	11840	8970	□	1556	8726441713310	✓
67	I	-	✓	80	4000	11540	8730	■	1256	3115683	✓
67	I	-	✓	80	3000	11200	8470	■	1256	3115682	✓
67	I	-	✓	80	4000	11540	8730	□	1256	8726441693410	✓
67	I	-	✓	80	3000	11200	8470	□	1256	8726441693310	✓
55	I	-	✓	80	4000	9770	7400	□	1256	8726441583410	✓
55	I	-	✓	80	3000	9480	7180	□	1256	8726441583310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
83	I	-	✓	80	4000	14430	10910	■	1556	3115693	✓
83	I	-	✓	80	3000	14000	10590	■	1556	3115692	✓
83	I	-	✓	80	4000	14430	10910	□	1556	8726441866410	✓
83	I	-	✓	80	3000	14000	10590	□	1556	8726441866310	✓
69	I	-	✓	80	4000	12210	9250	□	1556	8726441716410	✓
69	I	-	✓	80	3000	11840	8970	□	1556	8726441716310	✓
67	I	-	✓	80	4000	11540	8730	■	1256	3115685	✓
67	I	-	✓	80	3000	11200	8470	■	1256	3115684	✓
67	I	-	✓	80	4000	11540	8730	□	1256	8726441696410	✓
67	I	-	✓	80	3000	11200	8470	□	1256	8726441696310	✓
55	I	-	✓	80	4000	9770	7400	□	1256	8726441586410	✓
55	I	-	✓	80	3000	9480	7180	□	1256	8726441586310	✓
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz											
83	I	-	✓	80	4000	14430	10910	■	1556	3115695	✓
83	I	-	✓	80	3000	14000	10590	■	1556	3115694	✓
83	I	-	✓	80	4000	14430	10910	□	1556	8726441868410	✓
83	I	-	✓	80	3000	14000	10590	□	1556	8726441868310	✓
69	I	-	✓	80	4000	12210	9250	□	1556	8726441718410	✓
69	I	-	✓	80	3000	11840	8970	□	1556	8726441718310	✓
67	I	-	✓	80	4000	11540	8730	■	1256	3115687	✓
67	I	-	✓	80	3000	11200	8470	■	1256	3115686	✓
67	I	-	✓	80	4000	11540	8730	□	1256	8726441698410	✓
67	I	-	✓	80	3000	11200	8470	□	1256	8726441698310	✓
55	I	-	✓	80	4000	9770	7400	□	1256	8726441588410	✓
55	I	-	✓	80	3000	9480	7180	□	1256	8726441588310	✓
Power LED - Bluetooth sensor component for use with dimSMART! light control - 220-240 V 50/60 Hz											
83	I	-	✓	80	4000	14430	10910	■	1556	3115697	✓
83	I	-	✓	80	3000	14000	10590	■	1556	3115696	✓
83	I	-	✓	80	4000	14430	10910	□	1556	8726441869410	✓
83	I	-	✓	80	3000	14000	10590	□	1556	8726441869310	✓
69	I	-	✓	80	4000	12210	9250	□	1556	8726441719410	✓
69	I	-	✓	80	3000	11840	8970	□	1556	8726441719310	✓
67	I	-	✓	80	4000	11540	8730	■	1256	3115689	✓
67	I	-	✓	80	3000	11200	8470	■	1256	3115688	✓
67	I	-	✓	80	4000	11540	8730	□	1256	8726441699410	✓
67	I	-	✓	80	3000	11200	8470	□	1256	8726441699310	✓
55	I	-	✓	80	4000	9770	7400	□	1256	8726441589410	✓
55	I	-	✓	80	3000	9480	7180	□	1256	8726441589310	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMALL LINE PL			
Remote control "Master" for versions with a sensor function		8118000257	✓
Remote control "User" for versions with a sensor function		8118000647	✓



8118000257




8118000647





FL ROUND+ 333 PL



Scan the QR-code for the latest information


- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, round LED luminaire for indoor, comprising:


- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Light distribution direct or predominantly direct
 - 2 power levels adjustable
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and $3000\text{cd}/\text{m}^2 >65^\circ$)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver
 - Through-wiring designed
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy




MERCK KGAA Offices - Darmstadt - Germany



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 RE




FL ROUND 333 PL

FL ROUND+ 333 PL MP DIRECT

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3124299	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3124289	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3124303	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3124293	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3124297	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3124287	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3124301	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3124291	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	■	3124306	✓
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	□	3124308	✓



FL ROUND+ 333 PL OP DIRECT

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DM EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3124300	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3124290	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3124296	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3124286	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3124304	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3124294	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3124298	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3124288	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3124295	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3124285	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3124302	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3124292	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3124307	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3124305	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	□	3124309	✓



FL ROUND+ 333 PL MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1060 3160	■	3123834	✓
8 25		-	-	80	3000	1260 3880	1010 3000	■	3123824	✓
8 25		-	-	80	4000	1300 4000	1060 3160	□	3123838	✓
8 25		-	-	80	3000	1260 3880	1010 3000	□	3123828	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1060 3160	■	3123832	✓
8 25		-	-	80	3000	1260 3880	1010 3000	■	3123822	✓
8 25		-	-	80	4000	1300 4000	1060 3160	□	3123836	✓
8 25		-	-	80	3000	1260 3880	1010 3000	□	3123826	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3070	■	3123841	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3070	□	3123843	✓



FL ROUND+ 333 PL OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123835	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123825	✓
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123831	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123821	✓
8 25		-	-	80	4000	1300 4000	1080 3280	□	3123839	✓
8 25		-	-	80	3000	1260 3880	1030 3110	□	3123829	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123833	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123823	✓
8 25		-	-	80	4000	1300 4000	1080 3280	■	3123830	✓
8 25		-	-	80	3000	1260 3880	1030 3110	■	3123820	✓
8 25		-	-	80	4000	1300 4000	1080 3280	□	3123837	✓
8 25		-	-	80	3000	1260 3880	1030 3110	□	3123827	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	■	3123842	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	■	3123840	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1060 3230	□	3123844	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND+ 333 PL				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585




3122586



3122587

FL ROUND+ 555 PL



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Light distribution direct or predominantly direct
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR < 19 and < 3000cd/m² > 65°)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver
 - Through-wiring designed
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy




Pibank offices - Madrid - Spain



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 RE



max 5 kg

FL ROUND+ 555 PL

FL ROUND+ 555 PL MP DIRECT

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6070	■	3124349	✓
49	I	-	-	80	3000	7760	5770	■	3124339	✓
49	I	-	-	80	4000	8000	6070	□	3124353	✓
49	I	-	-	80	3000	7760	5770	□	3124343	✓
21	I	-	ü	80	4000	3800	2890	■	3124324	✓
21	I	-	ü	80	3000	3690	2740	■	3124314	✓
21	I	-	ü	80	4000	3800	2890	□	3124328	✓
21	I	-	ü	80	3000	3690	2740	□	3124318	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6070	■	3124347	✓
49	I	-	-	80	3000	7760	5770	■	3124337	✓
49	I	-	-	80	4000	8000	6070	□	3124351	✓
49	I	-	-	80	3000	7760	5770	□	3124341	✓
21	I	-	ü	80	4000	3800	2890	■	3124322	✓
21	I	-	ü	80	3000	3690	2740	■	3124312	✓
21	I	-	ü	80	4000	3800	2890	□	3124326	✓
21	I	-	ü	80	3000	3690	2740	□	3124316	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
49	I	-	-	80	tw 2700-6500	7600	5680	■	3124356	✓
49	I	-	-	80	tw 2700-6500	7600	5680	□	3124358	✓
21	I	-	-	80	tw 2700-6500	3600	2680	■	3124331	✓
21	I	-	-	80	tw 2700-6500	3600	2680	□	3124333	✓

FL ROUND+ 555 PL OP DIRECT

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6250	■	3124350	✓
49	I	-	-	80	3000	7760	5940	■	3124340	✓
49	I	-	-	80	4000	8000	6250	■	3124346	✓
49	I	-	-	80	3000	7760	5940	■	3124336	✓
49	I	-	-	80	4000	8000	6250	□	3124354	✓
49	I	-	-	80	3000	7760	5940	□	3124344	✓
21	I	-	-	80	4000	3800	2970	■	3124325	✓
21	I	-	-	80	3000	3690	2830	■	3124315	✓
21	I	-	-	80	4000	3800	2970	■	3124321	✓
21	I	-	-	80	3000	3690	2830	■	3124311	✓
21	I	-	-	80	4000	3800	2970	□	3124329	✓
21	I	-	-	80	3000	3690	2830	□	3124319	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6250	■	3124348	✓
49	I	-	-	80	3000	7760	5940	■	3124338	✓
49	I	-	-	80	4000	8000	6250	■	3124345	✓
49	I	-	-	80	3000	7760	5940	■	3124335	✓
49	I	-	-	80	4000	8000	6250	□	3124352	✓
49	I	-	-	80	3000	7760	5940	□	3124342	✓
21	I	-	-	80	4000	3800	2970	■	3124323	✓
21	I	-	-	80	3000	3690	2830	■	3124313	✓
21	I	-	-	80	4000	3800	2970	■	3124320	✓
21	I	-	-	80	3000	3690	2830	■	3124310	✓
21	I	-	-	80	4000	3800	2970	□	3124327	✓
21	I	-	-	80	3000	3690	2830	□	3124317	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
49	I	-	-	80	tw 2700-6500	7600	5660	■	3124357	✓
49	I	-	-	80	tw 2700-6500	7600	5660	■	3124355	✓
49	I	-	-	80	tw 2700-6500	7600	5660	□	3124359	✓
21	I	-	-	80	tw 2700-6500	3600	2630	■	3124332	✓
21	I	-	-	80	tw 2700-6500	3600	2630	■	3124330	✓
21	I	-	-	80	tw 2700-6500	3600	2630	□	3124334	✓

FL ROUND+ 555 PL MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6320	■	3123934	✓
49	I	-	-	80	3000	7760	6000	■	3123924	✓
49	I	-	-	80	4000	8000	6320	□	3123938	✓
49	I	-	-	80	3000	7760	6000	□	3123928	✓
21	I	-	ü	80	4000	3800	3030	■	3123909	✓
21	I	-	ü	80	3000	3690	2880	■	3123899	✓
21	I	-	ü	80	4000	3800	3030	□	3123913	✓
21	I	-	ü	80	3000	3690	2880	□	3123903	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

49	I	-	-	80	4000	8000	6320	■	3123932	✓
49	I	-	-	80	3000	7760	6000	■	3123922	✓
49	I	-	-	80	4000	8000	6320	□	3123936	✓
49	I	-	-	80	3000	7760	6000	□	3123926	✓
21	I	-	ü	80	4000	3800	3030	■	3123907	✓
21	I	-	ü	80	3000	3690	2880	■	3123897	✓
21	I	-	ü	80	4000	3800	3030	□	3123911	✓
21	I	-	ü	80	3000	3690	2880	□	3123901	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

49	I	-	-	80	tw 2700-6500	7600	5980	■	3123941	✓
49	I	-	-	80	tw 2700-6500	7600	5980	□	3123943	✓
21	I	-	ü	80	tw 2700-6500	3600	2820	■	3123916	✓
21	I	-	ü	80	tw 2700-6500	3600	2820	□	3123918	✓

FL ROUND+ 555 PL OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49	I	-	-	80	4000	8000	6500	■	3123935	✓
49	I	-	-	80	3000	7760	6170	■	3123925	✓
49	I	-	-	80	4000	8000	6500	■	3123931	✓
49	I	-	-	80	3000	7760	6170	■	3123921	✓
49	I	-	-	80	4000	8000	6500	□	3123939	✓
49	I	-	-	80	3000	7760	6170	□	3123929	✓
21	I	-	-	80	4000	3800	3110	■	3123910	✓
21	I	-	-	80	3000	3690	2950	■	3123900	✓
21	I	-	-	80	4000	3800	3110	■	3123906	✓
21	I	-	-	80	3000	3690	2950	■	3123896	✓
21	I	-	-	80	4000	3800	3110	□	3123914	✓
21	I	-	-	80	3000	3690	2950	□	3123904	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

49	I	-	-	80	4000	8000	6500	■	3123933	✓
49	I	-	-	80	3000	7760	6170	■	3123923	✓
49	I	-	-	80	4000	8000	6500	■	3123930	✓
49	I	-	-	80	3000	7760	6170	■	3123920	✓
49	I	-	-	80	4000	8000	6500	□	3123937	✓
49	I	-	-	80	3000	7760	6170	□	3123927	✓
21	I	-	-	80	4000	3800	3110	■	3123908	✓
21	I	-	-	80	3000	3690	2950	■	3123898	✓
21	I	-	-	80	4000	3800	3110	■	3123905	✓
21	I	-	-	80	3000	3690	2950	■	3123895	✓
21	I	-	-	80	4000	3800	3110	□	3123912	✓
21	I	-	-	80	3000	3690	2950	□	3123902	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz


49	I	-	-	80	tw 2700-6500	7600	6280	■	3123942	✓
49	I	-	-	80	tw 2700-6500	7600	6280	■	3123940	✓
49	I	-	-	80	tw 2700-6500	7600	6280	□	3123944	✓
21	I	-	-	80	tw 2700-6500	3600	2960	■	3123917	✓
21	I	-	-	80	tw 2700-6500	3600	2960	■	3123915	✓
21	I	-	-	80	tw 2700-6500	3600	2960	□	3123919	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND* 555 PL				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585




3122586



3122587

FL ROUND+ 777 PL



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Light distribution direct or predominantly direct
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 (UGR < 19 and < 3000cd/m² > 65°)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver
 - Through-wiring designed
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy




Maison Relais Kindergarten - Consdorf - Luxembourg



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 RE



max 7 kg

FL ROUND+ 777 PL

FL ROUND+ 777 PL MP DIRECT

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67		-	-	80	4000	12000	9120	■	3124399	✓
67		-	-	80	3000	11640	8670	■	3124389	✓
67		-	-	80	4000	12000	9120	□	3124403	✓
67		-	-	80	3000	11640	8670	□	3124393	✓
38		-	-	80	4000	7200	5450	■	3124374	✓
38		-	✓	80	3000	6980	5180	■	3124364	✓
38		-	-	80	4000	7200	5450	□	3124378	✓
38		-	✓	80	3000	6980	5180	□	3124368	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

67		-	-	80	4000	12000	9120	■	3124397	✓
67		-	-	80	3000	11640	8670	■	3124387	✓
67		-	-	80	4000	12000	9120	□	3124401	✓
67		-	-	80	3000	11640	8670	□	3124391	✓
38		-	-	80	4000	7200	5450	■	3124372	✓
38		-	✓	80	3000	6980	5180	■	3124362	✓
38		-	-	80	4000	7200	5450	□	3124376	✓
38		-	✓	80	3000	6980	5180	□	3124366	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

67		-	-	80	tw 2700-6500	11500	8540	■	3124406	✓
67		-	-	80	tw 2700-6500	11500	8540	□	3124408	✓
38		-	-	80	tw 2700-6500	6900	5130	■	3124381	✓
38		-	-	80	tw 2700-6500	6900	5130	□	3124383	✓

FL ROUND+ 777 PL OP DIRECT

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
69		-	-	80	4000	12000	8800	■	3124400	✓
69		-	-	80	4000	12000	8800	■	3124396	✓
69		-	-	80	4000	12000	8800	□	3124404	✓
67		-	-	80	3000	11640	8360	■	3124390	✓
67		-	-	80	3000	11640	8360	■	3124386	✓
67		-	-	80	3000	11640	8360	□	3124394	✓
38		-	-	80	4000	7200	5290	■	3124375	✓
38		-	-	80	3000	6980	5030	■	3124365	✓
38		-	-	80	4000	7200	5290	■	3124371	✓
38		-	-	80	3000	6980	5030	■	3124361	✓
38		-	-	80	4000	7200	5290	□	3124379	✓
38		-	-	80	3000	6980	5030	□	3124369	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

69		-	-	80	4000	12000	8800	■	3124398	✓
69		-	-	80	4000	12000	8800	■	3124395	✓
69		-	-	80	4000	12000	8800	□	3124402	✓
67		-	-	80	3000	11640	8360	■	3124388	✓
67		-	-	80	3000	11640	8360	■	3124385	✓
67		-	-	80	3000	11640	8360	□	3124392	✓
38		-	-	80	4000	7200	5290	■	3124373	✓
38		-	-	80	3000	6980	5030	■	3124363	✓
38		-	-	80	4000	7200	5290	■	3124370	✓
38		-	-	80	3000	6980	5030	■	3124360	✓
38		-	-	80	4000	7200	5290	□	3124377	✓
38		-	-	80	3000	6980	5030	□	3124367	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

67		-	-	80	tw 2700-6500	11500	8210	■	3124407	✓
67		-	-	80	tw 2700-6500	11500	8210	■	3124405	✓
67		-	-	80	tw 2700-6500	11500	8210	□	3124409	✓
38		-	-	80	tw 2700-6500	6900	4900	■	3124382	✓
38		-	-	80	tw 2700-6500	6900	4900	■	3124380	✓
38		-	-	80	tw 2700-6500	6900	4900	□	3124384	✓

FL ROUND+ 777 PL MP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9390	■	3124086	✓
67	I	-	-	80	3000	11640	8920	■	3124076	✓
67	I	-	-	80	4000	12000	9390	□	3124090	✓
67	I	-	-	80	3000	11640	8920	□	3124080	✓
38	I	-	✓	80	4000	7200	5620	■	3124061	✓
38	I	-	✓	80	3000	6980	5340	■	3124051	✓
38	I	-	✓	80	4000	7200	5620	□	3124065	✓
38	I	-	✓	80	3000	6980	5340	□	3124055	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

67	I	-	-	80	4000	12000	9390	■	3124084	✓
67	I	-	-	80	3000	11640	8920	■	3124074	✓
67	I	-	-	80	4000	12000	9390	□	3124088	✓
67	I	-	-	80	3000	11640	8920	□	3124078	✓
38	I	-	✓	80	4000	7200	5620	■	3124059	✓
38	I	-	✓	80	3000	6980	5340	■	3124049	✓
38	I	-	✓	80	4000	7200	5620	□	3124063	✓
38	I	-	✓	80	3000	6980	5340	□	3124053	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

67	I	-	-	80	tw 2700-6500	11500	8820	■	3124093	✓
67	I	-	-	80	tw 2700-6500	11500	8820	□	3124095	✓
38	I	-	✓	80	tw 2700-6500	6900	5280	■	3124068	✓
38	I	-	✓	80	tw 2700-6500	6900	5280	□	3124070	✓

FL ROUND+ 777 PL OP CORONA

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
67	I	-	-	80	4000	12000	9040	■	3124087	✓
67	I	-	-	80	3000	11640	8590	■	3124077	✓
67	I	-	-	80	4000	12000	9040	■	3124083	✓
67	I	-	-	80	3000	11640	8590	■	3124073	✓
67	I	-	-	80	4000	12000	9040	□	3124091	✓
67	I	-	-	80	3000	11640	8590	□	3124081	✓
38	I	-	-	80	4000	7200	5450	■	3124062	✓
38	I	-	-	80	3000	6980	5180	■	3124052	✓
38	I	-	-	80	4000	7200	5450	■	3124058	✓
38	I	-	-	80	3000	6980	5180	■	3124048	✓
38	I	-	-	80	4000	7200	5450	□	3124066	✓
38	I	-	-	80	3000	6980	5180	□	3124056	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

67	I	-	-	80	4000	12000	9040	■	3124085	✓
67	I	-	-	80	3000	11640	8590	■	3124075	✓
67	I	-	-	80	4000	12000	9040	■	3124082	✓
67	I	-	-	80	3000	11640	8590	■	3124072	✓
67	I	-	-	80	4000	12000	9040	□	3124089	✓
67	I	-	-	80	3000	11640	8590	□	3124079	✓
38	I	-	-	80	4000	7200	5450	■	3124060	✓
38	I	-	-	80	3000	6980	5180	■	3124050	✓
38	I	-	-	80	4000	7200	5450	■	3124057	✓
38	I	-	-	80	3000	6980	5180	■	3124047	✓
38	I	-	-	80	4000	7200	5450	□	3124064	✓
38	I	-	-	80	3000	6980	5180	□	3124054	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz


67	I	-	-	80	tw 2700-6500	11500	9080	■	3124094	✓
67	I	-	-	80	tw 2700-6500	11500	9080	■	3124092	✓
67	I	-	-	80	tw 2700-6500	11500	9080	□	3124096	✓
38	I	-	-	80	tw 2700-6500	6900	5440	■	3124069	✓
38	I	-	-	80	tw 2700-6500	6900	5440	■	3124067	✓
38	I	-	-	80	tw 2700-6500	6900	5440	□	3124071	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	EURO	UKCA
FL ROUND* 777 PL				
External Casambi module	■	3122585	213,00	✓
Single wireless wall switch	□	3122586	189,00	✓
Double wireless wall switch	□	3122587	194,00	✓



3122585




3122586



3122587

FL SQUARE PL




Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 / Textured

Suspended, square LED luminaire for indoor, comprising:

- Extruded aluminium housing profile, powder-coated
- LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the diffuser
- Direct light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m), transparent power cable and canopy
- Built-in driver



FL SQUARE SM



FL SQUARE 300 PL OP

FL SQUARE 300 PL OP


IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIV EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2260	<input type="checkbox"/>	8300291233400	✓
19	I	-	-	80	3000	2900	2200	<input type="checkbox"/>	8300291233300	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
19	I	-	-	80	4000	3000	2260	<input type="checkbox"/>	8300291236400	✓
19	I	-	-	80	3000	2900	2200	<input type="checkbox"/>	8300291236300	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FL SQUARE PL			
Casambi module for installation		3122584	✓
Single wireless wall switch	<input type="checkbox"/>	3122586	✓
Double wireless wall switch	<input type="checkbox"/>	3122587	✓



3122586




3122587



MERCK KGAA Offices - Darmstadt - Germany

FLEXILED PL





Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:

- Housing made of form-stable 1.0 mm sheet steel
 - Impact-resistant, impression-resistant powder coating
- The luminaire is available with different light engines:
- Black reflector ensures maximum efficiency and high visual comfort
 - Opal PMMA diffuser for optimal light distribution and uniformity
 - Barrier-free light
 - Glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <math><3000\text{cd}/\text{m}^2 >65^\circ</math>)
 - UGR <math><19</math> for all luminositities
 - Direct / indirect light distribution
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Reliable and low-maintenance 50,000h L80B10
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - 2 power levels adjustable
 - Through-wiring designed
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy
 - Configurable via LIGHT-PERFORMER®
 - Special colour versions available. Consult factory



FLEXILED PL

FLEXILED PL



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

FLEXILED PL LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
61	I	-	✓	80	4000	10910	9050	□	1500	3123687	✓
52	I	-	✓	80	4000	9320	7740	□	1200	3123684	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
61	I	-	✓	80	4000	10910	9050	□	1500	3123693	✓
52	I	-	✓	80	4000	9320	7740	□	1200	3123690	✓



FLEXILED PL MICROPRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	-	-	80	4000	4200	3690	□	1500	3123686	✓
70	I	-	-	80	4000	11500	9940	□	1500	3123686	✓
19	I	-	-	80	4000	3360	2930	□	1200	3123683	✓
60	I	-	-	80	4000	9840	8260	□	1200	3123683	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
24	I	-	-	80	4000	4200	3690	□	1500	3123692	✓
70	I	-	-	80	4000	11500	9940	□	1500	3123692	✓
19	I	-	-	80	4000	3360	2930	□	1200	3123689	✓
60	I	-	-	80	4000	9840	8260	□	1200	3123689	✓



FLEXILED PL OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	-	-	80	4000	4200	3770	□	1500	3123685	✓
70	I	-	-	80	4000	11500	10150	□	1500	3123685	✓
19	I	-	-	80	4000	3360	2990	□	1200	3123682	✓
60	I	-	-	80	4000	9840	8460	□	1200	3123682	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
24	I	-	-	80	4000	4200	3770	□	1500	3123691	✓
70	I	-	-	80	4000	11500	10150	□	1500	3123691	✓
19	I	-	-	80	4000	3360	2990	□	1200	3123688	✓
60	I	-	-	80	4000	9840	8460	□	1200	3123688	✓



SL629 PL



Warmteservice Group headquarters - Amsterdam - Netherlands



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:


- Steel sheet housing, die-cast aluminium end caps, polyester powder coat finish
- Prismatic diffuser for efficient light distribution, glare reduction and a high level of uniformity
- Light distribution direct or direct/ indirect
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- VDU application suitable acc. to EN 12464-1
- Barrier-free light
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Light engine can be replaced by means of a slide-in mechanism
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Complete with steel suspension cable (1.5 m), transparent power cable and canopy
- Through-wiring designed
- Motion sensor available with task-oriented PIR detector and daylight control. Consult factory
- Special colour versions available. Consult factory




SL629 AB



SL630 AB



SL629 PL PRISM



SL629 PL PRISM

SL629 PL PRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
31	I	✓	✓	80	4000	6000	4000	■	1544	8629261403430	✓
31	I	✓	✓	80	3000	5820	3880	■	1544	8629261403330	✓
31	I	✓	✓	80	4000	6000	4000	□	1544	8629261403410	✓
31	I	✓	✓	80	3000	5820	3880	□	1544	8629261403310	✓
26	I	✓	✓	80	4000	4700	3220	■	1244	8629261283430	✓
26	I	✓	✓	80	3000	4560	3120	■	1244	8629261283330	✓
26	I	✓	✓	80	4000	4700	3220	□	1244	8629261283410	✓
26	I	✓	✓	80	3000	4560	3120	□	1244	8629261283310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

31	I	-	✓	80	4000	6000	4000	■	1544	8629261406430	✓
31	I	-	✓	80	3000	5820	3880	■	1544	8629261406330	✓
31	I	-	✓	80	4000	6000	4000	□	1544	8629261406410	✓
31	I	-	✓	80	3000	5820	3880	□	1544	8629261406310	✓
26	I	-	✓	80	4000	4700	3220	■	1244	8629261286430	✓
26	I	-	✓	80	3000	4560	3120	■	1244	8629261286330	✓
26	I	-	✓	80	4000	4700	3220	□	1244	8629261286410	✓
26	I	-	✓	80	3000	4560	3120	□	1244	8629261286310	✓

SL629 PL PRISM D/I

IP20 - IK05 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
69	I	-	✓	90	4000	11310	8100	■	1544	3119898	✓
69	I	-	✓	90	4000	11310	8100	□	1544	3112452	✓
69	I	-	✓	90	3000	10960	7860	□	1544	3112450	✓
69	I	✓	✓	80	4000	12000	8680	■	1544	8629461783430	✓
69	I	✓	✓	80	3000	11640	8420	■	1544	8629461783330	✓
69	I	-	✓	80	4000	12000	8680	■	1544	3119886	✓
69	I	-	✓	80	3000	11640	8420	■	1544	3119888	✓
69	I	✓	✓	80	4000	12000	8680	□	1544	8629461783410	✓
69	I	✓	✓	80	3000	11640	8420	□	1544	8629461783310	✓
54	I	-	✓	90	4000	8350	6250	■	1244	3119897	✓
54	I	-	✓	90	4000	8350	6250	□	1244	3112480	✓
54	I	-	✓	90	3000	8100	5970	□	1244	3112448	✓
54	I	✓	✓	80	4000	8900	6830	■	1244	8629461543430	✓
54	I	✓	✓	80	3000	8630	6630	■	1244	8629461543330	✓
54	I	-	✓	80	4000	8900	6830	■	1244	3119890	✓
54	I	-	✓	80	3000	8630	6630	■	1244	3119892	✓
54	I	✓	✓	80	4000	8900	6830	□	1244	8629461543410	✓
54	I	✓	✓	80	3000	8630	6630	□	1244	8629461543310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

69	I	-	✓	90	4000	11310	8100	□	1544	3112453	✓
69	I	-	✓	90	3000	10960	7860	□	1544	3112451	✓
69	I	✓	✓	80	4000	12000	8680	■	1544	8629461786430	✓
69	I	✓	✓	80	3000	11640	8420	■	1544	8629461786330	✓
69	I	-	✓	80	4000	12000	8680	■	1544	3119885	✓
69	I	-	✓	80	3000	11640	8420	■	1544	3119887	✓
69	I	✓	✓	80	4000	12000	8680	□	1544	8629461786410	✓
69	I	✓	✓	80	3000	11640	8420	□	1544	8629461786310	✓
54	I	-	✓	90	4000	8350	6250	□	1244	3112481	✓
54	I	-	✓	90	3000	8100	5970	□	1244	3112449	✓
54	I	-	✓	80	4000	8900	6830	■	1244	8629461546430	✓
54	I	-	✓	80	3000	8630	6630	■	1244	8629461546330	✓
54	I	-	✓	80	4000	8900	6830	■	1244	3119889	✓
54	I	-	✓	80	3000	8630	6630	■	1244	3119891	✓
54	I	-	✓	80	4000	8900	6830	□	1244	8629461546410	✓
54	I	-	✓	80	3000	8630	6630	□	1244	8629461546310	✓



SL629 PL CM



- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Scan the QR-code for the latest information

- Suspended luminaire systems, consisting of one or more luminaire modules and individually selectable components
- Housing made of steel sheet
 - Die-cast aluminium connecting elements and end pieces, powder-coated
 - Prismatic diffuser for efficient light distribution, glare reduction and a high level of uniformity
 - Light distribution direct or direct/ indirect
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Light engine can be replaced by means of a slide-in mechanism
 - VDU application suitable acc. to EN 12464-1
 - Special colour versions available. Consult factory
 - Please have a look for the components at the list of accessories




Haus der Höfe - Bonn - Germany




SL629 AB



SL630 AB



SL629 PL CM PRISM



SL629 PL CM PRISM



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

SL629 PL CM PRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
31	I	✓	✓	80	4000	6000	4000	■	1538	8629261403438	✓
31	I	✓	✓	80	3000	5820	3880	■	1538	8629261403338	✓
31	I	✓	✓	80	4000	6000	4000	□	1538	8629261403418	✓
31	I	✓	✓	80	3000	5820	3880	□	1538	8629261403318	✓
26	I	✓	✓	80	4000	4700	3220	■	1238	8629261283438	✓
26	I	✓	✓	80	3000	4560	3120	■	1238	8629261283338	✓
26	I	✓	✓	80	4000	4700	3220	□	1238	8629261283418	✓
26	I	✓	✓	80	3000	4560	3120	□	1238	8629261283318	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz

31	I	-	✓	80	4000	6000	4000	■	1538	8629261406438	✓
31	I	-	✓	80	3000	5820	3880	■	1538	8629261406338	✓
31	I	-	✓	80	4000	6000	4000	□	1538	8629261406418	✓
31	I	-	✓	80	3000	5820	3880	□	1538	8629261406318	✓
26	I	-	✓	80	4000	4700	3220	■	1238	8629261286438	✓
26	I	-	✓	80	3000	4560	3120	■	1238	8629261286338	✓
26	I	-	✓	80	4000	4700	3220	□	1238	8629261286418	✓
26	I	-	✓	80	3000	4560	3120	□	1238	8629261286318	✓

SL629 PL CM PRISM D/I

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
69	I	-	✓	90	4000	11310	8100	□	1538	3112446	✓
69	I	-	✓	90	3000	10960	7860	□	1538	3112444	✓
69	I	✓	✓	80	4000	12000	8680	■	1538	8629461783438	✓
69	I	✓	✓	80	3000	11640	8420	■	1538	8629461783338	✓
69	I	✓	✓	80	4000	12000	8680	□	1538	8629461783418	✓
69	I	✓	✓	80	3000	11640	8420	□	1538	8629461783318	✓
54	I	-	✓	90	4000	8350	6250	□	1238	3112442	✓
54	I	-	✓	90	3000	8100	5970	□	1238	3112440	✓
54	I	✓	✓	80	4000	8900	6830	■	1238	8629461543438	✓
54	I	✓	✓	80	3000	8630	6630	■	1238	8629461543338	✓
54	I	✓	✓	80	4000	8900	6830	□	1238	8629461543418	✓
54	I	✓	✓	80	3000	8630	6630	□	1238	8629461543318	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz

69	I	-	✓	90	4000	11310	8100	□	1538	3112447	✓
69	I	-	✓	90	3000	10960	7860	□	1538	3112445	✓
69	I	✓	✓	80	4000	12000	8680	■	1538	8629461786438	✓
69	I	✓	✓	80	3000	11640	8420	■	1538	8629461786338	✓
69	I	✓	✓	80	4000	12000	8680	□	1538	8629461786418	✓
69	I	✓	✓	80	3000	11640	8420	□	1538	8629461786318	✓
54	I	-	✓	90	4000	8350	6250	□	1238	3112443	✓
54	I	-	✓	90	3000	8100	5970	□	1238	3112441	✓
54	I	-	✓	80	4000	8900	6830	■	1238	8629461546438	✓
54	I	-	✓	80	3000	8630	6630	■	1238	8629461546338	✓
54	I	-	✓	80	4000	8900	6830	□	1238	8629461546418	✓
54	I	-	✓	80	3000	8630	6630	□	1238	8629461546318	✓

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SL629PL CM			
SL629 Starter kit/ending kit RAL9006	■	862932230	✓
SL629 Starter kit/ending kit RAL9016	□	862932210	✓
SL629 Connection kit RAL9016	□	862932310	✓
SL629 Connection kit RAL9006	■	862932330	✓



862932230



862932210



862932310




862932330

NOTES:

For a light strip consisting of two luminaire modules, only one start/end kit is required.
A connection kit is required for each additional light module.

SL713PL ROUND LED




Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured


- Suspended, round LED luminaire for indoor, comprising:
- Die-cast aluminium housing and canopy, painted
 - Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Direct / indirect light distribution
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - VDU application suitable acc. to EN 12464-1
 - Barrier-free light
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Complete with steel suspension cable (1.5 m), transparent power cord and canopy
 - Built-in driver
 - Special colour versions available. Consult factory




SL713AB ROUND LED



SL713PL ROUND LED MICROPRISMATIC S



SL713PL ROUND LED MICROPRISMATIC M



SL713PL ROUND LED MICROPRISMATIC L

SL713PL ROUND LED MICROPRISMATIC S

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8		-	✓	80	4000	1500	1140	■	3122343	✓
18.5		-	✓	80	3000	3200	2430	■	3122337	✓
8		-	✓	80	4000	1500	1140	■	3122341	✓
18.5		-	✓	80	3000	3200	2430	■	3122335	✓
8		-	✓	80	4000	1500	1140	□	3122345	✓
18.5		-	✓	80	3000	3200	2430	□	3122339	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8		-	✓	80	4000	1500	1140	■	3122342	✓
18.5		-	✓	80	3000	3200	2430	■	3122336	✓
8		-	✓	80	4000	1500	1140	■	3122340	✓
18.5		-	✓	80	3000	3200	2430	■	3122334	✓
8		-	✓	80	4000	1500	1140	□	3122344	✓
18.5		-	✓	80	3000	3200	2430	□	3122338	✓

SL713PL ROUND LED MICROPRISMATIC M

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
49		-	✓	80	4000	8000	6460	■	8713461513430	✓
49		-	✓	80	3000	7760	6260	■	8713461513330	✓
49		-	✓	80	4000	8000	6460	■	3122391	✓
49		-	✓	80	3000	7760	6260	■	3122389	✓
49		-	✓	80	4000	8000	6460	□	8713461513410	✓
49		-	✓	80	3000	7760	6260	□	8713461513310	✓
26		-	✓	80	4000	4500	3670	■	8713461343430	✓
26		-	✓	80	3000	4370	3560	■	8713461343330	✓
26		-	✓	80	4000	4500	3670	■	3122387	✓
26		-	✓	80	3000	4370	3560	■	3122385	✓
26		-	✓	80	4000	4500	3670	□	8713461343410	✓
26		-	✓	80	3000	4370	3560	□	8713461343310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
49		-	✓	80	4000	8000	6460	■	8713461516430	✓
49		-	✓	80	3000	7760	6260	■	8713461516330	✓
49		-	✓	80	4000	8000	6460	■	3122390	✓
49		-	✓	80	3000	7760	6260	■	3122388	✓
49		-	✓	80	4000	8000	6460	□	8713461516410	✓
49		-	✓	80	3000	7760	6260	□	8713461516310	✓
26		-	✓	80	4000	4500	3670	■	8713461346430	✓
26		-	✓	80	3000	4370	3560	■	8713461346330	✓
26		-	✓	80	4000	4500	3670	■	3122386	✓
26		-	✓	80	3000	4370	3560	■	3122384	✓
26		-	✓	80	4000	4500	3670	□	8713461346410	✓
26		-	✓	80	3000	4370	3560	□	8713461346310	✓

SL713PL ROUND LED MICROPRISMATIC L

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz


70	I	-	✓	80	4000	11000	9200	■	8713461763430	✓
70	I	-	✓	80	3000	10670	8930	■	8713461763330	✓
70	I	-	✓	80	4000	11000	9200	■	3122298	✓
70	I	-	✓	80	3000	10670	8930	■	3122296	✓
70	I	-	✓	80	4000	11000	9200	□	8713461763410	✓
70	I	-	✓	80	3000	10670	8930	□	8713461763310	✓
46	I	-	✓	80	4000	8000	6400	■	8713461483430	✓
46	I	-	✓	80	3000	7760	6210	■	8713461483330	✓
46	I	-	✓	80	4000	8000	6400	■	3122294	✓
46	I	-	✓	80	3000	7760	6210	■	3122292	✓
46	I	-	✓	80	4000	8000	6400	□	8713461483410	✓
46	I	-	✓	80	3000	7760	6210	□	8713461483310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz


70	I	-	✓	80	4000	11000	9200	■	8713461766430	✓
70	I	-	✓	80	3000	10670	8930	■	8713461766330	✓
70	I	-	✓	80	4000	11000	9200	■	3122297	✓
70	I	-	✓	80	3000	10670	8930	■	3122295	✓
70	I	-	✓	80	4000	11000	9200	□	8713461766410	✓
70	I	-	✓	80	3000	10670	8930	□	8713461766310	✓
46	I	-	✓	80	4000	8000	6400	■	8713461486430	✓
46	I	-	✓	80	3000	7760	6210	■	8713461486330	✓
46	I	-	✓	80	4000	8000	6400	■	3122293	✓
46	I	-	✓	80	3000	7760	6210	■	3122291	✓
46	I	-	✓	80	4000	8000	6400	□	8713461486410	✓
46	I	-	✓	80	3000	7760	6210	□	8713461486310	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
SL713PL ROUND LED			
Casambi module for installation		3122584	✓
Single wireless wall switch	■	3122586	✓
Double wireless wall switch	■	3122587	✓



3122586



3122587





Microsoft Headquarters - Munich - Germany

SL713+ PL



Drägerwerk Offices - Lübeck - Germany





Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:

- Extruded aluminium housing profile, powder-coated
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician)
- Direct / indirect light distribution
- VDU application suitable acc. to EN 12464-1
- Barrier-free light
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through-wiring designed
- With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters
- In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
- In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8)
- Complete with steel suspension cable (1.5 m), transparent power cord and canopy
- Special colour versions available. Consult factory




SL713+ PL MP S/C


SL713+ PL MP S/C

SL713+ PL MP S/C

IP20 - IK05 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DMX DIM 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
69	I	-	✓	80	4000	11010	9010	■	1562	3111530	✓
69	I	-	✓	80	3000	10450	8950	■	1562	3111529	✓
69	I	-	✓	80	4000	11010	9010	■	1562	3120882	✓
69	I	-	✓	80	3000	10450	8950	■	1562	3120881	✓
69	I	-	✓	80	4000	11010	9010	□	1562	3111524	✓
69	I	-	✓	80	3000	10450	8950	□	1562	3111523	✓
53	I	-	✓	80	4000	8510	6930	■	1262	3111527	✓
53	I	-	✓	80	3000	8070	6930	■	1262	3111526	✓
53	I	-	✓	80	4000	8510	6930	■	1262	3120880	✓
53	I	-	✓	80	3000	8070	6930	■	1262	3120879	✓
53	I	-	✓	80	4000	8510	6930	□	1262	3111521	✓
53	I	-	✓	80	3000	8070	6930	□	1262	3111520	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
69	I	-	✓	80	4000	11010	9010	■	1562	3111598	✓
69	I	-	✓	80	3000	10450	8950	■	1562	3111597	✓
69	I	-	✓	80	4000	11010	9010	■	1562	3120886	✓
69	I	-	✓	80	3000	10450	8950	■	1562	3120885	✓
69	I	-	✓	80	4000	11010	9010	□	1562	3111594	✓
69	I	-	✓	80	3000	10450	8950	□	1562	3111593	✓
53	I	-	✓	80	4000	8510	6930	■	1262	3111596	✓
53	I	-	✓	80	3000	8070	6930	■	1262	3111595	✓
53	I	-	✓	80	4000	8510	6930	■	1262	3120884	✓
53	I	-	✓	80	3000	8070	6930	■	1262	3120883	✓
53	I	-	✓	80	4000	8510	6930	□	1262	3111592	✓
53	I	-	✓	80	3000	8070	6930	□	1262	3111591	✓
Power LED - dimmable DALI with bluetooth control - 220-240 V 50/60 Hz											
69	I	-	✓	80	4000	11010	9010	■	1562	3112744	✓
69	I	-	✓	80	3000	10450	8950	■	1562	3112743	✓
69	I	-	✓	80	4000	11010	9010	□	1562	3112740	✓
69	I	-	✓	80	3000	10450	8950	□	1562	3112739	✓
53	I	-	✓	80	4000	8510	6930	■	1262	3112742	✓
53	I	-	✓	80	3000	8070	6930	■	1262	3112741	✓
53	I	-	✓	80	4000	8510	6930	□	1262	3112738	✓
53	I	-	✓	80	3000	8070	6930	□	1262	3112737	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz											
67	I	-	✓	80	tw 2700-6500	10390	8040	■	1562	3111531	✓
67	I	-	✓	80	tw 2700-6500	10390	8040	□	1562	3111525	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	■	1262	3111528	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	□	1262	3111522	✓
TunableWhite Power LED - HCL with bluetooth control - 220-240 V 50/60 Hz											
67	I	-	✓	80	tw 2700-6500	10390	8040	■	1562	3112423	✓
67	I	-	✓	80	tw 2700-6500	10390	8040	□	1562	3112421	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	■	1262	3112422	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	□	1262	3112420	✓
TunableWhite Power LED - dimmable DALI DT8 with bluetooth control - 220-240 V 50/60 Hz											
67	I	-	✓	80	tw 2700-6500	10390	8040	■	1562	3112748	✓
67	I	-	✓	80	tw 2700-6500	10390	8040	□	1562	3112746	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	■	1262	3112747	✓
53	I	-	✓	80	tw 2700-6500	8130	6320	□	1262	3112745	✓



Fluxus Foundation - Zaandam - Netherlands

SL720+ PL






Scan the QR-code for the latest information


- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Suspended, LED luminaire for indoor, comprising:

- Extruded aluminium housing profile, powder-coated
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician)
- Direct / indirect light distribution
- VDU application suitable acc. to EN 12464-1
- Barrier-free light
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through-wiring designed
- With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters
- In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
- In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8)
- Sensor device available with task oriented PIR detector and daylight control
- Complete with steel suspension cable (1.5 m), transparent power cord and canopy
- Special colour versions available. Consult factory



SL720+ PL MP S/C



SL720+ PL MP S/C

SL720+ PL MP S/C

IP20 - IK05 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
69	I	-	✓	80	4000	11010	9010	■	1538	3115958	✓
69	I	-	✓	80	3000	10450	8950	■	1538	3115957	✓
69	I	-	✓	80	4000	11010	9010	□	1538	3115950	✓
69	I	-	✓	80	3000	10450	8950	□	1538	3115949	✓
53	I	-	✓	80	4000	8510	6930	■	1238	3115954	✓
53	I	-	✓	80	3000	8070	6930	■	1238	3115953	✓
53	I	-	✓	80	4000	8510	6930	□	1238	3115946	✓
53	I	-	✓	80	3000	8070	6930	□	1238	3115945	✓
47	I	-	✓	80	4000	7750	6340	■	1538	3115960	✓
47	I	-	✓	80	3000	7360	6280	■	1538	3115959	✓
47	I	-	✓	80	4000	7750	6340	□	1538	3115952	✓
47	I	-	✓	80	3000	7360	6280	□	1538	3115951	✓
37	I	-	✓	80	4000	6170	5000	■	1238	3115956	✓
37	I	-	✓	80	3000	5860	5010	■	1238	3115955	✓
37	I	-	✓	80	4000	6170	5000	□	1238	3115948	✓
37	I	-	✓	80	3000	5860	5010	□	1238	3115947	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

69	I	-	✓	80	4000	11010	9010	■	1538	3111810	✓
69	I	-	✓	80	3000	10450	8950	■	1538	3111809	✓
69	I	-	✓	80	4000	11010	9010	□	1538	3111806	✓
69	I	-	✓	80	3000	10450	8950	□	1538	3111805	✓
53	I	-	✓	80	4000	8510	6930	■	1238	3111808	✓
53	I	-	✓	80	3000	8070	6930	■	1238	3111807	✓
53	I	-	✓	80	4000	8510	6930	□	1238	3111804	✓
53	I	-	✓	80	3000	8070	6930	□	1238	3111803	✓
47	I	-	✓	80	4000	7750	6340	■	1538	3113286	✓
47	I	-	✓	80	3000	7360	6280	■	1538	3113285	✓
47	I	-	✓	80	4000	7750	6340	□	1538	3113282	✓
47	I	-	✓	80	3000	7360	6280	□	1538	3113281	✓
37	I	-	✓	80	4000	6170	5000	■	1238	3113284	✓
37	I	-	✓	80	3000	5860	5010	■	1238	3113283	✓
37	I	-	✓	80	4000	6170	5000	□	1238	3113280	✓
37	I	-	✓	80	3000	5860	5010	□	1238	3113279	✓

Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz

69	I	-	✓	80	4000	11010	9010	■	1538	3115942	✓
69	I	-	✓	80	3000	10450	8950	■	1538	3115941	✓
69	I	-	✓	80	4000	11010	9010	□	1538	3115934	✓
69	I	-	✓	80	3000	10450	8950	□	1538	3115933	✓
53	I	-	✓	80	4000	8510	6930	■	1238	3115938	✓
53	I	-	✓	80	3000	8070	6930	■	1238	3115937	✓
53	I	-	✓	80	4000	8510	6930	□	1238	3115930	✓
53	I	-	✓	80	3000	8070	6930	□	1238	3115929	✓
47	I	-	✓	80	4000	7750	6340	■	1538	3115944	✓
47	I	-	✓	80	3000	7360	6280	■	1538	3115943	✓
47	I	-	✓	80	4000	7750	6340	□	1538	3115936	✓
47	I	-	✓	80	3000	7360	6280	□	1538	3115935	✓
37	I	-	✓	80	4000	6170	5000	■	1238	3115940	✓
37	I	-	✓	80	3000	5860	5010	■	1238	3115939	✓
37	I	-	✓	80	4000	6170	5000	□	1238	3115932	✓
37	I	-	✓	80	3000	5860	5010	□	1238	3115931	✓



Power LED - dimmable DALI with bluetooth control - 220-240 V 50/60 Hz

69		-	✓	80	4000	11010	9010	■	1538	3113300	✓
69		-	✓	80	3000	10450	8950	■	1538	3113299	✓
69		-	✓	80	4000	11010	9010	□	1538	3113292	✓
69		-	✓	80	3000	10450	8950	□	1538	3113291	✓
53		-	✓	80	4000	8510	6930	■	1238	3113296	✓
53		-	✓	80	3000	8070	6930	■	1238	3113295	✓
53		-	✓	80	4000	8510	6930	□	1238	3113288	✓
53		-	✓	80	3000	8070	6930	□	1238	3113287	✓
47		-	✓	80	4000	7750	6340	■	1538	3113302	✓
47		-	✓	80	3000	7360	6280	■	1538	3113301	✓
47		-	✓	80	4000	7750	6340	□	1538	3113294	✓
47		-	✓	80	3000	7360	6280	□	1538	3113293	✓
37		-	✓	80	4000	6170	5000	■	1238	3113298	✓
37		-	✓	80	3000	5860	5010	■	1238	3113297	✓
37		-	✓	80	4000	6170	5000	□	1238	3113290	✓
37		-	✓	80	3000	5860	5010	□	1238	3113289	✓

TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3111770	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3111764	✓
53		-	✓	80	tw 2700-6500	8130	6320	■	1238	3111767	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3111761	✓

TunableWhite Power LED - HCL with bluetooth control - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3113306	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3113304	✓
53		-	✓	80	tw 2700-6500	8130	6320	■	1238	3113305	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3113303	✓

TunableWhite Power LED - dimmable DALI DT8 with daylight sensor and PIR detector - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3115963	✓
67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3115964	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3115962	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3115961	✓

TunableWhite Power LED - dimmable DALI DT8 with bluetooth control - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3113310	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3113308	✓
53		-	✓	80	tw 2700-6500	8130	6320	■	1238	3113309	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3113307	✓


TunableWhite Power LED - DALI DT8 with bluetooth control - daylight sensor + PIR detector - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3115972	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3115970	✓
53		-	✓	80	tw 2700-6500	8130	6320	■	1238	3115971	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3115969	✓

TunableWhite Power LED - HCL with daylight sensor and PIR-detector - 220-240 V 50/60 Hz

67		-	✓	80	tw 2700-6500	10390	8040	■	1538	3115968	✓
67		-	✓	80	tw 2700-6500	10390	8040	□	1538	3115966	✓
53		-	✓	80	tw 2700-6500	8130	6320	■	1238	3115967	✓
53		-	✓	80	tw 2700-6500	8130	6320	□	1238	3115965	✓

DL ROUND



Scan the QR-code for the latest information

- WH-87 / White / Textured
- SL-10 / Silver / Textured

Recessed, modular, round LED downlight for indoor, comprising:


- LED module, die-cast aluminium heat sink, reflector with integrated ceiling trim, diffuser and external supply unit
- All components can be tool-less replaced laterly
- High-shine modular reflector with integrated ceiling trim made of metallised injection-moulded ABS with light-tight connection to LED module
- Integrated diffuser grants an optimised uniformity
- Die-cast aluminium heat sink with Fast™ (Flexible air stream technology) cooling system grants an excellent dissipation and thermal management
- Built-in driver
- DALI dimmable
- Suitable for ceiling tile thickness from 1-25 mm
- Quick and toolless installation

Options:


- Wieland connector GST18i3
- Emergency 1h
- Emergency 3h
- High-shine modular radial louvre reflector with integrated ceiling frame made of metallised injection-moulded ABS with light-tight connection to LED module
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module and matte plastic pane (IP54)
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module



Musiikkitalo Music Centre - Helsinki - Finland



DL ROUND
MIDI



DL ROUND
MAXI

DL ROUND MIDI

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114246	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108964	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114248	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108966	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114240	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108958	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114242	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108960	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114250	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108968	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114251	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108969	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114244	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108962	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114245	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108963	✓

Power LED - Emergency 1/3h - 220-240 V 50/60 Hz

13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114247	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108965	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114249	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108967	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114241	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108959	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114243	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108961	✓

DL ROUND MIDI WIELAND

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114300	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3110056	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114301	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3110057	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114298	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3110054	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114299	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3110055	✓



DL ROUND MAXI

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3112233	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3108976	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114256	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3108978	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3111953	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108970	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3111834	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108972	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3112232	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3108980	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114258	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3108981	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114254	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108974	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114135	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108975	✓

Power LED - Emergency 1/3h - 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114255	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3108977	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114257	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3108979	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114252	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108971	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114253	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108973	✓

DL ROUND MAXI WIELAND


IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114304	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3110060	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114305	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3110061	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114302	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3110058	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114303	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3110059	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
DL ROUND MIDI			
White reflector DL ROUND MIDI		3109006	✓
Black reflector DL ROUND MIDI		3109007	✓
Louvre reflector DL ROUND MIDI		3109008	✓
Matte plastic panel (IP54) DL ROUND MIDI		3109009	✓
DL ROUND MAXI			
White reflector DL ROUND MAXI		3109010	✓
Black reflector DL ROUND MAXI		3109011	✓
Louvre reflector DL ROUND MAXI		3109012	✓
Matte plastic panel (IP54) DL ROUND MAXI		3109013	✓



DL SQUARE



Scan the QR-code for the latest information

- WH-87 / White / Textured
- SL-10 / Silver / Textured

Recessed, modular, LED downlight for indoor, comprising:


- LED module, die-cast aluminium heat sink, reflector with integrated ceiling trim, diffuser and external supply unit
- All components can be tool-less replaced laterly
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module and matte plastic pane (IP54)
- Integrated diffuser grants an optimised uniformity
- Die-cast aluminium heat sink with Fast™ (Flexible air stream technology) cooling system grants an excellent dissipation and thermal management
- Built-in driver
- DALI dimmable
- Suitable for ceiling tile thickness from 1-25 mm
- Quick and toolless installation
- Wieland connector GST18i3
- Emergency 1h
- Emergency 3h

Options:


- High-shine modular radial louvre reflector with integrated ceiling frame made of metallised injection-moulded ABS with light-tight connection to LED module
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module



Microsoft headquarters - Monaco - Germany




DL SQUARE
MIDI



DL SQUARE
MAXI

DL SQUARE MIDI

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12864-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114265	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108988	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114131	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108990	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114259	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108982	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114261	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108984	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz


13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114268	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108992	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114269	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108993	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114263	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108986	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114264	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108987	✓

Power LED - Emergency 1/3h - 220-240 V 50/60 Hz

13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114266	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3108989	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114267	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3108991	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114260	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3108983	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114262	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3108985	✓

DL SQUARE MIDI WIELAND

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12864-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3114308	✓
13	I	-	-	90	3000	1900	1640	<input type="checkbox"/>	3110064	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3114309	✓
13	I	-	-	80	4000	2100	1780	<input type="checkbox"/>	3110065	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3114306	✓
9	I	-	-	90	3000	1400	1180	<input type="checkbox"/>	3110062	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3114307	✓
9	I	-	-	80	4000	1500	1280	<input type="checkbox"/>	3110063	✓

DL SQUARE MAXI

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114276	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3109000	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114294	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3109002	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114270	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108994	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114272	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108996	✓



Power LED - dimmable DALI 220-240 V 50/60 Hz

21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114296	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3109004	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114297	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3109005	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114274	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108998	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114275	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108999	✓

Power LED - Emergency 1/3h - 220-240 V 50/60 Hz

21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114277	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3109001	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114295	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3109003	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114271	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3108995	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114273	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3108997	✓

DL SQUARE MAXI WIELAND




IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3114312	✓
21	I	-	-	90	3000	3300	2895	<input type="checkbox"/>	3110068	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3114313	✓
21	I	-	-	80	4000	3500	3130	<input type="checkbox"/>	3110069	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3114310	✓
15	I	-	-	90	3000	2350	2080	<input type="checkbox"/>	3110066	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3114311	✓
15	I	-	-	80	4000	2500	2260	<input type="checkbox"/>	3110067	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
DL SQUARE MIDI			
Louvre reflector DL SQUARE MIDI		3109016	✓
White reflector DL SQUARE MIDI		3109014	✓
White optic IP54 DL SQUARE MIDI		3109017	✓
Black reflector DL SQUARE MIDI		3109015	✓
DL SQUARE MAXI			
Louvre reflector DL SQUARE MAXI		3109020	✓
White reflector DL SQUARE MAXI		3109018	✓
Matte plastic panel (IP54) DL SQUARE MAXI		3109021	✓
Black reflector DL SQUARE MAXI		3109019	✓



DLSB LED




WH-RAL9016 / White RAL9016 / Textured

Scan the QR-code for the latest information

- Recessed, modular, round LED downlight for indoor, comprising:
- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
 - Light-tight housing (prevents light distribution in the suspended ceiling)
 - Suitable for ceiling tile thickness from 1-25 mm
 - Recessed frosted diffuser for optimal light distribution and high homogeneity
 - White modular reflector, ABS injection-moulded with light-tight connection of LED board
 - Excellent heat dissipation through die-cast aluminium heat sink with Fast™ (Flexible Air Stream) Technology
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver
 - Emergency 1/3h and DALI + emergency 1/3h upon request



Mitsui outlet park - Taichung - Taiwan



DLSB100 LED OPAL COVER - 95 MM

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

14	I	-	-	80	4000	1500	1090	<input type="checkbox"/>	810711334001	✓
14	I	-	-	80	3000	1400	1060	<input type="checkbox"/>	810711333001	✓
10	I	-	-	80	4000	1100	810	<input type="checkbox"/>	810710934001	✓
10	I	-	-	80	3000	1040	790	<input type="checkbox"/>	810710933001	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

14	I	-	-	80	4000	1500	1090	<input type="checkbox"/>	810711364001	✓
14	I	-	-	80	3000	1400	1060	<input type="checkbox"/>	810711363001	✓
10	I	-	-	80	4000	1100	810	<input type="checkbox"/>	810710964001	✓
10	I	-	-	80	3000	1040	790	<input type="checkbox"/>	810710963001	✓

DLSB150 LED OPAL COVER - 95 MM

IP20 - IK04 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

23	I	-	-	80	4000	3600	2247	<input type="checkbox"/>	815712334001	✓
23	I	-	-	80	3000	3360	2124	<input type="checkbox"/>	815712333001	✓
18.5	I	-	-	80	4000	2510	1700	<input type="checkbox"/>	815711834001	✓
18.5	I	-	-	80	3000	2560	1826	<input type="checkbox"/>	815711833001	✓
13	I	-	-	80	4000	1760	1344	<input type="checkbox"/>	815711234001	✓
13	I	-	-	80	3000	1600	1262	<input type="checkbox"/>	815711233001	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

23	I	-	-	80	4000	3600	2247	<input type="checkbox"/>	815712364001	✓
23	I	-	-	80	3000	3360	2124	<input type="checkbox"/>	815712363001	✓
18.5	I	-	-	80	4000	2510	1700	<input type="checkbox"/>	815711864001	✓
18.5	I	-	-	80	3000	2560	1826	<input type="checkbox"/>	815711863001	✓
13	I	-	-	80	4000	1760	1344	<input type="checkbox"/>	815711264001	✓
13	I	-	-	80	3000	1600	1262	<input type="checkbox"/>	815711263001	✓

DLSB185 LED OPAL COVER - 95 MM

IP20 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

31.5	I	-	-	80	4000	5170	3540	<input type="checkbox"/>	818713334001	✓
31.5	I	-	-	80	3000	4840	3273	<input type="checkbox"/>	818713333001	✓
25	I	-	-	80	4000	3822	2985	<input type="checkbox"/>	818712434001	✓
25	I	-	-	80	3000	3547	2752	<input type="checkbox"/>	818712433001	✓
18	I	-	-	80	4000	2942	2163	<input type="checkbox"/>	818711634001	✓
18	I	-	-	80	3000	2750	1995	<input type="checkbox"/>	818711633001	✓
13	I	-	-	80	4000	2062	1573	<input type="checkbox"/>	818711234001	✓
13	I	-	-	80	3000	1925	1436	<input type="checkbox"/>	818711233001	✓
9.5	I	-	-	80	4000	1540	1145	<input type="checkbox"/>	818710834001	✓
9.5	I	-	-	80	3000	1402	1095	<input type="checkbox"/>	818710833001	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

31.5	I	-	-	80	4000	5170	3540	<input type="checkbox"/>	818713364001	✓
31.5	I	-	-	80	3000	4840	3273	<input type="checkbox"/>	818713363001	✓
25	I	-	-	80	4000	3822	2985	<input type="checkbox"/>	818712464001	✓
25	I	-	-	80	3000	3547	2752	<input type="checkbox"/>	818712463001	✓
18	I	-	-	80	4000	2942	2163	<input type="checkbox"/>	818711664001	✓
18	I	-	-	80	3000	2750	1995	<input type="checkbox"/>	818711663001	✓
13	I	-	-	80	4000	2062	1573	<input type="checkbox"/>	818711264001	✓
13	I	-	-	80	3000	1925	1436	<input type="checkbox"/>	818711263001	✓
9.5	I	-	-	80	4000	1540	1145	<input type="checkbox"/>	818710864001	✓
9.5	I	-	-	80	3000	1402	1095	<input type="checkbox"/>	818710863001	✓

DLSB220 LED OPAL COVER - 95 MM

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

45	I	-	-	80	4000	7520	5197	<input type="checkbox"/>	822722334001	✓
45	I	-	-	80	3000	7040	5126	<input type="checkbox"/>	822722333001	✓
34.5	I	-	-	80	4000	5920	4120	<input type="checkbox"/>	822721734001	✓
34.5	I	-	-	80	3000	5520	4098	<input type="checkbox"/>	822721733001	✓
26	I	-	-	80	4000	4280	3107	<input type="checkbox"/>	822721234001	✓
26	I	-	-	80	3000	4000	3019	<input type="checkbox"/>	822721233001	✓
18.5	I	-	-	80	4000	3000	2315	<input type="checkbox"/>	822720834001	✓
18.5	I	-	-	80	3000	2800	2287	<input type="checkbox"/>	822720833001	✓
13	I	-	-	80	4000	2240	1636	<input type="checkbox"/>	822720534001	✓
13	I	-	-	80	3000	2040	1610	<input type="checkbox"/>	822720533001	✓


Power LED - dimmable DALI 220-240 V 50/60 Hz

45	I	-	-	80	4000	7520	5197	<input type="checkbox"/>	822722364001	✓
45	I	-	-	80	3000	7040	5126	<input type="checkbox"/>	822722363001	✓
34.5	I	-	-	80	4000	5920	4120	<input type="checkbox"/>	822721764001	✓
34.5	I	-	-	80	3000	5520	4098	<input type="checkbox"/>	822721763001	✓
26	I	-	-	80	4000	4280	3107	<input type="checkbox"/>	822721264001	✓
26	I	-	-	80	3000	4000	3019	<input type="checkbox"/>	822721263001	✓
18.5	I	-	-	80	4000	3000	2315	<input type="checkbox"/>	822720864001	✓
18.5	I	-	-	80	3000	2800	2287	<input type="checkbox"/>	822720863001	✓
13	I	-	-	80	4000	2240	1636	<input type="checkbox"/>	822720564001	✓
13	I	-	-	80	3000	2040	1610	<input type="checkbox"/>	822720563001	✓



MITSUI outlet park - Taichung - Taiwan

EB431-435 LED



- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9010 / White RAL9010 / Textured


Scan the QR-code for the latest information

Recessed LED luminaire for indoor, comprising:


- Die-cast aluminium spotlight body and ring, powder-coated
- Reflector can be swivelled horizontally inwards and outwards thanks to the unique swivel mechanism
- Adjustable about 60° (from -15° up to 45°, rotatable about 355°)
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Quick and toolless installation
- Built-in driver
- Anchor springs
- Clear safety glass



GEOX Store - Norteshopping - Oporto - Portugal



Identifying and classifying our optics



EB431 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	II	-	80	4000	C/I	2 x 9°	1120	910	■	8431154073480	✓
9	II	-	80	3000	C/I	2 x 9°	1070	870	■	8431154073380	✓
9	II	-	80	4000	C/I	2 x 9°	1120	910	□	8431154073410	✓
9	II	-	80	3000	C/I	2 x 9°	1070	870	□	8431154073310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	II	-	80	4000	C/I	2 x 9°	1120	910	■	8431154076480	✓
9	II	-	80	3000	C/I	2 x 9°	1070	870	■	8431154076380	✓
9	II	-	80	4000	C/I	2 x 9°	1120	910	□	8431154076410	✓
9	II	-	80	3000	C/I	2 x 9°	1070	870	□	8431154076310	✓

EB431 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	II	-	80	4000	C/M	2 x 12°	1120	890	■	8431164073480	✓
9	II	-	80	3000	C/M	2 x 12°	1070	870	■	8431164073380	✓
9	II	-	80	4000	C/M	2 x 12°	1120	890	□	8431164073410	✓
9	II	-	80	3000	C/M	2 x 12°	1070	870	□	8431164073310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	II	-	80	4000	C/M	2 x 12°	1120	890	■	8431164076480	✓
9	II	-	80	3000	C/M	2 x 12°	1070	870	■	8431164076380	✓
9	II	-	80	4000	C/M	2 x 12°	1120	890	□	8431164076410	✓
9	II	-	80	3000	C/M	2 x 12°	1070	870	□	8431164076310	✓

EB431 LED FLOOD REFLECTOR

IP20 - IK02 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	II	-	80	4000	C/IW	2 x 26°	1120	930	■	8431174073480	✓
9	II	-	80	3000	C/IW	2 x 25°	1070	880	■	8431174073380	✓
9	II	-	80	4000	C/IW	2 x 26°	1120	930	□	8431174073410	✓
9	II	-	80	3000	C/IW	2 x 25°	1070	880	□	8431174073310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	II	-	80	4000	C/IW	2 x 26°	1120	930	■	8431174076480	✓
9	II	-	80	3000	C/IW	2 x 25°	1070	880	■	8431174076380	✓
9	II	-	80	4000	C/IW	2 x 26°	1120	930	□	8431174076410	✓
9	II	-	80	3000	C/IW	2 x 25°	1070	880	□	8431174076310	✓

EB432 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	II	-	80	4000	C/I	2 x 8°	1520	1380	■	8432154133480	✓
14	II	-	80	3000	C/I	2 x 8°	1460	1290	■	8432154133380	✓
14	II	-	80	4000	C/I	2 x 8°	1520	1380	□	8432154133410	✓
14	II	-	80	3000	C/I	2 x 8°	1460	1290	□	8432154133310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	II	-	80	4000	C/I	2 x 8°	1520	1380	■	8432154136480	✓
14	II	-	80	3000	C/I	2 x 8°	1460	1290	■	8432154136380	✓
14	II	-	80	4000	C/I	2 x 8°	1520	1380	□	8432154136410	✓
14	II	-	80	3000	C/I	2 x 8°	1460	1290	□	8432154136310	✓



EB432 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	II	-	80	4000	C/M	2 x 11°	1520	1370	■	8432164133480	✓
14	II	-	80	3000	C/M	2 x 11°	1460	1280	■	8432164133380	✓
14	II	-	80	4000	C/M	2 x 11°	1520	1370	□	8432164133410	✓
14	II	-	80	3000	C/M	2 x 11°	1460	1280	□	8432164133310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	II	-	80	4000	C/M	2 x 11°	1520	1370	■	8432164136480	✓
14	II	-	80	3000	C/M	2 x 11°	1460	1280	■	8432164136380	✓
14	II	-	80	4000	C/M	2 x 11°	1520	1370	□	8432164136410	✓
14	II	-	80	3000	C/M	2 x 11°	1460	1280	□	8432164136310	✓



EB432 LED FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	II	-	80	4000	C/IW	2 x 26°	1520	1390	■	8432174133480	✓
14	II	-	80	3000	C/IW	2 x 26°	1460	1300	■	8432174133380	✓
14	II	-	80	4000	C/IW	2 x 26°	1520	1390	□	8432174133410	✓
14	II	-	80	3000	C/IW	2 x 26°	1460	1300	□	8432174133310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	II	-	80	4000	C/IW	2 x 26°	1520	1390	■	8432174136480	✓
14	II	-	80	3000	C/IW	2 x 26°	1460	1300	■	8432174136380	✓
14	II	-	80	4000	C/IW	2 x 26°	1520	1390	□	8432174136410	✓
14	II	-	80	3000	C/IW	2 x 26°	1460	1300	□	8432174136310	✓



EB433 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	C/I	2 x 8°	2890	2040	■	8433154193484	✓
20	II	-	80	3000	C/I	2 x 8°	2580	1960	■	8433154193384	✓
20	II	-	80	4000	C/I	2 x 8°	2890	2040	□	8433154193414	✓
20	II	-	80	3000	C/I	2 x 8°	2580	1960	□	8433154193314	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/I	2 x 8°	2890	2040	■	8433154196484	✓
20	II	-	80	3000	C/I	2 x 8°	2580	1960	■	8433154196384	✓
20	II	-	80	4000	C/I	2 x 8°	2890	2040	□	8433154196414	✓
20	II	-	80	3000	C/I	2 x 8°	2580	1960	□	8433154196314	✓



EB433 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	C/M	2 x 11°	2890	2120	■	8433164193484	✓
20	II	-	80	3000	C/M	2 x 11°	2580	2040	■	8433164193384	✓
20	II	-	80	4000	C/M	2 x 11°	2890	2120	□	8433164193414	✓
20	II	-	80	3000	C/M	2 x 11°	2580	2040	□	8433164193314	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/M	2 x 11°	2890	2120	■	8433164196484	✓
20	II	-	80	3000	C/M	2 x 11°	2580	2040	■	8433164196384	✓
20	II	-	80	4000	C/M	2 x 11°	2890	2120	□	8433164196414	✓
20	II	-	80	3000	C/M	2 x 11°	2580	2040	□	8433164196314	✓



EB433 LED FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	C/IW	2 x 23°	2890	2150	■	8433174193484	✓
20	II	-	80	3000	C/IW	2 x 23°	2580	2070	■	8433174193384	✓
20	II	-	80	4000	C/IW	2 x 23°	2890	2150	□	8433174193414	✓
20	II	-	80	3000	C/IW	2 x 23°	2580	2070	□	8433174193314	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/IW	2 x 23°	2890	2150	■	8433174196484	✓
20	II	-	80	3000	C/IW	2 x 23°	2580	2070	■	8433174196384	✓
20	II	-	80	4000	C/IW	2 x 23°	2890	2150	□	8433174196414	✓
20	II	-	80	3000	C/IW	2 x 23°	2580	2070	□	8433174196314	✓



EB433 LED WIDE FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	C/MW	2 x 34°	2890	2120	■	8433184193484	✓
20	II	-	80	3000	C/MW	2 x 34°	2580	2040	■	8433184193384	✓
20	II	-	80	4000	C/MW	2 x 34°	2890	2120	□	8433184193414	✓
20	II	-	80	3000	C/MW	2 x 34°	2580	2040	□	8433184193314	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/MW	2 x 34°	2890	2120	■	8433184196484	✓
20	II	-	80	3000	C/MW	2 x 34°	2580	2040	■	8433184196384	✓
20	II	-	80	4000	C/MW	2 x 34°	2890	2120	□	8433184196414	✓
20	II	-	80	3000	C/MW	2 x 34°	2580	2040	□	8433184196314	✓



EB434 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	C/I	2 x 8°	3520	2720	■	8434154253480	✓
27	II	-	80	3000	C/I	2 x 8°	3460	2610	■	8434154253380	✓
27	II	-	80	4000	C/I	2 x 8°	3520	2720	□	8434154253410	✓
27	II	-	80	3000	C/I	2 x 8°	3460	2610	□	8434154253310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	II	-	80	4000	C/I	2 x 8°	3520	2720	■	8434154256480	✓
27	II	-	80	3000	C/I	2 x 8°	3460	2610	■	8434154256380	✓
27	II	-	80	4000	C/I	2 x 8°	3520	2720	□	8434154256410	✓
27	II	-	80	3000	C/I	2 x 8°	3460	2610	□	8434154256310	✓



EB434 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	C/M	2 x 11°	3520	2830	■	8434164253480	✓
27	II	-	80	3000	C/M	2 x 11°	3460	2710	■	8434164253380	✓
27	II	-	80	4000	C/M	2 x 11°	3520	2830	□	8434164253410	✓
27	II	-	80	3000	C/M	2 x 11°	3460	2710	□	8434164253310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	II	-	80	4000	C/M	2 x 11°	3520	2830	■	8434164256480	✓
27	II	-	80	3000	C/M	2 x 11°	3460	2710	■	8434164256380	✓
27	II	-	80	4000	C/M	2 x 11°	3520	2830	□	8434164256410	✓
27	II	-	80	3000	C/M	2 x 11°	3460	2710	□	8434164256310	✓



EB434 LED FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	C/IW	2 x 23°	3520	2870	■	8434174253480	✓
27	II	-	80	3000	C/IW	2 x 23°	3460	2760	■	8434174253380	✓
27	II	-	80	4000	C/IW	2 x 23°	3520	2870	□	8434174253410	✓
27	II	-	80	3000	C/IW	2 x 23°	3460	2760	□	8434174253310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	II	-	80	4000	C/IW	2 x 23°	3520	2870	■	8434174256480	✓
27	II	-	80	3000	C/IW	2 x 23°	3460	2760	■	8434174256380	✓
27	II	-	80	4000	C/IW	2 x 23°	3520	2870	□	8434174256410	✓
27	II	-	80	3000	C/IW	2 x 23°	3460	2760	□	8434174256310	✓



EB434 LED WIDE FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	C/MW	2 x 34°	3520	2830	■	8434184253480	✓
27	II	-	80	3000	C/MW	2 x 34°	3460	2720	■	8434184253380	✓
27	II	-	80	4000	C/MW	2 x 34°	3520	2830	□	8434184253410	✓
27	II	-	80	3000	C/MW	2 x 34°	3460	2720	□	8434184253310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	II	-	80	4000	C/MW	2 x 34°	3520	2830	■	8434184256480	✓
27	II	-	80	3000	C/MW	2 x 34°	3460	2720	■	8434184256380	✓
27	II	-	80	4000	C/MW	2 x 34°	3520	2830	□	8434184256410	✓
27	II	-	80	3000	C/MW	2 x 34°	3460	2720	□	8434184256310	✓



EB435 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C




LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	80	4000	C/I	2 x 6°	5190	4290	■	8435154453480	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4120	■	8435154453380	✓
40	II	-	80	4000	C/I	2 x 6°	5190	4290	□	8435154453410	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4120	□	8435154453310	✓
35	II	-	80	4000	C/I	2 x 6°	4400	3560	■	8435154323480	✓
35	II	-	80	3000	C/I	2 x 6°	4280	3420	■	8435154323380	✓
35	II	-	80	4000	C/I	2 x 6°	4400	3560	□	8435154323410	✓
35	II	-	80	3000	C/I	2 x 6°	4280	3420	□	8435154323310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

40	II	-	80	4000	C/I	2 x 6°	5190	4290	■	8435154456480	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4120	■	8435154456380	✓
40	II	-	80	4000	C/I	2 x 6°	5190	4290	□	8435154456410	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4120	□	8435154456310	✓
35	II	-	80	4000	C/I	2 x 6°	4400	3560	■	8435154326480	✓
35	II	-	80	3000	C/I	2 x 6°	4280	3420	■	8435154326380	✓
35	II	-	80	4000	C/I	2 x 6°	4400	3560	□	8435154326410	✓
35	II	-	80	3000	C/I	2 x 6°	4280	3420	□	8435154326310	✓

EB435 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	80	4000	C/M	2 x 11°	5190	4300	■	8435164453480	✓
40	II	-	80	3000	C/M	2 x 11°	5070	4130	■	8435164453380	✓
40	II	-	80	4000	C/M	2 x 11°	5190	4300	□	8435164453410	✓
40	II	-	80	3000	C/M	2 x 11°	5070	4130	□	8435164453310	✓
35	II	-	80	4000	C/M	2 x 11°	4400	3570	■	8435164323480	✓
35	II	-	80	3000	C/M	2 x 11°	4280	3430	■	8435164323380	✓
35	II	-	80	4000	C/M	2 x 11°	4400	3570	□	8435164323410	✓
35	II	-	80	3000	C/M	2 x 11°	4280	3430	□	8435164323310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

40	II	-	80	4000	C/M	2 x 11°	5190	4300	■	8435164456480	✓
40	II	-	80	3000	C/M	2 x 11°	5070	4130	■	8435164456380	✓
40	II	-	80	4000	C/M	2 x 11°	5190	4300	□	8435164456410	✓
40	II	-	80	3000	C/M	2 x 11°	5070	4130	□	8435164456310	✓
35	II	-	80	4000	C/M	2 x 11°	4400	3570	■	8435164326480	✓
35	II	-	80	3000	C/M	2 x 11°	4280	3430	■	8435164326380	✓
35	II	-	80	4000	C/M	2 x 11°	4400	3570	□	8435164326410	✓
35	II	-	80	3000	C/M	2 x 11°	4280	3430	□	8435164326310	✓

EB435 LED FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	80	4000	C/IW	2 x 23°	5190	4330	■	8435174453480	✓
40	II	-	80	3000	C/IW	2 x 23°	5070	4160	■	8435174453380	✓
40	II	-	80	4000	C/IW	2 x 23°	5190	4330	□	8435174453410	✓
40	II	-	80	3000	C/IW	2 x 23°	5070	4160	□	8435174453310	✓
35	II	-	80	4000	C/IW	2 x 23°	4400	3600	■	8435174323480	✓
35	II	-	80	3000	C/IW	2 x 23°	4280	3450	■	8435174323380	✓
35	II	-	80	4000	C/IW	2 x 23°	4400	3600	□	8435174323410	✓
35	II	-	80	3000	C/IW	2 x 23°	4280	3450	□	8435174323310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

40	II	-	80	4000	C/IW	2 x 23°	5190	4330	■	8435174456480	✓
40	II	-	80	3000	C/IW	2 x 23°	5070	4160	■	8435174456380	✓
40	II	-	80	4000	C/IW	2 x 23°	5190	4330	□	8435174456410	✓
40	II	-	80	3000	C/IW	2 x 23°	5070	4160	□	8435174456310	✓
35	II	-	80	4000	C/IW	2 x 23°	4400	3600	■	8435174326480	✓
35	II	-	80	3000	C/IW	2 x 23°	4280	3450	■	8435174326380	✓
35	II	-	80	4000	C/IW	2 x 23°	4400	3600	□	8435174326410	✓
35	II	-	80	3000	C/IW	2 x 23°	4280	3450	□	8435174326310	✓



EB435 LED WIDE FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	80	4000	C/MW	2 x 34°	5190	4290	■	8435184453480	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4120	■	8435184453380	✓
40	II	-	80	4000	C/MW	2 x 34°	5190	4290	□	8435184453410	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4120	□	8435184453310	✓
35	II	-	80	4000	C/MW	2 x 34°	4400	3570	■	8435184323480	✓
35	II	-	80	3000	C/MW	2 x 34°	4280	3430	■	8435184323380	✓
35	II	-	80	4000	C/MW	2 x 34°	4400	3570	□	8435184323410	✓
35	II	-	80	3000	C/MW	2 x 34°	4280	3430	□	8435184323310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

40	II	-	80	4000	C/MW	2 x 34°	5190	4290	■	8435184456480	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4120	■	8435184456380	✓
40	II	-	80	4000	C/MW	2 x 34°	5190	4290	□	8435184456410	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4120	□	8435184456310	✓
35	II	-	80	4000	C/MW	2 x 34°	4400	3570	■	8435184326480	✓
35	II	-	80	3000	C/MW	2 x 34°	4280	3430	■	8435184326380	✓
35	II	-	80	4000	C/MW	2 x 34°	4400	3570	□	8435184326410	✓
35	II	-	80	3000	C/MW	2 x 34°	4280	3430	□	8435184326310	✓



Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
EB432			
Food glass filter for meat products		8432961	✓
Food glass filter for bakery products		8432962	✓
Food glass filters for fruits and cheese		8432963	✓
Food glass filter for vegetables		8432964	✓
Food glass filter for fish products		8432965	✓
EB433 + EB434			
Food glass filter for meat products		8433961	✓
Food glass filter for bakery products		8433962	✓
Food glass filters for fruits and cheese		8433963	✓
Food glass filter for vegetables		8433964	✓
Food glass filter for fish products		8433965	✓
Frosted safety glass pane		8414900	✓
EB435			
Food glass filter for meat products		8435961	✓
Food glass filter for bakery products		8435962	✓
Food glass filters for fruits and cheese		8435963	✓
Food glass filter for vegetables		8435964	✓
Food glass filter for fish products		8435965	✓
Frosted safety glass pane		8417900	✓



8432961
8433961
8435961

8432962
8433962
8435962

8432963
8433963
8435963




8432964
8433964
8435964

8432965
8433965
8435965

8414900
8417900

ELIA AL




□ WH-RAL9016 / White RAL9016 /

Scan the QR-code for the latest information

Flush-mounting LED device for accent lighting in commercial areas and offices

- This modular flush-mounting solution features a rotosymmetrical optic equipped with a passive heat removal system, in die-cast aluminium
- It is composed of a white powder-coated die-cast aluminium frame and 2 different optics (36° and 60°) that guarantee a UGR of less than 19
- Installation is quick and easy, thanks to the reduced weight of the device, the bayonet coupling and the simple wiring, with the connector located on the device and remote power supply included
- External emergency kit with 3h autonomy available (to be ordered separately)



ELIA AL
S2 18W

ELIA AL
M2 25W

ELIA AL S2 18W 36°

IP40 - IK06 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
18	II	✓	-	90	4000	-	1800	<input type="checkbox"/>	GWF1410GG940	✓
18	II	✓	-	90	3000	-	1700	<input type="checkbox"/>	GWF1410GG930	✓
18	II	✓	-	80	4000	-	2000	<input type="checkbox"/>	GWF1410GG840	✓
18	II	✓	-	80	3000	-	1900	<input type="checkbox"/>	GWF1410GG830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
18	II	✓	-	90	4000	-	1800	<input type="checkbox"/>	GWF1411GG940	✓
18	II	✓	-	90	3000	-	1700	<input type="checkbox"/>	GWF1411GG930	✓
18	II	✓	-	80	4000	-	2000	<input type="checkbox"/>	GWF1411GG840	✓
18	II	✓	-	80	3000	-	1900	<input type="checkbox"/>	GWF1411GG830	✓



ELIA AL S2 18W 60°

IP40 - IK06 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
18	II	✓	-	90	4000	-	1900	<input type="checkbox"/>	GWF1410GH940	✓
18	II	✓	-	90	3000	-	1800	<input type="checkbox"/>	GWF1410GH930	✓
18	II	✓	-	80	4000	-	2100	<input type="checkbox"/>	GWF1410GH840	✓
18	II	✓	-	80	3000	-	2000	<input type="checkbox"/>	GWF1410GH830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
18	II	✓	-	90	4000	-	1900	<input type="checkbox"/>	GWF1411GH940	✓
18	II	✓	-	90	3000	-	1800	<input type="checkbox"/>	GWF1411GH930	✓
18	II	✓	-	80	4000	-	2100	<input type="checkbox"/>	GWF1411GH840	✓
18	II	✓	-	80	3000	-	2000	<input type="checkbox"/>	GWF1411GH830	✓



ELIA AL M2 25W 36°

IP40 - IK06 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2500	<input type="checkbox"/>	GWF1410MG940	✓
25	II	✓	-	90	3000	-	2300	<input type="checkbox"/>	GWF1410MG930	✓
25	II	✓	-	80	4000	-	2700	<input type="checkbox"/>	GWF1410MG840	✓
25	II	✓	-	80	3000	-	2500	<input type="checkbox"/>	GWF1410MG830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2500	<input type="checkbox"/>	GWF1411MG940	✓
25	II	✓	-	90	3000	-	2300	<input type="checkbox"/>	GWF1411MG930	✓
25	II	✓	-	80	4000	-	2700	<input type="checkbox"/>	GWF1411MG840	✓
25	II	✓	-	80	3000	-	2500	<input type="checkbox"/>	GWF1411MG830	✓



ELIA AL M2 25W 60°

IP40 - IK06 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2600	<input type="checkbox"/>	GWF1410MH940	✓
25	II	✓	-	90	3000	-	2400	<input type="checkbox"/>	GWF1410MH930	✓
25	II	✓	-	80	4000	-	2800	<input type="checkbox"/>	GWF1410MH840	✓
25	II	✓	-	80	3000	-	2600	<input type="checkbox"/>	GWF1410MH830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2600	<input type="checkbox"/>	GWF1411MH940	✓
25	II	✓	-	90	3000	-	2400	<input type="checkbox"/>	GWF1411MH930	✓
25	II	✓	-	80	4000	-	2800	<input type="checkbox"/>	GWF1411MH840	✓
25	II	✓	-	80	3000	-	2600	<input type="checkbox"/>	GWF1411MH830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA AL Emergency kit 3h		GWS2992	✓



GWS2992

ELIA DL




Scan the QR-code for the latest information

□ WH-RAL9016 / White RAL9016 /

Flush-mounting LED downlight for lighting entrance areas, corridors and shared spaces

- Crafted from white power-coated die-cast aluminium with an opal diffusing shield
- Available in two power versions, with separate electronic power supply in the On/Off or DALI options provided as part of a kit, colour temperature of 4,000 K (neutral white) and colour rendering index of more than 80 or more than 90
- It was designed to withstand temperature variations from -20°C to +45°C, and offers protection from water and dust penetration of up to level IP54 and from shocks and impacts of up to level IK06
- Light and easy to handle, ELIA DL is easy to install thanks to the connector for the electrical wiring and the quick, simple fin-locking mechanism
- External emergency kit with 3h autonomy available (to be ordered separately)



ELIA DL

ELIA DL M2 25W OPAL

IP40 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2400	<input type="checkbox"/>	GWF1510MA940	✓
25	II	✓	-	80	4000	-	2600	<input type="checkbox"/>	GWF1510MA840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
25	II	✓	-	90	4000	-	2400	<input type="checkbox"/>	GWF1511MA940	✓
25	II	✓	-	80	4000	-	2600	<input type="checkbox"/>	GWF1511MA840	✓



ELIA DL L2 35W OPAL

IP40 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
35	II	✓	-	90	4000	-	3300	<input type="checkbox"/>	GWF1510QA940	✓
35	II	✓	-	80	4000	-	3600	<input type="checkbox"/>	GWF1510QA840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz										
35	II	✓	-	90	4000	-	3300	<input type="checkbox"/>	GWF1511QA940	✓
35	II	✓	-	80	4000	-	3600	<input type="checkbox"/>	GWF1511QA840	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA DL			
Emergency kit 3h		GWS2992	✓



GWS2992

MANGO+ MAXI




WH-RAL9010 / White RAL9010 / Textured

Scan the QR-code for the latest information

Recessed, modular, round LED downlight for indoor, comprising:


- Die-cast aluminium heat sink with Fast™ (Flexible air stream technology) cooling system grants an excellent dissipation and thermal management
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module
- Integrated diffuser grants an optimised uniformity
- Integral Dip-Switches to select one of two power levels, which can be field adjustable (MULTIPOWER models)
- Quick and toolless installation
- Rapid spring-type installation
- All components can be tool-less replaced lately
- Suitable for ceiling tile thickness from 1-25 mm



Neuroscience research - New South Wales - Australia



MANGO+ MIDI



MANGO+ MAXI

MANGO+ MAXI MULTIPOWER

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
18.5	II	-	-	80	4000	3450	2605	<input type="checkbox"/>	3109851	✓
24						2660	2010			
18.5	II	-	-	80	3000	3355	2555	<input type="checkbox"/>	3109850	✓
24						2580	1965			
Power LED - emergency 1h - 220-240 V 50/60 Hz										
18.5	II	-	-	80	4000	3450	2605	<input type="checkbox"/>	3109853	✓
24						2660	2010			
18.5	II	-	-	80	3000	3355	2555	<input type="checkbox"/>	3109852	✓
24						2580	1965			



MANGO+ MAXI WIELAND MULTIPOWER

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
18.5	II	-	-	80	4000	2660	2010	<input type="checkbox"/>	3109855	✓
24						3450	2605			
18.5	II	-	-	80	3000	2580	1965	<input type="checkbox"/>	3109854	✓
24						3355	2555			



MANGO+ MAXI

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz										
24	II	-	-	80	4000	3450	2605	<input type="checkbox"/>	3116578	✓
24	II	-	-	80	3000	3354	2555	<input type="checkbox"/>	3116577	✓



MANGO+ MIDI



WH-RAL9010 / White RAL9010 / Textured

Scan the QR-code for the latest information

Recessed, modular, round LED downlight for indoor, comprising:


- Die-cast aluminium heat sink with Fast™ (Flexible air stream technology) cooling system grants an excellent dissipation and thermal management
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module
- Integrated diffuser grants an optimised uniformity
- Integral Dip-Switches to select one of two power levels, which can be field adjustable (MULTIPOWER models)
- Quick and toolless installation
- Rapid spring-type installation
- All components can be tool-less replaced laterly
- Suitable for ceiling tile thickness from 1-25 mm



Tabor College Oscar Romero - Hoorn - Netherlands



MANGO+ MAXI



MANGO+ MIDI

MANGO+ MIDI MULTIPOWER

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
11.5 15	II	-	-	80	4000	1980 1520	1496 1150	<input type="checkbox"/>	3109843	✓
11.5 15	II	-	-	80	3000	1925 1475	1455 1115	<input type="checkbox"/>	3109842	✓
Power LED - emergency 1h - 220-240 V 50/60 Hz										
11.5 15	II	-	-	80	4000	1980 1520	1496 1150	<input type="checkbox"/>	3109845	✓
11.5 15	II	-	-	80	3000	1925 1475	1455 1115	<input type="checkbox"/>	3109844	✓

MANGO+ MIDI WIELAND MULTIPOWER

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
11.5 15	II	-	-	80	4000	1520 1980	1150 1496	<input type="checkbox"/>	3109847	✓
11.5 15	II	-	-	80	3000	1475 1925	1115 1455	<input type="checkbox"/>	3109846	✓


MANGO+ MIDI

IP20 - IK07 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz										
15	II	-	-	80	4000	1980	1496	<input type="checkbox"/>	3116576	✓
15	II	-	-	80	3000	1926	1455	<input type="checkbox"/>	3116575	✓

AS425 LED



- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9010 / White RAL9010 / Textured


Scan the QR-code for the latest information

LED track light for indoor, comprising:

- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Bayonet-closure ring for a toolless replacement of the reflector and the louvre
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Universal tri-phase adaptor included
- Built-in driver
- Clear safety glass
- Quick and toolless installation
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®




VOLVO Autosueco showroom - Oporto - Portugal



AS425 LED

AS425 LED

Identifying and classifying our optics



AS425 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	C/I	2 x 8°	2890	2290	■	8425453173480	✓
20	I	-	80	3000	C/I	2 x 8°	2580	2190	■	8425453173380	✓
20	I	-	80	4000	C/I	2 x 8°	2890	2290	□	8425453173410	✓
20	I	-	80	3000	C/I	2 x 8°	2580	2190	□	8425453173310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/I	2 x 8°	2890	2290	■	3108535	✓
20	II	-	80	3000	C/I	2 x 8°	2580	2190	■	3108536	✓
20	II	-	80	4000	C/I	2 x 8°	2890	2290	□	3108533	✓
20	II	-	80	3000	C/I	2 x 8°	2580	2190	□	3108534	✓



AS425 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	C/M	2 x 15°	2890	2250	■	8425463173480	✓
20	I	-	80	3000	C/M	2 x 15°	2580	2160	■	8425463173380	✓
20	I	-	80	4000	C/M	2 x 15°	2890	2250	□	8425463173410	✓
20	I	-	80	3000	C/M	2 x 15°	2580	2160	□	8425463173310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/M	2 x 15°	2890	2250	■	3108539	✓
20	II	-	80	3000	C/M	2 x 15°	2580	2160	■	3108540	✓
20	II	-	80	4000	C/M	2 x 15°	2890	2250	□	3108537	✓
20	II	-	80	3000	C/M	2 x 15°	2580	2160	□	3108538	✓



AS425 LED WIDE FLOOD REFLECTOR


IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	C/MW	2 x 33°	2890	2280	■	8425483173480	✓
20	I	-	80	3000	C/MW	2 x 33°	2580	2180	■	8425483173380	✓
20	I	-	80	4000	C/MW	2 x 33°	2890	2280	□	8425483173410	✓
20	I	-	80	3000	C/MW	2 x 33°	2580	2180	□	8425483173310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
20	II	-	80	4000	C/MW	2 x 33°	2890	2280	■	3108542	✓
20	II	-	80	3000	C/MW	2 x 33°	2580	2180	■	3108543	✓
20	II	-	80	4000	C/MW	2 x 33°	2890	2280	□	3108541	✓
20	II	-	80	3000	C/MW	2 x 33°	2580	2180	□	3108426	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
AS425 LED			
Frosted safety glass pane		8414900	✓
Food glass filter for meat products		8433961	✓
Food glass filter for bakery products		8433962	✓
Food glass filters for fruits and cheese		8433963	✓
Food glass filter for vegetables		8433964	✓
Food glass filter for fish products		8433965	✓





Showroom Pedrali - Bergamo - Italy

AS427 LED



- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9010 / White RAL9010 / Textured


Scan the QR-code for the latest information

LED track light for indoor, comprising:

- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Bayonet-closure ring for a toolless replacement of the reflector and the louvre
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Universal tri-phase adaptor included
- Built-in driver
- Clear safety glass
- Quick and toolless installation
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®




Showroom Pedrali - Bergamo - Italy



AS427 LED

AS427 LED

Identifying and classifying our optics



AS427 LED SPOT REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	I	-	80	4000	C/I	2 x 6°	5190	4310	■	8427453383480	✓
40	I	-	80	3000	C/I	2 x 6°	5070	4130	■	8427453383380	✓
40	I	-	80	4000	C/I	2 x 6°	5190	4310	□	8427453383410	✓
40	I	-	80	3000	C/I	2 x 6°	5070	4130	□	8427453383310	✓
35	I	-	80	4000	C/I	2 x 6°	4400	3530	■	8427453333480	✓
35	I	-	80	3000	C/I	2 x 6°	4280	3380	■	8427453333380	✓
35	I	-	80	4000	C/I	2 x 6°	4400	3530	□	8427453333410	✓
35	I	-	80	3000	C/I	2 x 6°	4280	3380	□	8427453333310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
40	II	-	80	4000	C/I	2 x 6°	5190	4310	■	3108560	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4130	■	3108561	✓
40	II	-	80	4000	C/I	2 x 6°	5190	4310	□	3108544	✓
40	II	-	80	3000	C/I	2 x 6°	5070	4130	□	3108545	✓



AS427 LED MEDIUM REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	I	-	80	4000	C/M	2 x 16°	5190	4340	■	8427463383480	✓
40	I	-	80	3000	C/M	2 x 16°	5070	4170	■	8427463383380	✓
40	I	-	80	4000	C/M	2 x 16°	5190	4340	□	8427463383410	✓
40	I	-	80	3000	C/M	2 x 16°	5070	4170	□	8427463383310	✓
35	I	-	80	4000	C/M	2 x 16°	4400	3550	■	8427463333480	✓
35	I	-	80	3000	C/M	2 x 16°	4280	3420	■	8427463333380	✓
35	I	-	80	4000	C/M	2 x 16°	4400	3550	□	8427463333410	✓
35	I	-	80	3000	C/M	2 x 16°	4280	3420	□	8427463333310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
40	II	-	80	4000	C/M	2 x 16°	5190	4340	■	3108562	✓
40	II	-	80	3000	C/M	2 x 16°	5070	4170	■	3108563	✓
40	II	-	80	4000	C/M	2 x 16°	5190	4340	□	3108427	✓
40	II	-	80	3000	C/M	2 x 16°	5070	4170	□	3108546	✓



AS427 LED WIDE FLOOD REFLECTOR

IP20 - IK02 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	I	-	80	4000	C/MW	2 x 34°	5190	4330	■	8427483383480	✓
40	I	-	80	3000	C/MW	2 x 34°	5070	4160	■	8427483383380	✓
40	I	-	80	4000	C/MW	2 x 34°	5190	4330	□	8427483383410	✓
40	I	-	80	3000	C/MW	2 x 34°	5070	4160	□	8427483383310	✓
35	I	-	80	4000	C/MW	2 x 34°	4400	3520	■	8427483333480	✓
35	I	-	80	3000	C/MW	2 x 34°	4280	3380	■	8427483333380	✓
35	I	-	80	4000	C/MW	2 x 34°	4400	3520	□	8427483333410	✓
35	I	-	80	3000	C/MW	2 x 34°	4280	3380	□	8427483333310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
40	II	-	80	4000	C/MW	2 x 34°	5190	4330	■	3108564	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4160	■	3108565	✓
40	II	-	80	4000	C/MW	2 x 34°	5190	4330	□	3108547	✓
40	II	-	80	3000	C/MW	2 x 34°	5070	4160	□	3108548	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
AS427 LED			
Frosted safety glass pane		8417900	✓
Food glass filter for meat products		8435961	✓
Food glass filter for bakery products		8435962	✓
Food glass filters for fruits and cheese		8435963	✓
Food glass filter for vegetables		8435964	✓
Food glass filter for fish products		8435965	✓



8417900

8435961

8435962




8435963

8435964

8435965

AS615




- BK-81 / Black / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information


Linear LED track light for indoors, comprising:

- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- High-transparency polycarbonate optics
- Symmetrical optics (S/EW - S/W) and double asymmetrical optics (2A/M)
- Luminaire compatible with OTR TRACKS RAILS range and accessories
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®
- Static ON/OFF or dimmable DALI options available
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory



AS615

Identifying and classifying our optics



AS615 S/EW

IP20 - IK04 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
68	I	-	80	4000	S/EW	-	11975	8981	■	3101721	✓
68	I	-	80	3000	S/EW	-	11310	8434	■	3101737	✓
68	I	-	80	4000	S/EW	-	11975	8981	□	3101717	✓
68	I	-	80	3000	S/EW	-	11310	8434	□	3101733	✓
43	I	-	80	4000	S/EW	-	7809	6076	■	3101720	✓
43	I	-	80	3000	S/EW	-	7375	5721	■	3101736	✓
43	I	-	80	4000	S/EW	-	7809	6076	□	3101716	✓
43	I	-	80	3000	S/EW	-	7375	5721	□	3101732	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

68	I	-	80	4000	S/EW	-	11975	8981	■	3101729	✓
68	I	-	80	3000	S/EW	-	11310	8434	■	3101745	✓
68	I	-	80	4000	S/EW	-	11975	8981	□	3101725	✓
68	I	-	80	3000	S/EW	-	11310	8434	□	3101741	✓
43	I	-	80	4000	S/EW	-	7809	6076	■	3101728	✓
43	I	-	80	3000	S/EW	-	7375	5721	■	3101744	✓
43	I	-	80	4000	S/EW	-	7809	6076	□	3101724	✓
43	I	-	80	3000	S/EW	-	7375	5721	□	3101740	✓

AS615 2A/M

IP20 - IK04 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
68	I	-	80	4000	2A/M	-	11975	9578	■	3101723	✓
68	I	-	80	3000	2A/M	-	11310	9058	■	3101739	✓
68	I	-	80	4000	2A/M	-	11975	9578	□	3101719	✓
68	I	-	80	3000	2A/M	-	11310	9058	□	3101735	✓
43	I	-	80	4000	2A/M	-	7809	6478	■	3101722	✓
43	I	-	80	3000	2A/M	-	7375	6134	■	3101738	✓
43	I	-	80	4000	2A/M	-	7809	6478	□	3101718	✓
43	I	-	80	3000	2A/M	-	7375	6134	□	3101734	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

68	I	-	80	4000	2A/M	-	11975	9578	■	3101731	✓
68	I	-	80	3000	2A/M	-	11310	9058	■	3101747	✓
68	I	-	80	4000	2A/M	-	11975	9578	□	3101727	✓
68	I	-	80	3000	2A/M	-	11310	9058	□	3101743	✓
43	I	-	80	4000	2A/M	-	7809	6478	■	3101730	✓
43	I	-	80	3000	2A/M	-	7375	6134	■	3101746	✓
43	I	-	80	4000	2A/M	-	7809	6478	□	3101726	✓
43	I	-	80	3000	2A/M	-	7375	6134	□	3101742	✓



OTR TRACKS RAILS



- GR-94 / Metallic grey / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured



Scan the QR-code for the latest information

The track system with 3 switches is a complete installation system designed for stores, hypermarkets, public facilities, museums, factories, etc.

- All designs can be easily implemented, and assembly is facilitated by the use of tracks and standard accessories
- Designed for exposed, recessed or suspension installation, and the luminaires can be easily moved, changed or modified
- Tracks and accessories are available in the shades white (BW), grey (AL) and black (NZ)
- The indication "earthing conductor on the right, left, inside or outside" for power supply units, corner and T- derivations is based on the position of the earthing conductor on the track. The position of the earthing conductor on the track depends on the visual direction. The visual direction follows the operating direction of the system on the cross cup of the track that opens downwards
- Compatible with 3F "standard" adaptors that do not use DIM
- The OTR binary system is a mixed three-phase system with two additional conductors for the management of any signal (e.g. DIM 1-10 V, DALI, DMX, LON, EIB, etc.).



VOLVO showroom - Almada - Portugal




ON REQUEST

OTR H | INDIRECT LIGHT

A new way of making room for all your lighting ideas.

While the bottom of the track carries out the typical direct lighting function, the top can be used to create indirect lighting by inserting strips or LED modules of different types. The top can also be used to pass the mounting cables or the control system of the lighting elements.



OTR
STANDARD

OTR
RECESSED

OTR TRACKS RAILS STANDARD

Length COLOUR/ RAL PART NUMBER EURO

OTR TRACKS RAILS STANDARD - 1 m

1 m	■	310817	46,00
1 m	■	310820	46,00
1 m	□	310822	46,00

OTR TRACKS RAILS STANDARD - 2 m

2 m	■	310871	90,00
2 m	■	310872	90,00
2 m	□	310874	90,00

OTR TRACKS RAILS STANDARD - 3 m

3 m	■	310884	134,00
3 m	■	310885	134,00
3 m	□	310889	134,00

OTR TRACKS RAILS STANDARD - 4 m

4 m	■	310898	176,00
4 m	■	310899	176,00
4 m	□	310900	176,00



OTR TRACKS RAILS RECESSED

Length COLOUR/ RAL PART NUMBER EURO

OTR TRACKS RAILS RECESSED - 1 m

1 m	■	310834	57,00
1 m	■	310835	57,00
1 m	□	310836	57,00

OTR TRACKS RAILS RECESSED - 2 m

2 m	■	310879	113,00
2 m	■	310880	113,00
2 m	□	310881	113,00

OTR TRACKS RAILS RECESSED - 3 m

3 m	■	310891	170,00
3 m	■	310892	170,00
3 m	□	310893	170,00

OTR TRACKS RAILS RECESSED - 4 m


4 m	■	310903	225,00
4 m	■	310904	225,00
4 m	□	310905	225,00



INSTALLATION




Ceiling surface mounted





Wall mounted
(horizontally)



Suspended



Ceiling recessed



Accessories | Electro-mechanical connections

Connections are available in all the versions needed to make up a complex lighting system.
Positioning of the mechanical wrench: internal, external, left, right, with reference to the red line shown in the drawing.

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------


9001 - OTR END - FEED RIGHT

Feeder - L - right mechanical wrench / left grounding	<input type="checkbox"/>	310758	22,00
	<input type="checkbox"/>	310755	22,00
	<input type="checkbox"/>	310752	22,00



9002 - OTR END - FEED LEFT

Feeder - R - right mechanical wrench / right grounding	<input type="checkbox"/>	310759	22,00
	<input type="checkbox"/>	310756	22,00
	<input type="checkbox"/>	310753	22,00



9003 - OTR TK CONNECTOR

Through joint	<input type="checkbox"/>	310713	14,00
	<input type="checkbox"/>	310712	14,00
	<input type="checkbox"/>	310711	14,00



9003-M - OTR TK CONNECTOR ONLY MACHA

Insulating connection	<input type="checkbox"/>	310667	10,00
	<input type="checkbox"/>	310666	10,00
	<input type="checkbox"/>	310664	10,00




9010 - OTR MIDDLE-FEED

Direct joint	<input type="checkbox"/>	310827	42,00
	<input type="checkbox"/>	310821	42,00
	<input type="checkbox"/>	310818	42,00



9018 - OTR FLEXIBLE CORNER

Flexible joint	<input type="checkbox"/>	310849	59,00
	<input type="checkbox"/>	310848	59,00
	<input type="checkbox"/>	310847	59,00



Accessories | Electro-mechanical connections

DESCRIPTION COLOR PART NUMBER EURO

9011 - OTR L - FEED INT

L-shaped joint - internal mechanical wrench / external grounding	□	310832	54,00
	■	310825	54,00
	■	310823	54,00




9012 - OTR L - FEED EXT

L-shaped joint - external mechanical wrench / internal grounding	□	310833	54,00
	■	310826	54,00
	■	310824	54,00




9013 - OTR T - FEED EXT LEFT

T-shaped joint - left mechanical wrench / right grounding	□	310858	77,00
	■	310854	77,00
	■	310850	77,00




9014 - OTR T - FEED EXT RIGHT

T-shaped joint - right external mechanical wrench / left internal grounding	□	310859	77,00
	■	310855	77,00
	■	310851	77,00




9015 - OTR T - FEED INT LEFT

T-shaped joint - left internal mechanical wrench / right external grounding	□	310860	77,00
	■	310856	77,00
	■	310852	77,00






9016 - OTR T - FEED INT RIGHT

T-shaped joint - right internal mechanical wrench / left external grounding	□	310861	77,00
	■	310857	77,00
	■	310853	77,00





















9017 - OTR X - FEED

X-shaped joint	□	310876	90,00
	■	310875	90,00
	■	310873	90,00




Accessories | accessories for connections

DESCRIPTION	COLOR	PART NUMBER	EURO
9001 - R/6			
Suspended ceiling cover for head		310674	12,00
		310673	12,00
		310672	12,00
9010-R/6			
Suspended ceiling cover for direct joint		310680	12,00
		310679	12,00
		310675	12,00
9011 - R/6			
Suspended ceiling cover for L-shaped joint		310687	12,00
		310683	12,00
		310681	12,00
9013 - R/6			
Suspended ceiling cover for T-shaped joint		310692	12,00
		310691	12,00
		310690	12,00
9017 - R/6			
Suspended ceiling cover for X-shaped joint		310706	12,00
		310701	12,00
		310700	12,00
9001 /115			
Gasket for feeder		310581	4,00
		310580	4,00




310674 310673 310672




310680 310679 310675




310687 310683 310681



310692 310691 310690



310706 310701 310700



310581 310580


Accessories | Track accessories

Unless otherwise indicated, all accessories are available in three colours: White W ral 9010 / Grey G RAL 7035 / Black B ral 9005

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------


9004

Closing cap with locking screw		310617	5,00
		310615	5,00
		310614	5,00




9004-R

Suspended ceiling closing cap with locking screw		310620	5,00
		310618	5,00
		310616	5,00




9000/H

Suspension hook		310630	8,00
		310629	8,00
		310628	8,00




S-9000/GP

Additional protective sheath (1 m)		310637	7,00
		310636	7,00
		310635	7,00




9000/TP

Additional protective cap for track slots		310621	4,00
---	---	---------------	-------------




Track-fastening accessories


Complete kit for suspended fastening



Accessories for mounting on ceiling



Individual accessories: various possible combinations for ceiling mounting



Accessories | brackets

DESCRIPTION COLOR PART NUMBER EURO

S-9000/113

Short suspension clamp (40 mm)		310653	10,00
		310645	10,00
		310652	10,00



310653 310645 310652

S-9000/123

Long suspension clamp for use with through joint (100 mm)		310728	19,00
		310715	19,00
		310727	19,00



310728 310715 310727

S-9000/313

Short suspension clamp (25 mm)		310655	8,00
		310646	8,00
		310654	8,00



310655 310646 310654

S-9000/333

Long suspension clamp (180 mm)		310730	19,00
		310716	19,00
		310729	19,00



310730 310716 310729

S-9000/131

Ceiling-mounting clamp		310698	14,00
		310682	14,00
		310697	14,00



310698 310682 310697

S-9000/132

Ceiling-mounting clamp for suspensions	-	310642	9,00
--	---	---------------	-------------



310642

9000/231

Clamp with automatic tensioner	-	310740	22,00
--------------------------------	---	---------------	--------------






310740

Accessories | brackets

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------



9000/312-LA

Short suspension clamp with hole for automatic tensioner (35 mm)		311048	10,00
		311047	10,00
		311046	10,00



311048 311047 311046




9000/312-SV

Short suspension clamp with hole for cable with ball terminal (35 mm)		311051	10,00
		311050	10,00
		311049	10,00



311051 311050 311049




9000/322-LA

Medium suspension clamp with hole for automatic tensioner (100 mm)		311054	19,00
		311053	19,00
		311052	19,00



311054 311053 311052



9000/322-SV

Medium suspension clamp with hole for cable with ball terminal (100 mm)		311057	19,00
		311056	19,00
		311055	19,00



311057 311056 311055




9000/332-LA

Long suspension clamp with hole for automatic tensioner for use with through joint (180 mm)		310738	25,00
		311076	25,00
		310754	25,00



310738 311076 310754

9000/332-SV

Long suspension clamp with hole for cable with ball terminal for use with through joint (180 mm)		311077	25,00
		310739	25,00
		311078	25,00



311077 310739 311078

Accessories | Clip

DESCRIPTION COLOR PART NUMBER EURO

S-9000/111

Steel clip for mounting on ceiling - **310625** **7,00**



310625

S-9000/114-T

Clip with automatic tensioner for quick mounting

<input type="checkbox"/>	310744	23,00
<input type="checkbox"/>	310743	23,00
<input type="checkbox"/>	310742	23,00



310744

310743

310742

S-9000/115

Clip for quick mounting

<input type="checkbox"/>	310651	11,00
<input type="checkbox"/>	310650	11,00
<input type="checkbox"/>	310649	11,00



310651

310650

310649

S-9000/116

Clamp with automatic tensioner - **310699** **15,00**



310699

S-9000/118

Clip for quick mounting with M6 tensioner

<input type="checkbox"/>	310696	15,00
<input type="checkbox"/>	310695	15,00
<input type="checkbox"/>	310694	15,00



310696

310695

310694

S-9000/119-TB

Clip for quick mounting of track on T-bar

<input type="checkbox"/>	310689	14,00
<input type="checkbox"/>	310688	14,00



310689

310688

S-9000/5

Plastic cover for clips and clamps

<input type="checkbox"/>	310613	5,00
<input type="checkbox"/>	310612	5,00
<input type="checkbox"/>	310611	5,00



310613

310612

310611

Accessories | Cables

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9000/211

Steel cable (Ø 1.5 mm - 1.5 m length)	-	310634	8,00
Steel cable (Ø 1.5 mm - 2 m length)	-	310643	10,00
Steel cable (Ø 1.5 mm - 3 m length)	-	310657	11,00
Steel cable (Ø 1.5 mm - 5 m length)	-	310718	22,00



9000/211-S

Steel cable (Ø 1.5 mm - 1.5 m length) with ball terminal	-	310647	10,00
Steel cable (Ø 1.5 mm - 2 m length) with ball terminal	-	310658	10,00
Steel cable (Ø 1.5 mm - 3 m length) with ball terminal	-	310668	13,00
Steel cable (Ø 1.5 mm - 5 m length) with ball terminal	-	310726	23,00
Steel cable (Ø 1.5 mm - 6 m length) with ball terminal	-	310741	25,00



Accessories | Tensioners

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9000/218

M5 automatic tensioner with lateral hole, in chromed brass	-	310665	11,00
--	---	---------------	--------------



310665

9000/213

Automatic hook tensioner, in nickel-plated brass	-	310671	10,00
--	---	---------------	--------------



310671

9000/214

Automatic locking tensioner, in nickel-plated brass	-	310693	12,00
---	---	---------------	--------------



310693

9000/215

Screw tensioner, in nickel-plated brass	-	310619	4,00
---	---	---------------	-------------



310619

Accessories | complete kit for suspended mounting

DESCRIPTION COLOR PART NUMBER EURO

9000-KIT2 - 1,5 m

Bracket for mounting on ceiling, screw tensioner, plastic ceiling rose, Ø 1.5 mm 1.5 m-long steel cable with ball end, clip for quick mounting	<input type="checkbox"/>	310778	25,00
	<input type="checkbox"/>	310777	25,00
	<input type="checkbox"/>	310776	25,00

9000-KIT2 - 3 m

Ceiling-mounting bracket, screw tensioner, plastic ceiling rose, Ø 1.5 mm 3 m-long steel cable with ball end, clip for quick mounting	<input type="checkbox"/>	310787	26,00
	<input type="checkbox"/>	310786	26,00
	<input type="checkbox"/>	310785	26,00

9000-KIT2 - 5 m

Bracket for mounting on ceiling, screw tensioner, plastic ceiling rose, Ø 1.5 mm 5 m-long steel cable with ball end, clip for quick mounting	<input type="checkbox"/>	310813	35,00
	<input type="checkbox"/>	310812	35,00
	<input type="checkbox"/>	310811	35,00

9000-KIT4 - 1,5 m

Metal ball ceiling rose with hole, Ø 1.5 mm 1.5 m-long steel cable with ball end, with automatic tensioner	-	310801	32,00
--	---	---------------	--------------

9000-KIT4 - 3 m

Rosace métallique sphérique avec trou, câble en acier Ø 1,5 mm ongueur 3 m avec extrémité sphérique, avec tendeur automatique	-	310805	33,00
---	---	---------------	--------------

9000-KIT4 - 5 m

Metal ball ceiling rose with hole, Ø 1.5 mm 5 m-long steel cable with ball end, with automatic tensioner	-	310831	42,00
--	---	---------------	--------------

9000-KIT6 - 1,5 m


Screw tensioner, plastic ceiling rose, Ø 1.5 mm 1.5 m-long steel cable with ball end, bracket with milled hole and automatic tensioner	<input type="checkbox"/>	310781	25,00
	<input type="checkbox"/>	310780	25,00
	<input type="checkbox"/>	310779	25,00

9000-KIT6 - 3 m


Screw tensioner, plastic ceiling rose, Ø 1.5 mm 3 m-long steel cable with ball end, bracket with milled hole and automatic tensioner	<input type="checkbox"/>	310794	28,00
	<input type="checkbox"/>	310793	28,00
	<input type="checkbox"/>	310792	28,00

9000-KIT6 - 5 m


Screw tensioner, plastic ceiling rose, Ø 1.5 mm 5 m-long steel cable with ball end, bracket with milled hole and automatic tensioner	<input type="checkbox"/>	310810	34,00
	<input type="checkbox"/>	310809	34,00
	<input type="checkbox"/>	310808	34,00



310778 - 1,5 m 310777 - 1,5 m 310776 - 1,5 m
310787 - 3 m 310786 - 3 m 310785 - 3 m
310813 - 5 m 310812 - 5 m 310811 - 5 m



310801 - 1,5 m
310805 - 3 m
310831 - 5 m







310781 - 1,5 m 310780 - 1,5 m 310779 - 1,5 m
310794 - 3 m 310793 - 3 m 310792 - 3 m
310810 - 5 m 310809 - 5 m 310808 - 5 m

Accessories | suspended mounting set

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9000-P3-KIT4 - 1 m

Bracket for mounting on ceiling, M6 nut, plastic ceiling rose, M6 1 m-long threaded bar with cover sheath		310770	23,00
		310769	23,00
		310768	23,00



310770 310769 310768

9000-P2

Bracket with M6 tensioner and plastic cover		310736	16,00
		310735	16,00
		310734	16,00



310736 310735 310734

Accessories | Ceiling roses

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9000/3

Plastic ceiling rose for Ø 1.5 mm steel cable		310603	5,00
		310602	5,00
		310601	5,00



310603 310602 310601

9000/4

Plastic ceiling rose for threaded bar in M6 steel		310606	5,00
		310605	5,00
		310604	5,00



310606 310605 310604

9000/216

Metal ball ceiling rose with hole	-	310644	7,00
-----------------------------------	---	---------------	-------------



310644

Accessories | Adapters

OTR adapters are equipped with a phase selector that allows the selection to be maintained even when the adapter is removed and/or reinserted into the line. This also allows for the selection of the phase before assembly, thus simplifying the operation.

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9009

6-Conductor DALI adapter (3-phase + control system) (maximum load 100 N = 10.2 kg)	□	310751	22,00
	■	310750	22,00
	■	310749	22,00



310751 310750 310749

9009-4

4-Conductor adapter (3-phase) (maximum load 100 N = 10.2 kg)	□	310725	15,00
	■	310722	15,00
	■	310721	15,00



310725 310722 310721

S-9209

Asymmetric 4-conductor adapter (3-phase) (maximum load 100 N = 10.2 kg)	□	310764	22,00
	■	310760	22,00
	■	310757	22,00



310764 310760 310757

S-9209-4

Asymmetric 4-conductor adapter (3-phase) (maximum load 100 N = 10.2 kg)	□	310737	16,00
	■	310733	16,00
	■	310732	16,00



310737 310733 310732

9409-4

Asymmetric 4-conductor adapter (3-phase) (maximum load 50 N = 5.1 kg)	□	311060	13,00
	■	311059	13,00
	■	311058	13,00



311060 311059 311058

9409-4-DRI

Compact 4-conductor adapter with integrated driver (3-phase) (100-850 mA - max. 40 VDC)	□	311063	69,00
	■	311062	69,00
	■	311061	69,00



311063 311062 311061

9909-DRI

Integrated 6-conductor DALI adapter with integrated driver (3-phase + control system) (350-500 mA - max. 50VDC)	□	310897	154,00
	■	310896	154,00
	■	310895	154,00



310897 310896 310895

9909-4-DRI

Integrated 4-conductor adapter with integrated driver (3-phase) (100-850 mA - max. 40 VDC)	□	310888	121,00
	■	310887	121,00
	■	310886	121,00



310888 310887 310886

Accessories | Accessories for adapters

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------




S-9000/BP-D

Adapter ceiling-mounting base (without using the track)		310845	51,00
		310844	51,00
		310843	51,00



310845 310844 310843

9000/BR

Adapter suspended ceiling-mounting base (without using the track)		310830	42,00
		310829	42,00
		310828	42,00



310830 310829 310828

S-9000/M

Mechanical adapter		310678	12,00
		310677	12,00
		310676	12,00



310678 310677 310676

S-9000/BC


External cable clamp with plastic grub screw		310624	6,00
		310623	6,00
		310622	6,00



310624 310623 310622

S-9000/D

Nut for M10 connector		310609	5,00
Nut for M13 connector		310610	5,00



310609 310610

9009/IP40


IP40 Housing for symmetrical adapter		310592	5,00
		310590	5,00
		310588	5,00



310592 310590 310588

S-9000

Aluminium M10 connector for adapter	-	310638	7,00
Aluminium M13 connector for adapter	-	310639	7,00



310638 310639

S-9000/SC

Aluminium M10 connector without collar for adapter	-	310662	9,00
Aluminium M13 connector without collar for adapter	-	310663	9,00



310662 310663

S-9000/FI

Aluminium M10 connector with internal thread for adapter	-	310648	8,00
--	---	---------------	-------------



310648

9009/T-INS

Adapter wiring insert	-	310862	77,00
-----------------------	---	---------------	--------------



310862

9009/T-HAN

Handle for adapter wiring insert	-	310846	53,00
----------------------------------	---	---------------	--------------



310846

9009/10

Internal cable clamp for symmetrical adapter		310586	4,00
		310584	4,00
		310582	4,00



310586 310584 310582

9009/51

Aluminium ring with block grub screw to prevent twisting of adapter connectors	-	310656	8,00
--	---	---------------	-------------



310656

Accessories | Accessories for adapters

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9209/IP40

IP40 Housing for asymmetrical adapter	<input type="checkbox"/>	310593	5,00
	<input type="checkbox"/>	310591	5,00
	<input checked="" type="checkbox"/>	310589	5,00



310593 310591 310589

9209/20

Internal cable clamp for asymmetrical adapter	<input type="checkbox"/>	310587	4,00
	<input type="checkbox"/>	310585	4,00
	<input checked="" type="checkbox"/>	310583	4,00



310587 310585 310583

9909-DRI/11

Plastic friction ring for retractable adapter	<input type="checkbox"/>	310600	4,00
	<input type="checkbox"/>	310599	4,00
	<input checked="" type="checkbox"/>	310598	4,00



310600 310599 310598

9909/M10

M10 Terminal for retractable adapter	-	310731	15,00
--------------------------------------	---	---------------	--------------




310731

Accessories | Driver box and accessories

DESCRIPTION	COLOR	PART NUMBER	EURO
-------------	-------	-------------	------

9209/BD-M


LED driver box. For use with asymmetrical adaptor 9209.... Max. size for driver housing: 116x52x30 mm	<input type="checkbox"/>	310720	14,00
	<input checked="" type="checkbox"/>	310719	14,00



310720 310719

9209/BD-L


LED driver box. For use with asymmetrical adaptor 9209.... Max. size for driver housing: 162x52x30 mm	<input type="checkbox"/>	310724	15,00
	<input checked="" type="checkbox"/>	310723	15,00



310724 310723

9209-BD/3

Plastic cover and screws for LED driver box connectors	<input type="checkbox"/>	310608	4,00
	<input checked="" type="checkbox"/>	310607	4,00



310608 310607

9209-BD

Aluminium M10 connector for LED driver box	-	310669	10,00
Aluminium M13 connector for LED driver box	-	310670	10,00



310669 310670

9209-BD-10/4

Adapter for M10 connector for LED driver box	<input type="checkbox"/>	310595	4,00
	<input checked="" type="checkbox"/>	310594	4,00



310595 310594

9209-BD-13/4


Adapter for M13 connector for LED driver box	<input type="checkbox"/>	310597	4,00
	<input checked="" type="checkbox"/>	310596	4,00



310597 310596

DRV BX KIT-BD/M10


Kit for LED driver box - complete set for M10 mounting	<input type="checkbox"/>	310708	13,00
	<input checked="" type="checkbox"/>	310707	13,00




310708 310707

DRV BX KIT-BD/M13

Kit for LED driver box - complete set for M13 mounting	<input type="checkbox"/>	310710	13,00
	<input checked="" type="checkbox"/>	310709	13,00



310710 310709



De Romein Group - Veendam - Netherlands

TRY



Van EE Steel Specialist - Barneveld - Netherlands



Scan the QR-code for the latest information



WH-RAL9003 / White RAL9003 / Glossy

LED system for indoor lighting consisting of luminaires and electrified RAIL, suitable for commercial and industrial applications, comprising:

- Extruded aluminium luminaire housing, polyester powder coat, white finish
- High-transparency polycarbonate optics
- Symmetrical optics (S/EW - S/W), asymmetrical right (A/M R), asymmetrical left (A/M L) and double asymmetrical (2A/M)
- Available with ON-OFF driver, dimmable DALI, and emergency unit that ensures 3 hours of autonomy
- Tool-free springs installation of the luminaire to the electric RAIL
- SMART systems can be designed using the dedicated wireless KITS available as accessories, combined with the "7-pole DALI" RAIL and the DALI luminaire
- The SMART solution includes an electronic device for intelligent management of light, as well as occupancy and luminosity sensors based on an 868 MHz wireless platform. It can be used to create systems that interact with the surrounding environment
- 5-pole RAIL accessories only to be used in the ON-OFF versions
- The 7-pole DALI accessories available only for TRY DALI versions or combining TRY DALI with TRY ON/OFF
- 7-pole EM accessories are available only for TRY EM versions or combining TRY EM with TRY ON/OFF
- 9-pole DALI/EM accessories only for TRY EM, TRY DALI/EM, or for versions combining TRY EM, TRY DALI, and TRY EM + DALI
- EUROSTANDARD PLUS® electric track module for installation of compatible projectors (AS... LED) available as accessory
- RAILS feature internal 3 phases 2.5 mm² cables, fast connectors and circuit breakers for a quick installation of the luminaire
- DALI dimming (25 W - 34 W) versions on request
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Consult factory for S/M 30 degrees optics option, suitable for lighting warehouse shelving aisles, from high ceilings
- Continuous mounted options and many other configurations are available at www.light-performer.com





CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com



TRY

Identifying and classifying our optics





TRY S/W

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
85	I	-	80	4000	S/W	-	14969	11599	☐	1434	305927	✓
85	I	-	80	3000	S/W	-	14138	11122	☐	1434	305926	✓
71	I	-	80	4000	S/W	-	12800	10355	☐	1434	305681	✓
71	I	-	80	3000	S/W	-	12089	9929	☐	1434	305680	✓
53	I	-	80	4000	S/W	-	9762	8154	☐	1434	305675	✓
53	I	-	80	3000	S/W	-	9219	7819	☐	1434	305674	✓
42	I	-	80	4000	S/W	-	7765	6553	☐	1434	305669	✓
42	I	-	80	3000	S/W	-	7334	6284	☐	1434	305668	✓
34	I	-	80	4000	S/W	-	6292	5393	☐	1434	305921	✓
34	I	-	80	3000	S/W	-	5943	5171	☐	1434	305920	✓
25	I	-	80	4000	S/W	-	4815	4023	☐	1434	305663	✓
25	I	-	80	3000	S/W	-	4547	3858	☐	1434	305662	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

85	I	-	80	4000	S/W	-	14969	11599	☐	1434	305937	✓
85	I	-	80	3000	S/W	-	14138	11122	☐	1434	305936	✓
71	I	-	80	4000	S/W	-	12800	10355	☐	1434	305707	✓
71	I	-	80	3000	S/W	-	12089	9929	☐	1434	305706	✓
53	I	-	80	4000	S/W	-	9762	8154	☐	1434	305701	✓
53	I	-	80	3000	S/W	-	9219	7819	☐	1434	305700	✓
42	I	-	80	4000	S/W	-	7765	6553	☐	1434	305695	✓
42	I	-	80	3000	S/W	-	7334	6284	☐	1434	305694	✓

TRY S/W EM

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
85	I	-	80	4000	S/W	-	14969	11599	☐	1434	306865	✓
85	I	-	80	3000	S/W	-	14138	11122	☐	1434	306864	✓
71	I	-	80	4000	S/W	-	12800	10355	☐	1434	306863	✓
71	I	-	80	3000	S/W	-	12089	9929	☐	1434	306862	✓
53	I	-	80	4000	S/W	-	9762	8154	☐	1434	306860	✓
53	I	-	80	3000	S/W	-	9219	7819	☐	1434	306861	✓
42	I	-	80	4000	S/W	-	7765	6553	☐	1434	306859	✓
42	I	-	80	3000	S/W	-	7334	6284	☐	1434	306858	✓
34	I	-	80	4000	S/W	-	6292	5393	☐	1434	306857	✓
34	I	-	80	3000	S/W	-	5943	5171	☐	1434	306856	✓
25	I	-	80	4000	S/W	-	4815	4023	☐	1434	306855	✓
25	I	-	80	3000	S/W	-	4547	3858	☐	1434	306854	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h

85	I	-	80	4000	S/W	-	14969	11599	☐	1434	306504	✓
85	I	-	80	3000	S/W	-	14138	11122	☐	1434	306503	✓
71	I	-	80	4000	S/W	-	12800	10355	☐	1434	306502	✓
71	I	-	80	3000	S/W	-	12089	9929	☐	1434	306501	✓
53	I	-	80	4000	S/W	-	9762	8154	☐	1434	306500	✓
53	I	-	80	3000	S/W	-	9219	7819	☐	1434	306499	✓
42	I	-	80	4000	S/W	-	7765	6553	☐	1434	306498	✓
42	I	-	80	3000	S/W	-	7334	6284	☐	1434	306497	✓

TRY S/EW

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
85	I	-	80	4000	S/EW	-	14969	11593	☐	1434	305925	✓
85	I	-	80	3000	S/EW	-	14138	11116	☐	1434	305924	✓
71	I	-	80	4000	S/EW	-	12800	10350	☐	1434	305679	✓
71	I	-	80	3000	S/EW	-	12089	9925	☐	1434	305678	✓
53	I	-	80	4000	S/EW	-	9762	8150	☐	1434	305673	✓
53	I	-	80	3000	S/EW	-	9219	7815	☐	1434	305672	✓
42	I	-	80	4000	S/EW	-	7765	6550	☐	1434	305667	✓
42	I	-	80	3000	S/EW	-	7334	6281	☐	1434	305666	✓
34	I	-	80	4000	S/EW	-	6292	5390	☐	1434	305919	✓
34	I	-	80	3000	S/EW	-	5943	5169	☐	1434	305918	✓
25	I	-	80	4000	S/EW	-	4815	4021	☐	1434	305661	✓
25	I	-	80	3000	S/EW	-	4547	3856	☐	1434	305660	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
85	I	-	80	4000	S/EW	-	14969	11593	☐	1434	305935	✓
85	I	-	80	3000	S/EW	-	14138	11116	☐	1434	305934	✓
71	I	-	80	4000	S/EW	-	12800	10350	☐	1434	305705	✓
71	I	-	80	3000	S/EW	-	12089	9925	☐	1434	305704	✓
53	I	-	80	4000	S/EW	-	9762	8150	☐	1434	305699	✓
53	I	-	80	3000	S/EW	-	9219	7815	☐	1434	305698	✓
42	I	-	80	4000	S/EW	-	7765	6550	☐	1434	305693	✓
42	I	-	80	3000	S/EW	-	7334	6281	☐	1434	305692	✓



TRY S/EW EM

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
85	I	-	80	4000	S/EW	-	14969	11593	☐	1434	305933	✓
85	I	-	80	3000	S/EW	-	14138	11116	☐	1434	305932	✓
71	I	-	80	4000	S/EW	-	12800	10350	☐	1434	305691	✓
71	I	-	80	3000	S/EW	-	12089	9925	☐	1434	305690	✓
53	I	-	80	4000	S/EW	-	9762	8150	☐	1434	305689	✓
53	I	-	80	3000	S/EW	-	9219	7815	☐	1434	305688	✓
42	I	-	80	4000	S/EW	-	7765	6550	☐	1434	305687	✓
42	I	-	80	3000	S/EW	-	7334	6281	☐	1434	305686	✓
34	I	-	80	4000	S/EW	-	6292	5390	☐	1434	305931	✓
34	I	-	80	3000	S/EW	-	5943	5169	☐	1434	305930	✓
25	I	-	80	4000	S/EW	-	4815	4021	☐	1434	305685	✓
25	I	-	80	3000	S/EW	-	4547	3856	☐	1434	305684	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h												
85	I	-	80	4000	S/EW	-	14969	11593	☐	1434	306905	✓
85	I	-	80	3000	S/EW	-	14138	11116	☐	1434	306904	✓
71	I	-	80	4000	S/EW	-	12800	10350	☐	1434	306903	✓
71	I	-	80	3000	S/EW	-	12089	9925	☐	1434	306902	✓
53	I	-	80	4000	S/EW	-	9762	8150	☐	1434	306901	✓
53	I	-	80	3000	S/EW	-	9219	7815	☐	1434	306900	✓
42	I	-	80	4000	S/EW	-	7765	6550	☐	1434	306899	✓
42	I	-	80	3000	S/EW	-	7334	6281	☐	1434	306898	✓



TRY 2A/M

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
85	I	-	80	4000	2A/M	-	14969	11620	☐	1434	305929	✓
85	I	-	80	3000	2A/M	-	14138	11143	☐	1434	305928	✓
71	I	-	80	4000	2A/M	-	12800	10374	☐	1434	305683	✓
71	I	-	80	3000	2A/M	-	12089	9948	☐	1434	305682	✓
53	I	-	80	4000	2A/M	-	9762	8169	☐	1434	305677	✓
53	I	-	80	3000	2A/M	-	9219	7833	☐	1434	305676	✓
42	I	-	80	4000	2A/M	-	7765	6565	☐	1434	305671	✓
42	I	-	80	3000	2A/M	-	7334	6296	☐	1434	305670	✓
34	I	-	80	4000	2A/M	-	6292	5403	☐	1434	305923	✓
34	I	-	80	3000	2A/M	-	5943	5181	☐	1434	305922	✓
25	I	-	80	4000	2A/M	-	4815	4031	☐	1434	305665	✓
25	I	-	80	3000	2A/M	-	4547	3865	☐	1434	305664	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
85	I	-	80	4000	2A/M	-	14969	11620	☐	1434	305939	✓
85	I	-	80	3000	2A/M	-	14138	11143	☐	1434	305938	✓
71	I	-	80	4000	2A/M	-	12800	10374	☐	1434	305709	✓
71	I	-	80	3000	2A/M	-	12089	9948	☐	1434	305708	✓
53	I	-	80	4000	2A/M	-	9762	8169	☐	1434	305703	✓
53	I	-	80	3000	2A/M	-	9219	7833	☐	1434	305702	✓
42	I	-	80	4000	2A/M	-	7765	6565	☐	1434	305697	✓
42	I	-	80	3000	2A/M	-	7334	6296	☐	1434	305696	✓



TRY 2A/M EM

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
85	I	-	80	4000	2A/M	-	14969	11620	☐	1434	306853	✓
85	I	-	80	3000	2A/M	-	14138	11143	☐	1434	306852	✓
71	I	-	80	4000	2A/M	-	12800	10374	☐	1434	306851	✓
71	I	-	80	3000	2A/M	-	12089	9948	☐	1434	306850	✓
53	I	-	80	4000	2A/M	-	9762	8169	☐	1434	306848	✓
53	I	-	80	3000	2A/M	-	9219	7833	☐	1434	306849	✓
42	I	-	80	4000	2A/M	-	7765	6565	☐	1434	306847	✓
42	I	-	80	3000	2A/M	-	7334	6296	☐	1434	306846	✓
34	I	-	80	4000	2A/M	-	6992	5403	☐	1434	306845	✓
34	I	-	80	3000	2A/M	-	5943	5181	☐	1434	306844	✓
25	I	-	80	4000	2A/M	-	4815	4031	☐	1434	306843	✓
25	I	-	80	3000	2A/M	-	4547	3865	☐	1434	306842	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h												
85	I	-	80	4000	2A/M	-	14969	11620	☐	1434	306897	✓
85	I	-	80	3000	2A/M	-	14138	11143	☐	1434	306896	✓
71	I	-	80	4000	2A/M	-	12800	10374	☐	1434	306895	✓
71	I	-	80	3000	2A/M	-	12089	9946	☐	1434	306894	✓
53	I	-	80	4000	2A/M	-	9762	8169	☐	1434	306893	✓
53	I	-	80	3000	2A/M	-	9219	7833	☐	1434	306892	✓
42	I	-	80	4000	2A/M	-	7765	6565	☐	1434	306891	✓
42	I	-	80	3000	2A/M	-	7334	6296	☐	1434	306890	✓



TRY A/M L

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306813	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306812	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306811	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306810	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306809	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306808	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306807	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306806	✓
34	I	-	80	4000	A21/M	-	6292	5155	☐	1434	306805	✓
34	I	-	80	3000	A21/M	-	5943	4960	☐	1434	306804	✓
25	I	-	80	4000	A21/M	-	4815	3860	☐	1434	306803	✓
25	I	-	80	3000	A21/M	-	4547	3696	☐	1434	306802	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306833	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306832	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306831	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306830	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306829	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306828	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306827	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306826	✓



TRY A/M L EM

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306877	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306876	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306875	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306874	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306872	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306873	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306871	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306870	✓
34	I	-	80	4000	A21/M	-	6292	5155	☐	1434	306869	✓
34	I	-	80	3000	A21/M	-	5943	4960	☐	1434	306868	✓
25	I	-	80	4000	A21/M	-	4815	3860	☐	1434	306867	✓
25	I	-	80	3000	A21/M	-	4547	3696	☐	1434	306866	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306913	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306912	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306911	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306910	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306909	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306908	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306907	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306906	✓



TRY A/M R

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306825	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306824	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306823	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306822	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306821	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306820	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306819	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306818	✓
34	I	-	80	4000	A21/M	-	6292	5155	☐	1434	306817	✓
34	I	-	80	3000	A21/M	-	5943	4960	☐	1434	306816	✓
25	I	-	80	4000	A21/M	-	4815	3860	☐	1434	306815	✓
25	I	-	80	3000	A21/M	-	4547	3696	☐	1434	306814	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306841	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306840	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306839	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306838	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306837	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306836	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306835	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306834	✓

TRY A/M R EM

IP40 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306889	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306888	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306887	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306886	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306884	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306885	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306883	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306882	✓
34	I	-	80	4000	A21/M	-	6292	5155	☐	1434	306881	✓
34	I	-	80	3000	A21/M	-	5943	4960	☐	1434	306880	✓
25	I	-	80	4000	A21/M	-	4815	3860	☐	1434	306879	✓
25	I	-	80	3000	A21/M	-	4547	3696	☐	1434	306878	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h

85	I	-	80	4000	A21/M	-	14969	11128	☐	1434	306921	✓
85	I	-	80	3000	A21/M	-	14138	10669	☐	1434	306920	✓
71	I	-	80	4000	A21/M	-	12800	9933	☐	1434	306919	✓
71	I	-	80	3000	A21/M	-	12089	9525	☐	1434	306918	✓
53	I	-	80	4000	A21/M	-	9762	7821	☐	1434	306917	✓
53	I	-	80	3000	A21/M	-	9219	7501	☐	1434	306916	✓
42	I	-	80	4000	A21/M	-	7765	6287	☐	1434	306915	✓
42	I	-	80	3000	A21/M	-	7334	6022	☐	1434	306914	✓

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
RAIL-A TRY 5P			
RAIL-A TRY 5P - L 1435 mm (2 stainless steel brackets included)		310554	✓
RAIL-M TRY 5P			
RAIL-M TRY 5P - L 1435 mm (2 stainless steel brackets included)		310555	✓
RAIL-M TRY 5P - L 2870 mm (4 stainless steel brackets included)		310556	✓
RAIL-M TRY 5P - L 4305 mm (6 stainless steel brackets included)		310557	✓
RAIL-A TRY 7P DALI			
RAIL-A TRY 7P DALI - L 1435 mm (2 stainless steel brackets included)		310558	✓
RAIL-M TRY 7P DALI			
RAIL-M TRY 7P DALI - L 1435 mm (2 stainless steel brackets included)		310559	✓
RAIL-M TRY 7P DALI - L 2870 mm (4 stainless steel brackets included)		310560	✓
RAIL-M TRY 7P DALI - L 4305 mm (6 stainless steel brackets included)		310561	✓
RAIL-A TRY 7P EM			
RAIL-A TRY 7P EM - L 1435 mm (2 stainless steel brackets included)		310562	✓
RAIL-M TRY 7P EM			
RAIL-M TRY 7P EM - L 1435 mm (2 stainless steel brackets included)		310563	✓
RAIL-M TRY 7P EM - L 2870 mm (4 stainless steel brackets included)		310564	✓
RAIL-M TRY 7P EM - L 4305 mm (6 stainless steel brackets included)		310565	✓
RAIL-A TRY 9P DALI/EM			
RAIL-A TRY 9P DALI/EM - L 1435 mm (2 stainless steel brackets included)		310934	✓
RAIL-M TRY 9P DALI/EM			
RAIL-M TRY 9P DALI/EM - L 1435 mm (2 stainless steel brackets included)		310935	✓
RAIL-M TRY 9P DALI/EM - L 2870 mm (4 stainless steel brackets included)		310936	✓
RAIL-M TRY 9P DALI/EM - L 4305 mm (6 stainless steel brackets included)		310937	✓



RAIL 5P



RAIL 7P DALI




RAIL 9P DALI / EM

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TRY			
Suspension kit (2 m)		14-00354	✓
Chain suspension		310550	✓
Closing plates for RAIL (nr. 2)		310551	✓
Cover PC RAIL - L 1435 mm		310553	✓
Stainless steel fast fit strong for quick ceiling mount (2 pieces)		3100243	✓
Stainless steel fast fit strong for quick ceiling mount (50 pieces)		3100244	✓
Stainless steel fast fit strong for quick ceiling mount+ hooks (2 pieces)		3100245	✓
Stainless steel fast fit strong for quick ceiling mount + hooks (50 pieces)		3100246	✓
TRY TRACK SYSTEM			
Rail system for floodlights		310566	✓



310550



310551




310553



3100243
3100244



3100245
3100246




310566

LIGHT CONTROL SYSTEM - 868 Mhz

COMPLETE UNIT

SMART systems can be produced using the dedicated wireless KITS available as accessories, to be combined with the "7-pole DALI" RAIL and the DALI ceiling light.




SMART accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TRY SMART			
Kit TRY SMART A receiver		310568	✓
Kit TRY SMART A receiver + sensor		310914	✓
Kit TRY SMART M sensor		310567	✓
USB flash drive to use with PC for wireless programming		14469720	✓
Remote control with four configurable buttons		14469820	✓
Wireless control pad with four configurable buttons		14477420	✓





SMART [4]




■ Grey RAL 7035 / Grey RAL7035 /


Scan the QR-code for the latest information

Highbay LEDSpecial Versions

- Cutting-edge flexibility
- Smart [4] is the range of lighting fixtures developed and produced in Italy with latest generation LEDs and new optics solutions (reflector optics and PMMA lenses), that warranties excellent lighting performance and always more energy efficiency. A wide and flexible range, available in three sizes (1 module, 2 modules and 4 modules), luminous fluxes up to 36.400 lm and different colour temperature options (3000K, 4000K, 5700K). The new design (grey RAL 7035) adapts perfectly to medium and large contexts (such as industries or indoor sports areas), both with Stand Alone application and through wiring, thanks to the special accessories that allow a wide flexibility during installation also



Identifying and classifying our optics



SMART [4] 1M HE

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
48	I	✓	80	5700	SYMM	30°	-	7600	■	GWS4120AF857	✓
48	I	✓	80	5700	SYMM	60°	-	7700	■	GWS4120AH857	✓
48	I	✓	80	5700	SYMM	90°	-	7700	■	GWS4120AP857	✓
48	I	✓	80	5700	ARRAY	-	-	7700	■	GWS4120AA857	✓
48	I	✓	80	5700	ASYMM	-	-	6900	■	GWS4120AC857	✓
48	I	✓	80	5700	ELL	-	-	7100	■	GWS4120AQ857	✓
48	I	✓	80	4000	SYMM	30°	-	7600	■	GWS4120AF840	✓
48	I	✓	80	4000	SYMM	60°	-	7700	■	GWS4120AH840	✓
48	I	✓	80	4000	SYMM	90°	-	7700	■	GWS4120AP840	✓
48	I	✓	80	4000	ARRAY	-	-	7700	■	GWS4120AA840	✓
48	I	✓	80	4000	ASYMM	-	-	6900	■	GWS4120AC840	✓
48	I	✓	80	4000	ELL	-	-	7100	■	GWS4120AQ840	✓
48	I	✓	80	3000	SYMM	30°	-	7200	■	GWS4120AF830	✓
48	I	✓	80	3000	SYMM	60°	-	7300	■	GWS4120AH830	✓
48	I	✓	80	3000	SYMM	90°	-	7300	■	GWS4120AP830	✓
48	I	✓	80	3000	ARRAY	-	-	7300	■	GWS4120AA830	✓
48	I	✓	80	3000	ASYMM	-	-	6500	■	GWS4120AC830	✓
48	I	✓	80	3000	ELL	-	-	6800	■	GWS4120AQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
48	I	✓	80	5700	SYMM	30°	-	7600	■	GWS4122AF857	✓
48	I	✓	80	5700	SYMM	60°	-	7700	■	GWS4122AH857	✓
48	I	✓	80	5700	SYMM	90°	-	7700	■	GWS4122AP857	✓
48	I	✓	80	5700	ARRAY	-	-	7700	■	GWS4122AA857	✓
48	I	✓	80	5700	ASYMM	-	-	6900	■	GWS4122AC857	✓
48	I	✓	80	5700	ELL	-	-	7100	■	GWS4122AQ857	✓
48	I	✓	80	4000	SYMM	30°	-	7600	■	GWS4122AF840	✓
48	I	✓	80	4000	SYMM	60°	-	7700	■	GWS4122AH840	✓
48	I	✓	80	4000	SYMM	90°	-	7700	■	GWS4122AP840	✓
48	I	✓	80	4000	ARRAY	-	-	7700	■	GWS4122AA840	✓
48	I	✓	80	4000	ASYMM	-	-	6900	■	GWS4122AC840	✓
48	I	✓	80	4000	ELL	-	-	7100	■	GWS4122AQ840	✓
48	I	✓	80	3000	SYMM	30°	-	7200	■	GWS4122AF830	✓
48	I	✓	80	3000	SYMM	60°	-	7300	■	GWS4122AH830	✓
48	I	✓	80	3000	SYMM	90°	-	7300	■	GWS4122AP830	✓
48	I	✓	80	3000	ARRAY	-	-	7300	■	GWS4122AA830	✓
48	I	✓	80	3000	ASYMM	-	-	6500	■	GWS4122AC830	✓
48	I	✓	80	3000	ELL	-	-	6800	■	GWS4122AQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
48	I	✓	80	5700	SYMM	30°	-	7600	■	GWS4121AF857	✓
48	I	✓	80	5700	SYMM	60°	-	7700	■	GWS4121AH857	✓
48	I	✓	80	5700	SYMM	90°	-	7700	■	GWS4121AP857	✓
48	I	✓	80	5700	ARRAY	-	-	7700	■	GWS4121AA857	✓
48	I	✓	80	5700	ASYMM	-	-	6900	■	GWS4121AC857	✓
48	I	✓	80	5700	ELL	-	-	7100	■	GWS4121AQ857	✓
48	I	✓	80	4000	SYMM	30°	-	7600	■	GWS4121AF840	✓
48	I	✓	80	4000	SYMM	60°	-	7700	■	GWS4121AH840	✓
48	I	✓	80	4000	SYMM	90°	-	7700	■	GWS4121AP840	✓
48	I	✓	80	4000	ARRAY	-	-	7700	■	GWS4121AA840	✓
48	I	✓	80	4000	ASYMM	-	-	6900	■	GWS4121AC840	✓
48	I	✓	80	4000	ELL	-	-	7100	■	GWS4121AQ840	✓
48	I	✓	80	3000	SYMM	30°	-	7200	■	GWS4121AF830	✓
48	I	✓	80	3000	SYMM	60°	-	7300	■	GWS4121AH830	✓
48	I	✓	80	3000	SYMM	90°	-	7300	■	GWS4121AP830	✓
48	I	✓	80	3000	ARRAY	-	-	7300	■	GWS4121AA830	✓
48	I	✓	80	3000	ASYMM	-	-	6500	■	GWS4121AC830	✓
48	I	✓	80	3000	ELL	-	-	6800	■	GWS4121AQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

48	I	✓	80	5700	SYMM	30°	-	7600	■	GWS4123AF857	✓
48	I	✓	80	5700	SYMM	60°	-	7700	■	GWS4123AH857	✓
48	I	✓	80	5700	SYMM	90°	-	7700	■	GWS4123AP857	✓
48	I	✓	80	5700	ARRAY	-	-	7700	■	GWS4123AA857	✓
48	I	✓	80	5700	ASYMM	-	-	6900	■	GWS4123AC857	✓
48	I	✓	80	5700	ELL	-	-	7100	■	GWS4123AQ857	✓
48	I	✓	80	4000	SYMM	30°	-	7600	■	GWS4123AF840	✓
48	I	✓	80	4000	SYMM	60°	-	7700	■	GWS4123AH840	✓
48	I	✓	80	4000	SYMM	90°	-	7700	■	GWS4123AP840	✓
48	I	✓	80	4000	ARRAY	-	-	7700	■	GWS4123AA840	✓
48	I	✓	80	4000	ASYMM	-	-	6900	■	GWS4123AC840	✓
48	I	✓	80	4000	ELL	-	-	7100	■	GWS4123AQ840	✓
48	I	✓	80	3000	SYMM	30°	-	7200	■	GWS4123AF830	✓
48	I	✓	80	3000	SYMM	60°	-	7300	■	GWS4123AH830	✓
48	I	✓	80	3000	SYMM	90°	-	7300	■	GWS4123AP830	✓
48	I	✓	80	3000	ARRAY	-	-	7300	■	GWS4123AA830	✓
48	I	✓	80	3000	ASYMM	-	-	6500	■	GWS4123AC830	✓
48	I	✓	80	3000	ELL	-	-	6800	■	GWS4123AQ830	✓

SMART [4] 1M HE EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
48	I	-	80	5700	SYMM	30°	-	7600	■	GWS4124AF857	✓
48	I	-	80	5700	SYMM	60°	-	7700	■	GWS4124AH857	✓
48	I	-	80	5700	SYMM	90°	-	7700	■	GWS4124AP857	✓
48	I	-	80	5700	ARRAY	-	-	7700	■	GWS4124AA857	✓
48	I	-	80	5700	ASYMM	-	-	6900	■	GWS4124AC857	✓
48	I	-	80	5700	ELL	-	-	7100	■	GWS4124AQ857	✓
48	I	-	80	4000	SYMM	30°	-	7600	■	GWS4124AF840	✓
48	I	-	80	4000	SYMM	60°	-	7700	■	GWS4124AH840	✓
48	I	-	80	4000	SYMM	90°	-	7700	■	GWS4124AP840	✓
48	I	-	80	4000	ARRAY	-	-	7700	■	GWS4124AA840	✓
48	I	-	80	4000	ASYMM	-	-	6900	■	GWS4124AC840	✓
48	I	-	80	4000	ELL	-	-	7100	■	GWS4124AQ840	✓
48	I	-	80	3000	SYMM	30°	-	7200	■	GWS4124AF830	✓
48	I	-	80	3000	SYMM	60°	-	7300	■	GWS4124AH830	✓
48	I	-	80	3000	SYMM	90°	-	7300	■	GWS4124AP830	✓
48	I	-	80	3000	ARRAY	-	-	7300	■	GWS4124AA830	✓
48	I	-	80	3000	ASYMM	-	-	6500	■	GWS4124AC830	✓
48	I	-	80	3000	ELL	-	-	6800	■	GWS4124AQ830	✓



SMART [4] 1M HLO

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
64	I	✓	80	5700	SYMM	30°	-	9800	■	GWS4120BF857	✓
64	I	✓	80	5700	SYMM	60°	-	9900	■	GWS4120BH857	✓
64	I	✓	80	5700	SYMM	90°	-	9900	■	GWS4120BP857	✓
64	I	✓	80	5700	ARRAY	-	-	9900	■	GWS4120BA857	✓
64	I	✓	80	5700	ASYMM	-	-	8900	■	GWS4120BC857	✓
64	I	✓	80	5700	ELL	-	-	9200	■	GWS4120BQ857	✓
64	I	✓	80	4000	SYMM	30°	-	9800	■	GWS4120BF840	✓
64	I	✓	80	4000	SYMM	60°	-	9900	■	GWS4120BH840	✓
64	I	✓	80	4000	SYMM	90°	-	9900	■	GWS4120BP840	✓
64	I	✓	80	4000	ARRAY	-	-	9900	■	GWS4120BA840	✓
64	I	✓	80	4000	ASYMM	-	-	8900	■	GWS4120BC840	✓
64	I	✓	80	4000	ELL	-	-	9200	■	GWS4120BQ840	✓
64	I	✓	80	3000	SYMM	30°	-	9400	■	GWS4120BF830	✓
64	I	✓	80	3000	SYMM	60°	-	9500	■	GWS4120BH830	✓
64	I	✓	80	3000	SYMM	90°	-	9500	■	GWS4120BP830	✓
64	I	✓	80	3000	ARRAY	-	-	9500	■	GWS4120BA830	✓
64	I	✓	80	3000	ASYMM	-	-	8500	■	GWS4120BC830	✓
64	I	✓	80	3000	ELL	-	-	8800	■	GWS4120BQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
64	I	✓	80	5700	SYMM	30°	-	9800	■	GWS4122BF857	✓
64	I	✓	80	5700	SYMM	60°	-	9900	■	GWS4122BH857	✓
64	I	✓	80	5700	SYMM	90°	-	9900	■	GWS4122BP857	✓
64	I	✓	80	5700	ARRAY	-	-	9900	■	GWS4122BA857	✓
64	I	✓	80	5700	ASYMM	-	-	8900	■	GWS4122BC857	✓
64	I	✓	80	5700	ELL	-	-	9200	■	GWS4122BQ857	✓
64	I	✓	80	4000	SYMM	30°	-	9800	■	GWS4122BF840	✓
64	I	✓	80	4000	SYMM	60°	-	9900	■	GWS4122BH840	✓
64	I	✓	80	4000	SYMM	90°	-	9900	■	GWS4122BP840	✓
64	I	✓	80	4000	ARRAY	-	-	9900	■	GWS4122BA840	✓
64	I	✓	80	4000	ASYMM	-	-	8900	■	GWS4122BC840	✓
64	I	✓	80	4000	ELL	-	-	9200	■	GWS4122BQ840	✓
64	I	✓	80	3000	SYMM	30°	-	9400	■	GWS4122BF830	✓
64	I	✓	80	3000	SYMM	60°	-	9500	■	GWS4122BH830	✓
64	I	✓	80	3000	SYMM	90°	-	9500	■	GWS4122BP830	✓
64	I	✓	80	3000	ARRAY	-	-	9500	■	GWS4122BA830	✓
64	I	✓	80	3000	ASYMM	-	-	8500	■	GWS4122BC830	✓
64	I	✓	80	3000	ELL	-	-	8800	■	GWS4122BQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
64	I	✓	80	5700	SYMM	30°	-	9800	■	GWS4121BF857	✓
64	I	✓	80	5700	SYMM	60°	-	9900	■	GWS4121BH857	✓
64	I	✓	80	5700	SYMM	90°	-	9900	■	GWS4121BP857	✓
64	I	✓	80	5700	ARRAY	-	-	9900	■	GWS4121BA857	✓
64	I	✓	80	5700	ASYMM	-	-	8900	■	GWS4121BC857	✓
64	I	✓	80	5700	ELL	-	-	9200	■	GWS4121BQ857	✓
64	I	✓	80	4000	SYMM	30°	-	9800	■	GWS4121BF840	✓
64	I	✓	80	4000	SYMM	60°	-	9900	■	GWS4121BH840	✓
64	I	✓	80	4000	SYMM	90°	-	9900	■	GWS4121BP840	✓
64	I	✓	80	4000	ARRAY	-	-	9900	■	GWS4121BA840	✓
64	I	✓	80	4000	ASYMM	-	-	8900	■	GWS4121BC840	✓
64	I	✓	80	4000	ELL	-	-	9200	■	GWS4121BQ840	✓
64	I	✓	80	3000	SYMM	30°	-	9400	■	GWS4121BF830	✓
64	I	✓	80	3000	SYMM	60°	-	9500	■	GWS4121BH830	✓
64	I	✓	80	3000	SYMM	90°	-	9500	■	GWS4121BP830	✓
64	I	✓	80	3000	ARRAY	-	-	9500	■	GWS4121BA830	✓
64	I	✓	80	3000	ASYMM	-	-	8500	■	GWS4121BC830	✓
64	I	✓	80	3000	ELL	-	-	8800	■	GWS4121BQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

64	I	✓	80	5700	SYMM	30°	-	9800	■	GWS4123BF857	✓
64	I	✓	80	5700	SYMM	60°	-	9900	■	GWS4123BH857	✓
64	I	✓	80	5700	SYMM	90°	-	9900	■	GWS4123BP857	✓
64	I	✓	80	5700	ARRAY	-	-	9900	■	GWS4123BA857	✓
64	I	✓	80	5700	ASYMM	-	-	8900	■	GWS4123BC857	✓
64	I	✓	80	5700	ELL	-	-	9200	■	GWS4123BQ857	✓
64	I	✓	80	4000	SYMM	30°	-	9800	■	GWS4123BF840	✓
64	I	✓	80	4000	SYMM	60°	-	9900	■	GWS4123BH840	✓
64	I	✓	80	4000	SYMM	90°	-	9900	■	GWS4123BP840	✓
64	I	✓	80	4000	ARRAY	-	-	9900	■	GWS4123BA840	✓
64	I	✓	80	4000	ASYMM	-	-	8900	■	GWS4123BC840	✓
64	I	✓	80	4000	ELL	-	-	9200	■	GWS4123BQ840	✓
64	I	✓	80	3000	SYMM	30°	-	9400	■	GWS4123BF830	✓
64	I	✓	80	3000	SYMM	60°	-	9500	■	GWS4123BH830	✓
64	I	✓	80	3000	SYMM	90°	-	9500	■	GWS4123BP830	✓
64	I	✓	80	3000	ARRAY	-	-	9500	■	GWS4123BA830	✓
64	I	✓	80	3000	ASYMM	-	-	8500	■	GWS4123BC830	✓
64	I	✓	80	3000	ELL	-	-	8800	■	GWS4123BQ830	✓

SMART [4] 1M HLO EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
64	I	-	80	5700	SYMM	30°	-	9800	■	GWS4124BF857	✓
64	I	-	80	5700	SYMM	60°	-	9900	■	GWS4124BH857	✓
64	I	-	80	5700	SYMM	90°	-	9900	■	GWS4124BP857	✓
64	I	-	80	5700	ARRAY	-	-	9900	■	GWS4124BA857	✓
64	I	-	80	5700	ASYMM	-	-	8900	■	GWS4124BC857	✓
64	I	-	80	5700	ELL	-	-	9200	■	GWS4124BQ857	✓
64	I	-	80	4000	SYMM	30°	-	9800	■	GWS4124BF840	✓
64	I	-	80	4000	SYMM	60°	-	9900	■	GWS4124BH840	✓
64	I	-	80	4000	SYMM	90°	-	9900	■	GWS4124BP840	✓
64	I	-	80	4000	ARRAY	-	-	9900	■	GWS4124BA840	✓
64	I	-	80	4000	ASYMM	-	-	8900	■	GWS4124BC840	✓
64	I	-	80	4000	ELL	-	-	9200	■	GWS4124BQ840	✓
64	I	-	80	3000	SYMM	30°	-	9400	■	GWS4124BF830	✓
64	I	-	80	3000	SYMM	60°	-	9500	■	GWS4124BH830	✓
64	I	-	80	3000	SYMM	90°	-	9500	■	GWS4124BP830	✓
64	I	-	80	3000	ARRAY	-	-	9500	■	GWS4124BA830	✓
64	I	-	80	3000	ASYMM	-	-	8500	■	GWS4124BC830	✓
64	I	-	80	3000	ELL	-	-	8800	■	GWS4124BQ830	✓



SMART [4] 2M HE

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
95	I	✓	80	5700	SYMM	30°	-	15200	■	GWS4220AF857	✓
95	I	✓	80	5700	SYMM	60°	-	15400	■	GWS4220AH857	✓
95	I	✓	80	5700	SYMM	90°	-	15400	■	GWS4220AP857	✓
95	I	✓	80	5700	ARRAY	-	-	15400	■	GWS4220AA857	✓
95	I	✓	80	5700	ASYMM	-	-	13800	■	GWS4220AC857	✓
95	I	✓	80	5700	ELL	-	-	14200	■	GWS4220AQ857	✓
95	I	✓	80	4000	SYMM	30°	-	15200	■	GWS4220AF840	✓
95	I	✓	80	4000	SYMM	60°	-	15400	■	GWS4220AH840	✓
95	I	✓	80	4000	SYMM	90°	-	15400	■	GWS4220AP840	✓
95	I	✓	80	4000	ARRAY	-	-	15400	■	GWS4220AA840	✓
95	I	✓	80	4000	ASYMM	-	-	13800	■	GWS4220AC840	✓
95	I	✓	80	4000	ELL	-	-	14200	■	GWS4220AQ840	✓
95	I	✓	80	3000	SYMM	30°	-	14400	■	GWS4220AF830	✓
95	I	✓	80	3000	SYMM	60°	-	14600	■	GWS4220AH830	✓
95	I	✓	80	3000	SYMM	90°	-	14600	■	GWS4220AP830	✓
95	I	✓	80	3000	ARRAY	-	-	14600	■	GWS4220AA830	✓
95	I	✓	80	3000	ASYMM	-	-	13000	■	GWS4220AC830	✓
95	I	✓	80	3000	ELL	-	-	13600	■	GWS4220AQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
95	I	✓	80	5700	SYMM	30°	-	15200	■	GWS4222AF857	✓
95	I	✓	80	5700	SYMM	60°	-	15400	■	GWS4222AH857	✓
95	I	✓	80	5700	SYMM	90°	-	15400	■	GWS4222AP857	✓
95	I	✓	80	5700	ARRAY	-	-	15400	■	GWS4222AA857	✓
95	I	✓	80	5700	ASYMM	-	-	13800	■	GWS4222AC857	✓
95	I	✓	80	5700	ELL	-	-	14200	■	GWS4222AQ857	✓
95	I	✓	80	4000	SYMM	30°	-	15200	■	GWS4222AF840	✓
95	I	✓	80	4000	SYMM	60°	-	15400	■	GWS4222AH840	✓
95	I	✓	80	4000	SYMM	90°	-	15400	■	GWS4222AP840	✓
95	I	✓	80	4000	ARRAY	-	-	15400	■	GWS4222AA840	✓
95	I	✓	80	4000	ASYMM	-	-	13800	■	GWS4222AC840	✓
95	I	✓	80	4000	ELL	-	-	14200	■	GWS4222AQ840	✓
95	I	✓	80	3000	SYMM	30°	-	14400	■	GWS4222AF830	✓
95	I	✓	80	3000	SYMM	60°	-	14600	■	GWS4222AH830	✓
95	I	✓	80	3000	SYMM	90°	-	14600	■	GWS4222AP830	✓
95	I	✓	80	3000	ARRAY	-	-	14600	■	GWS4222AA830	✓
95	I	✓	80	3000	ASYMM	-	-	13000	■	GWS4222AC830	✓
95	I	✓	80	3000	ELL	-	-	13600	■	GWS4222AQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
95	I	✓	80	5700	SYMM	30°	-	15200	■	GWS4221AF857	✓
95	I	✓	80	5700	SYMM	60°	-	15400	■	GWS4221AH857	✓
95	I	✓	80	5700	SYMM	90°	-	15400	■	GWS4221AP857	✓
95	I	✓	80	5700	ARRAY	-	-	15400	■	GWS4221AA857	✓
95	I	✓	80	5700	ASYMM	-	-	13800	■	GWS4221AC857	✓
95	I	✓	80	5700	ELL	-	-	14200	■	GWS4221AQ857	✓
95	I	✓	80	4000	SYMM	30°	-	15200	■	GWS4221AF840	✓
95	I	✓	80	4000	SYMM	60°	-	15400	■	GWS4221AH840	✓
95	I	✓	80	4000	SYMM	90°	-	15400	■	GWS4221AP840	✓
95	I	✓	80	4000	ARRAY	-	-	15400	■	GWS4221AA840	✓
95	I	✓	80	4000	ASYMM	-	-	13800	■	GWS4221AC840	✓
95	I	✓	80	4000	ELL	-	-	14200	■	GWS4221AQ840	✓
95	I	✓	80	3000	SYMM	30°	-	14400	■	GWS4221AF830	✓
95	I	✓	80	3000	SYMM	60°	-	14600	■	GWS4221AH830	✓
95	I	✓	80	3000	SYMM	90°	-	14600	■	GWS4221AP830	✓
95	I	✓	80	3000	ARRAY	-	-	14600	■	GWS4221AA830	✓
95	I	✓	80	3000	ASYMM	-	-	13000	■	GWS4221AC830	✓
95	I	✓	80	3000	ELL	-	-	13600	■	GWS4221AQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

95	I	✓	80	5700	SYMM	30°	-	15200	■	GWS4223AF857	✓
95	I	✓	80	5700	SYMM	60°	-	15400	■	GWS4223AH857	✓
95	I	✓	80	5700	SYMM	90°	-	15400	■	GWS4223AP857	✓
95	I	✓	80	5700	ARRAY	-	-	15400	■	GWS4223AA857	✓
95	I	✓	80	5700	ASYMM	-	-	13800	■	GWS4223AC857	✓
95	I	✓	80	5700	ELL	-	-	14200	■	GWS4223AQ857	✓
95	I	✓	80	4000	SYMM	30°	-	15200	■	GWS4223AF840	✓
95	I	✓	80	4000	SYMM	60°	-	15400	■	GWS4223AH840	✓
95	I	✓	80	4000	SYMM	90°	-	15400	■	GWS4223AP840	✓
95	I	✓	80	4000	ARRAY	-	-	15400	■	GWS4223AA840	✓
95	I	✓	80	4000	ASYMM	-	-	13800	■	GWS4223AC840	✓
95	I	✓	80	4000	ELL	-	-	14200	■	GWS4223AQ840	✓
95	I	✓	80	3000	SYMM	30°	-	14400	■	GWS4223AF830	✓
95	I	✓	80	3000	SYMM	60°	-	14600	■	GWS4223AH830	✓
95	I	✓	80	3000	SYMM	90°	-	14600	■	GWS4223AP830	✓
95	I	✓	80	3000	ARRAY	-	-	14600	■	GWS4223AA830	✓
95	I	✓	80	3000	ASYMM	-	-	13000	■	GWS4223AC830	✓
95	I	✓	80	3000	ELL	-	-	13600	■	GWS4223AQ830	✓

SMART [4] 2M HE EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
95	I	-	80	5700	SYMM	30°	-	15200	■	GWS4224AF857	✓
95	I	-	80	5700	SYMM	60°	-	15400	■	GWS4224AH857	✓
95	I	-	80	5700	SYMM	90°	-	15400	■	GWS4224AP857	✓
95	I	-	80	5700	ARRAY	-	-	15400	■	GWS4224AA857	✓
95	I	-	80	5700	ASYMM	-	-	13800	■	GWS4224AC857	✓
95	I	-	80	5700	ELL	-	-	14200	■	GWS4224AQ857	✓
95	I	-	80	4000	SYMM	30°	-	15200	■	GWS4224AF840	✓
95	I	-	80	4000	SYMM	60°	-	15400	■	GWS4224AH840	✓
95	I	-	80	4000	SYMM	90°	-	15400	■	GWS4224AP840	✓
95	I	-	80	4000	ARRAY	-	-	15400	■	GWS4224AA840	✓
95	I	-	80	4000	ASYMM	-	-	13800	■	GWS4224AC840	✓
95	I	-	80	4000	ELL	-	-	14200	■	GWS4224AQ840	✓
95	I	-	80	3000	SYMM	30°	-	14400	■	GWS4224AF830	✓
95	I	-	80	3000	SYMM	60°	-	14600	■	GWS4224AH830	✓
95	I	-	80	3000	SYMM	90°	-	14600	■	GWS4224AP830	✓
95	I	-	80	3000	ARRAY	-	-	14600	■	GWS4224AA830	✓
95	I	-	80	3000	ASYMM	-	-	13000	■	GWS4224AC830	✓
95	I	-	80	3000	ELL	-	-	13600	■	GWS4224AQ830	✓



SMART [4] 2M HLO

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
125	I	✓	80	5700	SYMM	30°	-	19600	■	GWS4220BF857	✓
125	I	✓	80	5700	SYMM	60°	-	19800	■	GWS4220BH857	✓
125	I	✓	80	5700	SYMM	90°	-	19800	■	GWS4220BP857	✓
125	I	✓	80	5700	ARRAY	-	-	19800	■	GWS4220BA857	✓
125	I	✓	80	5700	ASYMM	-	-	17800	■	GWS4220BC857	✓
125	I	✓	80	5700	ELL	-	-	18400	■	GWS4220BQ857	✓
125	I	✓	80	4000	SYMM	30°	-	19600	■	GWS4220BF840	✓
125	I	✓	80	4000	SYMM	60°	-	19800	■	GWS4220BH840	✓
125	I	✓	80	4000	SYMM	90°	-	19800	■	GWS4220BP840	✓
125	I	✓	80	4000	ARRAY	-	-	19800	■	GWS4220BA840	✓
125	I	✓	80	4000	ASYMM	-	-	17800	■	GWS4220BC840	✓
125	I	✓	80	4000	ELL	-	-	18400	■	GWS4220BQ840	✓
125	I	✓	80	3000	SYMM	30°	-	18800	■	GWS4220BF830	✓
125	I	✓	80	3000	SYMM	60°	-	19000	■	GWS4220BH830	✓
125	I	✓	80	3000	SYMM	90°	-	19000	■	GWS4220BP830	✓
125	I	✓	80	3000	ARRAY	-	-	19000	■	GWS4220BA830	✓
125	I	✓	80	3000	ASYMM	-	-	17000	■	GWS4220BC830	✓
125	I	✓	80	3000	ELL	-	-	17600	■	GWS4220BQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
125	I	✓	80	5700	SYMM	30°	-	19600	■	GWS4222BF857	✓
125	I	✓	80	5700	SYMM	60°	-	19800	■	GWS4222BH857	✓
125	I	✓	80	5700	SYMM	90°	-	19800	■	GWS4222BP857	✓
125	I	✓	80	5700	ARRAY	-	-	19800	■	GWS4222BA857	✓
125	I	✓	80	5700	ASYMM	-	-	17800	■	GWS4222BC857	✓
125	I	✓	80	5700	ELL	-	-	18400	■	GWS4222BQ857	✓
125	I	✓	80	4000	SYMM	30°	-	19600	■	GWS4222BF840	✓
125	I	✓	80	4000	SYMM	60°	-	19800	■	GWS4222BH840	✓
125	I	✓	80	4000	SYMM	90°	-	19800	■	GWS4222BP840	✓
125	I	✓	80	4000	ARRAY	-	-	19800	■	GWS4222BA840	✓
125	I	✓	80	4000	ASYMM	-	-	17800	■	GWS4222BC840	✓
125	I	✓	80	4000	ELL	-	-	18400	■	GWS4222BQ840	✓
125	I	✓	80	3000	SYMM	30°	-	18800	■	GWS4222BF830	✓
125	I	✓	80	3000	SYMM	60°	-	19000	■	GWS4222BH830	✓
125	I	✓	80	3000	SYMM	90°	-	19000	■	GWS4222BP830	✓
125	I	✓	80	3000	ARRAY	-	-	19000	■	GWS4222BA830	✓
125	I	✓	80	3000	ASYMM	-	-	17000	■	GWS4222BC830	✓
125	I	✓	80	3000	ELL	-	-	17600	■	GWS4222BQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
125	I	✓	80	5700	SYMM	30°	-	19600	■	GWS4221BF857	✓
125	I	✓	80	5700	SYMM	60°	-	19800	■	GWS4221BH857	✓
125	I	✓	80	5700	SYMM	90°	-	19800	■	GWS4221BP857	✓
125	I	✓	80	5700	ARRAY	-	-	19800	■	GWS4221BA857	✓
125	I	✓	80	5700	ASYMM	-	-	17800	■	GWS4221BC857	✓
125	I	✓	80	5700	ELL	-	-	18400	■	GWS4221BQ857	✓
125	I	✓	80	4000	SYMM	30°	-	19600	■	GWS4221BF840	✓
125	I	✓	80	4000	SYMM	60°	-	19800	■	GWS4221BH840	✓
125	I	✓	80	4000	SYMM	90°	-	19800	■	GWS4221BP840	✓
125	I	✓	80	4000	ARRAY	-	-	19800	■	GWS4221BA840	✓
125	I	✓	80	4000	ASYMM	-	-	17800	■	GWS4221BC840	✓
125	I	✓	80	4000	ELL	-	-	18400	■	GWS4221BQ840	✓
125	I	✓	80	3000	SYMM	30°	-	18800	■	GWS4221BF830	✓
125	I	✓	80	3000	SYMM	60°	-	19000	■	GWS4221BH830	✓
125	I	✓	80	3000	SYMM	90°	-	19000	■	GWS4221BP830	✓
125	I	✓	80	3000	ARRAY	-	-	19000	■	GWS4221BA830	✓
125	I	✓	80	3000	ASYMM	-	-	17000	■	GWS4221BC830	✓
125	I	✓	80	3000	ELL	-	-	17600	■	GWS4221BQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

125	I	✓	80	5700	SYMM	30°	-	19600	■	GWS4223BF857	✓
125	I	✓	80	5700	SYMM	60°	-	19800	■	GWS4223BH857	✓
125	I	✓	80	5700	SYMM	90°	-	19800	■	GWS4223BP857	✓
125	I	✓	80	5700	ARRAY	-	-	19800	■	GWS4223BA857	✓
125	I	✓	80	5700	ASYMM	-	-	17800	■	GWS4223BC857	✓
125	I	✓	80	5700	ELL	-	-	18400	■	GWS4223BQ857	✓
125	I	✓	80	4000	SYMM	30°	-	19600	■	GWS4223BF840	✓
125	I	✓	80	4000	SYMM	60°	-	19800	■	GWS4223BH840	✓
125	I	✓	80	4000	SYMM	90°	-	19800	■	GWS4223BP840	✓
125	I	✓	80	4000	ARRAY	-	-	19800	■	GWS4223BA840	✓
125	I	✓	80	4000	ASYMM	-	-	17800	■	GWS4223BC840	✓
125	I	✓	80	4000	ELL	-	-	18400	■	GWS4223BQ840	✓
125	I	✓	80	3000	SYMM	30°	-	18800	■	GWS4223BF830	✓
125	I	✓	80	3000	SYMM	60°	-	19000	■	GWS4223BH830	✓
125	I	✓	80	3000	SYMM	90°	-	19000	■	GWS4223BP830	✓
125	I	✓	80	3000	ARRAY	-	-	19000	■	GWS4223BA830	✓
125	I	✓	80	3000	ASYMM	-	-	17000	■	GWS4223BC830	✓
125	I	✓	80	3000	ELL	-	-	17600	■	GWS4223BQ830	✓

SMART [4] 2M HLO EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h

125	I	-	80	5700	SYMM	30°	-	19600	■	GWS4224BF857	✓
125	I	-	80	5700	SYMM	60°	-	19800	■	GWS4224BH857	✓
125	I	-	80	5700	SYMM	90°	-	19800	■	GWS4224BP857	✓
125	I	-	80	5700	ARRAY	-	-	19800	■	GWS4224BA857	✓
125	I	-	80	5700	ASYMM	-	-	17800	■	GWS4224BC857	✓
125	I	-	80	5700	ELL	-	-	18400	■	GWS4224BQ857	✓
125	I	-	80	4000	SYMM	30°	-	19600	■	GWS4224BF840	✓
125	I	-	80	4000	SYMM	60°	-	19800	■	GWS4224BH840	✓
125	I	-	80	4000	SYMM	90°	-	19800	■	GWS4224BP840	✓
125	I	-	80	4000	ARRAY	-	-	19800	■	GWS4224BA840	✓
125	I	-	80	4000	ASYMM	-	-	17800	■	GWS4224BC840	✓
125	I	-	80	4000	ELL	-	-	18400	■	GWS4224BQ840	✓
125	I	-	80	3000	SYMM	30°	-	18800	■	GWS4224BF830	✓
125	I	-	80	3000	SYMM	60°	-	19000	■	GWS4224BH830	✓
125	I	-	80	3000	SYMM	90°	-	19000	■	GWS4224BP830	✓
125	I	-	80	3000	ARRAY	-	-	19000	■	GWS4224BA830	✓
125	I	-	80	3000	ASYMM	-	-	17000	■	GWS4224BC830	✓
125	I	-	80	3000	ELL	-	-	17600	■	GWS4224BQ830	✓



SMART [4] 4M HE

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
189	I	✓	80	5700	SYMM	30°	-	30400	■	GWS4420AF857	✓
189	I	✓	80	5700	SYMM	60°	-	30800	■	GWS4420AH857	✓
189	I	✓	80	5700	SYMM	90°	-	30800	■	GWS4420AP857	✓
189	I	✓	80	5700	ARRAY	-	-	30800	■	GWS4420AA857	✓
189	I	✓	80	5700	ASYMM	-	-	27600	■	GWS4420AC857	✓
189	I	✓	80	5700	ELL	-	-	28400	■	GWS4420AQ857	✓
189	I	✓	80	4000	SYMM	30°	-	30400	■	GWS4420AF840	✓
189	I	✓	80	4000	SYMM	60°	-	30800	■	GWS4420AH840	✓
189	I	✓	80	4000	SYMM	90°	-	30800	■	GWS4420AP840	✓
189	I	✓	80	4000	ARRAY	-	-	30800	■	GWS4420AA840	✓
189	I	✓	80	4000	ASYMM	-	-	27600	■	GWS4420AC840	✓
189	I	✓	80	4000	ELL	-	-	28400	■	GWS4420AQ840	✓
189	I	✓	80	3000	SYMM	30°	-	28800	■	GWS4420AF830	✓
189	I	✓	80	3000	SYMM	60°	-	29200	■	GWS4420AH830	✓
189	I	✓	80	3000	SYMM	90°	-	29200	■	GWS4420AP830	✓
189	I	✓	80	3000	ARRAY	-	-	29200	■	GWS4420AA830	✓
189	I	✓	80	3000	ASYMM	-	-	26000	■	GWS4420AC830	✓
189	I	✓	80	3000	ELL	-	-	27200	■	GWS4420AQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
189	I	✓	80	5700	SYMM	30°	-	30400	■	GWS4422AF857	✓
189	I	✓	80	5700	SYMM	60°	-	30800	■	GWS4422AH857	✓
189	I	✓	80	5700	SYMM	90°	-	30800	■	GWS4422AP857	✓
189	I	✓	80	5700	ARRAY	-	-	30800	■	GWS4422AA857	✓
189	I	✓	80	5700	ASYMM	-	-	27600	■	GWS4422AC857	✓
189	I	✓	80	5700	ELL	-	-	28400	■	GWS4422AQ857	✓
189	I	✓	80	4000	SYMM	30°	-	30400	■	GWS4422AF840	✓
189	I	✓	80	4000	SYMM	60°	-	30800	■	GWS4422AH840	✓
189	I	✓	80	4000	SYMM	90°	-	30800	■	GWS4422AP840	✓
189	I	✓	80	4000	ARRAY	-	-	30800	■	GWS4422AA840	✓
189	I	✓	80	4000	ASYMM	-	-	27600	■	GWS4422AC840	✓
189	I	✓	80	4000	ELL	-	-	28400	■	GWS4422AQ840	✓
189	I	✓	80	3000	SYMM	30°	-	28800	■	GWS4422AF830	✓
189	I	✓	80	3000	SYMM	60°	-	29200	■	GWS4422AH830	✓
189	I	✓	80	3000	SYMM	90°	-	29200	■	GWS4422AP830	✓
189	I	✓	80	3000	ARRAY	-	-	29200	■	GWS4422AA830	✓
189	I	✓	80	3000	ASYMM	-	-	26000	■	GWS4422AC830	✓
189	I	✓	80	3000	ELL	-	-	27200	■	GWS4422AQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
189	I	✓	80	5700	SYMM	30°	-	30400	■	GWS4421AF857	✓
189	I	✓	80	5700	SYMM	60°	-	30800	■	GWS4421AH857	✓
189	I	✓	80	5700	SYMM	90°	-	30800	■	GWS4421AP857	✓
189	I	✓	80	5700	ARRAY	-	-	30800	■	GWS4421AA857	✓
189	I	✓	80	5700	ASYMM	-	-	27600	■	GWS4421AC857	✓
189	I	✓	80	5700	ELL	-	-	28400	■	GWS4421AQ857	✓
189	I	✓	80	4000	SYMM	30°	-	30400	■	GWS4421AF840	✓
189	I	✓	80	4000	SYMM	60°	-	30800	■	GWS4421AH840	✓
189	I	✓	80	4000	SYMM	90°	-	30800	■	GWS4421AP840	✓
189	I	✓	80	4000	ARRAY	-	-	30800	■	GWS4421AA840	✓
189	I	✓	80	4000	ASYMM	-	-	27600	■	GWS4421AC840	✓
189	I	✓	80	4000	ELL	-	-	28400	■	GWS4421AQ840	✓
189	I	✓	80	3000	SYMM	30°	-	28800	■	GWS4421AF830	✓
189	I	✓	80	3000	SYMM	60°	-	29200	■	GWS4421AH830	✓
189	I	✓	80	3000	SYMM	90°	-	29200	■	GWS4421AP830	✓
189	I	✓	80	3000	ARRAY	-	-	29200	■	GWS4421AA830	✓
189	I	✓	80	3000	ASYMM	-	-	26000	■	GWS4421AC830	✓
189	I	✓	80	3000	ELL	-	-	27200	■	GWS4421AQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

189	I	✓	80	5700	SYMM	30°	-	30400	■	GWS4423AF857	✓
189	I	✓	80	5700	SYMM	60°	-	30800	■	GWS4423AH857	✓
189	I	✓	80	5700	SYMM	90°	-	30800	■	GWS4423AP857	✓
189	I	✓	80	5700	ARRAY	-	-	30800	■	GWS4423AA857	✓
189	I	✓	80	5700	ASYMM	-	-	27600	■	GWS4423AC857	✓
189	I	✓	80	5700	ELL	-	-	28400	■	GWS4423AQ857	✓
189	I	✓	80	4000	SYMM	30°	-	30400	■	GWS4423AF840	✓
189	I	✓	80	4000	SYMM	60°	-	30800	■	GWS4423AH840	✓
189	I	✓	80	4000	SYMM	90°	-	30800	■	GWS4423AP840	✓
189	I	✓	80	4000	ARRAY	-	-	30800	■	GWS4423AA840	✓
189	I	✓	80	4000	ASYMM	-	-	27600	■	GWS4423AC840	✓
189	I	✓	80	4000	ELL	-	-	28400	■	GWS4423AQ840	✓
189	I	✓	80	3000	SYMM	30°	-	28800	■	GWS4423AF830	✓
189	I	✓	80	3000	SYMM	60°	-	29200	■	GWS4423AH830	✓
189	I	✓	80	3000	SYMM	90°	-	29200	■	GWS4423AP830	✓
189	I	✓	80	3000	ARRAY	-	-	29200	■	GWS4423AA830	✓
189	I	✓	80	3000	ASYMM	-	-	26000	■	GWS4423AC830	✓
189	I	✓	80	3000	ELL	-	-	27200	■	GWS4423AQ830	✓

SMART [4] 4M HE EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
189	I	-	80	5700	SYMM	30°	-	30400	■	GWS4424AF857	✓
189	I	-	80	5700	SYMM	60°	-	30800	■	GWS4424AH857	✓
189	I	-	80	5700	SYMM	90°	-	30800	■	GWS4424AP857	✓
189	I	-	80	5700	ARRAY	-	-	30800	■	GWS4424AA857	✓
189	I	-	80	5700	ASYMM	-	-	27600	■	GWS4424AC857	✓
189	I	-	80	5700	ELL	-	-	28400	■	GWS4424AQ857	✓
189	I	-	80	4000	SYMM	30°	-	30400	■	GWS4424AF840	✓
189	I	-	80	4000	SYMM	60°	-	30800	■	GWS4424AH840	✓
189	I	-	80	4000	SYMM	90°	-	30800	■	GWS4424AP840	✓
189	I	-	80	4000	ARRAY	-	-	30800	■	GWS4424AA840	✓
189	I	-	80	4000	ASYMM	-	-	27600	■	GWS4424AC840	✓
189	I	-	80	4000	ELL	-	-	28400	■	GWS4424AQ840	✓
189	I	-	80	3000	SYMM	30°	-	28800	■	GWS4424AF830	✓
189	I	-	80	3000	SYMM	60°	-	29200	■	GWS4424AH830	✓
189	I	-	80	3000	SYMM	90°	-	29200	■	GWS4424AP830	✓
189	I	-	80	3000	ARRAY	-	-	29200	■	GWS4424AA830	✓
189	I	-	80	3000	ASYMM	-	-	26000	■	GWS4424AC830	✓
189	I	-	80	3000	ELL	-	-	27200	■	GWS4424AQ830	✓



SMART [4] 4M HLO

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
253	I	✓	80	5700	SYMM	30°	-	39200	■	GWS4420BF857	✓
253	I	✓	80	5700	SYMM	60°	-	39600	■	GWS4420BH857	✓
253	I	✓	80	5700	SYMM	90°	-	39600	■	GWS4420BP857	✓
253	I	✓	80	5700	ARRAY	-	-	39600	■	GWS4420BA857	✓
253	I	✓	80	5700	ASYMM	-	-	35600	■	GWS4420BC857	✓
253	I	✓	80	5700	ELL	-	-	36800	■	GWS4420BQ857	✓
253	I	✓	80	4000	SYMM	30°	-	39200	■	GWS4420BF840	✓
253	I	✓	80	4000	SYMM	60°	-	39600	■	GWS4420BH840	✓
253	I	✓	80	4000	SYMM	90°	-	39600	■	GWS4420BP840	✓
253	I	✓	80	4000	ARRAY	-	-	39600	■	GWS4420BA840	✓
253	I	✓	80	4000	ASYMM	-	-	35600	■	GWS4420BC840	✓
253	I	✓	80	4000	ELL	-	-	36800	■	GWS4420BQ840	✓
253	I	✓	80	3000	SYMM	30°	-	37600	■	GWS4420BF830	✓
253	I	✓	80	3000	SYMM	60°	-	38000	■	GWS4420BH830	✓
253	I	✓	80	3000	SYMM	90°	-	38000	■	GWS4420BP830	✓
253	I	✓	80	3000	ARRAY	-	-	38000	■	GWS4420BA830	✓
253	I	✓	80	3000	ASYMM	-	-	34000	■	GWS4420BC830	✓
253	I	✓	80	3000	ELL	-	-	35200	■	GWS4420BQ830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
253	I	✓	80	5700	SYMM	30°	-	39200	■	GWS4422BF857	✓
253	I	✓	80	5700	SYMM	60°	-	39600	■	GWS4422BH857	✓
253	I	✓	80	5700	SYMM	90°	-	39600	■	GWS4422BP857	✓
253	I	✓	80	5700	ARRAY	-	-	39600	■	GWS4422BA857	✓
253	I	✓	80	5700	ASYMM	-	-	35600	■	GWS4422BC857	✓
253	I	✓	80	5700	ELL	-	-	36800	■	GWS4422BQ857	✓
253	I	✓	80	4000	SYMM	30°	-	39200	■	GWS4422BF840	✓
253	I	✓	80	4000	SYMM	60°	-	39600	■	GWS4422BH840	✓
253	I	✓	80	4000	SYMM	90°	-	39600	■	GWS4422BP840	✓
253	I	✓	80	4000	ARRAY	-	-	39600	■	GWS4422BA840	✓
253	I	✓	80	4000	ASYMM	-	-	35600	■	GWS4422BC840	✓
253	I	✓	80	4000	ELL	-	-	36800	■	GWS4422BQ840	✓
253	I	✓	80	3000	SYMM	30°	-	37600	■	GWS4422BF830	✓
253	I	✓	80	3000	SYMM	60°	-	38000	■	GWS4422BH830	✓
253	I	✓	80	3000	SYMM	90°	-	38000	■	GWS4422BP830	✓
253	I	✓	80	3000	ARRAY	-	-	38000	■	GWS4422BA830	✓
253	I	✓	80	3000	ASYMM	-	-	34000	■	GWS4422BC830	✓
253	I	✓	80	3000	ELL	-	-	35200	■	GWS4422BQ830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
253	I	✓	80	5700	SYMM	30°	-	39200	■	GWS4421BF857	✓
253	I	✓	80	5700	SYMM	60°	-	39600	■	GWS4421BH857	✓
253	I	✓	80	5700	SYMM	90°	-	39600	■	GWS4421BP857	✓
253	I	✓	80	5700	ARRAY	-	-	39600	■	GWS4421BA857	✓
253	I	✓	80	5700	ASYMM	-	-	35600	■	GWS4421BC857	✓
253	I	✓	80	5700	ELL	-	-	36800	■	GWS4421BQ857	✓
253	I	✓	80	4000	SYMM	30°	-	39200	■	GWS4421BF840	✓
253	I	✓	80	4000	SYMM	60°	-	39600	■	GWS4421BH840	✓
253	I	✓	80	4000	SYMM	90°	-	39600	■	GWS4421BP840	✓
253	I	✓	80	4000	ARRAY	-	-	39600	■	GWS4421BA840	✓
253	I	✓	80	4000	ASYMM	-	-	35600	■	GWS4421BC840	✓
253	I	✓	80	4000	ELL	-	-	36800	■	GWS4421BQ840	✓
253	I	✓	80	3000	SYMM	30°	-	37600	■	GWS4421BF830	✓
253	I	✓	80	3000	SYMM	60°	-	38000	■	GWS4421BH830	✓
253	I	✓	80	3000	SYMM	90°	-	38000	■	GWS4421BP830	✓
253	I	✓	80	3000	ARRAY	-	-	38000	■	GWS4421BA830	✓
253	I	✓	80	3000	ASYMM	-	-	34000	■	GWS4421BC830	✓
253	I	✓	80	3000	ELL	-	-	35200	■	GWS4421BQ830	✓

Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring

253	I	✓	80	5700	SYMM	30°	-	39200	■	GWS4423BF857	✓
253	I	✓	80	5700	SYMM	60°	-	39600	■	GWS4423BH857	✓
253	I	✓	80	5700	SYMM	90°	-	39600	■	GWS4423BP857	✓
253	I	✓	80	5700	ARRAY	-	-	39600	■	GWS4423BA857	✓
253	I	✓	80	5700	ASYMM	-	-	35600	■	GWS4423BC857	✓
253	I	✓	80	5700	ELL	-	-	36800	■	GWS4423BQ857	✓
253	I	✓	80	4000	SYMM	30°	-	39200	■	GWS4423BF840	✓
253	I	✓	80	4000	SYMM	60°	-	39600	■	GWS4423BH840	✓
253	I	✓	80	4000	SYMM	90°	-	39600	■	GWS4423BP840	✓
253	I	✓	80	4000	ARRAY	-	-	39600	■	GWS4423BA840	✓
253	I	✓	80	4000	ASYMM	-	-	35600	■	GWS4423BC840	✓
253	I	✓	80	4000	ELL	-	-	36800	■	GWS4423BQ840	✓
253	I	✓	80	3000	SYMM	30°	-	37600	■	GWS4423BF830	✓
253	I	✓	80	3000	SYMM	60°	-	38000	■	GWS4423BH830	✓
253	I	✓	80	3000	SYMM	90°	-	38000	■	GWS4423BP830	✓
253	I	✓	80	3000	ARRAY	-	-	38000	■	GWS4423BA830	✓
253	I	✓	80	3000	ASYMM	-	-	34000	■	GWS4423BC830	✓
253	I	✓	80	3000	ELL	-	-	35200	■	GWS4423BQ830	✓

SMART [4] 4M HLO EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
253	I	-	80	5700	SYMM	30°	-	39200	■	GWS4424BF857	✓
253	I	-	80	5700	SYMM	60°	-	39600	■	GWS4424BH857	✓
253	I	-	80	5700	SYMM	90°	-	39600	■	GWS4424BP857	✓
253	I	-	80	5700	ARRAY	-	-	39600	■	GWS4424BA857	✓
253	I	-	80	5700	ASYMM	-	-	35600	■	GWS4424BC857	✓
253	I	-	80	5700	ELL	-	-	36800	■	GWS4424BQ857	✓
253	I	-	80	4000	SYMM	30°	-	39200	■	GWS4424BF840	✓
253	I	-	80	4000	SYMM	60°	-	39600	■	GWS4424BH840	✓
253	I	-	80	4000	SYMM	90°	-	39600	■	GWS4424BP840	✓
253	I	-	80	4000	ARRAY	-	-	39600	■	GWS4424BA840	✓
253	I	-	80	4000	ASYMM	-	-	35600	■	GWS4424BC840	✓
253	I	-	80	4000	ELL	-	-	36800	■	GWS4424BQ840	✓
253	I	-	80	3000	SYMM	30°	-	37600	■	GWS4424BF830	✓
253	I	-	80	3000	SYMM	60°	-	38000	■	GWS4424BH830	✓
253	I	-	80	3000	SYMM	90°	-	38000	■	GWS4424BP830	✓
253	I	-	80	3000	ARRAY	-	-	38000	■	GWS4424BA830	✓
253	I	-	80	3000	ASYMM	-	-	34000	■	GWS4424BC830	✓
253	I	-	80	3000	ELL	-	-	35200	■	GWS4424BQ830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [4]			
Replacement glass		GWL1907	✓
Adjustable suspension kit with safety clamp		GWL1901	✓
Pole fixing kit		GWL1926	✓
SMART [4] 1M			
Floodlight bracket 1M		GWL1943	✓
SMART [4] 2M			
Ceiling-mounting kit		GWL1927	✓
Pole fixing kit		GWL1930	✓
Floodlight bracket 2M		GWL1944	✓
SMART [4] 4M			
Ceiling-mounting kit 4M		GWL1948	✓
Floodlight bracket 4M		GWL1945	✓



GWL1907



GWL1901



GWL1926




GWL1943



GWL1927





GWL1944



GWL1945

SMART [4] SPECIAL VERSIONS




■ Grey RAL 7035 / Grey RAL7035 /


Scan the QR-code for the latest information

LED device suitable for the indoor lighting of industries and sports facilities


- Body in "Halogen-free" nylon loaded with grey glass fibre (RAL7035) with vent and anti-condensation device, heat sink in aluminium alloy EN AB 44300
- Available in 3 sizes (1M, 2M and 4M), according to version
- Available in 4000 K and 5700 K, with CRI ≥80 (according to version)
- ATEX: series of LED indoor lighting appliances ideal for use in areas where flammable gases, vapours and dust are present. The electrical connection is via a 3x1.5 mm² H07RN-F cable with anti-condensation device exiting the product via a PG13.5 ATEX certified metal cable gland. The industrial reflector is certified ATEX II 3 G Ex nR IIC T6 Gc - II 3 D Ex tc IIC T65°C Dc
- HACCP: series of indoor LED lighting devices suitable for lighting in the food and beverage industry, ideal for illuminating production areas, warehouses and logistics areas. It is equipped with a double optical system that provides a metallic reflector with ARRAY optics and a metallic reflector with PMMA lenses stabilized at UV, high efficiency and front screen in PMMA
- HT: series of LED indoor appliances suitable for the food industry, production areas or warehouses where critical temperatures develop. Three different sizes available: 1M, 2M and 4M. Operating temperature range "Ta" between -30°C and +60°C
- UL: series of indoor LED lighting devices suitable for lighting of industries and sports facilities. The electrical connection will be via 3x16 AWG tear-proof cable coming out of the product via a PG13.5 plastic cable gland UL certified. Industrial reflector is UL certified UL (UL 1598 - CSA C22.2 No. 250.0-18)
- Available in On/Off and DALI versions (according to version)
- It is equipped with a dual optical system that includes a metallic reflector with ARRAY optics and a metallic reflector with UV stabilized PMMA lenses, with high efficiency, which allow a wide variety of light distributions 30°, 60°, 90°, Asymmetric and Elliptical (according to version)
- Suspension, wall and projection appliances can be installed




SMART [4] 1M
HT HACCP




SMART [4] 1M
ATEX




SMART [4] 1M
UL




SMART [4] 2M
HT HACCP




SMART [4] 2M
ATEX



SMART [4] 2M
UL




SMART [4] 4M
HT HACCP




SMART [4] 4M
UL


Identifying and classifying our optics




SYMM 30° - 253 W - 5700 K
180° — 0° | 90° — 270°




SYMM 60° - 253 W - 5700 K
180° — 0° | 90° — 270°




SYMM 90° - 253 W - 5700 K
180° — 0° | 90° — 270°



ARRAY - 253 W - 5700 K
180° — 0° | 90° — 270°



ASYMM - 253 W - 5700 K
180° — 0° | 90° — 270°



ELL - 253 W - 5700 K
180° — 0° | 90° — 270°

SMART [4] 1M HT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
48	I	-	80	5700	SYMM	60°	-	7700	■	GWS4120CH857	✓
48	I	-	80	5700	SYMM	90°	-	7700	■	GWS4120CP857	✓
48	I	-	80	5700	ARRAY	-	-	7700	■	GWS4120CA857	✓
48	I	-	80	5700	ELL	-	-	7100	■	GWS4120CQ857	✓
48	I	-	80	4000	SYMM	60°	-	7700	■	GWS4120CH840	✓
48	I	-	80	4000	SYMM	90°	-	7700	■	GWS4120CP840	✓
48	I	-	80	4000	ARRAY	-	-	7700	■	GWS4120CA840	✓
48	I	-	80	4000	ELL	-	-	7100	■	GWS4120CQ840	✓



SMART [4] 1M ATEX

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
64	I	✓	80	5700	SYMM	60°	-	9900	■	GWS4120FH857	✓
64	I	✓	80	5700	SYMM	90°	-	9900	■	GWS4120FP857	✓
64	I	✓	80	5700	ARRAY	-	-	9900	■	GWS4120FA857	✓
64	I	✓	80	5700	ASYMM	-	-	8900	■	GWS4120FC857	✓
64	I	✓	80	4000	SYMM	60°	-	9900	■	GWS4120FH840	✓
64	I	✓	80	4000	SYMM	90°	-	9900	■	GWS4120FP840	✓
64	I	✓	80	4000	ARRAY	-	-	9900	■	GWS4120FA840	✓
64	I	✓	80	4000	ASYMM	-	-	8900	■	GWS4120FC840	✓



SMART [4] 1M UL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 120-277 V 50/60 Hz											
65	I	-	80	5700	SYMM	60°	-	9900	■	GWS4120GH857	✓
65	I	-	80	5700	SYMM	90°	-	9900	■	GWS4120GP857	✓
65	I	-	80	5700	ARRAY	-	-	9900	■	GWS4120GA857	✓
65	I	-	80	4000	SYMM	60°	-	9900	■	GWS4120GH840	✓
65	I	-	80	4000	SYMM	90°	-	9900	■	GWS4120GP840	✓
65	I	-	80	4000	ARRAY	-	-	9900	■	GWS4120GA840	✓



SMART [4] 1M HACCP

IP65 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
64	I	-	80	5700	SYMM	30°	-	9800	■	GWS4120HF857	✓
64	I	-	80	5700	SYMM	60°	-	9900	■	GWS4120HH857	✓
64	I	-	80	5700	SYMM	90°	-	9900	■	GWS4120HP857	✓
64	I	-	80	5700	ARRAY	-	-	9900	■	GWS4120HA857	✓
64	I	-	80	5700	ASYMM	-	-	8900	■	GWS4120HC857	✓
64	I	-	80	5700	ELL	-	-	9200	■	GWS4120HQ857	✓
64	I	-	80	4000	SYMM	30°	-	9800	■	GWS4120HF840	✓
64	I	-	80	4000	SYMM	60°	-	9900	■	GWS4120HH840	✓
64	I	-	80	4000	SYMM	90°	-	9900	■	GWS4120HP840	✓
64	I	-	80	4000	ARRAY	-	-	9900	■	GWS4120HA840	✓
64	I	-	80	4000	ASYMM	-	-	8900	■	GWS4120HC840	✓
64	I	-	80	4000	ELL	-	-	9200	■	GWS4120HQ840	✓



Power LED dimmable DALI - 220-240 V 50/60 Hz

64	I	-	80	5700	SYMM	30°	-	9800	■	GWS4121HF857	✓
64	I	-	80	5700	SYMM	60°	-	9900	■	GWS4121HH857	✓
64	I	-	80	5700	SYMM	90°	-	9900	■	GWS4121HP857	✓
64	I	-	80	5700	ARRAY	-	-	9900	■	GWS4121HA857	✓
64	I	-	80	5700	ASYMM	-	-	8900	■	GWS4121HC857	✓
64	I	-	80	5700	ELL	-	-	9200	■	GWS4121HQ857	✓
64	I	-	80	4000	SYMM	30°	-	9800	■	GWS4121HF840	✓
64	I	-	80	4000	SYMM	60°	-	9900	■	GWS4121HH840	✓
64	I	-	80	4000	SYMM	90°	-	9900	■	GWS4121HP840	✓
64	I	-	80	4000	ARRAY	-	-	9900	■	GWS4121HA840	✓
64	I	-	80	4000	ASYMM	-	-	8900	■	GWS4121HC840	✓
64	I	-	80	4000	ELL	-	-	9200	■	GWS4121HQ840	✓

SMART [4] 2M HT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
95	I	-	80	5700	SYMM	60°	-	15400	■	GWS4220CH857	✓
95	I	-	80	5700	SYMM	90°	-	15400	■	GWS4220CP857	✓
95	I	-	80	5700	ARRAY	-	-	15400	■	GWS4220CA857	✓
95	I	-	80	5700	ELL	-	-	14200	■	GWS4220CQ857	✓
95	I	-	80	4000	SYMM	60°	-	15400	■	GWS4220CH840	✓
95	I	-	80	4000	SYMM	90°	-	15400	■	GWS4220CP840	✓
95	I	-	80	4000	ARRAY	-	-	15400	■	GWS4220CA840	✓
95	I	-	80	4000	ELL	-	-	14200	■	GWS4220CQ840	✓



SMART [4] 2M ATEX

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
127	I	✓	80	5700	SYMM	60°	-	19800	■	GWS4220FH857	✓
127	I	✓	80	5700	SYMM	90°	-	19800	■	GWS4220FP857	✓
127	I	✓	80	5700	ARRAY	-	-	19800	■	GWS4220FA857	✓
127	I	✓	80	5700	ASYMM	-	-	17800	■	GWS4220FC857	✓
127	I	✓	80	4000	SYMM	60°	-	19800	■	GWS4220FH840	✓
127	I	✓	80	4000	SYMM	90°	-	19800	■	GWS4220FP840	✓
127	I	✓	80	4000	ARRAY	-	-	19800	■	GWS4220FA840	✓
127	I	✓	80	4000	ASYMM	-	-	17800	■	GWS4220FC840	✓



SMART [4] 2M UL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 120-277 V 50/60 Hz											
129	I	-	80	5700	SYMM	60°	-	19800	■	GWS4220GH857	✓
129	I	-	80	5700	SYMM	90°	-	19800	■	GWS4220GP857	✓
129	I	-	80	5700	ARRAY	-	-	19800	■	GWS4220GA857	✓
129	I	-	80	4000	SYMM	60°	-	19800	■	GWS4220GH840	✓
129	I	-	80	4000	SYMM	90°	-	19800	■	GWS4220GP840	✓
129	I	-	80	4000	ARRAY	-	-	19800	■	GWS4220GA840	✓



SMART [4] 2M HACCP

IP65 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
125	I	-	80	5700	SYMM	30°	-	19600	■	GWS4220HF857	✓
125	I	-	80	5700	SYMM	60°	-	19800	■	GWS4220HH857	✓
125	I	-	80	5700	SYMM	90°	-	19800	■	GWS4220HP857	✓
125	I	-	80	5700	ARRAY	-	-	19800	■	GWS4220HA857	✓
125	I	-	80	5700	ASYMM	-	-	17800	■	GWS4220HC857	✓
125	I	-	80	5700	ELL	-	-	18400	■	GWS4220HQ857	✓
125	I	-	80	4000	SYMM	30°	-	19600	■	GWS4220HF840	✓
125	I	-	80	4000	SYMM	60°	-	19800	■	GWS4220HH840	✓
125	I	-	80	4000	SYMM	90°	-	19800	■	GWS4220HP840	✓
125	I	-	80	4000	ARRAY	-	-	19800	■	GWS4220HA840	✓
125	I	-	80	4000	ASYMM	-	-	17800	■	GWS4220HC840	✓
125	I	-	80	4000	ELL	-	-	18400	■	GWS4220HQ840	✓



Power LED dimmable DALI - 220-240 V 50/60 Hz

125	I	-	80	5700	SYMM	30°	-	19600	■	GWS4221HF857	✓
125	I	-	80	5700	SYMM	60°	-	19800	■	GWS4221HH857	✓
125	I	-	80	5700	SYMM	90°	-	19800	■	GWS4221HP857	✓
125	I	-	80	5700	ARRAY	-	-	19800	■	GWS4221HA857	✓
125	I	-	80	5700	ASYMM	-	-	17800	■	GWS4221HC857	✓
125	I	-	80	5700	ELL	-	-	18400	■	GWS4221HQ857	✓
125	I	-	80	4000	SYMM	30°	-	19600	■	GWS4221HF840	✓
125	I	-	80	4000	SYMM	60°	-	19800	■	GWS4221HH840	✓
125	I	-	80	4000	SYMM	90°	-	19800	■	GWS4221HP840	✓
125	I	-	80	4000	ARRAY	-	-	19800	■	GWS4221HA840	✓
125	I	-	80	4000	ASYMM	-	-	17800	■	GWS4221HC840	✓
125	I	-	80	4000	ELL	-	-	18400	■	GWS4221HQ840	✓

SMART [4] 4M HT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
189	I	-	80	5700	SYMM	60°	-	30800	■	GWS4420CH857	✓
189	I	-	80	5700	SYMM	90°	-	30800	■	GWS4420CP857	✓
189	I	-	80	5700	ARRAY	-	-	30800	■	GWS4420CA857	✓
189	I	-	80	5700	ELL	-	-	28400	■	GWS4420CQ857	✓
189	I	-	80	4000	SYMM	60°	-	30800	■	GWS4420CH840	✓
189	I	-	80	4000	SYMM	90°	-	30800	■	GWS4420CP840	✓
189	I	-	80	4000	ARRAY	-	-	30800	■	GWS4420CA840	✓
189	I	-	80	4000	ELL	-	-	28400	■	GWS4420CQ840	✓



SMART [4] 4M UL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 120-277 V 50/60 Hz											
256	I	-	80	5700	SYMM	60°	-	39600	■	GWS4420GH857	✓
256	I	-	80	5700	SYMM	90°	-	39600	■	GWS4420GP857	✓
256	I	-	80	5700	ARRAY	-	-	39600	■	GWS4420GA857	✓
256	I	-	80	4000	SYMM	60°	-	39600	■	GWS4420GH840	✓
256	I	-	80	4000	SYMM	90°	-	39600	■	GWS4420GP840	✓
256	I	-	80	4000	ARRAY	-	-	39600	■	GWS4420GA840	✓



SMART [4] 4M HACCP

IP65 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
253	I	-	80	5700	SYMM	30°	-	39200	■	GWS4420HF857	✓
253	I	-	80	5700	SYMM	60°	-	39600	■	GWS4420HH857	✓
253	I	-	80	5700	SYMM	90°	-	39600	■	GWS4420HP857	✓
253	I	-	80	5700	ARRAY	-	-	39600	■	GWS4420HA857	✓
253	I	-	80	5700	ASYMM	-	-	35600	■	GWS4420HC857	✓
253	I	-	80	5700	ELL	-	-	36800	■	GWS4420HQ857	✓
253	I	-	80	4000	SYMM	30°	-	39200	■	GWS4420HF840	✓
253	I	-	80	4000	SYMM	60°	-	39600	■	GWS4420HH840	✓
253	I	-	80	4000	SYMM	90°	-	39600	■	GWS4420HP840	✓
253	I	-	80	4000	ARRAY	-	-	39600	■	GWS4420HA840	✓
253	I	-	80	4000	ASYMM	-	-	35600	■	GWS4420HC840	✓
253	I	-	80	4000	ELL	-	-	36800	■	GWS4420HQ840	✓



Power LED dimmable DALI - 220-240 V 50/60 Hz

253	I	-	80	5700	SYMM	30°	-	39200	■	GWS4421HF857	✓
253	I	-	80	5700	SYMM	60°	-	39600	■	GWS4421HH857	✓
253	I	-	80	5700	SYMM	90°	-	39600	■	GWS4421HP857	✓
253	I	-	80	5700	ARRAY	-	-	39600	■	GWS4421HA857	✓
253	I	-	80	5700	ASYMM	-	-	35600	■	GWS4421HC857	✓
253	I	-	80	5700	ELL	-	-	36800	■	GWS4421HQ857	✓
253	I	-	80	4000	SYMM	30°	-	39200	■	GWS4421HF840	✓
253	I	-	80	4000	SYMM	60°	-	39600	■	GWS4421HH840	✓
253	I	-	80	4000	SYMM	90°	-	39600	■	GWS4421HP840	✓
253	I	-	80	4000	ARRAY	-	-	39600	■	GWS4421HA840	✓
253	I	-	80	4000	ASYMM	-	-	35600	■	GWS4421HC840	✓
253	I	-	80	4000	ELL	-	-	36800	■	GWS4421HQ840	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [4] SPECIAL VERSIONS			
Adjustable suspension kit with safety clamp		GWL1901	✓
Ceiling-mounting kit		GWL1927	✓
Replacement glass		GWL1907	✓
Pole fixing kit		GWL1926	✓
Ceiling-mounting kit 4M		GWL1948	✓
Pole fixing kit		GWL1930	✓
SMART [4] 1M			
Floodlight bracket 1M		GWL1943	✓
SMART [4] 2M			
Floodlight bracket 2M		GWL1944	✓
SMART [4] 4M			
Floodlight bracket 4M		GWL1945	✓



GWL1901



GWL1927




GWL1907




GWL1926



GWL1943



GWL1944



GWL1945


UNIQUO




■ GR-RAL7035 / Grey RAL7035 / Matt

Scan the QR-code for the latest information

- High bay luminaire designed with a modular concept to adapt to continuously advancing industrial, logistics, sports, and tertiary contexts that require flexible, efficient, reliable, and future-proof solutions
- Die-cast aluminum body with integrated heatsink fins
 - Embedded internal heatsink fins for optimal heat dissipation of the LED sources
 - Extruded aluminium driver box
 - Polyester powder-coat finish in grey RAL 7035 colour
 - Technopolymer end caps
 - Galvanized steel locking hardware
 - LED board featuring a metal core PCB and high-efficacy LEDs
 - SENSOR version features an integrated daylight and PIR sensor
 - EMERGENCY version features an integrated battery pack with 3 hours of autonomy
 - Exclusively designed PMMA lenses with high optical transmittance for maximum long-term stability and performance, even at elevated temperatures
 - Standard tempered 4 mm transparent glass, offering high impact resistance and suitable for demanding applications such as sports halls
 - Fast-mounting clips made of polished stainless steel for quick and easy intervention
 - It can withstand high ambient temperatures while delivering maximum luminous output without compromising the product's lifespan
 - The product comes standard with a suspension kit and can be installed in alternative configurations using the available mounting accessories, which can be ordered separately
 - Additional accessories and spare parts are available
 - The range is certified by third-party entities
 - It is certified to the DIN 18032-2 ball impact resistance standard, making it suitable for installation in gymnasiums and indoor sports facilities. Some mounting options may not be compatible with this type of application



Identifying and classifying our optics



UNIQUO 1M HE

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

72	I	✓	80	5700	C/W	70°	13500	12250	■	LTH1111AH857	✓
72	I	✓	80	5700	C/EW	100°	13500	12250	■	LTH1111AP857	✓
72	I	✓	80	5700	ELL	35°x90°	13500	12000	■	LTH1111AQ857	✓
72	I	✓	80	4000	C/W	70°	13500	12250	■	LTH1111AH840	✓
72	I	✓	80	4000	C/EW	100°	13500	12250	■	LTH1111AP840	✓
72	I	✓	80	4000	ELL	35°x90°	13500	12000	■	LTH1111AQ840	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

72	I	✓	80	5700	C/W	70°	13500	12250	■	LTH1111DH857	✓
72	I	✓	80	5700	C/EW	100°	13500	12250	■	LTH1111DP857	✓
72	I	✓	80	5700	ELL	35°x90°	13500	12000	■	LTH1111DQ857	✓
72	I	✓	80	4000	C/W	70°	13500	12250	■	LTH1111DH840	✓
72	I	✓	80	4000	C/EW	100°	13500	12250	■	LTH1111DP840	✓
72	I	✓	80	4000	ELL	35°x90°	13500	12000	■	LTH1111DQ840	✓



UNIQUO 1M HE EM

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h

72	I	✓	80	5700	C/W	70°	13500	12250	■	LTH1111EH857	✓
72	I	✓	80	5700	C/EW	100°	13500	12250	■	LTH1111EP857	✓
72	I	✓	80	5700	ELL	35°x90°	13500	12000	■	LTH1111EQ857	✓
72	I	✓	80	4000	C/W	70°	13500	12250	■	LTH1111EH840	✓
72	I	✓	80	4000	C/EW	100°	13500	12250	■	LTH1111EP840	✓
72	I	✓	80	4000	ELL	35°x90°	13500	12000	■	LTH1111EQ840	✓



UNIQUO 1M HLO

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

88	I	✓	80	5700	C/W	70°	16000	14500	■	LTH1112AH857	✓
88	I	✓	80	5700	C/EW	100°	16000	14500	■	LTH1112AP857	✓
88	I	✓	80	5700	ELL	35°x90°	16000	14200	■	LTH1112AQ857	✓
88	I	✓	80	4000	C/W	70°	16000	14500	■	LTH1112AH840	✓
88	I	✓	80	4000	C/EW	100°	16000	14500	■	LTH1112AP840	✓
88	I	✓	80	4000	ELL	35°x90°	16000	14200	■	LTH1112AQ840	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

88	I	✓	80	5700	C/W	70°	16000	14500	■	LTH1112DH857	✓
88	I	✓	80	5700	C/EW	100°	16000	14500	■	LTH1112DP857	✓
88	I	✓	80	5700	ELL	35°x90°	16000	14200	■	LTH1112DQ857	✓
88	I	✓	80	4000	C/W	70°	16000	14500	■	LTH1112DH840	✓
88	I	✓	80	4000	C/EW	100°	16000	14500	■	LTH1112DP840	✓
88	I	✓	80	4000	ELL	35°x90°	16000	14200	■	LTH1112DQ840	✓



UNIQUO 1M HLO EM

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h

88	I	✓	80	5700	C/W	70°	16000	14500	■	LTH1112EH857	✓
88	I	✓	80	5700	C/EW	100°	16000	14500	■	LTH1112EP857	✓
88	I	✓	80	5700	ELL	35°x90°	16000	14200	■	LTH1112EQ857	✓
88	I	✓	80	4000	C/W	70°	16000	14500	■	LTH1112EH840	✓
88	I	✓	80	4000	C/EW	100°	16000	14500	■	LTH1112EP840	✓
88	I	✓	80	4000	ELL	35°x90°	16000	14200	■	LTH1112EQ840	✓



UNIQUO 2M HE

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
142	I	✓	80	5700	C/W	70°	27000	24250	■	LTH1211AH857	✓
142	I	✓	80	5700	C/EW	100°	27000	24250	■	LTH1211AP857	✓
142	I	✓	80	5700	ELL	35°x90°	27000	23760	■	LTH1211AQ857	✓
142	I	✓	80	4000	C/W	70°	27000	24250	■	LTH1211AH840	✓
142	I	✓	80	4000	C/EW	100°	27000	24250	■	LTH1211AP840	✓
142	I	✓	80	4000	ELL	35°x90°	27000	23760	■	LTH1211AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
142	I	✓	80	5700	C/W	70°	27000	24250	■	LTH1211DH857	✓
142	I	✓	80	5700	C/EW	100°	27000	24250	■	LTH1211DP857	✓
142	I	✓	80	5700	ELL	35°x90°	27000	23760	■	LTH1211DQ857	✓
142	I	✓	80	4000	C/W	70°	27000	24250	■	LTH1211DH840	✓
142	I	✓	80	4000	C/EW	100°	27000	24250	■	LTH1211DP840	✓
142	I	✓	80	4000	ELL	35°x90°	27000	23760	■	LTH1211DQ840	✓



UNIQUO 2M HE EM

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
142	I	✓	80	5700	C/W	70°	27000	24250	■	LTH1211EH857	✓
142	I	✓	80	5700	C/EW	100°	27000	24250	■	LTH1211EP857	✓
142	I	✓	80	5700	ELL	35°x90°	27000	23760	■	LTH1211EQ857	✓
142	I	✓	80	4000	C/W	70°	27000	24250	■	LTH1211EH840	✓
142	I	✓	80	4000	C/EW	100°	27000	24250	■	LTH1211EP840	✓
142	I	✓	80	4000	ELL	35°x90°	27000	23760	■	LTH1211EQ840	✓



UNIQUO 2M HLO

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
178	I	✓	80	5700	C/W	70°	32000	28710	■	LTH1212AH857	✓
178	I	✓	80	5700	C/EW	100°	32000	28710	■	LTH1212AP857	✓
178	I	✓	80	5700	ELL	35°x90°	32000	28100	■	LTH1212AQ857	✓
178	I	✓	80	4000	C/W	70°	32000	28710	■	LTH1212AH840	✓
178	I	✓	80	4000	C/EW	100°	32000	28710	■	LTH1212AP840	✓
178	I	✓	80	4000	ELL	35°x90°	32000	28100	■	LTH1212AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
178	I	✓	80	5700	C/W	70°	32000	28710	■	LTH1212DH857	✓
178	I	✓	80	5700	C/EW	100°	32000	28710	■	LTH1212DP857	✓
178	I	✓	80	5700	ELL	35°x90°	32000	28100	■	LTH1212DQ857	✓
178	I	✓	80	4000	C/W	70°	32000	28710	■	LTH1212DH840	✓
178	I	✓	80	4000	C/EW	100°	32000	28710	■	LTH1212DP840	✓
178	I	✓	80	4000	ELL	35°x90°	32000	28100	■	LTH1212DQ840	✓



UNIQUO 2M HLO EM

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
178	I	✓	80	5700	C/W	70°	32000	28710	■	LTH1212EH857	✓
178	I	✓	80	5700	C/EW	100°	32000	28710	■	LTH1212EP857	✓
178	I	✓	80	5700	ELL	35°x90°	32000	28100	■	LTH1212EQ857	✓
178	I	✓	80	4000	C/W	70°	32000	28710	■	LTH1212EH840	✓
178	I	✓	80	4000	C/EW	100°	32000	28710	■	LTH1212EP840	✓
178	I	✓	80	4000	ELL	35°x90°	32000	28100	■	LTH1212EQ840	✓



UNIQO 3M HE

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
218	I	✓	80	5700	C/W	70°	40500	36990	■	LTH1311AH857	✓
218	I	✓	80	5700	C/EW	100°	40500	36990	■	LTH1311AP857	✓
218	I	✓	80	5700	ELL	35°x90°	40500	36240	■	LTH1311AQ857	✓
218	I	✓	80	4000	C/W	70°	40500	36990	■	LTH1311AH840	✓
218	I	✓	80	4000	C/EW	100°	40500	36990	■	LTH1311AP840	✓
218	I	✓	80	4000	ELL	35°x90°	40500	36240	■	LTH1311AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
218	I	✓	80	5700	C/W	70°	40500	36990	■	LTH1311DH857	✓
218	I	✓	80	5700	C/EW	100°	40500	36990	■	LTH1311DP857	✓
218	I	✓	80	5700	ELL	35°x90°	40500	36240	■	LTH1311DQ857	✓
218	I	✓	80	4000	C/W	70°	40500	36990	■	LTH1311DH840	✓
218	I	✓	80	4000	C/EW	100°	40500	36990	■	LTH1311DP840	✓
218	I	✓	80	4000	ELL	35°x90°	40500	36240	■	LTH1311DQ840	✓



UNIQO 3M HE EM

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
218	I	✓	80	5700	C/W	70°	40500	36990	■	LTH1311EH857	✓
218	I	✓	80	5700	C/EW	100°	40500	36990	■	LTH1311EP857	✓
218	I	✓	80	5700	ELL	35°x90°	40500	36240	■	LTH1311EQ857	✓
218	I	✓	80	4000	C/W	70°	40500	36990	■	LTH1311EH840	✓
218	I	✓	80	4000	C/EW	100°	40500	36990	■	LTH1311EP840	✓
218	I	✓	80	4000	ELL	35°x90°	40500	36240	■	LTH1311EQ840	✓



UNIQO 3M HLO

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
258	I	✓	80	5700	C/W	70°	48000	43790	■	LTH1312AH857	✓
258	I	✓	80	5700	C/EW	100°	48000	43790	■	LTH1312AP857	✓
258	I	✓	80	5700	ELL	35°x90°	48000	42880	■	LTH1312AQ857	✓
258	I	✓	80	4000	C/W	70°	48000	43790	■	LTH1312AH840	✓
258	I	✓	80	4000	C/EW	100°	48000	43790	■	LTH1312AP840	✓
258	I	✓	80	4000	ELL	35°x90°	48000	42880	■	LTH1312AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
258	I	✓	80	5700	C/W	70°	48000	43790	■	LTH1312DH857	✓
258	I	✓	80	5700	C/EW	100°	48000	43790	■	LTH1312DP857	✓
258	I	✓	80	5700	ELL	35°x90°	48000	42880	■	LTH1312DQ857	✓
258	I	✓	80	4000	C/W	70°	48000	43790	■	LTH1312DH840	✓
258	I	✓	80	4000	C/EW	100°	48000	43790	■	LTH1312DP840	✓
258	I	✓	80	4000	ELL	35°x90°	48000	42880	■	LTH1312DQ840	✓



UNIQO 3M HLO EM


IP66 - IK08 - 850°C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
258	I	✓	80	5700	C/W	70°	48000	43790	■	LTH1312EH857	✓
258	I	✓	80	5700	C/EW	100°	48000	43790	■	LTH1312EP857	✓
258	I	✓	80	5700	ELL	35°x90°	48000	42880	■	LTH1312EQ857	✓
258	I	✓	80	4000	C/W	70°	48000	43790	■	LTH1312EH840	✓
258	I	✓	80	4000	C/EW	100°	48000	43790	■	LTH1312EP840	✓
258	I	✓	80	4000	ELL	35°x90°	48000	42880	■	LTH1312EQ840	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
UNIQO			
Bracket kit for 1M version		LTH1A2110	✓
Bracket kit for 2M version		LTH1A2210	✓
Bracket kit for 3M version		LTH1A2310	✓
Support bracket 3M version		LTH1A2360	✓
Ceiling-mounting kit for 1M version		LTH1A2120	✓
Ceiling-mounting kit for 2M and 3M versions		LTH1A2220	✓



LTH1A2110
LTH1A2210
LTH1A2310





LTH1A2120



LTH1A2220

UNIQUO REUSE




■ GR-RAL7035 / Grey RAL7035 / Matt


Scan the QR-code for the latest information

High bay luminaire designed with a modular concept to adapt to continuously advancing industrial, logistics, sports, and tertiary contexts that require flexible, efficient, reliable, and future-proof solutions


- Die-cast aluminum body with integrated heatsink fins
- Embedded internal heatsink fins for optimal heat dissipation of the LED sources
- Extruded aluminium driver box
- Polyester powder-coat finish in grey RAL 7035 colour
- The driver box of the REUSE version is specifically reworked to allow direct housing of the LED modules and their quick, tool-free detachment, facilitating rapid maintenance
- Technopolymer end caps
- Galvanized steel locking hardware
- Patented lever for tool-free attachment and detachment of the LED module directly to the driver box
- LED board featuring a metal core PCB and high-efficacy LEDs
- Exclusively designed PMMA lenses with high optical transmittance for maximum long-term stability and performance, even at elevated temperatures
- Standard tempered 4 mm transparent glass, offering high impact resistance and suitable for demanding applications such as sports halls
- Fast-mounting clips made of polished stainless steel for quick and easy intervention
- Fast-mounting 3-pole connectors made of technopolymer connect each LED module to the driver box, enabling quick, tool-free intervention and replacement of individual LED modules
- It can withstand high ambient temperatures while delivering maximum luminous output without compromising the product's lifespan
- The product comes standard with a suspension kit and can be installed in alternative configurations using the available mounting accessories, which can be ordered separately
- Tilting bracket accessory for individual adjustment of each LED module in $\pm 15^\circ$ increments, ranging from -45° to $+45^\circ$
- Additional accessories and spare parts are available
- The range is certified by third-party entities
- It is certified to the DIN 18032-2 ball impact resistance standard, making it suitable for installation in gymnasiums and indoor sports facilities. Some mounting options may not be compatible with this type of application



UNIQUO REUSE
1M




UNIQUO REUSE
2M



UNIQUO REUSE
3M

Identifying and classifying our optics



UNIQA REUSE 1M HE

IP66 - IK08 - 850°C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
72	I	✓	80	5700	C/W	70°	13500	12250	■	LTH0111AH857	✓
72	I	✓	80	5700	C/EW	100°	13500	12250	■	LTH0111AP857	✓
72	I	✓	80	5700	ELL	35°x90°	13500	12000	■	LTH0111AQ857	✓
72	I	✓	80	4000	C/W	70°	13500	12250	■	LTH0111AH840	✓
72	I	✓	80	4000	C/EW	100°	13500	12250	■	LTH0111AP840	✓
72	I	✓	80	4000	ELL	35°x90°	13500	12000	■	LTH0111AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
72	I	✓	80	5700	C/W	70°	13500	12250	■	LTH0111DH857	✓
72	I	✓	80	5700	C/EW	100°	13500	12250	■	LTH0111DP857	✓
72	I	✓	80	5700	ELL	35°x90°	13500	12000	■	LTH0111DQ857	✓
72	I	✓	80	4000	C/W	70°	13500	12250	■	LTH0111DH840	✓
72	I	✓	80	4000	C/EW	100°	13500	12250	■	LTH0111DP840	✓
72	I	✓	80	4000	ELL	35°x90°	13500	12000	■	LTH0111DQ840	✓

UNIQA REUSE 1M HLO

IP66 - IK08 - 850°C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
88	I	✓	80	5700	C/W	70°	16000	14500	■	LTH0112AH857	✓
88	I	✓	80	5700	C/EW	100°	16000	14500	■	LTH0112AP857	✓
88	I	✓	80	5700	ELL	35°x90°	16000	14200	■	LTH0112AQ857	✓
88	I	✓	80	4000	C/W	70°	16000	14500	■	LTH0112AH840	✓
88	I	✓	80	4000	C/EW	100°	16000	14500	■	LTH0112AP840	✓
88	I	✓	80	4000	ELL	35°x90°	16000	14200	■	LTH0112AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
88	I	✓	80	5700	C/W	70°	16000	14500	■	LTH0112DH857	✓
88	I	✓	80	5700	C/EW	100°	16000	14500	■	LTH0112DP857	✓
88	I	✓	80	5700	ELL	35°x90°	16000	14200	■	LTH0112DQ857	✓
88	I	✓	80	4000	C/W	70°	16000	14500	■	LTH0112DH840	✓
88	I	✓	80	4000	C/EW	100°	16000	14500	■	LTH0112DP840	✓
88	I	✓	80	4000	ELL	35°x90°	16000	14200	■	LTH0112DQ840	✓

UNIQA REUSE 2M HE

IP66 - IK08 - 850°C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
142	I	✓	80	5700	C/W	70°	27000	24250	■	LTH0211AH857	✓
142	I	✓	80	5700	C/EW	100°	27000	24250	■	LTH0211AP857	✓
142	I	✓	80	5700	ELL	35°x90°	27000	23760	■	LTH0211AQ857	✓
142	I	✓	80	4000	C/W	70°	27000	24250	■	LTH0211AH840	✓
142	I	✓	80	4000	C/EW	100°	27000	24250	■	LTH0211AP840	✓
142	I	✓	80	4000	ELL	35°x90°	27000	23760	■	LTH0211AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
142	I	✓	80	5700	C/W	70°	27000	24250	■	LTH0211DH857	✓
142	I	✓	80	5700	C/EW	100°	27000	24250	■	LTH0211DP857	✓
142	I	✓	80	5700	ELL	35°x90°	27000	23760	■	LTH0211DQ857	✓
142	I	✓	80	4000	C/W	70°	27000	24250	■	LTH0211DH840	✓
142	I	✓	80	4000	C/EW	100°	27000	24250	■	LTH0211DP840	✓
142	I	✓	80	4000	ELL	35°x90°	27000	23760	■	LTH0211DQ840	✓

UNIQU REUSE 2M HLO

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
178	I	✓	80	5700	C/W	70°	32000	28710	■	LTH0212AH857	✓
178	I	✓	80	5700	C/EW	100°	32000	28710	■	LTH0212AP857	✓
178	I	✓	80	5700	ELL	35°x90°	32000	28100	■	LTH0212AQ857	✓
178	I	✓	80	4000	C/W	70°	32000	28710	■	LTH0212AH840	✓
178	I	✓	80	4000	C/EW	100°	32000	28710	■	LTH0212AP840	✓
178	I	✓	80	4000	ELL	35°x90°	32000	28100	■	LTH0212AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
178	I	✓	80	5700	C/W	70°	32000	28710	■	LTH0212DH857	✓
178	I	✓	80	5700	C/EW	100°	32000	28710	■	LTH0212DP857	✓
178	I	✓	80	5700	ELL	35°x90°	32000	28100	■	LTH0212DQ857	✓
178	I	✓	80	4000	C/W	70°	32000	28710	■	LTH0212DH840	✓
178	I	✓	80	4000	C/EW	100°	32000	28710	■	LTH0212DP840	✓
178	I	✓	80	4000	ELL	35°x90°	32000	28100	■	LTH0212DQ840	✓



UNIQU REUSE 3M HE

IP66 - IK08 - 850°C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
218	I	✓	80	5700	C/W	70°	40500	36990	■	LTH0311AH857	✓
218	I	✓	80	5700	C/EW	100°	40500	36990	■	LTH0311AP857	✓
218	I	✓	80	5700	ELL	35°x90°	40500	36240	■	LTH0311AQ857	✓
218	I	✓	80	4000	C/W	70°	40500	36990	■	LTH0311AH840	✓
218	I	✓	80	4000	C/EW	100°	40500	36990	■	LTH0311AP840	✓
218	I	✓	80	4000	ELL	35°x90°	40500	36240	■	LTH0311AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
218	I	✓	80	5700	C/W	70°	40500	36990	■	LTH0311DH857	✓
218	I	✓	80	5700	C/EW	100°	40500	36990	■	LTH0311DP857	✓
218	I	✓	80	5700	ELL	35°x90°	40500	36240	■	LTH0311DQ857	✓
218	I	✓	80	4000	C/W	70°	40500	36990	■	LTH0311DH840	✓
218	I	✓	80	4000	C/EW	100°	40500	36990	■	LTH0311DP840	✓
218	I	✓	80	4000	ELL	35°x90°	40500	36240	■	LTH0311DQ840	✓



UNIQU REUSE 3M HLO


IP66 - IK08 - 850°C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
258	I	✓	80	5700	C/W	70°	48000	43790	■	LTH0312AH857	✓
258	I	✓	80	5700	C/EW	100°	48000	43790	■	LTH0312AP857	✓
258	I	✓	80	5700	ELL	35°x90°	48000	42880	■	LTH0312AQ857	✓
258	I	✓	80	4000	C/W	70°	48000	43790	■	LTH0312AH840	✓
258	I	✓	80	4000	C/EW	100°	48000	43790	■	LTH0312AP840	✓
258	I	✓	80	4000	ELL	35°x90°	48000	42880	■	LTH0312AQ840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
258	I	✓	80	5700	C/W	70°	48000	43790	■	LTH0312DH857	✓
258	I	✓	80	5700	C/EW	100°	48000	43790	■	LTH0312DP857	✓
258	I	✓	80	5700	ELL	35°x90°	48000	42880	■	LTH0312DQ857	✓
258	I	✓	80	4000	C/W	70°	48000	43790	■	LTH0312DH840	✓
258	I	✓	80	4000	C/EW	100°	48000	43790	■	LTH0312DP840	✓
258	I	✓	80	4000	ELL	35°x90°	48000	42880	■	LTH0312DQ840	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
UNIQO REUSE			
Ceiling-mounting kit for 1M version		LTH1A2120	✓
Ceiling-mounting kit for 2M and 3M versions		LTH1A2220	✓
Tilting bracket for Reuse version		LTH0A2030	✓



LTH1A2120




LTH1A2220



LTH0A2030

ELIA HL




■ Black RAL 9017 / Black RAL9017 /


Scan the QR-code for the latest information

LED highbay designed for indoor industrial, logistics and tertiary applications, where efficiency, high luminous output, precision and resistance are required

- Available in 3 power steps (120 W, 150 W and 200 W) with a standard colour temperature of 4,000 K (neutral white) and a colour rendering index of 80, the range allows for great flexibility with its multiple possible combinations: 3 optics options (60°, 90° and 120° beam angles in polycarbonate lenses) and 2 integrated power supply options (On/Off and DALI)
- Thanks to its black powder-coated die-cast aluminium body with incorporated heatsink, it is tough, durable (IP65 and IK08) and able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- The luminaire can be suspension-mounted through the hook attachment integrated into the upper part of the device



ELIA HL
ON/OFF



ELIA HL
DALI

ELIA HL M2 120W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
120	I	✓	80	4000	SYMM	60°	-	17900	■	GWF1000MH840	✓
120	I	✓	80	4000	SYMM	90°	-	18200	■	GWF1000ML840	✓
120	I	✓	80	4000	SYMM	120°	-	18000	■	GWF1000MM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
120	I	✓	80	4000	SYMM	60°	-	17900	■	GWF1001MH840	✓
120	I	✓	80	4000	SYMM	90°	-	18200	■	GWF1001ML840	✓
120	I	✓	80	4000	SYMM	120°	-	18000	■	GWF1001MM840	✓



ELIA HL M3 150W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
150	I	✓	80	4000	SYMM	60°	-	22400	■	GWF1000NH840	✓
150	I	✓	80	4000	SYMM	90°	-	22800	■	GWF1000NL840	✓
150	I	✓	80	4000	SYMM	120°	-	22500	■	GWF1000NM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
150	I	✓	80	4000	SYMM	60°	-	22400	■	GWF1001NH840	✓
150	I	✓	80	4000	SYMM	90°	-	22800	■	GWF1001NL840	✓
150	I	✓	80	4000	SYMM	120°	-	22500	■	GWF1001NM840	✓



ELIA HL L2 200W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
200	I	✓	80	4000	SYMM	60°	-	29800	■	GWF1000QH840	✓
200	I	✓	80	4000	SYMM	90°	-	30300	■	GWF1000QL840	✓
200	I	✓	80	4000	SYMM	120°	-	30000	■	GWF1000QM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
200	I	✓	80	4000	SYMM	60°	-	29800	■	GWF1001QH840	✓
200	I	✓	80	4000	SYMM	90°	-	30300	■	GWF1001QL840	✓
200	I	✓	80	4000	SYMM	120°	-	30000	■	GWF1001QM840	✓





Welzorg distribution center - Raamsdonksveer - Netherlands



LAMA+



ABI BV - Haarlem - Netherlands




Scan the QR-code for the latest information

WH-87 / White / Textured


Suspended LED fixture for industrial lighting, for indoor use, consisting of:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- UV and heat stabilised, technopolymer diffuser with integral custom moulded optics
- High-transparency polycarbonate optics
- S/W optic with UGR<25
- EPDM sealing gasket
- Technopolymer cable compartment cover
- Stainless steel suspension hook designed to be mounted on the fixture body quickly and without the use of tools to optimize installation time
- The IP66-rated socket-plug fast connector for mains connection without opening the luminaire. Made in PA66 with silver-plated brass contacts for cables Ø 9 - Ø 12 mm
- Stainless steel locking hardware
- The protective glass, available as accessory, shall be used in environments with mineral or natural oils or in atmospheres that are not compatible with polycarbonate
- Openable and maintainable luminaire (future-proof)
- The SOFT versions feature diffuser optics
- Appliance certified in accordance with the DIN 18032-2 standard, therefore suitable for installation in fitness centres or indoor sports structures
- Installation in gyms or sports facilities must be carried out using the mounting bracket or, if the fixtures must be suspended, using the specific carabiners. All these fastening elements are available as accessories



LAMA+

Identifying and classifying our optics



LAMA+ 70

IP66 - IK07 - 750 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
59	I	-	80	5700	S/W	-	12384	12750	□	LTH3152AH857	✓
59	I	-	80	5700	ELL	-	12384	10690	□	LTH3152AQ857	✓
59	I	-	80	5700	S/EW	SOFT	12384	11370	□	LTH3152AR857	✓
59	I	-	80	5700	S/EW	-	12384	11540	□	LTH3152AP857	✓
59	I	-	80	4000	S/W	-	12384	10750	□	LTH3152AH840	✓
59	I	-	80	4000	ELL	45°x85°	12384	10690	□	LTH3152AQ840	✓
59	I	-	80	4000	S/EW	SOFT	12384	11370	□	LTH3152AR840	✓
59	I	-	80	4000	S/EW	-	12384	11540	□	LTH3152AP840	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

59	I	-	80	5700	S/W	-	12384	12750	□	LTH3152DH857	✓
59	I	-	80	5700	ELL	-	12384	10690	□	LTH3152DQ857	✓
59	I	-	80	5700	S/EW	SOFT	12384	11370	□	LTH3152DR857	✓
59	I	-	80	5700	S/EW	-	12384	11540	□	LTH3152DP857	✓
59	I	-	80	4000	S/W	-	12384	10750	□	LTH3152DH840	✓
59	I	-	80	4000	ELL	45°x85°	12384	10690	□	LTH3152DQ840	✓
59	I	-	80	4000	S/EW	SOFT	12384	11370	□	LTH3152DR840	✓
59	I	-	80	4000	S/EW	-	12384	11540	□	LTH3152DP840	✓

LAMA+ 70 EM

IP65 - IK07 - 750 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
59	I	-	80	5700	S/W	-	12384	12750	□	LTH3152EH857	✓
59	I	-	80	5700	ELL	-	12384	10690	□	LTH3152EQ857	✓
59	I	-	80	5700	S/EW	SOFT	12384	11370	□	LTH3152ER857	✓
59	I	-	80	5700	S/EW	-	12384	11540	□	LTH3152EP857	✓
59	I	-	80	4000	S/W	-	12384	10750	□	LTH3152EH840	✓
59	I	-	80	4000	ELL	45°x85°	12384	10690	□	LTH3152EQ840	✓
59	I	-	80	4000	S/EW	SOFT	12384	11370	□	LTH3152ER840	✓
59	I	-	80	4000	S/EW	-	12384	11540	□	LTH3152EP840	✓

LAMA+ 100

IP66 - IK07 - 750 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
99	I	-	80	5700	S/W	-	20736	17070	□	LTH3153AH857	✓
99	I	-	80	5700	ELL	-	20736	16970	□	LTH3153AQ857	✓
99	I	-	80	5700	S/EW	SOFT	20736	18060	□	LTH3153AR857	✓
99	I	-	80	5700	S/EW	-	20736	18340	□	LTH3153AP857	✓
99	I	-	80	4000	S/W	-	20736	17070	□	LTH3153AH840	✓
99	I	-	80	4000	ELL	45°x85°	20736	16970	□	LTH3153AQ840	✓
99	I	-	80	4000	S/EW	SOFT	20736	18060	□	LTH3153AR840	✓
99	I	-	80	4000	S/EW	-	20736	18340	□	LTH3153AP840	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

99	I	-	80	5700	S/W	-	20736	17070	□	LTH3153DH857	✓
99	I	-	80	5700	ELL	-	20736	16970	□	LTH3153DQ857	✓
99	I	-	80	5700	S/EW	SOFT	20736	18060	□	LTH3153DR857	✓
99	I	-	80	5700	S/EW	-	20736	18340	□	LTH3153DP857	✓
99	I	-	80	4000	S/W	-	20736	17070	□	LTH3153DH840	✓
99	I	-	80	4000	ELL	45°x85°	20736	16970	□	LTH3153DQ840	✓
99	I	-	80	4000	S/EW	SOFT	20736	18060	□	LTH3153DR840	✓
99	I	-	80	4000	S/EW	-	20736	18340	□	LTH3153DP840	✓

LAMA+ 100 EM

IP65 - IK07 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
99	I	-	80	5700	S/W	-	20736	17070	<input type="checkbox"/>	LTH3153EH857	✓
99	I	-	80	5700	ELL	-	20736	16970	<input type="checkbox"/>	LTH3153EQ857	✓
99	I	-	80	5700	S/EW	SOFT	20736	18060	<input type="checkbox"/>	LTH3153ER857	✓
99	I	-	80	5700	S/EW	-	20736	18340	<input type="checkbox"/>	LTH3153EP857	✓
99	I	-	80	4000	S/W	-	20736	17070	<input type="checkbox"/>	LTH3153EH840	✓
99	I	-	80	4000	ELL	45°x85°	20736	16970	<input type="checkbox"/>	LTH3153EQ840	✓
99	I	-	80	4000	S/EW	SOFT	20736	18060	<input type="checkbox"/>	LTH3153ER840	✓
99	I	-	80	4000	S/EW	-	20736	18340	<input type="checkbox"/>	LTH3153EP840	✓



LAMA+ 150

IP66 - IK07 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
138	I	-	80	5700	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154AH857	✓
138	I	-	80	5700	ELL	-	28224	23520	<input type="checkbox"/>	LTH3154AQ857	✓
138	I	-	80	5700	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154AR857	✓
138	I	-	80	5700	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154AP857	✓
138	I	-	80	4000	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154AH840	✓
138	I	-	80	4000	ELL	45°x85°	28224	23520	<input type="checkbox"/>	LTH3154AQ840	✓
138	I	-	80	4000	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154AR840	✓
138	I	-	80	4000	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154AP840	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
138	I	-	80	5700	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154DH857	✓
138	I	-	80	5700	ELL	-	28224	23520	<input type="checkbox"/>	LTH3154DQ857	✓
138	I	-	80	5700	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154DR857	✓
138	I	-	80	5700	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154DP857	✓
138	I	-	80	4000	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154DH840	✓
138	I	-	80	4000	ELL	45°x85°	28224	23520	<input type="checkbox"/>	LTH3154DQ840	✓
138	I	-	80	4000	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154DR840	✓
138	I	-	80	4000	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154DP840	✓



LAMA+ 150 EM

IP65 - IK07 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
138	I	-	80	5700	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154EH857	✓
138	I	-	80	5700	ELL	-	28224	23520	<input type="checkbox"/>	LTH3154EQ857	✓
138	I	-	80	5700	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154ER857	✓
138	I	-	80	5700	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154EP857	✓
138	I	-	80	4000	S/W	-	28224	23550	<input type="checkbox"/>	LTH3154EH840	✓
138	I	-	80	4000	ELL	45°x85°	28224	23520	<input type="checkbox"/>	LTH3154EQ840	✓
138	I	-	80	4000	S/EW	SOFT	28224	24900	<input type="checkbox"/>	LTH3154ER840	✓
138	I	-	80	4000	S/EW	-	28224	25300	<input type="checkbox"/>	LTH3154EP840	✓



LAMA+ 200

IP66 - IK07 - 750 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
184	I	-	80	5700	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155AH857	✓
184	I	-	80	5700	ELL	-	37177	29770	<input type="checkbox"/>	LTH3155AQ857	✓
184	I	-	80	5700	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155AR857	✓
184	I	-	80	5700	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155AP857	✓
184	I	-	80	4000	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155AH840	✓
184	I	-	80	4000	ELL	45°x85°	37177	29770	<input type="checkbox"/>	LTH3155AQ840	✓
184	I	-	80	4000	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155AR840	✓
184	I	-	80	4000	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155AP840	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

184	I	-	80	5700	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155DH857	✓
184	I	-	80	5700	ELL	-	37177	29770	<input type="checkbox"/>	LTH3155DQ857	✓
184	I	-	80	5700	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155DR857	✓
184	I	-	80	5700	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155DP857	✓
184	I	-	80	4000	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155DH840	✓
184	I	-	80	4000	ELL	45°x85°	37177	29770	<input type="checkbox"/>	LTH3155DQ840	✓
184	I	-	80	4000	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155DR840	✓
184	I	-	80	4000	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155DP840	✓

LAMA+ 200 EM


IP65 - IK07 - 750 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
184	I	-	80	5700	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155EH857	✓
184	I	-	80	5700	ELL	-	37177	29770	<input type="checkbox"/>	LTH3155EQ857	✓
184	I	-	80	5700	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155ER857	✓
184	I	-	80	5700	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155EP857	✓
184	I	-	80	4000	S/W	-	37177	29950	<input type="checkbox"/>	LTH3155EH840	✓
184	I	-	80	4000	ELL	45°x85°	37177	29770	<input type="checkbox"/>	LTH3155EQ840	✓
184	I	-	80	4000	S/EW	SOFT	37177	31670	<input type="checkbox"/>	LTH3155ER840	✓
184	I	-	80	4000	S/EW	-	37177	32170	<input type="checkbox"/>	LTH3155EP840	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
LAMA+			
LAMA+ wall/ceiling bracket kit	<input type="checkbox"/>	LTH3A2015	✓
Stainless steel spring carabiner kit (2 pcs.)		LTH3A2053	✓
Transparent protective glass IK 10		LTH3A5033	✓



LTH3A2015




LTH3A2053



LTH3A5033

LAMA+ MINI





WH-87 / White / Textured

Scan the QR-code for the latest information


Suspended LED luminaire for indoor and outdoor industrial applications, comprising:

- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- High-transparency polycarbonate optics
- The IP66-rated socket-plug fast connector for mains connection without opening the luminaire. Made in PA66 with silver-plated brass contacts for cables Ø 9 - Ø 12 mm
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Galvanised steel suspension hooks
- Stainless steel locking hardware
- Stainless steel locking springs for the glass
- EM versions are complete with emergency device that can operate on battery for 1 hour. Product can be used for general or emergency lighting
- Static ON/OFF or dimmable DALI options available
- Design by ROBERTO FIORATO



LAMA+ MINI

Identifying and classifying our optics



LAMA+ MINI S/W

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	S/W	-	16732	13921,9	<input type="checkbox"/>	3101184	✓
72	I	-	80	4000	S/W	-	12479	10636,4	<input type="checkbox"/>	3101185	✓
50	I	-	80	4000	S/W	-	9195	7721	<input type="checkbox"/>	3101186	✓
35	I	-	80	4000	S/W	-	6690	5963,8	<input type="checkbox"/>	3101187	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
101	I	-	80	4000	S/W	-	16732	13921,9	<input type="checkbox"/>	3101192	✓
72	I	-	80	4000	S/W	-	12479	10636,5	<input type="checkbox"/>	3101193	✓
50	I	-	80	4000	S/W	-	9195	7721	<input type="checkbox"/>	3101194	✓
35	I	-	80	4000	S/W	-	6690	5963,8	<input type="checkbox"/>	3101195	✓



LAMA+ MINI S/W EM

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - emergency 1h - 220-240 V 50/60 Hz											
50	I	-	80	4000	S/W	-	9195	7721	<input type="checkbox"/>	3101750	✓
35	I	-	80	4000	S/W	-	6690	5963	<input type="checkbox"/>	3101751	✓



LAMA+ MINI S/EW

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	S/EW	-	16732	14765	<input type="checkbox"/>	3101188	✓
72	I	-	80	4000	S/EW	-	12479	11332,3	<input type="checkbox"/>	3101189	✓
50	I	-	80	4000	S/EW	-	9195	8101	<input type="checkbox"/>	3101190	✓
35	I	-	80	4000	S/EW	-	6690	6260,83	<input type="checkbox"/>	3101191	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
101	I	-	80	4000	S/EW	-	16732	14765	<input type="checkbox"/>	3101196	✓
72	I	-	80	4000	S/EW	-	12479	11332,3	<input type="checkbox"/>	3101197	✓
50	I	-	80	4000	S/EW	-	9195	8101	<input type="checkbox"/>	3101198	✓
35	I	-	80	4000	S/EW	-	6690	6260,8	<input type="checkbox"/>	3101199	✓



LAMA+ MINI S/EW EM

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - emergency 1h - 220-240 V 50/60 Hz											
50	I	-	80	4000	S/EW	-	9195	8101	<input type="checkbox"/>	3101754	✓
35	I	-	80	4000	S/EW	-	6690	6260	<input type="checkbox"/>	3101755	✓



LAMA+ MINI ELL

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	ELL	45°x85°	16732	13944	<input type="checkbox"/>	3105993	✓
72	I	-	80	4000	ELL	45°x85°	12479	10702	<input type="checkbox"/>	3105995	✓
50	I	-	80	4000	ELL	45°x85°	9195	7812	<input type="checkbox"/>	3105997	✓
35	I	-	80	4000	ELL	45°x85°	6690	6037	<input type="checkbox"/>	3106000	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
101	I	-	80	4000	ELL	45°x85°	16732	13944	<input type="checkbox"/>	3105994	✓
72	I	-	80	4000	ELL	45°x85°	12479	10702	<input type="checkbox"/>	3105996	✓
50	I	-	80	4000	ELL	45°x85°	9195	7812	<input type="checkbox"/>	3105998	✓
35	I	-	80	4000	ELL	45°x85°	6690	6037	<input type="checkbox"/>	3106001	✓



LAMA+ MINI ELL EM

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - emergency 1h - 220-240 V 50/60 Hz											
50	I	-	80	4000	ELL	45°x85°	9195	7812	<input type="checkbox"/>	3105999	✓
35	I	-	80	4000	ELL	45°x85°	6690	6037	<input type="checkbox"/>	3106002	✓




A+




■ BK-RAL9005 / Black RAL9005 / Textured

Scan the QR-code for the latest information


- Suspended LED luminaire for indoor and outdoor industrial applications, comprising:
- Die-cast aluminium housing and trim polyester powder coat finish, coat finish prior chemical conversion surface treatment
 - UV and heat stabilised, technopolymer diffuser with integral custom moulded optics
 - Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
 - Stainless steel locking hardware
 - Suspension hook in painted aluminium with safety screw
 - Complete with cable H05RN-F
 - Built-in driver
- Options:
- Painted steel bracket
 - Infrared remote control for sensor module




A+
MULTIPOWER




A+
60



A+
100



A+
150



A+
200

A+ MULTIPOWER

IP65 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 0-10 V 220-240 50/60 Hz											
85							17430	15191			
100	I	-	80	4000	C/EW	90°	21480	17362	■	3119399	✓
150							29750	24724			
200							38140	30373			



A+ 60

IP65 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
60	I	-	80	5700	C/EW	90°	10350	9787	■	3124700	✓
60	I	-	80	4000	C/EW	90°	9630	8456	■	3111273	✓



A+ 100

IP65 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
100	I	-	80	5700	C/IW	60°	19300	16235	■	3124702	✓
100	I	-	80	5700	C/EW	90°	19300	17662	■	3124701	✓
100	I	-	80	4000	C/IW	60°	18540	16486	■	3124703	✓
100	I	-	80	4000	C/EW	90°	18540	16110	■	3111274	✓



A+ 150

IP65 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
150	I	-	80	5700	C/IW	60°	29500	25564	■	3124705	✓
150	I	-	80	5700	C/EW	90°	29500	26215	■	3124704	✓
150	I	-	80	4000	C/IW	60°	28290	24453	■	3124706	✓
150	I	-	80	4000	C/EW	90°	28290	24414	■	3111275	✓



A+ 200

IP65 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
200	I	-	80	5700	C/IW	60°	38850	33105	■	3124708	✓
200	I	-	80	5700	C/EW	90°	38850	34091	■	3124707	✓
200	I	-	80	4000	C/IW	60°	37480	32270	■	3124709	✓
200	I	-	80	4000	C/EW	90°	37480	31900	■	3111276	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
A+ MULTIPOWER			
Polycarbonate diffuser A+ MULTIPOWER	■	3124453	✓
Driver DALI		3119400	✓
Microwave motion sensor		3119401	✓
Remote control		3119402	✓
Fixing bracket A+ MULTIPOWER	■	3119403	✓
Kit EM3P		3119404	✓
A+			
Fixing bracket A+60	■	3111280	✓
Fixing bracket A+100	■	3111281	✓
Fixing bracket A+150	■	3111282	✓
Fixing bracket A+200	■	3111283	✓
A+ 100			
Polycarbonate diffuser A+ 100		311019	✓
A+ 100 / A+ 150 / A+ 200			
Microwave motion sensor		3111277	✓
Remote control		3111278	✓
DALI converter		3111279	✓



3111277
3119400
3119401



3111278
3119402



3111280
3111281
3111282
3111283
3119403



3119404




311019



3111279

GYM+



■ WH-87 / White / Glossy


Scan the QR-code for the latest information

High protection grid luminaire for gym and indoor sports facilities, comprising:

- Polyester powder coat finish sheet steel housing
- High transmission optical system with integrated PMMA prismatic diffuser (>92%)
- Reinforced protective grid (IK10) with safety look
- The DA versions are dual power switch
- The GYM+ 3 model with double switch allows three lighting options: central lighting only, two lateral lighting and full lighting
- Static ON/OFF or dimmable DALI options available
- Ceiling installation or suspension through steel chain only
- Rotation option using rotation kit accessory
- Ball-Proof compliant (DIN 18032-3)



Primary school het Epos - Rotterdam - Netherlands



GYM+
2

GYM+
3

GYM+ 2

IP20 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
143	I	-	80	4000	S/EW	-	19584	18300	■	1548	3107127	✓
114	I	-	80	4000	S/EW	-	13500	11523	■	1548	3100004	✓
83	I	-	80	4000	S/EW	-	10050	8991	■	1548	3100003	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
114	I	-	80	4000	S/EW	-	13500	11523	■	1548	3100006	✓



GYM+ 3

IP20 - IK10 - 650 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
144 + 74	I	-	80	4000	S/EW	-	29376	27505	■	1548	3107125	✓
125 + 66	I	-	80	4000	S/EW	-	25228	24000	■	1548	3107126	✓
105 + 55	I	-	80	4000	S/EW	-	17136	16113	■	1548	3100005	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
160	I	-	80	4000	S/EW	-	17136	16113	■	1548	3100007	✓







SMART [3] PLUS





■ Grey RAL 7035 / Grey RAL7035 /



Scan the QR-code for the latest information

Watertight fixture IP66/69 for industrial applications, ideal for production areas, warehouses, and logistics areas



- Designed to replace high-flux fluorescent devices and lowbays up to 10,000lm
- IK08 body in RAL7035 colored self-exhausting polycarbonate
- Available in 3 sizes (800, 1200 and 1600 mm)
- Available in 3000 K, 4000 K and 5700 K, with CRI ≥80 or ≥90
- Available with powers ranging from 25 W to 63 W and flux ranging from 4,000 lm to 10,000 lm
- Mid-power LED flip chip type
- Available with integrated On/Off or DALI driver
- The through wiring version has pre-wired mechanical and electrical connections as accessories (to be ordered separately), allowing up to 25 fixtures installed in a continuous row
- Available in 4 different optical solutions: transparent or opal diffuser in UV-stabilized, self-extinguishing polycarbonate; the transparent version can be equipped with TIR lenses in PMMA with medium or elliptical beam
- The device can be hung or wall-mounted through bracket accessory with a tilt of 30° or 45° on the vertical axis
- Available in DALI version with integrated emergency kit with 3h autonomy
- Available with external emergency kit with 3h autonomy compatible with through wiring versions (to be ordered separately)



SMART [3] PLUS
800



SMART [3] PLUS
1200



SMART [3] PLUS
1600

SMART [3] PLUS 800 OPAL

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	✓	90	5700	OPAL	-	-	2900	■	GWS3120AP957	✓
25	II	✓	90	4000	OPAL	-	-	2900	■	GWS3120AP940	✓
25	II	✓	90	3000	OPAL	-	-	2700	■	GWS3120AP930	✓
25	II	✓	80	5700	OPAL	-	-	3700	■	GWS3120AP857	✓
25	II	✓	80	4000	OPAL	-	-	3700	■	GWS3120AP840	✓
25	II	✓	80	3000	OPAL	-	-	3500	■	GWS3120AP830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
25	II	✓	90	5700	OPAL	-	-	2900	■	GWS3122AP957	✓
25	II	✓	90	4000	OPAL	-	-	2900	■	GWS3122AP940	✓
25	II	✓	90	3000	OPAL	-	-	2700	■	GWS3122AP930	✓
25	II	✓	80	5700	OPAL	-	-	3700	■	GWS3122AP857	✓
25	II	✓	80	4000	OPAL	-	-	3700	■	GWS3122AP840	✓
25	II	✓	80	3000	OPAL	-	-	3500	■	GWS3122AP830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
26	II	✓	90	5700	OPAL	-	-	2900	■	GWS3121AP957	✓
26	II	✓	90	4000	OPAL	-	-	2900	■	GWS3121AP940	✓
26	II	✓	90	3000	OPAL	-	-	2700	■	GWS3121AP930	✓
26	II	✓	80	5700	OPAL	-	-	3700	■	GWS3121AP857	✓
26	II	✓	80	4000	OPAL	-	-	3700	■	GWS3121AP840	✓
26	II	✓	80	3000	OPAL	-	-	3500	■	GWS3121AP830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
26	II	✓	90	5700	OPAL	-	-	2900	■	GWS3123AP957	✓
26	II	✓	90	4000	OPAL	-	-	2900	■	GWS3123AP940	✓
26	II	✓	90	3000	OPAL	-	-	2700	■	GWS3123AP930	✓
26	II	✓	80	5700	OPAL	-	-	3700	■	GWS3123AP857	✓
26	II	✓	80	4000	OPAL	-	-	3700	■	GWS3123AP840	✓
26	II	✓	80	3000	OPAL	-	-	3500	■	GWS3123AP830	✓

SMART [3] PLUS 800 TRANSPARENT

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
25	II	✓	90	5700	TRNSP	-	-	3100	■	GWS3120AT957	✓
25	II	✓	90	4000	TRNSP	-	-	3100	■	GWS3120AT940	✓
25	II	✓	90	3000	TRNSP	-	-	2900	■	GWS3120AT930	✓
25	II	✓	80	5700	TRNSP	-	-	3900	■	GWS3120AT857	✓
25	II	✓	80	4000	TRNSP	-	-	3900	■	GWS3120AT840	✓
25	II	✓	80	3000	TRNSP	-	-	3700	■	GWS3120AT830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
25	II	✓	90	5700	TRNSP	-	-	3100	■	GWS3122AT957	✓
25	II	✓	90	4000	TRNSP	-	-	3100	■	GWS3122AT940	✓
25	II	✓	90	3000	TRNSP	-	-	2900	■	GWS3122AT930	✓
25	II	✓	80	5700	TRNSP	-	-	3900	■	GWS3122AT857	✓
25	II	✓	80	4000	TRNSP	-	-	3900	■	GWS3122AT840	✓
25	II	✓	80	3000	TRNSP	-	-	3700	■	GWS3122AT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
26	II	✓	90	5700	TRNSP	-	-	3100	■	GWS3121AT957	✓
26	II	✓	90	4000	TRNSP	-	-	3100	■	GWS3121AT940	✓
26	II	✓	90	3000	TRNSP	-	-	2900	■	GWS3121AT930	✓
26	II	✓	80	5700	TRNSP	-	-	3900	■	GWS3121AT857	✓
26	II	✓	80	4000	TRNSP	-	-	3900	■	GWS3121AT840	✓
26	II	✓	80	3000	TRNSP	-	-	3700	■	GWS3121AT830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
26	II	✓	90	5700	TRNSP	-	-	3100	■	GWS3123AT957	✓
26	II	✓	90	4000	TRNSP	-	-	3100	■	GWS3123AT940	✓
26	II	✓	90	3000	TRNSP	-	-	2900	■	GWS3123AT930	✓
26	II	✓	80	5700	TRNSP	-	-	3900	■	GWS3123AT857	✓
26	II	✓	80	4000	TRNSP	-	-	3900	■	GWS3123AT840	✓
26	II	✓	80	3000	TRNSP	-	-	3700	■	GWS3123AT830	✓

SMART [3] PLUS 1200 OPAL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
36	II	✓	90	5700	OPAL	-	-	4200	■	GWS3220AP957	✓
36	II	✓	90	4000	OPAL	-	-	4200	■	GWS3220AP940	✓
36	II	✓	90	3000	OPAL	-	-	4000	■	GWS3220AP930	✓
36	II	✓	80	5700	OPAL	-	-	5400	■	GWS3220AP857	✓
36	II	✓	80	4000	OPAL	-	-	5400	■	GWS3220AP840	✓
36	II	✓	80	3000	OPAL	-	-	5100	■	GWS3220AP830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
36	II	✓	90	5700	OPAL	-	-	4200	■	GWS3222AP957	✓
36	II	✓	90	4000	OPAL	-	-	4200	■	GWS3222AP940	✓
36	II	✓	90	3000	OPAL	-	-	4000	■	GWS3222AP930	✓
36	II	✓	80	5700	OPAL	-	-	5400	■	GWS3222AP857	✓
36	II	✓	80	4000	OPAL	-	-	5400	■	GWS3222AP840	✓
36	II	✓	80	3000	OPAL	-	-	5100	■	GWS3222AP830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
38	II	✓	90	5700	OPAL	-	-	4200	■	GWS3221AP957	✓
38	II	✓	90	4000	OPAL	-	-	4200	■	GWS3221AP940	✓
38	II	✓	90	3000	OPAL	-	-	4000	■	GWS3221AP930	✓
38	II	✓	80	5700	OPAL	-	-	5400	■	GWS3221AP857	✓
38	II	✓	80	4000	OPAL	-	-	5400	■	GWS3221AP840	✓
38	II	✓	80	3000	OPAL	-	-	5100	■	GWS3221AP830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
38	II	✓	90	5700	OPAL	-	-	4200	■	GWS3223AP957	✓
38	II	✓	90	4000	OPAL	-	-	4200	■	GWS3223AP940	✓
38	II	✓	90	3000	OPAL	-	-	4000	■	GWS3223AP930	✓
38	II	✓	80	5700	OPAL	-	-	5400	■	GWS3223AP857	✓
38	II	✓	80	4000	OPAL	-	-	5400	■	GWS3223AP840	✓
38	II	✓	80	3000	OPAL	-	-	5100	■	GWS3223AP830	✓



SMART [3] PLUS 1200 OPAL EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
38	II	-	90	5700	OPAL	-	-	4200	■	GWS3225AP957	✓
38	II	-	90	4000	OPAL	-	-	4200	■	GWS3225AP940	✓
38	II	-	90	3000	OPAL	-	-	4000	■	GWS3225AP930	✓
38	II	-	80	5700	OPAL	-	-	5400	■	GWS3225AP857	✓
38	II	-	80	4000	OPAL	-	-	5400	■	GWS3225AP840	✓
38	II	-	80	3000	OPAL	-	-	5100	■	GWS3225AP830	✓



SMART [3] PLUS 1200 TRANSPARENT

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
36	II	✓	90	5700	TRNSP	-	-	4500	■	GWS3220AT957	✓
36	II	✓	90	4000	TRNSP	-	-	4500	■	GWS3220AT940	✓
36	II	✓	90	3000	TRNSP	-	-	4200	■	GWS3220AT930	✓
36	II	✓	80	5700	TRNSP	-	-	5700	■	GWS3220AT857	✓
36	II	✓	80	4000	TRNSP	-	-	5700	■	GWS3220AT840	✓
36	II	✓	80	3000	TRNSP	-	-	5400	■	GWS3220AT830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
36	II	✓	90	5700	TRNSP	-	-	4500	■	GWS3222AT957	✓
36	II	✓	90	4000	TRNSP	-	-	4500	■	GWS3222AT940	✓
36	II	✓	90	3000	TRNSP	-	-	4200	■	GWS3222AT930	✓
36	II	✓	80	5700	TRNSP	-	-	5700	■	GWS3222AT857	✓
36	II	✓	80	4000	TRNSP	-	-	5700	■	GWS3222AT840	✓
36	II	✓	80	3000	TRNSP	-	-	5400	■	GWS3222AT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
38	II	✓	90	5700	TRNSP	-	-	4500	■	GWS3221AT957	✓
38	II	✓	90	4000	TRNSP	-	-	4500	■	GWS3221AT940	✓
38	II	✓	90	3000	TRNSP	-	-	4200	■	GWS3221AT930	✓
38	II	✓	80	5700	TRNSP	-	-	5700	■	GWS3221AT857	✓
38	II	✓	80	4000	TRNSP	-	-	5700	■	GWS3221AT840	✓
38	II	✓	80	3000	TRNSP	-	-	5400	■	GWS3221AT830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
38	II	✓	90	5700	TRNSP	-	-	4500	■	GWS3223AT957	✓
38	II	✓	90	4000	TRNSP	-	-	4500	■	GWS3223AT940	✓
38	II	✓	90	3000	TRNSP	-	-	4200	■	GWS3223AT930	✓
38	II	✓	80	5700	TRNSP	-	-	5700	■	GWS3223AT857	✓
38	II	✓	80	4000	TRNSP	-	-	5700	■	GWS3223AT840	✓
38	II	✓	80	3000	TRNSP	-	-	5400	■	GWS3223AT830	✓

SMART [3] PLUS 1200 TRANSPARENT EM

IP65 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
38	II	-	90	5700	TRNSP	-	-	4500	■	GWS3225AT957	✓
38	II	-	90	4000	TRNSP	-	-	4500	■	GWS3225AT940	✓
38	II	-	90	3000	TRNSP	-	-	4200	■	GWS3225AT930	✓
38	II	-	80	5700	TRNSP	-	-	5700	■	GWS3225AT857	✓
38	II	-	80	4000	TRNSP	-	-	5700	■	GWS3225AT840	✓
38	II	-	80	3000	TRNSP	-	-	5400	■	GWS3225AT830	✓

SMART [3] PLUS 1600 OPAL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
46	II	✓	90	5700	OPAL	-	-	5600	■	GWS3320AP957	✓
46	II	✓	90	4000	OPAL	-	-	5600	■	GWS3320AP940	✓
46	II	✓	90	3000	OPAL	-	-	5300	■	GWS3320AP930	✓
46	II	✓	80	5700	OPAL	-	-	7100	■	GWS3320AP857	✓
46	II	✓	80	4000	OPAL	-	-	7100	■	GWS3320AP840	✓
46	II	✓	80	3000	OPAL	-	-	6800	■	GWS3320AP830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
46	II	✓	90	5700	OPAL	-	-	5600	■	GWS3322AP957	✓
46	II	✓	90	4000	OPAL	-	-	5600	■	GWS3322AP940	✓
46	II	✓	90	3000	OPAL	-	-	5300	■	GWS3322AP930	✓
46	II	✓	80	5700	OPAL	-	-	7100	■	GWS3322AP857	✓
46	II	✓	80	4000	OPAL	-	-	7100	■	GWS3322AP840	✓
46	II	✓	80	3000	OPAL	-	-	6800	■	GWS3322AP830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	90	5700	OPAL	-	-	5600	■	GWS3321AP957	✓
50	II	✓	90	4000	OPAL	-	-	5600	■	GWS3321AP940	✓
50	II	✓	90	3000	OPAL	-	-	5300	■	GWS3321AP930	✓
50	II	✓	80	5700	OPAL	-	-	7100	■	GWS3321AP857	✓
50	II	✓	80	4000	OPAL	-	-	7100	■	GWS3321AP840	✓
50	II	✓	80	3000	OPAL	-	-	6800	■	GWS3321AP830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	90	5700	OPAL	-	-	5600	■	GWS3323AP957	✓
50	II	✓	90	4000	OPAL	-	-	5600	■	GWS3323AP940	✓
50	II	✓	90	3000	OPAL	-	-	5300	■	GWS3323AP930	✓
50	II	✓	80	5700	OPAL	-	-	7100	■	GWS3323AP857	✓
50	II	✓	80	4000	OPAL	-	-	7100	■	GWS3323AP840	✓
50	II	✓	80	3000	OPAL	-	-	6800	■	GWS3323AP830	✓



SMART [3] PLUS 1600 OPAL EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
50	II	-	90	5700	OPAL	-	-	5600	■	GWS3325AP957	✓
50	II	-	90	4000	OPAL	-	-	5600	■	GWS3325AP940	✓
50	II	-	90	3000	OPAL	-	-	5300	■	GWS3325AP930	✓
50	II	-	80	5700	OPAL	-	-	7100	■	GWS3325AP857	✓
50	II	-	80	4000	OPAL	-	-	7100	■	GWS3325AP840	✓
50	II	-	80	3000	OPAL	-	-	6800	■	GWS3325AP830	✓



SMART [3] PLUS 1600 TRANSPARENT

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
46	II	✓	90	5700	TRNSP	-	-	5900	■	GWS3320AT957	✓
46	II	✓	90	4000	TRNSP	-	-	5900	■	GWS3320AT940	✓
46	II	✓	90	3000	TRNSP	-	-	5500	■	GWS3320AT930	✓
46	II	✓	80	5700	TRNSP	-	-	7500	■	GWS3320AT857	✓
46	II	✓	80	4000	TRNSP	-	-	7500	■	GWS3320AT840	✓
46	II	✓	80	3000	TRNSP	-	-	7100	■	GWS3320AT830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
46	II	✓	90	5700	TRNSP	-	-	5900	■	GWS3322AT957	✓
46	II	✓	90	4000	TRNSP	-	-	5900	■	GWS3322AT940	✓
46	II	✓	90	3000	TRNSP	-	-	5500	■	GWS3322AT930	✓
46	II	✓	80	5700	TRNSP	-	-	7500	■	GWS3322AT857	✓
46	II	✓	80	4000	TRNSP	-	-	7500	■	GWS3322AT840	✓
46	II	✓	80	3000	TRNSP	-	-	7100	■	GWS3322AT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	90	5700	TRNSP	-	-	5900	■	GWS3321AT957	✓
50	II	✓	90	4000	TRNSP	-	-	5900	■	GWS3321AT940	✓
50	II	✓	90	3000	TRNSP	-	-	5500	■	GWS3321AT930	✓
50	II	✓	80	5700	TRNSP	-	-	7500	■	GWS3321AT857	✓
50	II	✓	80	4000	TRNSP	-	-	7500	■	GWS3321AT840	✓
50	II	✓	80	3000	TRNSP	-	-	7100	■	GWS3321AT830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	90	5700	TRNSP	-	-	5900	■	GWS3323AT957	✓
50	II	✓	90	4000	TRNSP	-	-	5900	■	GWS3323AT940	✓
50	II	✓	90	3000	TRNSP	-	-	5500	■	GWS3323AT930	✓
50	II	✓	80	5700	TRNSP	-	-	7500	■	GWS3323AT857	✓
50	II	✓	80	4000	TRNSP	-	-	7500	■	GWS3323AT840	✓
50	II	✓	80	3000	TRNSP	-	-	7100	■	GWS3323AT830	✓

SMART [3] PLUS 1600 TRANSPARENT EM

IP65 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
50	II	-	90	5700	TRNSP	-	-	5900	■	GWS3325AT957	✓
50	II	-	90	4000	TRNSP	-	-	5900	■	GWS3325AT940	✓
50	II	-	90	3000	TRNSP	-	-	5500	■	GWS3325AT930	✓
50	II	-	80	5700	TRNSP	-	-	7500	■	GWS3325AT857	✓
50	II	-	80	4000	TRNSP	-	-	7500	■	GWS3325AT840	✓
50	II	-	80	3000	TRNSP	-	-	7100	■	GWS3325AT830	✓

SMART [3] PLUS 1600 MEDIUM BEAM

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
46	II	✓	90	5700	SYMM	-	-	5600	■	GWS3320AC957	✓
46	II	✓	90	4000	SYMM	-	-	5600	■	GWS3320AC940	✓
46	II	✓	90	3000	SYMM	-	-	5200	■	GWS3320AC930	✓
46	II	✓	80	5700	SYMM	-	-	7100	■	GWS3320AC857	✓
46	II	✓	80	4000	SYMM	-	-	7100	■	GWS3320AC840	✓
46	II	✓	80	3000	SYMM	-	-	6700	■	GWS3320AC830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
46	II	✓	90	5700	SYMM	-	-	5600	■	GWS3322AC957	✓
46	II	✓	90	4000	SYMM	-	-	5600	■	GWS3322AC940	✓
46	II	✓	90	3000	SYMM	-	-	5200	■	GWS3322AC930	✓
46	II	✓	80	5700	SYMM	-	-	7100	■	GWS3322AC857	✓
46	II	✓	80	4000	SYMM	-	-	7100	■	GWS3322AC840	✓
46	II	✓	80	3000	SYMM	-	-	6700	■	GWS3322AC830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	90	5700	SYMM	-	-	5600	■	GWS3321AC957	✓
50	II	✓	90	4000	SYMM	-	-	5600	■	GWS3321AC940	✓
50	II	✓	90	3000	SYMM	-	-	5200	■	GWS3321AC930	✓
50	II	✓	80	5700	SYMM	-	-	7100	■	GWS3321AC857	✓
50	II	✓	80	4000	SYMM	-	-	7100	■	GWS3321AC840	✓
50	II	✓	80	3000	SYMM	-	-	6700	■	GWS3321AC830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	90	5700	SYMM	-	-	5600	■	GWS3323AC957	✓
50	II	✓	90	4000	SYMM	-	-	5600	■	GWS3323AC940	✓
50	II	✓	90	3000	SYMM	-	-	5200	■	GWS3323AC930	✓
50	II	✓	80	5700	SYMM	-	-	7100	■	GWS3323AC857	✓
50	II	✓	80	4000	SYMM	-	-	7100	■	GWS3323AC840	✓
50	II	✓	80	3000	SYMM	-	-	6700	■	GWS3323AC830	✓



SMART [3] PLUS 1600 PARKING

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
46	II	✓	80	5700	ELL	-	-	6600	■	GWS3320AB857	✓
46	II	✓	80	4000	ELL	-	-	6600	■	GWS3320AB840	✓
46	II	-	80	3000	ELL	-	-	6200	■	GWS3320AB830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
46	II	✓	80	5700	ELL	-	-	6600	■	GWS3322AB857	✓
46	II	✓	80	4000	ELL	-	-	6600	■	GWS3322AB840	✓
46	II	✓	80	3000	ELL	-	-	6200	■	GWS3322AB830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	80	5700	ELL	-	-	6600	■	GWS3321AB857	✓
50	II	-	80	4000	ELL	-	-	6600	■	GWS3321AB840	✓
50	II	-	80	3000	ELL	-	-	6200	■	GWS3321AB830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	-	80	5700	ELL	-	-	6600	■	GWS3323AB857	✓
50	II	-	80	4000	ELL	-	-	6600	■	GWS3323AB840	✓
50	II	-	80	3000	ELL	-	-	6200	■	GWS3323AB830	✓



SMART [3] PLUS 1600 PARKING EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
50	II	-	80	5700	ELL	-	-	6600	■	GWS3325AB857	✓
50	II	-	80	4000	ELL	-	-	6600	■	GWS3325AB840	✓



SMART [3] PLUS 1600 HLO OPAL

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
61	II	✓	90	5700	OPAL	-	-	7100	■	GWS3320BP957	✓
61	II	✓	90	4000	OPAL	-	-	7100	■	GWS3320BP940	✓
61	II	✓	90	3000	OPAL	-	-	6600	■	GWS3320BP930	✓
61	II	✓	80	5700	OPAL	-	-	9000	■	GWS3320BP857	✓
61	II	✓	80	4000	OPAL	-	-	9000	■	GWS3320BP840	✓
61	II	✓	80	3000	OPAL	-	-	8500	■	GWS3320BP830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
61	II	✓	90	5700	OPAL	-	-	7100	■	GWS3322BP957	✓
61	II	✓	90	4000	OPAL	-	-	7100	■	GWS3322BP940	✓
61	II	✓	90	3000	OPAL	-	-	6600	■	GWS3322BP930	✓
61	II	✓	80	5700	OPAL	-	-	9000	■	GWS3322BP857	✓
61	II	✓	80	4000	OPAL	-	-	9000	■	GWS3322BP840	✓
61	II	✓	80	3000	OPAL	-	-	8500	■	GWS3322BP830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
63	II	✓	90	5700	OPAL	-	-	7100	■	GWS3321BP957	✓
63	II	✓	90	4000	OPAL	-	-	7100	■	GWS3321BP940	✓
63	II	✓	90	3000	OPAL	-	-	6600	■	GWS3321BP930	✓
63	II	✓	80	5700	OPAL	-	-	9000	■	GWS3321BP857	✓
63	II	✓	80	4000	OPAL	-	-	9000	■	GWS3321BP840	✓
63	II	✓	80	3000	OPAL	-	-	8500	■	GWS3321BP830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
63	II	✓	90	5700	OPAL	-	-	7100	■	GWS3323BP957	✓
63	II	✓	90	4000	OPAL	-	-	7100	■	GWS3323BP940	✓
63	II	✓	90	3000	OPAL	-	-	6600	■	GWS3323BP930	✓
63	II	✓	80	5700	OPAL	-	-	9000	■	GWS3323BP857	✓
63	II	✓	80	4000	OPAL	-	-	9000	■	GWS3323BP840	✓
63	II	✓	80	3000	OPAL	-	-	8500	■	GWS3323BP830	✓

SMART [3] PLUS 1600 HLO OPAL EM

IP65 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
63	II	-	90	5700	OPAL	-	-	7100	■	GWS3325BP957	✓
63	II	-	90	4000	OPAL	-	-	7100	■	GWS3325BP940	✓
63	II	-	90	3000	OPAL	-	-	6600	■	GWS3325BP930	✓
63	II	-	80	5700	OPAL	-	-	9000	■	GWS3325BP857	✓
63	II	-	80	4000	OPAL	-	-	9000	■	GWS3325BP840	✓
63	II	-	80	3000	OPAL	-	-	8500	■	GWS3325BP830	✓

SMART [3] PLUS 1600 HLO TRANSPARENT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
61	II	✓	90	5700	TRNSP	-	-	7400	■	GWS3320BT957	✓
61	II	✓	90	4000	TRNSP	-	-	7400	■	GWS3320BT940	✓
61	II	✓	90	3000	TRNSP	-	-	6900	■	GWS3320BT930	✓
61	II	✓	80	5700	TRNSP	-	-	9400	■	GWS3320BT857	✓
61	II	✓	80	4000	TRNSP	-	-	9400	■	GWS3320BT840	✓
61	II	✓	80	3000	TRNSP	-	-	8900	■	GWS3320BT830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
61	II	✓	90	5700	TRNSP	-	-	7400	■	GWS3322BT957	✓
61	II	✓	90	4000	TRNSP	-	-	7400	■	GWS3322BT940	✓
61	II	✓	90	3000	TRNSP	-	-	6900	■	GWS3322BT930	✓
61	II	✓	80	5700	TRNSP	-	-	9400	■	GWS3322BT857	✓
61	II	✓	80	4000	TRNSP	-	-	9400	■	GWS3322BT840	✓
61	II	✓	80	3000	TRNSP	-	-	8900	■	GWS3322BT830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
63	II	✓	90	5700	TRNSP	-	-	7400	■	GWS3321BT957	✓
63	II	✓	90	4000	TRNSP	-	-	7400	■	GWS3321BT940	✓
63	II	✓	90	3000	TRNSP	-	-	6900	■	GWS3321BT930	✓
63	II	✓	80	5700	TRNSP	-	-	9400	■	GWS3321BT857	✓
63	II	✓	80	4000	TRNSP	-	-	9400	■	GWS3321BT840	✓
63	II	✓	80	3000	TRNSP	-	-	8900	■	GWS3321BT830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
63	II	✓	90	5700	TRNSP	-	-	7400	■	GWS3323BT957	✓
63	II	✓	90	4000	TRNSP	-	-	7400	■	GWS3323BT940	✓
63	II	✓	90	3000	TRNSP	-	-	6900	■	GWS3323BT930	✓
63	II	✓	80	5700	TRNSP	-	-	9400	■	GWS3323BT857	✓
63	II	✓	80	4000	TRNSP	-	-	9400	■	GWS3323BT840	✓
63	II	✓	80	3000	TRNSP	-	-	8900	■	GWS3323BT830	✓



SMART [3] PLUS 1600 HLO TRANSPARENT EM

IP65 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
63	II	-	90	5700	TRNSP	-	-	7400	■	GWS3325BT957	✓
63	II	-	90	4000	TRNSP	-	-	7400	■	GWS3325BT940	✓
63	II	-	90	3000	TRNSP	-	-	6900	■	GWS3325BT930	✓
63	II	-	80	5700	TRNSP	-	-	9400	■	GWS3325BT857	✓
63	II	-	80	4000	TRNSP	-	-	9400	■	GWS3325BT840	✓
63	II	-	80	3000	TRNSP	-	-	8900	■	GWS3325BT830	✓



SMART [3] PLUS 1600 HLO MEDIUM BEAM

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
61	II	✓	90	5700	SYMM	-	-	7100	■	GWS3320BC957	✓
61	II	✓	90	4000	SYMM	-	-	7100	■	GWS3320BC940	✓
61	II	✓	90	3000	SYMM	-	-	6600	■	GWS3320BC930	✓
61	II	✓	80	5700	SYMM	-	-	8900	■	GWS3320BC857	✓
61	II	✓	80	4000	SYMM	-	-	8900	■	GWS3320BC840	✓
61	II	✓	80	3000	SYMM	-	-	8500	■	GWS3320BC830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
61	II	✓	90	5700	SYMM	-	-	7100	■	GWS3322BC957	✓
61	II	✓	90	4000	SYMM	-	-	7100	■	GWS3322BC940	✓
61	II	✓	90	3000	SYMM	-	-	6600	■	GWS3322BC930	✓
61	II	✓	80	5700	SYMM	-	-	8900	■	GWS3322BC857	✓
61	II	✓	80	4000	SYMM	-	-	8900	■	GWS3322BC840	✓
61	II	✓	80	3000	SYMM	-	-	8500	■	GWS3322BC830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
63	II	✓	90	5700	SYMM	-	-	7100	■	GWS3321BC957	✓
63	II	✓	90	4000	SYMM	-	-	7100	■	GWS3321BC940	✓
63	II	✓	90	3000	SYMM	-	-	6600	■	GWS3321BC930	✓
63	II	✓	80	5700	SYMM	-	-	8900	■	GWS3321BC857	✓
63	II	✓	80	4000	SYMM	-	-	8900	■	GWS3321BC840	✓
63	II	✓	80	3000	SYMM	-	-	8500	■	GWS3321BC830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
63	II	✓	90	5700	SYMM	-	-	7100	■	GWS3323BC957	✓
63	II	✓	90	4000	SYMM	-	-	7100	■	GWS3323BC940	✓
63	II	✓	90	3000	SYMM	-	-	6600	■	GWS3323BC930	✓
63	II	✓	80	5700	SYMM	-	-	8900	■	GWS3323BC857	✓
63	II	✓	80	4000	SYMM	-	-	8900	■	GWS3323BC840	✓
63	II	✓	80	3000	SYMM	-	-	8500	■	GWS3323BC830	✓

SMART [3] PLUS 1600 HLO PARKING

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
61	II	✓	80	5700	ELL	-	-	8200	■	GWS3320BB857	✓
61	II	✓	80	4000	ELL	-	-	8200	■	GWS3320BB840	✓
61	II	✓	80	3000	ELL	-	-	7800	■	GWS3320BB830	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
61	II	✓	80	5700	ELL	-	-	8200	■	GWS3322BB857	✓
61	II	✓	80	4000	ELL	-	-	8200	■	GWS3322BB840	✓
61	II	✓	80	3000	ELL	-	-	7800	■	GWS3322BB830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
63	II	✓	80	5700	ELL	-	-	8200	■	GWS3321BB857	✓
63	II	✓	80	4000	ELL	-	-	8200	■	GWS3321BB840	✓
63	II	✓	80	3000	ELL	-	-	7800	■	GWS3321BB830	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
63	II	✓	80	5700	ELL	-	-	8200	■	GWS3323BB857	✓
63	II	✓	80	4000	ELL	-	-	8200	■	GWS3323BB840	✓
63	II	✓	80	3000	ELL	-	-	7800	■	GWS3323BB830	✓

SMART [3] PLUS 1600 HLO PARKING EM

IP65 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
63	II	-	80	5700	ELL	-	-	8200	■	GWS3325BB857	✓
63	II	-	80	4000	ELL	-	-	8200	■	GWS3325BB840	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [3] PLUS			
Wall-mounting bracket 30°/45°		GWS3191	✓
Rigid pipe adaptor		GWS3193	✓
RINA clamp kit		GWS3296	✓
SMART [3] PLUS - THROUGH WIRING			
Male connector 4 poles 10 A		GWS3194	✓
Continuous line connection kit		GWS3197	✓
Emergency kit 3h for through wiring version		GWS3198	✓



GWS3191



GWS3194



GWS3198





Orobia Climbing - Curno - Italy

SMART [3]



Albinoleffe stadium - Zanica - Italy





Scan the QR-code for the latest information



■ Grey RAL 7035 / Grey RAL7035 /

Watertight fixture IP66/69 for industrial applications, ideal for production areas, warehouses, and logistics areas



- Designed to replace fluorescent devices and lowbays up to 6,500 lm
- IK08 body in RAL7035 colored self-exhausting polycarbonate
- Available in 3 sizes: 800 mm, 1200 mm and 1600 mm
- Available in 3000 K, 4000 K and 5700 K, with CRI ≥80
- Available with powers ranging from 18W to 58W and flux ranging from 1,700lm to 6,500lm
- Mid-power LED with wire bonding
- Available with integrated On/Off or DALI driver
- The through wiring version has pre-wired mechanical and electrical connections as accessories (to be ordered separately), allowing up to 25 fixtures installed in a continuous row
- Available in 2 different optical solutions: transparent or opal diffuser in UV-stabilized, self-extinguishing polycarbonate
- The device can be hung or wall-mounted through bracket accessory with a tilt of 30° or 45° on the vertical axis
- External emergency kit with 3h autonomy compatible with through wiring versions available (to be ordered separately)



SMART [3]
800



SMART [3]
1200



SMART [3]
1600

SMART [3] 800 OPAL

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218P57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218P	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218P30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PL57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PL	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PL30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PD57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PD	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PD30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PLD57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PLD	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PLD30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PLD	✓

SMART [3] 800 TRANSPARENT

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218T57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218T	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218T30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TL57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TL	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TL30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TD57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TD	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TD30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TLD57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TLD	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TLD30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TLD	✓

SMART [3] 1200 OPAL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236P57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236P	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236P30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PL57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PL	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PL30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PD57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PD	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PD30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PLD57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PLD	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PLD30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PLD	✓



SMART [3] 1200 TRANSPARENT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236T57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236T	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236T30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TL57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TL	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TL30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TD57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TD	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TD30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TLD57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TLD	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TLD30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TLD	✓



SMART [3] 1600 OPAL

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258P57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258P	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258P30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PL57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PL	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PL30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PD57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PD	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PD30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PLD57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PLD	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PLD30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PLD	✓

SMART [3] 1600 TRANSPARENT

IP66 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258T57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258T	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258T30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TL57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TL	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TL30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TD57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TD	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TD30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TLD57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TLD	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TLD30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TLD	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [3]			
Wall-mounting bracket 30°/45°		GWS3191	✓
Rigid pipe adaptor		GWS3193	✓
RINA clamp kit		GWS3296	✓
SMART [3] - THROUGH WIRING			
Male connector 4 poles 10 A		GWS3194	✓
Continuous line connection kit		GWS3197	✓
Emergency kit 3h for through wiring version		GWS3198	✓



GWS3191



GWS3194




GWS3198

SMART [3]E



Municipal stadium Giovanni Battista Maffei - Brescia - Italy





Scan the QR-code for the latest information


■ Grey RAL 7035 / Grey RAL7035 /

Watertight fixture IP66/69 for industrial applications, ideal for production areas, warehouses, and logistics areas

- Designed to replace fluorescent devices and lowbays up to 6,500lm
- IK08 body in RAL7035 colored self-exhausting polycarbonate
- Available in 2 sizes (800 and 1200 mm)
- Available in 4000K and 5700K with CRI ≥ 80
- Available with powers ranging from 34 W to 52 W and flux ranging from 3,700 lm to 6,300 lm
- Mid-power LED with wire bonding
- Equipped with integrated On/Off driver
- The through wiring version has pre-wired mechanical and electrical connections as accessories (to be ordered separately), allowing up to 25 fixtures installed in a continuous row
- Available in 2 different optical solutions: transparent or opal diffuser in UV-stabilized, self-extinguishing polycarbonate
- The device can be hung or wall-mounted through bracket accessory with a tilt of 30° or 45° on the vertical axis
- Available with external emergency kit with 3h autonomy compatible with through wiring versions (to be ordered separately)



SMART [3]E
800



SMART [3]E
1200

SMART [3]E 800 OPAL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
34	II	✓	80	5700	OPAL	-	-	3700	■	GWS3120EP857	✓
34	II	✓	80	4000	OPAL	-	-	3700	■	GWS3120EP840	✓



SMART [3]E 800 TRANSPARENT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
34	II	✓	80	5700	TRNSP	-	-	3900	■	GWS3120ET857	✓
34	II	✓	80	4000	TRNSP	-	-	3900	■	GWS3120ET840	✓



SMART [3]E 1200 OPAL

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
52	II	✓	80	5700	OPAL	-	-	6000	■	GWS3220EP857	✓
52	II	✓	80	4000	OPAL	-	-	6000	■	GWS3220EP840	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
52	II	✓	80	5700	OPAL	-	-	6000	■	GWS3222EP857	✓
52	II	✓	80	4000	OPAL	-	-	6000	■	GWS3222EP840	✓



SMART [3]E 1200 TRANSPARENT

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
52	II	✓	80	5700	TRNSP	-	-	6300	■	GWS3220ET857	✓
52	II	✓	80	4000	TRNSP	-	-	6300	■	GWS3220ET840	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
52	II	✓	80	5700	TRNSP	-	-	6300	■	GWS3222ET857	✓
52	II	✓	80	4000	TRNSP	-	-	6300	■	GWS3222ET840	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [3]E			
Wall-mounting bracket 30°/45°		GWS3191	✓
Rigid pipe adaptor		GWS3193	✓
RINA clamp kit		GWS3296	✓
SMART [3]E - THROUGH WIRING			
Male connector 4 poles 10 A		GWS3194	✓
Continuous line connection kit		GWS3197	✓
Emergency kit 3h for through wiring version		GWS3198	✓



GWS3191




GWS3194



GWS3198

LM4




Scan the QR-code for the latest information

■ GR-94 / Metallic grey / Textured

Ceiling mounted LED luminaire for indoor and outdoor industrial applications, comprising:

- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser, matt and silk-screened on the inside
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- IP66-rated, PA66 with silver-plated brass contacts, fast connector, complete with factory pre-wired cable, for mains connection without opening the luminaire, for cables Ø 9 - Ø 12 mm
- Stainless steel locking hardware
- Stainless steel locking springs for the glass
- Stainless steel springs for quick installation
- EM versions are complete with emergency device that can operate on battery for 1 hour. Product can be used for general or emergency lighting
- Static ON/OFF or dimmable DALI options available
- Through-wiring version available . Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory



LM4

LM4 S/EW

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
101	I	-	80	4000	S/EW	-	16732	13985	■	630	3101704	✓
72	I	-	80	4000	S/EW	-	12479	10767	■	630	3101705	✓
50	I	-	80	4000	S/EW	-	9195	7625	■	630	3101706	✓
35	I	-	80	4000	S/EW	-	6690	5614	■	630	3101707	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
101	I	-	80	4000	S/EW	-	16732	13895	■	630	3101708	✓
72	I	-	80	4000	S/EW	-	12479	10767,2	■	630	3101709	✓
50	I	-	80	4000	S/EW	-	9195	7625	■	630	3101710	✓
35	I	-	80	4000	S/EW	-	6690	5614	■	630	3101711	✓




LM4 S/EW EM

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED - emergency 1h - 220-240 V 50/60 Hz												
50	I	-	80	4000	S/EW	-	8890	7625	■	630	3101714	✓
35	I	-	80	4000	S/EW	-	6690	5614	■	630	3101715	✓



ACRO PRO



Scan the QR-code for the latest information


■ GR-RAL7035 / Grey RAL7035 / Matt

Weatherproof LED luminaire, comprising:


- Fibreglass reinforced polyester housing
- Diffuser in frosted polycarbonate, glow wire 850 °C (EN 60695-2-11)
- Anti-ageing custom moulded silicone sealing gasket(s)
- 4000K multi-chip LED board
- Fully integrated stainless steel safety spring clips
- Quick ceiling fixing bracket (stainless steel)
- Integral Dip-Switches to select one of four power levels, which can be field adjusted (MULTIPOWER models)
- Emergency - 1 hour
- EM/1P are maintained emergency versions (1h)
- Hyper-frequency (HF) sensor operating at 5.8 Ghz+/- 75 Mhz
- Dimmable DALI




Factory Profel - Overpelt - Belgique



ACRO PRO
EQ218 MULTIPOWER



ACRO PRO
EQ236



ACRO PRO
EQ258

ACRO PRO EQ218 MULTIPOWER

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
11.5							1700	1528				
15	I	-	80	4000	S/EW	-	2100	1857	■	615	3114690	✓
17							2460	2208				
20							2800	2506				



ACRO PRO EQ236

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	URCA
Power LED - dimmable DALI 220-240 V 50/60 Hz												
31	I	-	80	4000	S/EW	-	5350	4981	■	1174	3114692	✓



ACRO PRO EQ236 MULTIPOWER

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
18							3200	2923				
22.5	I	-	80	4000	S/EW	-	3950	3598	■	1174	3114691	✓
27.5							4750	4343				
31							5350	4981				



Power LED 220-240 V 50/60 Hz + HF Sensor

18							3200	2923				
22.5	I	-	80	4000	S/EW	-	3950	3598	■	1174	3114694	✓
27.5							4750	4343				
31							5350	4981				

Power LED - emergency 1h - 220-240 V 50/60 Hz

18							3200	2923				
22.5	I	-	80	4000	S/EW	-	3950	3598	■	1174	3114693	✓
27.5							4750	4343				
31							5350	4981				

Power LED - Emergency 1h - 220-240 V 50/60 Hz + HF Sensor

18							3200	2923				
22.5	I	-	80	4000	S/EW	-	3950	3598	■	1174	3114695	✓
27.5							4750	4343				
31							5350	4981				

ACRO PRO EQ258

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	URCA
Power LED - dimmable DALI 220-240 V 50/60 Hz												
42	I	-	80	4000	S/EW	-	7100	6588	■	1454	3114697	✓



ACRO PRO EQ258 MULTIPOWER

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
24							4300	3865				
29	I	-	80	4000	S/EW	-	5300	4758	■	1454	3114696	✓
36							6250	5746				
42							7100	6588				



Power LED 220-240 V 50/60 Hz + HF Sensor

24							4300	3865				
29	I	-	80	4000	S/EW	-	5300	4758	■	1454	3114699	✓
36							6250	5746				
42							7100	6588				


Power LED - emergency 1h - 220-240 V 50/60 Hz

24							4300	3865				
29	I	-	80	4000	S/EW	-	5300	4758	■	1454	3114698	✓
36							6250	5746				
42							7100	6588				

Power LED - Emergency 1h - 220-240 V 50/60 Hz + HF Sensor

24							4300	3865				
29	I	-	80	4000	S/EW	-	5300	4758	■	1454	3114700	✓
36							6250	5746				
42							7100	6588				

ACRO+



■ GR-RAL7035 / Grey RAL7035 / Matt


Scan the QR-code for the latest information

Weatherproof LED luminaire, comprising:

- Fibreglass reinforced polyester housing
- Opal PMMA diffuser for optimal light distribution and uniformity
- Anti-ageing custom moulded silicone sealing gasket(s)
- 4000K multi-chip LED board
- Stainless steel retaining clips
- Quick ceiling fixing bracket (stainless steel)
- Integral Dip-Switches to select one of four power levels, which can be field adjusted (MULTIPOWER models)
- Suitable for extreme operating temp. conditions, -40°C (EXTREME options only)
- Emergency and extreme versions have a polycarbonate diffuser, 850°C glow wire



Factory Febo - Amsterdam - Netherlands



ACRO+
EQ118 / EQ136 / EQ158

ACRO+
EQ236 / EQ258

EQ = EQUIVALENT

		Dimensions (LxWxH)	LED Module	lm	W
3103915	ACRO+ EQ136 S/EW 840	Same dimensions 1x36 W	Equivalent lm output 136	2700	23,5
3103919	ACRO+ EQ236 S/EW 840	Same dimensions 2x36 W	Equivalent lm output 236	5500	51
3103923	ACRO+ EQ236 HO S/EW 840	Same dimensions 2x36 W	Equivalent High lm output 236	8100	59
3103927	ACRO+ EQ158 S/EW 840	Same dimensions 1x58 W	Equivalent lm output 158	4100	33
3103931	ACRO+ EQ258 S/EW 840	Same dimensions 2x58 W	Equivalent lm output 258	6500	59
3103935	ACRO+ EQ258 HO S/EW 840	Same dimensions 2x58 W	Equivalent High lm output 258	10200	73

ACRO+ EQ118

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
17.5	I	✓	80	4000	S/EW	-	-	1900	■	669	3103914	✓



ACRO+ EQ136

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
23.5	I	✓	80	4000	S/EW	-	-	2700	■	1277	3103915	✓
Power LED 220-240 V 50/60 Hz + HF Sensor												
23.5	I	-	80	4000	S/EW	-	-	2700	■	1277	3103918	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
23.5	I	-	80	4000	S/EW	-	-	2700	■	1277	3103916	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
23.5	I	-	80	4000	S/EW	-	-	2700	■	1277	3103917	✓



ACRO+ EQ158

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
33	I	✓	80	4000	S/EW	-	-	4100	■	1577	3103927	✓
Power LED 220-240 V 50/60 Hz + HF Sensor												
33	I	-	80	4000	S/EW	-	-	4100	■	1577	3103930	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
33	I	-	80	4000	S/EW	-	-	4100	■	1577	3103928	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
33	I	-	80	4000	S/EW	-	-	4100	■	1577	3103929	✓



ACRO+ EQ236

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz + HF Sensor												
51	I	-	80	4000	S/EW	-	-	5500	■	1277	3103922	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
51	I	-	80	4000	S/EW	-	-	5500	■	1277	3103920	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
51	I	-	80	4000	S/EW	-	-	5500	■	1277	3103921	✓



ACRO+ EQ236 MULTIPOWER

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	URCA
Power LED 220-240 V 50/60 Hz												
22							3465	3300				
28							4300	4094				
33	I	✓	80	4000	S/EW	-	5050	4811	■	1277	3109254	✓
39							5540	5276				



ACRO+ EQ236 HO

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
59	I	✓	80	4000	S/EW	-	-	8100	■	1277	3103923	✓
Power LED 220-240 V 50/60 Hz + HF Sensor												
59	I	-	80	4000	S/EW	-	-	8100	■	1277	3103926	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
59	I	-	80	4000	S/EW	-	-	8100	■	1277	3103924	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
59	I	-	80	4000	S/EW	-	-	8100	■	1277	3103925	✓



ACRO+ EQ236 HO EXTREME-40°

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
59	I	-	80	4000	S/EW	-	-	7700	■	1277	3103947	✓



ACRO+ EQ258

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + HF Sensor												
59	I	-	80	4000	S/EW	-	-	6500	■	1577	3103934	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
59	I	-	80	4000	S/EW	-	-	6500	■	1577	3103932	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
59	I	-	80	4000	S/EW	-	-	6500	■	1577	3103933	✓



ACRO+ EQ258 MULTIPOWER

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
27							4290	4173				
34	I	✓	80	4000	S/EW	-	5300	5161	■	1577	3109253	✓
41							6240	6074				
47							6980	6794				



ACRO+ EQ258 HO

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
73	I	✓	80	4000	S/EW	-	-	10200	■	1577	3103935	✓
Power LED 220-240 V 50/60 Hz + HF Sensor												
73	I	-	80	4000	S/EW	-	-	10200	■	1577	3103938	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
73	I	-	80	4000	S/EW	-	-	10200	■	1577	3103936	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz												
73	I	-	80	4000	S/EW	-	-	10200	■	1577	3103937	✓



ACRO+ EQ258 HO EXTREME-40°

IP66 - IK08 - 850 °C


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
73	I	-	80	4000	S/EW	-	-	9600	■	1577	3103948	✓





Unidex warehouse - De Zilk - Netherlands

ACRO BASIC



■ GR-RAL7035 / Grey RAL7035 / Matt


Scan the QR-code for the latest information

Weatherproof LED luminaire, comprising:

- Fibreglass reinforced polyester housing
- Opal PMMA diffuser for optimal light distribution and uniformity
- Anti-ageing custom moulded silicone sealing gasket(s)
- 4000K multi-chip LED board
- Stainless steel retaining clips
- Quick ceiling fixing bracket (stainless steel)



Factory Profel - Overpelt - Belgique



ACRO BASIC
EQ218

ACRO BASIC
EQ136
EQ236

ACRO BASIC
EQ158
EQ258

ACRO BASIC EQ218

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
24	I	-	80	4000	S/EW	-	3500	3296	■	605	3109252	✓

ACRO BASIC EQ136

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
23	I	✓	80	4000	S/EW	-	-	3000	■	1185	3103939	✓

ACRO BASIC EQ236

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
37	I	✓	80	4000	S/EW	-	-	4800	■	1185	3103940	✓

ACRO BASIC EQ158

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
29	I	✓	80	4000	S/EW	-	-	4300	■	1477	3103941	✓

ACRO BASIC EQ258

IP66 - IK03 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
50	I	✓	80	4000	S/EW	-	-	6800	■	1477	3103942	✓



NORMA+



■ GR-RAL7035 / Grey RAL7035 / Matt


Scan the QR-code for the latest information

Weatherproof LED luminaire, comprising:

- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment
- Technopolymers end caps
- Anti-ageing custom moulded silicone sealing gasket(s)
- Tool-less bayonet opening polycarbonate cap for mains connection
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Aluminium heat sink
- Stainless steel springs for quick installation
- The CL (Continuous Line) versions are suitable for through wiring continuous line installations (5x2,5 mm²)
- EM versions are complete with emergency device that can operate on battery for 1 hour. Product can be used for general or emergency lighting



ABI BV production facilities- Haarlem - Netherlands



NORMA+ 6o

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
23	I	-	80	4000	S/EW	-	4662	3951	■	630	305949	✓
16	I	-	80	4000	S/EW	-	3347	2836	■	630	305948	✓



NORMA+ 6o CL

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
23	I	-	80	4000	S/EW	-	4662	3951	■	660	305941	✓
16	I	-	80	4000	S/EW	-	3347	2836	■	660	305940	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
23	I	-	80	4000	S/EW	-	4662	3951	■	660	305989	✓
16	I	-	80	4000	S/EW	-	3347	2836	■	660	305988	✓



NORMA+ 12o

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
34	I	-	80	4000	S/EW	-	6153	5215	■	1230	305952	✓
25	I	-	80	4000	S/EW	-	3775	3002	■	1230	305950	✓
25	I	-	80	4000	S/EW	-	4428	3753	■	1230	305951	✓



NORMA+ 12o CL

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
34	I	-	80	4000	S/EW	-	6153	5215	■	1260	305944	✓
25	I	-	80	4000	S/EW	-	3775	3002	■	1260	305942	✓
25	I	-	80	4000	S/EW	-	4428	3752	■	1260	305943	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
34	I	-	80	4000	S/EW	-	6153	5215	■	1260	305992	✓
25	I	-	80	4000	S/EW	-	3775	3002	■	1260	305990	✓
25	I	-	80	4000	S/EW	-	4428	3752	■	1260	305991	✓
Power LED - emergency 1h - 220-240 V 50/60 Hz												
34	I	-	80	4000	S/EW	-	6153	5215	■	1260	306000	✓
25	I	-	80	4000	S/EW	-	3261	2836	■	1260	305998	✓
25	I	-	80	4000	S/EW	-	4428	3752	■	1260	305999	✓



NORMA+ 150

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
76	I	-	80	4000	S/EW	-	12977	10998	■	1500	3122630	✓
50	I	-	80	4000	S/EW	-	8998	7625	■	1530	305954	✓



NORMA+ 150 CL

IP65 - IK09 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
76	I	-	80	4000	S/EW	-	12977	10998	■	1560	3122533	✓
59	I	-	80	4000	S/EW	-	10742	9104	■	1560	305947	✓
50	I	-	80	4000	S/EW	-	8998	7625	■	1560	305946	✓
29	I	-	80	4000	S/EW	-	5285	4295	■	1560	305945	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
76	I	-	80	4000	S/EW	-	12977	10998	■	1560	3122534	✓
59	I	-	80	4000	S/EW	-	10742	9104	■	1560	305995	✓
50	I	-	80	4000	S/EW	-	8768	7625	■	1560	305994	✓
29	I	-	80	4000	S/EW	-	5285	4295	■	1560	305993	✓
Power LED - emergency 1h - 220-240 V 50/60 Hz												
76	I	-	80	4000	S/EW	-	12977	10998	■	1560	3122535	✓
59	I	-	80	4000	S/EW	-	10742	9103	■	1560	306003	✓
50	I	-	80	4000	S/EW	-	8768	7625	■	1560	306002	✓
29	I	-	80	4000	S/EW	-	5285	4295	■	1560	306001	✓





Body shop K. Van Oudenaren - Zaandam - Netherlands

BLIZ



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Scan the QR-code for the latest information


- Series of ceiling, wall and post mounted luminaires for indoor et outdoor, comprising:
- Die-cast aluminium housing, ring and screen, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated
 - EPDM sealing gasket
 - Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
 - Stainless steel locking hardware




Residential Tower De Verkenner - Utrecht - Netherlands




BLIZ SQUARE 40



BLIZ SQUARE 40/G



BLIZ RING



BLIZ GUARD

BLIZ LED RING

IP65 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	14	I	-	80	4000	S/EW	-	1642	842	■	303413	✓
LED	14	I	-	80	3000	S/EW	-	1555	734	■	303412	✓
LED	14	I	-	80	4000	S/EW	-	1642	842	■	303415	✓
LED	14	I	-	80	3000	S/EW	-	1555	734	■	303414	✓



BLIZ RING

IP65 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	✓	-	-	S/EW	-	-	-	■	700192	✓
E27	60	I	✓	-	-	S/EW	-	-	-	■	700193	✓



BLIZ LED GUARD

IP65 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	14	I	-	80	4000	S/EW	-	1642	554	■	303417	✓
LED	14	I	-	80	3000	S/EW	-	1555	483	■	303416	✓
LED	14	I	-	80	4000	S/EW	-	1642	554	■	303419	✓
LED	14	I	-	80	3000	S/EW	-	1555	483	■	303418	✓



BLIZ GUARD


IP65 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	✓	-	-	S/EW	-	-	-	■	700195	✓
E27	60	I	✓	-	-	S/EW	-	-	-	■	700196	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
BLIZ			
Post Bliz 530 mm	■	315027	✓
Post Bliz 530 mm	■	315028	✓
Post Bliz 1030 mm	■	315025	✓
Post Bliz 1030 mm	■	315026	✓




Complete unit
1A+1B = please order 2 codes
2A+1B = please order 3 codes

COMPONENTS	
A	luminaire
B	pole



BLIZ MARINE



■ BR-10 / Natural brass / Glossy

Scan the QR-code for the latest information

Wall and ceiling mounted luminaire for indoor and outdoor, comprising:


- Die-cast corrosion resistant aluminium housing
- Die-cast marine brass guard/screen with mass finishing process ISO 9223 (CX)
- Pressed glass diffuser, internally coated
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- EPDM sealing gasket
- Stainless steel locking hardware
- Metals with natural finish surface may oxidise with age. To restore the original brightness use commercial metal polish



INSERT+ 1 MARINE



CRICKET+ 10 MARINE



BLIZ MARINE

BLIZ MARINE

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
13.5	I	-	80	4000	S/EW	-	1680	745	■	3100279	✓
13.5	I	-	80	3000	S/EW	-	1584	616	■	3100278	✓





L-FLAT - Laan Van Vollenhove - Zeist - Netherlands


BLIZ ROUND 30/40



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

- Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:
- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Through-wiring designed
 - 4000K and 3000K mid-power LED board
 - Built-in driver
 - Stainless steel locking hardware
 - Static ON/OFF or dimmable DALI options available
 - EM/3P version is designed for multipurpose 3 hours sustained emergency lighting





















BLIZ ROUND
30

BLIZ ROUND
40

BLIZ ROUND 30







IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	-	80	4000	S/EW	-	4539	2343		304215	✓
30	I	-	80	3000	S/EW	-	4236	2178		304212	✓
30	I	-	80	4000	S/EW	-	4539	2343		304216	✓
30	I	-	80	3000	S/EW	-	4236	2178		304213	✓
30	I	-	80	4000	S/EW	-	4539	2343		304217	✓
30	I	-	80	3000	S/EW	-	4236	2178		304214	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304245	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304242	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304246	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304243	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304247	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304244	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
30	I	-	80	4000	S/EW	-	4539	2343		304227	✓
30	I	-	80	3000	S/EW	-	4236	2178		304224	✓
30	I	-	80	4000	S/EW	-	4539	2343		304228	✓
30	I	-	80	3000	S/EW	-	4236	2178		304225	✓
30	I	-	80	4000	S/EW	-	4539	2343		304229	✓
30	I	-	80	3000	S/EW	-	4236	2178		304226	✓



BLIZ ROUND 30 EM/3P













IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
21.5	I	-	80	4000	S/EW	-	3229	1673		304239	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304236	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304240	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304237	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304241	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304238	✓



BLIZ ROUND 40







IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304257	✓
39	I	-	80	3000	S/EW	-	5798	2739		304254	✓
39	I	-	80	4000	S/EW	-	5998	2912		304258	✓
39	I	-	80	3000	S/EW	-	5798	2739		304255	✓
39	I	-	80	4000	S/EW	-	5998	2912		304259	✓
39	I	-	80	3000	S/EW	-	5798	2739		304256	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304269	✓
39	I	-	80	3000	S/EW	-	5798	2739		304266	✓
39	I	-	80	4000	S/EW	-	5998	2912		304270	✓
39	I	-	80	3000	S/EW	-	5798	2739		304267	✓
39	I	-	80	4000	S/EW	-	5998	2912		304271	✓
39	I	-	80	3000	S/EW	-	5798	2739		304268	✓



BLIZ ROUND 40 EM/3P

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304281	✓
39	I	-	80	3000	S/EW	-	5798	2739		304278	✓
39	I	-	80	4000	S/EW	-	5998	2912		304282	✓
39	I	-	80	3000	S/EW	-	5798	2739		304279	✓
39	I	-	80	4000	S/EW	-	5998	2912		304283	✓
39	I	-	80	3000	S/EW	-	5798	2739		304280	✓



BLIZ SQUARE 40



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

- Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:
- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Through-wiring designed
 - 4000K and 3000K mid-power LED board
 - Built-in driver
 - Stainless steel locking hardware
 - Static ON/OFF or dimmable DALI options available
 - EM/3P version is designed for multipurpose 3 hours sustained emergency lighting




Abessinio stadium - Wilmington - Delaware - USA



BLIZ



BLIZ POST















BLIZ SQUARE 40

BLIZ SQUARE 40 /G

BLIZ SQUARE 40







IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	6732	2495		304650	✓
39	I	-	80	3000	S/EW	-	6732	2515		304647	✓
39	I	-	80	4000	S/EW	-	6732	2495		304651	✓
39	I	-	80	3000	S/EW	-	6732	2515		304648	✓
39	I	-	80	4000	S/EW	-	6732	2495		304652	✓
39	I	-	80	3000	S/EW	-	6732	2515		304649	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	6732	2495		304662	✓
39	I	-	80	3000	S/EW	-	6732	2515		304659	✓
39	I	-	80	4000	S/EW	-	6732	2495		304663	✓
39	I	-	80	3000	S/EW	-	6732	2515		304660	✓
39	I	-	80	4000	S/EW	-	6732	2495		304664	✓
39	I	-	80	3000	S/EW	-	6732	2515		304661	✓



BLIZ SQUARE 40 EM/3P













IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	6732	2495		304668	✓
39	I	-	80	3000	S/EW	-	6732	2515		304665	✓
39	I	-	80	4000	S/EW	-	6732	2495		304669	✓
39	I	-	80	3000	S/EW	-	6732	2515		304666	✓
39	I	-	80	4000	S/EW	-	6732	2495		304670	✓
39	I	-	80	3000	S/EW	-	6732	2515		304667	✓



BLIZ SQUARE 40/G

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	6732	2495		304782	✓
39	I	-	80	3000	S/EW	-	6732	2515		304779	✓
39	I	-	80	4000	S/EW	-	6732	2495		304783	✓
39	I	-	80	3000	S/EW	-	6732	2515		304780	✓
39	I	-	80	4000	S/EW	-	6732	2495		304784	✓
39	I	-	80	3000	S/EW	-	6732	2515		304781	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	6732	2495		304788	✓
39	I	-	80	3000	S/EW	-	6732	2515		304785	✓
39	I	-	80	4000	S/EW	-	6732	2495		304789	✓
39	I	-	80	3000	S/EW	-	6732	2515		304786	✓
39	I	-	80	4000	S/EW	-	6732	2495		304790	✓
39	I	-	80	3000	S/EW	-	6732	2515		304787	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
BLIZ SQUARE 40 Polycarbonate diffusor		310255	✓



310255

EKO+19




Scan the QR-code for the latest information

- GR-20 / Metallic grey / Glossy
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Indoor and outdoor wall mounted luminaire, comprising:


- Die-cast aluminium housing, ring and screen, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Diffuser stays securely hinged to the frame
- Pressed glass diffuser, internally coated
- Aluminium reflector for E27 versions
- EPDM sealing gasket
- Built-in driver
- Stainless steel locking hardware
- No through wiring
- All versions are available with polycarbonate diffuser IK10 upon request
- Design by ROBERTO FIORATO



EKO+21



EKO+26









EKO+19

EKO+19
/G

EKO+19
GRILL

EKO+19 LED




IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	10	I	-	80	4000	S/EW	-	738	508		301382	✓
LED	10	I	-	80	3000	S/EW	-	672	479		3013826	✓
LED	10	I	-	80	4000	S/EW	-	738	508		301383	✓
LED	10	I	-	80	3000	S/EW	-	672	479		3013836	✓
LED	10	I	-	80	4000	S/EW	-	738	508		301381	✓
LED	10	I	-	80	3000	S/EW	-	672	479		3013816	✓



EKO+19







IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-		302011	✓
E27	60	I	-	-	-	S/EW	-	-	-		302012	✓
E27	60	I	-	-	-	S/EW	-	-	-		302010	✓



EKO+19/G LED




IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	10	I	-	80	4000	S/EW	-	738	235		301644	✓
LED	10	I	-	80	3000	S/EW	-	672	229		3016446	✓
LED	10	I	-	80	4000	S/EW	-	738	235		301645	✓
LED	10	I	-	80	3000	S/EW	-	672	229		3016456	✓
LED	10	I	-	80	4000	S/EW	-	738	235		301643	✓
LED	10	I	-	80	3000	S/EW	-	672	229		3016436	✓



EKO+19/G







IP66 - IK10

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-		302017	✓
E27	60	I	-	-	-	S/EW	-	-	-		302018	✓
E27	60	I	-	-	-	S/EW	-	-	-		302016	✓



EKO+19 GRILL LED




IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	10	I	-	80	4000	A/EW	-	738	248		301650	✓
LED	10	I	-	80	3000	A/EW	-	672	241		3016506	✓
LED	10	I	-	80	4000	A/EW	-	738	248		301651	✓
LED	10	I	-	80	3000	A/EW	-	672	241		3016516	✓
LED	10	I	-	80	4000	A/EW	-	738	248		301649	✓
LED	10	I	-	80	3000	A/EW	-	672	241		3016496	✓



EKO+19 GRILL

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	A/EW	-	-	-		302023	✓
E27	60	I	-	-	-	A/EW	-	-	-		302024	✓
E27	60	I	-	-	-	A/EW	-	-	-		302022	✓



EKO+21/26




Scan the QR-code for the latest information

- GR-20 / Metallic grey / Glossy
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Series of wall and ceiling mounted luminaire for indoor and outdoor, comprising::

- Die-cast aluminium housing, ring and screen, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Pressed glass diffuser, internally coated
- Diffuser stays securely hinged to the frame
- Aluminium reflector for E27 versions
- EPDM sealing gasket
- Stainless steel locking hardware
- No through wiring
- Tilting LED board for easy wiring during installation
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Hyper-frequency (HF) sensor operating at 5.8 Ghz+/- 75 Mhz
- Fully adjustable daylight sensor (5-1000 lux), timing sensor (10-300 s) and sensitivity sensor (20-100%)
- Widest detection field up to 8 m
- The integral sensor' protection module grants no reciprocal interference between multiple luminaires in one area
- Built-in driver
- All versions are available with polycarbonate diffuser IK10 upon request
- Design by ROBERTO FIORATO



EKO+21 LED

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11	I	-	80	4000	S/EW	-	1281	734	■	303476	✓
LED	11	I	-	80	3000	S/EW	-	1214	701	■	303478	✓
LED	11	I	-	80	4000	S/EW	-	1281	734	□	303477	✓
LED	11	I	-	80	3000	S/EW	-	1214	701	□	303479	✓



EKO+21

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-	■	302035	✓
E27	60	I	-	-	-	S/EW	-	-	-	■	302036	✓
E27	60	I	-	-	-	S/EW	-	-	-	□	302034	✓



EKO+21/G

IP66 - IK10

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-	■	302044	✓
E27	60	I	-	-	-	S/EW	-	-	-	■	302045	✓
E27	60	I	-	-	-	S/EW	-	-	-	□	302043	✓



EKO+21 GRILL

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	40	I	-	-	-	A/EW	-	-	-	■	302053	✓
E27	40	I	-	-	-	A/EW	-	-	-	■	302054	✓
E27	40	I	-	-	-	A/EW	-	-	-	□	302052	✓



EKO+26 LED

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16	I	-	80	4000	S/EW	-	2447	1245	■	302631	✓
LED	16	I	-	80	3000	S/EW	-	2226	1161	■	302633	✓
LED	16	I	-	80	4000	S/EW	-	2447	1245	□	302632	✓
LED	16	I	-	80	3000	S/EW	-	2226	1161	□	302634	✓



EKO+26

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	I	-	-	-	S/EW	-	-	-	■	302062	✓
E27	100	I	-	-	-	S/EW	-	-	-	■	302063	✓
E27	100	I	-	-	-	S/EW	-	-	-	□	302061	✓



EKO+26 LED DETEK HF

IP66 - IK07

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16	I	-	80	4000	S/EW	-	2447	1245	■	303638	✓
LED	16	I	-	80	3000	S/EW	-	2226	1161	■	303636	✓
LED	16	I	-	80	4000	S/EW	-	2447	1245	□	303637	✓
LED	16	I	-	80	3000	S/EW	-	2226	1161	□	303635	✓



EKO+26/G

IP66 - IK10

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	I	-	-	-	S/EW	-	-	-	■	302074	✓
E27	100	I	-	-	-	S/EW	-	-	-	■	302075	✓
E27	100	I	-	-	-	S/EW	-	-	-	□	302073	✓





LANTERNA NK 21/27



Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- RB-10 / Rust / Textured

- Series of wall mounted luminaires in two sizes for indoor and outdoor, comprising:
- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated, secured with the ring
 - Transparent, pressed glass diffuser (E27 versions)
 - Aluminium reflector and gear tray
 - Technopolymer silicone sealing gasket
 - Burnished stainless steel fixing screws
 - Built-in driver
 - Design by ROBERTO FIORATO



LANTERNA NK
21

LANTERNA NK
27

LANTERNA NK 21

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11	I	-	80	4000	S/EW	-	1282	755	■	3102570	✓
LED	11	I	-	80	3000	S/EW	-	1242	730	■	3102569	✓
LED	11	I	-	80	4000	S/EW	-	1282	755	■	3102572	✓
LED	11	I	-	80	3000	S/EW	-	1242	730	■	3102571	✓



LANTERNA NK 27

IP65 - IK08

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	I	-	-	-	-	-	-	-	■	3102163	✓
E27	100	I	-	-	-	-	-	-	-	■	3102164	✓
Power LED 220-240 V 50/60 Hz												
LED	15	I	-	80	4000	S/EW	-	1697	1020	■	3102566	✓
LED	15	I	-	80	3000	S/EW	-	1644	990	■	3102564	✓
LED	15	I	-	80	4000	S/EW	-	1697	1020	■	3102568	✓
LED	15	I	-	80	3000	S/EW	-	1644	990	■	3102567	✓




NIKKO+21/27




- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Scan the QR-code for the latest information

- Wall and post mounted luminaire in two sizes for indoor and outdoor, comprising:
- Die-cast aluminium housing, ring and screen, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated, secured with the ring
 - Aluminium reflector and gear tray
 - Technopolymer silicone sealing gasket
 - Stainless steel locking hardware
 - Design by ROBERTO FIORATO



Apartment building De Boel - Amsterdam - Netherlands



NIKKO+21 LED

IP65 - IK05

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	10	I	-	80	4000	S/EW	-	1282	745	■	301410	✓
LED	10	I	-	80	3000	S/EW	-	1242	699	■	3014106	✓
LED	10	I	-	80	4000	S/EW	-	1282	745	■	301411	✓
LED	10	I	-	80	3000	S/EW	-	1242	699	■	3014116	✓



NIKKO+21

IP65 - IK05

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-	■	002001	✓
E27	60	I	-	-	-	S/EW	-	-	-	■	002002	✓



NIKKO+21/G LED

IP65 - IK05

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	10	I	-	80	4000	S/EW	-	1282	408	■	301656	✓
LED	10	I	-	80	3000	S/EW	-	1242	381	■	3016566	✓
LED	10	I	-	80	4000	S/EW	-	1282	408	■	301657	✓
LED	10	I	-	80	3000	S/EW	-	1242	381	■	3016576	✓



NIKKO+21/G

IP65 - IK05

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	I	-	-	-	S/EW	-	-	-	■	002011	✓
E27	60	I	-	-	-	S/EW	-	-	-	■	002012	✓



NIKKO+27 LED

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	13.5	I	-	80	4000	S/EW	-	1697	928	■	301414	✓
LED	13.5	I	-	80	3000	S/EW	-	1644	909	■	3014146	✓
LED	13.5	I	-	80	4000	S/EW	-	1697	928	■	301415	✓
LED	13.5	I	-	80	3000	S/EW	-	1644	909	■	3014156	✓



NIKKO+27

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	I	-	-	-	S/EW	-	-	-	■	002031	✓
E27	100	I	-	-	-	S/EW	-	-	-	■	002032	✓



NIKKO+27/G LED

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	13.5	I	-	80	4000	S/EW	-	1697	474	■	301664	✓
LED	13.5	I	-	80	3000	S/EW	-	1644	464	■	3016646	✓
LED	13.5	I	-	80	4000	S/EW	-	1697	474	■	301665	✓
LED	13.5	I	-	80	3000	S/EW	-	1644	464	■	3016656	✓



NIKKO+27/G

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	I	-	-	-	S/EW	-	-	-	■	002046	✓
E27	100	I	-	-	-	S/EW	-	-	-	■	002047	✓



Optional accessories





Bracket suitable for single or twin (back to back) luminaire mounting, comprising:

- Support in painted extruded aluminium
- Wall mounting bracket with simple fix installation system, in painted die-cast aluminium

Post comprising:

- Painted extruded aluminium post, suitable for single or twin (back to back) luminaire mounting.
- Painted die-cast aluminium base plate
- Die-cast aluminium junction box with a 4-pole 4 mm² terminal suitable for loop in wiring connection.

DESCRIPTION	COLOR	PART NUMBER	UKCA
NIKKO+21			
Wall bracket 21	■	000401	✓
Wall bracket 21	■	000402	✓
Post 21 235 mm	■	000405	✓
Post 21 235 mm	■	000406	✓
Post 21 583 mm	■	000410	✓
Post 21 583 mm	■	000409	✓
NIKKO+27			
Wall bracket 27	■	000421	✓
Wall bracket 27	■	000422	✓
Post 27 297 mm	■	000425	✓
Post 27 297 mm	■	000426	✓
Post 27 833 mm	■	000429	✓
Post 27 833 mm	■	000430	✓



NIKKO+45




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured

Wall and post mounted luminaire, for indoor and outdoor, comprising:

- Die-cast aluminium housing, ring and screen, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Pressed glass diffuser, internally coated, secured with the ring
- Aluminium reflector and gear tray
- Technopolymer silicone sealing gasket
- Stainless steel locking hardware
- DA versions are dual power switch versions, designed with two drivers in parallel. Requires two separate lines
- Design by ROBERTO FIORATO



NIKKO+45 LED DA

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	7.5 + 7.5	I	-	80	4000	S/EW	-	1540	1013	■	303115	✓
LED	7.5 + 7.5	I	-	80	3000	S/EW	-	1086	843	■	303103	✓
LED	7.5 + 7.5	I	-	80	4000	S/EW	-	1540	1013	■	303116	✓
LED	7.5 + 7.5	I	-	80	3000	S/EW	-	1086	843	■	303104	✓



NIKKO+45

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	40	I	-	-	-	S/EW	-	-	-	■	002076	✓
E27	40	I	-	-	-	S/EW	-	-	-	■	002077	✓



NIKKO+45/G LED DA

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	7.5 + 7.5	I	-	80	4000	S/EW	-	1540	766	■	303119	✓
LED	7.5 + 7.5	I	-	80	3000	S/EW	-	1086	641	■	303107	✓
LED	7.5 + 7.5	I	-	80	4000	S/EW	-	1540	766	■	303120	✓
LED	7.5 + 7.5	I	-	80	3000	S/EW	-	1086	641	■	303108	✓



NIKKO+45/G

IP65 - IK06

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	40	I	-	-	-	S/EW	-	-	-	■	002097	✓
E27	40	I	-	-	-	S/EW	-	-	-	■	002098	✓



Optional accessories

Bracket suitable for single or twin (back to back) luminaire mounting, comprising:
 → Support in painted extruded aluminium
 → Wall mounting bracket with simple fix installation system, in painted die-cast aluminium


Post comprising:
 → Painted extruded aluminium post, suitable for single or twin (back to back) luminaire mounting.
 → Painted die-cast aluminium base plate
 → Die-cast aluminium junction box with a 4-pole 4 mm² terminal suitable for loop in wiring connection.

DESCRIPTION	COLOR	PART NUMBER	UKCA
NIKKO+45			
Wall bracket 45	■	000441	✓
Wall bracket 45	■	000442	✓
Post 45 444 mm	■	000445	✓
Post 45 444 mm	■	000446	✓
Post 45 833 mm	■	000449	✓
Post 45 833 mm	■	000450	✓
Post 45 1233 mm	■	000453	✓
Post 45 1233 mm	■	000454	✓




Complete unit
 1A+1B = please order 2 codes
 2A+1B = please order 3 codes

COMPONENTS	
A	luminaire
B	bracket





Complete unit
 1A+1B = please order 2 codes
 2A+1B = please order 3 codes

COMPONENTS	
A	luminaire
B	pole



CHIP OVALE



- BK-81 / Black / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information

Series of ceiling, wall, bracket and post mounted luminaires for indoor and outdoor, comprising:


- Technopolymer housing, trim or screen
- Pressed glass diffuser, internally coated
- Aluminium reflector for E27 versions
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel locking hardware
- Built-in driver
- Side entry for 20 mm conduits (drill out holes in housing arrangement)
- Anti-tampering screws available upon request
- Design by ROBERTO FIORATO



Stockholm Airport - Stockholm - Sweden



CHIP TONDO



CHIP OVALE
25

CHIP OVALE
25

CHIP OVALE
30

CHIP OVALE
30

CHIP OVALE 25 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	6.5	I	-	80	4000	S/EW	-	930	485	■	3100140	✓
LED	6.5	I	-	80	3000	S/EW	-	868	455	■	3100139	✓
LED	6.5	I	-	80	4000	S/EW	-	930	485	□	3100136	✓
LED	6.5	I	-	80	3000	S/EW	-	868	455	□	3100135	✓



CHIP OVALE 25

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	21	II	-	-	-	S/EW	-	-	-	■	005702	✓
E27	21	II	-	-	-	S/EW	-	-	-	□	005700	✓



CHIP OVALE 25 LED GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	6.5	I	-	80	4000	A/EW	-	930	354	■	3100146	✓
LED	6.5	I	-	80	3000	A/EW	-	868	332	■	3100145	✓
LED	6.5	I	-	80	4000	A/EW	-	930	354	□	3100142	✓
LED	6.5	I	-	80	3000	A/EW	-	868	332	□	3100141	✓



CHIP OVALE 25 GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	21	II	-	-	-	A/EW	-	-	-	■	005707	✓
E27	21	II	-	-	-	A/EW	-	-	-	□	005706	✓



CHIP OVALE 30 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	S/EW	-	1860	1059	■	3100152	✓
LED	11.5	I	-	80	3000	S/EW	-	1736	994	■	3100151	✓
LED	11.5	I	-	80	4000	S/EW	-	1860	1059	□	3100148	✓
LED	11.5	I	-	80	3000	S/EW	-	1736	994	□	3100147	✓



CHIP OVALE 30

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	30	II	-	-	-	S/EW	-	-	-	■	005782	✓
E27	30	II	-	-	-	S/EW	-	-	-	□	005780	✓



CHIP OVALE 30 LED GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	A/EW	-	1860	766	■	3100158	✓
LED	11.5	I	-	80	3000	A/EW	-	1736	718	■	3100157	✓
LED	11.5	I	-	80	4000	A/EW	-	1860	766	□	3100154	✓
LED	11.5	I	-	80	3000	A/EW	-	1736	718	□	3100153	✓



CHIP OVALE 30 GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	30	II	-	-	-	A/EW	-	-	-	■	005787	✓
E27	30	II	-	-	-	A/EW	-	-	-	□	005786	✓



Optional accessories

CHIP OVALE 25 Brackets

Technopolymer range of accessories suitable for wall and post mounting the Chip Ovale 25 only.

Suitable for single or twin (back to back) luminaire mounting either vertically or on a 40° angled position. To ensure correct drainage a 6mm hole should be drilled on the lower part of the trim (please refer to installation and maintenance instruction sheet).

The accessories for post mount are suitable for either standard Ø 60 mm posts or Ø 42 mm posts.



DESCRIPTION	COLOR	PART NUMBER	UKCA
CHIP OVALE 25			
Corner bracket (vertical mount)	■	000790	✓
Corner bracket(angled mount)	■	000792	✓
Angled bracket 40°	■	000502	✓
Angled bracket for 42 mm post	■	000800	✓
Angled bracket for Ø 60 mm post	■	000802	✓
Twin angled bracket for 60 mm post	■	000810	✓



Complete unit

1A+1B = please order 2 codes

COMPONENTS
A luminaire
B bracket




Complete unit

1A+1B = please order 2 codes


2A+1B = please order 3 codes

COMPONENTS
A luminaire
B bracket



000800 Ø 42 **000810** Ø 60
000802 Ø 60

CHIP TONDO




Scan the QR-code for the latest information


- BK-81 / Black / Textured
- WH-87 / White / Textured

Series of wall, ceiling and post mounted luminaires in two dimensions for indoor and outdoor, comprising:


- Technopolymer housing, trim or screen
- Pressed glass diffuser, internally coated
- Aluminium reflector for E27 versions
- Technopolymer reflector for fluorescent versions
- Anti-ageing custom moulded silicone sealing gasket(s)
- Side entry for 20 mm conduits (drill out holes in housing arrangement)
- Anti-tampering screws available upon request
- Built-in driver
- Design by ROBERTO FIORATO




CHIP OVALE




CHIP TONDO
25



CHIP TONDO
25



CHIP TONDO
30



CHIP TONDO
30

CHIP TONDO 25 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	S/EW	-	1281	712	■	3100164	✓
LED	11.5	I	-	80	3000	S/EW	-	1214	690	■	3100163	✓
LED	11.5	I	-	80	4000	S/EW	-	1281	712	□	3100160	✓
LED	11.5	I	-	80	3000	S/EW	-	1214	690	□	3100159	✓



CHIP TONDO 25

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	21	II	-	-	-	S/EW	-	-	-	■	005742	✓
E27	21	II	-	-	-	S/EW	-	-	-	□	005740	✓



CHIP TONDO 25 LED GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	A/EW	-	1281	512	■	3100170	✓
LED	11.5	I	-	80	3000	A/EW	-	1214	486	■	3100169	✓
LED	11.5	I	-	80	4000	A/EW	-	1281	512	□	3100166	✓
LED	11.5	I	-	80	3000	A/EW	-	1214	486	□	3100165	✓



CHIP TONDO 25 GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	21	II	-	-	-	A/EW	-	-	-	■	005747	✓
E27	21	II	-	-	-	A/EW	-	-	-	□	005746	✓



CHIP TONDO 30 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16.5	I	-	80	4000	S/EW	-	2447	1305	■	3100176	✓
LED	16.5	I	-	80	3000	S/EW	-	2226	1229	■	3100175	✓
LED	16.5	I	-	80	4000	S/EW	-	2447	1305	□	3100172	✓
LED	16.5	I	-	80	3000	S/EW	-	2226	1229	□	3100171	✓



CHIP TONDO 30

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	30	II	-	-	-	S/EW	-	-	-	■	005823	✓
E27	30	II	-	-	-	S/EW	-	-	-	□	005821	✓



CHIP TONDO 30 LED GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16.5	I	-	80	4000	A/EW	-	2447	905	■	3100182	✓
LED	16.5	I	-	80	3000	A/EW	-	2226	852	■	3100181	✓
LED	16.5	I	-	80	4000	A/EW	-	2447	905	□	3100178	✓
LED	16.5	I	-	80	3000	A/EW	-	2226	852	□	3100177	✓



CHIP TONDO 30 GRILL

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	30	II	-	-	-	S/EW	-	-	-	■	005828	✓
E27	30	II	-	-	-	S/EW	-	-	-	□	005827	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
CHIP TONDO			
Double Post	■	000500	✓






Complete unit
 1A+1B = please order 2 codes
 2A+1B = please order 3 codes

COMPONENTS	
A	luminaire
B	pole



CLY




□ WH-87 / White / Matt



Scan the QR-code for the latest information

Wall and ceiling mounted luminaire for indoor and outdoor, comprising:

- Technopolymer housing, trim and diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Class II
- Tilting easy-maintenance SMD LED board
- Dip switch for LED CCT control at 3000K or 4000K, field adjustable
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Hyper-frequency (HF) sensor operating at 5.8 Ghz +/- 75 Mhz
- The DLS+DETEK versions are supplied with an electronic device complete with a High Frequency sensor and a daylight sensor (DLS). This is programmed to switch the device on automatically when natural light is low, ensuring constant secure lighting at 30% of the luminous flow and reaching 100% of the flow when any presence is detected
- The luminous flux data shown refer to the maximum power operating level



CLY



OFF
0%

ON - DLS+DETEK
30%

ON - DLS+DETEK
100%

CLY

IP65 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
17	II	-	80	3000 4000	S/EW	-	2534	1695	□	3116565	✓



CLY DLS+DETEK

IP65 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + HF Sensor											
17	II	-	80	3000 4000	S/EW	-	2534	1695	□	3116566	✓



CLY EM/3P

IP65 - IK10 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
17	II	-	80	3000 4000	S/EW	-	2534	1695	□	3116567	✓



CLY EM/3P+DLS+DETEK

IP65 - IK10 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz + HF Sensor											
17	II	-	80	3000 4000	S/EW	-	2534	1695	□	3116568	✓




DROP 20/25



Scan the QR-code for the latest information

WH-87 / White / Textured

- Series of wall and ceiling mounted luminaire for indoor and outdoor, comprising:
- Technopolymer housing
 - Satin pressed glass diffuser, internally coated, for homogeneous light distribution
 - Aluminium reflector (incandescent version only)
 - Easy opening diffuser
 - Side cable entry
 - Design by ROBERTO FIORATO



DROP 20

IP43 - IK08 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	II	-	-	-	S/EW	-	-	-	<input type="checkbox"/>	005000	✓



DROP 25

IP43 - IK08 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	II	-	-	-	S/EW	-	-	-	<input type="checkbox"/>	005010	✓





DROP 22/28




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured

- Series of wall and ceiling mounted luminaire for indoor and outdoor, comprising::
- Satin pressed glass diffuser, internally coated, for homogeneous light distribution
 - Technopolymer housing
 - Aluminium reflector
 - Technopolymer silicone sealing gasket
 - Chromed steel spring locks to secure the diffuser to housing
 - Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
 - Toolless glass diffuser opening: quick to install and easy to maintain, helping to save time and reduce servicing costs
 - Hyper-frequency (HF) sensor operating at 5.8 Ghz+/- 75 Mhz
 - The integral sensor protection module grants no reciprocal interference between multiple luminaires in one area
 - Widest detection field up to 8 m
 - Side entry for 20 mm conduits (drill out holes in housing arrangement)
 - Self-adhesive pictograms available as accessory (ordered separately)
 - Design by ROBERTO FIORATO



DROP 22



DROP 28

DROP 22 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	11	II	-	80	3000	S/EW	-	1214	758	■	303472	✓
LED	11	II	-	80	3000	S/EW	-	1214	758	■	303474	✓
LED	11	II	-	80	4000	S/EW	-	1281	816	■	3109455	✓
LED	11	II	-	80	3000	S/EW	-	1214	758	■	3109456	✓
LED	11	II	-	80	4000	S/EW	-	1281	816	□	303066	✓
LED	11	II	-	80	3000	S/EW	-	1214	758	□	303065	✓



DROP 22

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	II	-	-	-	S/EW	-	-	-	■	004962	✓
E27	60	II	-	-	-	S/EW	-	-	-	■	004960	✓
E27	60	II	-	-	-	S/EW	-	-	-	□	004961	✓



DROP 28 LED HF

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16	II	-	80	4000	S/EW	-	2447	1382	□	303632	✓
LED	16	II	-	80	3000	S/EW	-	2226	1336	□	303629	✓



DROP 28 LED

IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	16	II	-	80	3000	S/EW	-	2226	1336	■	303468	✓
LED	16	II	-	80	3000	S/EW	-	2226	1336	■	303470	✓
LED	16	II	-	80	4000	S/EW	-	2447	1382	■	3109457	✓
LED	16	II	-	80	3000	S/EW	-	2226	1336	■	3109458	✓
LED	16	II	-	80	4000	S/EW	-	2447	1382	□	303064	✓
LED	16	II	-	80	3000	S/EW	-	2226	1336	□	303063	✓



DROP 28


IP55 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
E27	100	II	-	-	-	S/EW	-	-	-	■	004972	✓
E27	100	II	-	-	-	S/EW	-	-	-	■	004970	✓
E27	100	II	-	-	-	S/EW	-	-	-	□	004951	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
DROP 22			
Arrow		008342	✓
Extinguisher		008343	✓
Man		008344	✓
Woman		008345	✓
Disabled		008346	✓
Toilet		008347	✓
DROP 28			
Right		008350	✓
Left		008351	✓
Up/Right		008352	✓
Up/Left		008353	✓
Down/Right		008354	✓
Down/Left		008355	✓
Arrow		008356	✓
Exit		008357	✓



EKO 19




Scan the QR-code for the latest information


- BK-81 / Black / Textured
- WH-87 / White / Textured

Indoor and outdoor wall mounted luminaire, comprising:


- Technopolymer housing, trim or screen
- Pressed glass diffuser, internally coated
- Aluminium reflector for E27 versions
- Stainless steel locking hardware
- Anti-tampering locking kit available as accessory
- All versions are available with polycarbonate diffuser IK10 upon request
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Built-in driver
- Design by ROBERTO FIORATO



EKO 21/26



EKO 19



EKO 19
GRILL

EKO 19

IP44 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	15	II	-	-	-	S/EW	-	-	-	■	300255	✓
E27	15	II	-	-	-	S/EW	-	-	-	□	300254	✓
Power LED 220-240 V 50/60 Hz												
LED	6.5	I	-	80	4000	S/EW	-	930	649	■	3100201	✓
LED	6.5	I	-	80	3000	S/EW	-	868	609	■	3100200	✓
LED	6.5	I	-	80	4000	S/EW	-	930	649	□	3100195	✓
LED	6.5	I	-	80	3000	S/EW	-	868	609	□	3100194	✓



EKO 19 GRILL

IP44 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	15	II	-	-	-	A/EW	-	-	-	■	300275	✓
E27	15	II	-	-	-	A/EW	-	-	-	□	300274	✓
Power LED 220-240 V 50/60 Hz												
LED	6.5	I	-	80	4000	A/EW	-	930	460	■	3100209	✓
LED	6.5	I	-	80	3000	A/EW	-	868	432	■	3100208	✓
LED	6.5	I	-	80	4000	A/EW	-	930	460	□	3100203	✓
LED	6.5	I	-	80	3000	A/EW	-	868	432	□	3100202	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
EKO 19			
Anti-tamper		310176	✓
Anti-tamper		310177	✓
Diffuser pc EKO 19		310310	✓



310176



310177



310310

EKO 21/26




- BK-81 / Black / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information


- Series of wall and ceiling mounted luminaire for indoor and outdoor, comprising:
- Technopolymer housing, ring and screen
 - Pressed glass diffuser, internally coated
 - Aluminium reflector for E27 versions
 - Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
 - Built-in driver
 - Stainless steel locking hardware
 - Anti-tampering locking kit available as accessory
 - All versions are available with polycarbonate diffuser IK10 upon request
 - Design by ROBERTO FIORATO




EKO 19



EKO 21



EKO 21 GRILL



EKO 26

EKO 21

IP44 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	15	II	-	-	-	S/EW	-	-	-	■	300455	✓
E27	15	II	-	-	-	S/EW	-	-	-	□	300454	✓
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	S/EW	-	1281	1086	■	3100217	✓
LED	11.5	I	-	80	3000	S/EW	-	1214	1029	■	3100216	✓
LED	11.5	I	-	80	4000	S/EW	-	1281	1086	□	3100211	✓
LED	11.5	I	-	80	3000	S/EW	-	1214	1029	□	3100210	✓



EKO 21 GRILL

IP44 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	15	II	-	-	-	A/EW	-	-	-	■	300485	✓
E27	15	II	-	-	-	A/EW	-	-	-	□	300484	✓
Power LED 220-240 V 50/60 Hz												
LED	11.5	I	-	80	4000	A/EW	-	1281	756	■	3100225	✓
LED	11.5	I	-	80	3000	A/EW	-	1214	716	■	3100224	✓
LED	11.5	I	-	80	4000	A/EW	-	1281	756	□	3100219	✓
LED	11.5	I	-	80	3000	A/EW	-	1214	716	□	3100218	✓



EKO 26

IP44 - IK06 - 750 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	23	II	-	-	-	S/EW	-	-	-	■	300335	✓
E27	23	II	-	-	-	S/EW	-	-	-	□	300334	✓
Power LED 220-240 V 50/60 Hz												
LED	16.5	I	-	80	4000	S/EW	-	2447	1234	■	3100233	✓
LED	16.5	I	-	80	3000	S/EW	-	2226	1181	■	3100232	✓
LED	16.5	I	-	80	4000	S/EW	-	2447	1234	□	3100227	✓
LED	16.5	I	-	80	3000	S/EW	-	2226	1181	□	3100226	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
EKO 21/26			
Anti-tamper		310176	✓
Anti-tamper		310177	✓
EKO 26			
Diffuser PC EKO 26		310312	✓



310176




310177



310312

ELIA EL





Scan the QR-code for the latest information

- BK-RAL9005 / Black RAL9005 /
- WH-RAL9016 / White RAL9016 /

Die-cast aluminum LED luminaire for ceiling or wall mounting, ideal for the lighting of exteriors and interiors such as: stairs, passageways, service rooms, simple and quick to install, with a clean line and essential

- Designed in two different finishes (black and white), with opal diffuser in polycarbonate, color temperatures 3.000K, 4.000 K and 5.700 K and color rendering index higher than 80
- It has been designed to withstand temperature variations from -20 ° C to + 50 ° C, water and dust penetration up to IP65 degree and shocks up to IK08 degree
- Lightweight and handy ELIA EL is easy to install thanks to the quick connection terminal for the electrical wiring placed in the rear part and to the second cable outlet for pass-through wiring



ELIA EL


ELIA EL

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	-	80	5700	OPAL	-	-	1700.0	■	GWF2200LA857	✓
18	I	-	80	4000	OPAL	-	-	1650.0	■	GWF2200LA840	✓
18	I	-	80	3000	OPAL	-	-	1500.0	■	GWF2200LA830	✓
18	I	-	80	5700	OPAL	-	-	1700.0	□	GWF2210LA857	✓
18	I	-	80	4000	OPAL	-	-	1650.0	□	GWF2210LA840	✓
18	I	-	80	3000	OPAL	-	-	1500.0	□	GWF2210LA830	✓



EXTRO




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information

Multifunctional lighting device for residential and urban areas with body made in PC:

- Also available in 13W and 26W LED versions
- Sandblasted glass diffuser
- Possibility of wall, ceiling, pole and column mounting



EXTRO

EXTRO LED

IP55 - IK09 - 850 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
LED	26	I	-	90	4000	OPAL	-	-	1950	■	GWS2402	✓
LED	26	I	-	90	3000	OPAL	-	-	1850	■	GWS240230K	✓
LED	13	I	-	90	4000	OPAL	-	-	1000	■	GWS2401	✓
LED	13	I	-	90	3000	OPAL	-	-	950	■	GWS240130K	✓



EXTRO E27

IP55 - IK09 - 850 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27 220-240 V 50/60 Hz												
E27	-	I	-	-	-	OPAL	-	-	-	■	GW82206	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
EXTRO			
Swivel bracket		GW82290	✓
Angle bracket		GW82291	✓
Pole mounting single swivel bracket		GW82298	✓
Pole mounting double swivel bracket		GW82299	✓
Rectangular base for support column		GW82297	✓
Pole for single device h = 1300 mm		GW82292	✓
Replacement glass		GW88272	✓



GW82290

GW82291

GW82298



GW82299

GW82297

GW82292




GW88272

MULTI+ 30 PC



Primary school Het Epos - Rotterdam - Netherlands




- BK-81 / Black / Textured
- WH-87 / White / Textured


Scan the QR-code for the latest information

Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:

- Technopolymer housing
- Technopolymer vandal-proof opal diffuser, 960°C glow wire test rated
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel, anti-tampering locking screws
- Through-wiring designed
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Class II
- Built-in driver
- Max 20 mm diameter for cable/conduit entry
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Hyper-frequency (HF) sensor operating at 5.8 Ghz +/- 75 Mhz
- SMART versions are equipped with customised electronic devices that allow energy savings reducing the luminous flux, whilst providing a 30% working flux for safety lighting and reaching 100% flux when necessary
- SMART HF versions are complete with integrated High Frequency (HF) sensor that operates from 30% up to 100% of the flux when it detects the presence of people
- SMART DA versions are suitable for use in systems with two separate lines where the demand for 100% of the flux is managed by a push button or line sensor



MULTI+ 30 PC



OFF
0%

ON - SMART
30%

ON - SMART
100%

MULTI+ 30 PC

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	■	30416190101	✓
16	II	-	80	3000	S/EW	-	2226	1270	■	30416090101	✓
16	II	-	80	4000	S/EW	-	2447	1292	□	304161	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304160	✓
9.5	II	-	80	4000	S/EW	-	1613	793	□	304175	✓
9.5	II	-	80	3000	S/EW	-	1478	783	□	304174	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	□	304165	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304164	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	□	304163	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304162	✓



MULTI+ 30 PC SMART HF

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	□	304207	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304206	✓



MULTI+ 30 PC HF

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	■	30416990100	✓
16	II	-	80	3000	S/EW	-	2226	1270	■	30416890100	✓
16	II	-	80	4000	S/EW	-	2447	1292	□	304169	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304168	✓



MULTI+ 30 PC SMART DA

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
16	II	-	80	4000	S/EW	-	2447	1292	□	304205	✓
16	II	-	80	3000	S/EW	-	2226	1270	□	304204	✓



MULTI+ 30 PC EM/3P

IP65 - IK10 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
9.5	II	-	80	4000	S/EW	-	1613	793	■	30417390100	✓
9.5	II	-	80	3000	S/EW	-	1478	783	■	30417290100	✓
9.5	II	-	80	4000	S/EW	-	1613	793	□	304173	✓
9.5	II	-	80	3000	S/EW	-	1478	783	□	304172	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
MULTI+ 30 PC			
Tool TORX		310514	✓



310514

MULTI+ 40 PC



WH-87 / White / Textured


Scan the QR-code for the latest information

Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:


- Technopolymer housing
- Technopolymer vandal-proof opal diffuser, 960°C glow wire test rated
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel, anti-tampering locking screws
- Through-wiring designed
- Class II
- Built-in driver
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Max 20 mm diameter for cable/conduit entry
- Hyper-frequency (HF) sensor operating at 5.8 Ghz +/- 75 Mhz
- SMART versions are equipped with customised electronic devices that allow energy savings reducing the luminous flux, whilst providing a 30% working flux for safety lighting and reaching 100% flux when necessary
- SMART HF versions are complete with integrated High Frequency (HF) sensor that operates from 30% up to 100% of the flux when it detects the presence of people
- SMART DA versions are suitable for use in systems with two separate lines where the demand for 100% of the flux is managed by a push button or line sensor



Residential building de Bever - Heerhugowaard - Netherlands



MULTI+ 40 PC



OFF
0%

ON - SMART
30%

ON - SMART
100%

MULTI+ 40 PC

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304127	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304126	✓
19.5	II	-	80	4000	S/EW	-	3121	1502	<input type="checkbox"/>	304141	✓
19.5	II	-	80	3000	S/EW	-	3017	1464	<input type="checkbox"/>	304140	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304131	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304130	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304129	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304128	✓



MULTI+ 40 PC SMART HF

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304211	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304210	✓



MULTI+ 40 PC HF

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304135	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304134	✓



MULTI+ 40 PC SMART DA

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	-	80	4000	S/EW	-	4284	2278	<input type="checkbox"/>	304209	✓
27	II	-	80	3000	S/EW	-	4141	2146	<input type="checkbox"/>	304208	✓



MULTI+ 40 PC EM/3P

IP65 - IK10 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
19.5	II	-	80	4000	S/EW	-	3121	1502	<input type="checkbox"/>	304139	✓
19.5	II	-	80	3000	S/EW	-	3017	1464	<input type="checkbox"/>	304138	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
MULTI+ 40 PC			
Tool TORX		310514	✓



310514

MULTI+ 35




- BK-81 / Black / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information

Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:

- Technopolymer housing
- Technopolymer vandal-proof opal diffuser, 960°C glow wire test rated
- Anti-ageing custom moulded silicone sealing gasket(s)
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Stainless steel, anti-tampering locking screws
- Through-wiring designed
- Class II
- Max 20 mm diameter for cable/conduit entry
- EM/1P are maintained emergency versions (1h)
- Twilight models (C versions) are complete with dusk sensor



MULTI+ 35

MULTI+ 35

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10.5	II	-	80	4000	S/EW	-	1479	763	■	3109461	✓
10.5	II	-	80	3000	S/EW	-	1377	724	■	3109460	✓
10.5	II	-	80	4000	S/EW	-	1479	763	□	306142	✓
10.5	II	-	80	3000	S/EW	-	1377	724	□	306139	✓
6	II	-	80	4000	S/EW	-	612	448	■	3108201	✓
6	II	-	80	3000	S/EW	-	576	417	■	3109459	✓
6	II	-	80	4000	S/EW	-	612	448	□	306706	✓
6	II	-	80	3000	S/EW	-	576	417	□	306705	✓



MULTI+ 35/C

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
10.5	II	-	80	4000	S/EW	-	1479	763	□	306143	✓
10.5	II	-	80	3000	S/EW	-	1377	724	□	306140	✓
6	II	-	80	4000	S/EW	-	612	448	□	3100038	✓
6	II	-	80	3000	S/EW	-	576	417	□	3100037	✓



MULTI+ 35 EM/1P

IP65 - IK10 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 1P 220-240 V 50/60 Hz											
10.5	II	-	80	4000	S/EW	-	1479	763	□	306144	✓
10.5	II	-	80	3000	S/EW	-	1377	724	□	306141	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
MULTI+ 35			
Tool TORX		310514	✓



310514

SUPERDELTA TONDO



Scan the QR-code for the latest information


- BK-81 / Black / Textured
- IVORY-10 / Ivory / Textured

- Wall, ceiling and post mounted luminaire for indoor and outdoor, comprising:
- Technopolymer housing and ring
 - Pressed glass diffuser, internally coated, or polycarbonate opal diffuser
 - Aluminium reflector for E27 versions
 - Foam polymer sealing gasket
 - Built-in driver
 - Stainless steel locking hardware
 - Design by ROBERTO FIORATO

SUPERDELTA TONDO

IP54 - IK08 - 960 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	75	II	-	-	-	S/EW	-	-	-	■	001724	✓
E27	75	II	-	-	-	S/EW	-	-	-	■	001720	✓







SUPERDELTA TONDO

Optional accessories

- Post suitable for single or twin (back to back) luminaire mounting, comprising:
- Two painted extruded aluminium uprights
 - Painted aluminium connecting flange
 - Technopolymer shank connector acts as a junction box with 4-pole 16 mm² terminal


DESCRIPTION	COLOR	PART NUMBER	UKCA
SUPERDELTA TONDO			
Bracket		008943	✓
Double Post	■	000500	✓





Assisted Living María Auxiliadora - Churriana de la Vega - Granada - Spain

SUPERDELTA OVALE/33




Scan the QR-code for the latest information


- BK-81 / Black / Textured
- IVORY-10 / Ivory / Textured

Series of ceiling, wall, bracket and post mounted luminaires for indoor and outdoor, comprising:

- Technopolymer housing and ring
- Pressed glass diffuser, internally coated
- Aluminium reflector for E27 versions
- Foam polymer sealing gasket
- Stainless steel locking hardware
- Built-in driver
- Design by ROBERTO FIORATO



SUPERDELTA TONDO



SUPERDELTA OVALE

SUPERDELTA 33

SUPERDELTA OVALE

IP54 - IK06 - 960 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	60	II	-	-	-	S/EW	-	-	-	■	001704	✓
E27	60	II	-	-	-	S/EW	-	-	-	■	001700	✓



SUPERDELTA 33

IP54 - IK06 - 960 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27	75	II	-	-	-	S/EW	-	-	-	■	001804	✓
E27	75	II	-	-	-	S/EW	-	-	-	■	001800	✓



Optional accessories

33D - Mini 33D Post

Aluminium post suitable for single or twin (back to back) luminaire mounting, comprising:

- Painted extruded aluminium post suitable for single or twin (back to back) luminaire mounting
- Self-extinguishing technopolymer junction box with 4-pole 16 mm² terminal
- Painted die-cast aluminium flange for ground anchoring

33 M1/M2 Post

Mini 33 M1/M2 Post





Aluminium post suitable for single or twin (back to back) luminaire mounting, comprising:

- Painted extruded aluminium post suitable for single or twin (back to back) luminaire mounting
- Self-extinguishing technopolymer brackets
- Self-extinguishing technopolymer junction box with 4-pole 16 mm² terminal block


Ovale and Tondo Bracket/33 Bracket

- Self-extinguishing technopolymer bracket angled at 45°.
- Supplied complete with plugs for wall mounting

DESCRIPTION	COLOR	PART NUMBER	UKCA
SUPERDELTA OVALE			
Bracket		008943	✓
SUPERDELTA OVALE 33			
Bracket 33	■	008953	✓







TONDA ES



Scan the QR-code for the latest information

Compact watertight lamp, entirely made of polycarbonate and suitable for indoor and outdoor applications

- It is characterized by high shock resistance and electrical safety, with double feeding terminals: at the bottom or at the side of the luminaire



TONDA ES
180

TONDA ES
230

TONDA ES 180

IP44 - IK10 - 850 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27 220-240 V 50/60 Hz												
E27	-	II	-	-	-	TRNSP	-	-	-		GW80651	✓





TONDA ES 230

IP44 - IK10 - 850 °C

LAMPHOLDER	LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
E27 220-240 V 50/60 Hz												
E27	-	II	-	-	-	TRNSP	-	-	-		GW80652	✓



MIMIK 10 CEILING



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Ceiling surface mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Matt, toughened, flat glass diffuser for the MIMIK 10 CEILING versions
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (MIMIK 10 CEILING TECH versions)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- Openable and maintainable luminaire (future-proof)




Timing sport center - Brescia - Italy



MIMIK 10



MIMIK 10 POST



MIMIK 10 CEILING

MIMIK 10 CEILING C/I

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	✓	70	4000	C/I	20°	1120	704	■	304875	✓
10	I	✓	70	3000	C/I	20°	1040	612	■	304872	✓
10	I	✓	70	4000	C/I	20°	1120	704	■	304874	✓
10	I	✓	70	3000	C/I	20°	1040	612	■	304871	✓
10	I	✓	70	4000	C/I	20°	1120	704	□	304876	✓
10	I	✓	70	3000	C/I	20°	1040	612	□	304873	✓




MIMIK 10 CEILING TECH

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	✓	70	4000	C/EW	-	1120	822	■	304881	✓
10	I	✓	70	3000	C/EW	-	1040	715	■	304878	✓
10	I	✓	70	4000	C/EW	-	1120	822	■	304880	✓
10	I	✓	70	3000	C/EW	-	1040	715	■	304877	✓
10	I	✓	70	4000	C/EW	-	1120	822	□	304882	✓
10	I	✓	70	3000	C/EW	-	1040	715	□	304879	✓



MIMIK 20 CEILING



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Ceiling surface mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Static ON/OFF or dimmable DALI options available
- Stainless steel locking hardware
- Openable and maintainable luminaire (future-proof)



MIMIK 20



MIMIK 20 CEILING

MIMIK 20 CEILING

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	3560	1854	■	3105851	✓
22	I	-	80	3000	S/EW	-	3335	1797	■	3105850	✓
22	I	-	80	4000	S/EW	-	3560	1854	■	3105849	✓
22	I	-	80	3000	S/EW	-	3335	1797	■	3105848	✓
22	I	-	80	4000	S/EW	-	3560	1854	□	3105853	✓
22	I	-	80	3000	S/EW	-	3335	1797	□	3105852	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	3560	1854	■	3105857	✓
22	I	-	80	3000	S/EW	-	3335	1797	■	3105856	✓
22	I	-	80	4000	S/EW	-	3560	1854	■	3105855	✓
22	I	-	80	3000	S/EW	-	3335	1797	■	3105854	✓
22	I	-	80	4000	S/EW	-	3560	1854	□	3105859	✓
22	I	-	80	3000	S/EW	-	3335	1797	□	3105858	✓





Private Villa - Verona - Italy

MASK+ ROUND



- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information

Wall and ceiling mounted luminaire for indoor and outdoor, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium base for wall and ceiling applications, painted
- Glass diffusers, internally coated, for homogeneous light distribution
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Anti-ageing custom moulded silicone sealing gasket(s)
- Chromed steel spring locks for quick attachment of the body to the housing
- PIR versions have a motion sensor fitted into the ring, suitable for resistive and inductive load
- Sensor settings from 10 to 2000 lux
- Opening angle 120°
- Adjustable operation time (10 s to 7 min)
- Design by ROBERTO FIORATO




MASK+



MASK+ MINI



MASK+ ROUND



MASK+ ROUND
PIR

MASK+ ROUND

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	2650	1227	■	3105007	✓
22	I	-	80	3000	S/EW	-	2590	1188	■	3105005	✓
22	I	-	80	4000	S/EW	-	2650	1227	□	3105008	✓
22	I	-	80	3000	S/EW	-	2590	1188	□	3105006	✓




MASK+ ROUND PIR

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	2650	1227	■	3105011	✓
22	I	-	80	3000	S/EW	-	2590	1188	■	3105009	✓
22	I	-	80	4000	S/EW	-	2650	1227	□	3105012	✓
22	I	-	80	3000	S/EW	-	2590	1188	□	3105010	✓



QUASAR 10 CEILING



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Ceiling surface mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Foam polymer sealing gasket
- Built-in driver
- Stainless steel locking hardware
- Openable and maintainable luminaire (future-proof)



QUASAR 10



QUASAR 10 CEILING

QUASAR 10 CEILING

IP40 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 230 V 50 Hz											
5	I	-	80	4000	S/EW	-	500	289,4	■	304488	✓
5	I	-	80	3000	S/EW	-	500	268,48	■	304487	✓
5	I	-	80	4000	S/EW	-	500	289,4	■	304490	✓
5	I	-	80	3000	S/EW	-	500	268,48	■	304489	✓
5	I	-	80	4000	S/EW	-	500	289,4	□	304492	✓
5	I	-	80	3000	S/EW	-	500	268,48	□	304491	✓



QUASAR 30 CEILING



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Ceiling surface mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (TECH versions)
- Satin finish pure aluminium reflector (Al 99.98)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Openable and maintainable luminaire (future-proof)



QUASAR 30



QUASAR 30 CEILING TECH


QUASAR 30 CEILING TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	S/I	-	2384	1652	■	306177	✓
20	I	✓	80	3000	S/I	-	2276	1482	■	306178	✓
20	I	✓	80	4000	S/I	-	2384	1652	■	306175	✓
20	I	✓	80	3000	S/I	-	2276	1482	■	306176	✓
20	I	✓	80	4000	S/I	-	2384	1652	□	306174	✓
20	I	✓	80	3000	S/I	-	2276	1482	□	306131	✓



MIMIK 10



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- Single (M) and dual (B) emission versions available
- The MIMIK versions are available with asymmetric (CP) or circular (C/I) optic options. In the dual emission versions (B), the two different beam types are combined.
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Openable and maintainable luminaire (future-proof)




Restaurant Burg Landshut - Bernkastel-Kues - Germany




MIMIK 10 CEILING



MIMIK 10 POST




MIMIK 10 FLAT









MIMIK 10


Identifying and classifying our optics



MIMIK 10 FLAT M







IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	A/W	-	700	517		304827	✓
5	I	-	80	3000	A/W	-	650	501		304824	✓
5	I	-	80	4000	A/W	-	700	517		304826	✓
5	I	-	80	3000	A/W	-	650	501		304823	✓
5	I	-	80	4000	A/W	-	700	517		304828	✓
5	I	-	80	3000	A/W	-	650	501		304825	✓



MIMIK 10 FLAT B







IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	A/W	-	1357	1071		304833	✓
9.5	I	-	80	3000	A/W	-	1140	1028		304830	✓
9.5	I	-	80	4000	A/W	-	1357	1071		304832	✓
9.5	I	-	80	3000	A/W	-	1140	1028		304829	✓
9.5	I	-	80	4000	A/W	-	1357	1071		304834	✓
9.5	I	-	80	3000	A/W	-	1140	1028		304831	✓



MIMIK 10 M C/I







IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	✓	70	4000	C/I	20°	593	454		304851	✓
5	I	✓	70	3000	C/I	20°	561	398		304848	✓
5	I	✓	70	4000	C/I	20°	593	454		304850	✓
5	I	✓	70	3000	C/I	20°	561	398		304847	✓
5	I	✓	70	4000	C/I	20°	593	454		304852	✓
5	I	✓	70	3000	C/I	20°	561	398		304849	✓



MIMIK 10 B C/I







IP65 - IK05


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	✓	70	4000	C/I	20°	1120	932		304863	✓
10	I	✓	70	3000	C/I	20°	1040	818		304860	✓
10	I	✓	70	4000	C/I	20°	1120	932		304862	✓
10	I	✓	70	3000	C/I	20°	1040	818		304859	✓
10	I	✓	70	4000	C/I	20°	1120	932		304864	✓
10	I	✓	70	3000	C/I	20°	1040	818		304861	✓



MIMIK 10 M CP/T3

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	✓	70	4000	CP/T3	-	593	376		304857	✓
5	I	✓	70	3000	CP/T3	-	561	330		304854	✓
5	I	✓	70	4000	CP/T3	-	593	376		304856	✓
5	I	✓	70	3000	CP/T3	-	561	330		304853	✓
5	I	✓	70	4000	CP/T3	-	593	376		304858	✓
5	I	✓	70	3000	CP/T3	-	561	330		304855	✓




Optional accessories


Complete unit

1A+1B = please order 2 codes

COMPONENTS	
A	luminaire
B	customising ring




DESCRIPTION	COLOR	PART NUMBER	UKCA
MIMIK 10 - FLAT M			
Customising ring / Facade Accessory	■	310919	✓
Customising ring / Facade Accessory M	■	3106884	✓
Customising ring / Facade Accessory M	■	3106887	✓
Customising ring / Facade Accessory M	□	3106890	✓
Customising ring / Facade Accessory	■	3106087	✓
Customising ring / Facade Accessory	□	3106088	✓
MIMIK 10 - FLAT B			
Customising ring / Facade Accessory	■	3106883	✓
Customising ring / Facade Accessory B	■	3106885	✓
Customising ring / Facade Accessory	■	3106886	✓
Customising ring / Facade Accessory B	■	3106888	✓
Customising ring / Facade Accessory	□	3106889	✓
Customising ring / Facade Accessory B	□	3106891	✓





Maffei Palace - Verona - Italy

MIMIK 20



Private Villa - Verona - Italy





Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (MIMIK FLAT versions)
- Single (M) and dual (B) emission versions available
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside (MIMIK models)
- MIMIK models are equipped with high-transmittance polycarbonate optics with different light distributions to meet a large variety of lighting schemes
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Built-in driver
- Stainless steel locking hardware
- EM/1P are maintained emergency versions (1h)
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Openable and maintainable luminaire (future-proof)



MIMIK 20 CEILING




MIMIK 20 FLAT



MIMIK 20


Identifying and classifying our optics



MIMIK 20 FLAT M

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12	I	-	80	4000	A/W	-	1710	1273	■	303744	✓
12	I	-	80	3000	A/W	-	1653	1230	■	303746	✓
12	I	-	80	4000	A/W	-	1710	1273	■	303745	✓
12	I	-	80	3000	A/W	-	1653	1230	■	303747	✓
12	I	-	80	4000	A/W	-	1710	1273	□	303795	✓
12	I	-	80	3000	A/W	-	1653	1230	□	303842	✓



MIMIK 20 FLAT M EM1P

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - emergency 1h - 220-240 V 50/60 Hz											
12	I	-	80	4000	A/W	-	1710	1273	■	304201	✓
12	I	-	80	3000	A/W	-	1653	1230	■	304198	✓
12	I	-	80	4000	A/W	-	1710	1273	■	304202	✓
12	I	-	80	3000	A/W	-	1653	1230	■	304199	✓
12	I	-	80	4000	A/W	-	1710	1273	□	304203	✓
12	I	-	80	3000	A/W	-	1653	1230	□	304200	✓



MIMIK 20 FLAT B

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22.5	I	-	80	4000	A/W	-	3420	2516	■	303748	✓
22.5	I	-	80	3000	A/W	-	3306	2435	■	303750	✓
22.5	I	-	80	4000	A/W	-	3420	2516	■	303749	✓
22.5	I	-	80	3000	A/W	-	3306	2435	■	303751	✓
22.5	I	-	80	4000	A/W	-	3420	2516	□	303797	✓
22.5	I	-	80	3000	A/W	-	3306	2435	□	303794	✓



MIMIK 20 CP/T2

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	CP/T2	-	3360	2384	■	303752	✓
26	I	✓	70	3000	CP/T2	-	3120	2346	■	303754	✓
26	I	✓	70	4000	CP/T2	-	3360	2384	■	303753	✓
26	I	✓	70	3000	CP/T2	-	3120	2346	■	303755	✓
26	I	✓	70	4000	CP/T2	-	3360	2384	□	303841	✓
26	I	✓	70	3000	CP/T2	-	3120	2346	□	303840	✓
21	I	✓	70	4000	CP/T2	-	2453	2005	■	304419	✓
21	I	✓	70	3000	CP/T2	-	2278	1973	■	304416	✓
21	I	✓	70	4000	CP/T2	-	2453	2005	■	304420	✓
21	I	✓	70	3000	CP/T2	-	2278	1973	■	304417	✓
21	I	✓	70	4000	CP/T2	-	2453	2005	□	304421	✓
21	I	✓	70	3000	CP/T2	-	2278	1973	□	304418	✓



MIMIK 20 CP/T2 EM3P

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
21	I	-	70	4000	CP/T2	-	2453	2005	■	304395	✓
21	I	-	70	3000	CP/T2	-	2278	1973	■	304394	✓
21	I	-	70	4000	CP/T2	-	2453	2005	■	304397	✓
21	I	-	70	3000	CP/T2	-	2278	1973	■	304396	✓
21	I	-	70	4000	CP/T2	-	2453	2005	□	304399	✓
21	I	-	70	3000	CP/T2	-	2278	1973	□	304398	✓



MIMIK 20 CP/T3

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	CP/T3	-	3360	2401	■	303756	✓
26	I	✓	70	3000	CP/T3	-	3120	2364	■	303758	✓
26	I	✓	70	4000	CP/T3	-	3360	2401	■	303757	✓
26	I	✓	70	3000	CP/T3	-	3120	2364	■	303759	✓
26	I	✓	70	4000	CP/T3	-	3360	2401	□	303733	✓
26	I	✓	70	3000	CP/T3	-	3120	2364	□	303734	✓
21	I	✓	70	4000	CP/T3	-	2453	2012	■	304425	✓
21	I	✓	70	3000	CP/T3	-	2278	1988	■	304422	✓
21	I	✓	70	4000	CP/T3	-	2453	2012	■	304426	✓
21	I	✓	70	3000	CP/T3	-	2278	1988	■	304423	✓
21	I	✓	70	4000	CP/T3	-	2453	2012	□	304427	✓
21	I	✓	70	3000	CP/T3	-	2278	1988	□	304424	✓



MIMIK 20 CP/T3 EM3P

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
21	I	-	70	4000	CP/T3	-	2453	2012	■	304401	✓
21	I	-	70	3000	CP/T3	-	2278	1988	■	304400	✓
21	I	-	70	4000	CP/T3	-	2453	2012	■	304403	✓
21	I	-	70	3000	CP/T3	-	2278	1988	■	304402	✓
21	I	-	70	4000	CP/T3	-	2453	2012	□	304405	✓
21	I	-	70	3000	CP/T3	-	2278	1988	□	304404	✓



MIMIK 20 A60/W

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	A60/W	-	3360	2183	■	303760	✓
26	I	✓	70	3000	A60/W	-	3120	2149	■	303762	✓
26	I	✓	70	4000	A60/W	-	3360	2183	■	303761	✓
26	I	✓	70	3000	A60/W	-	3120	2149	■	303763	✓
26	I	✓	70	4000	A60/W	-	3360	2183	□	303735	✓
26	I	✓	70	3000	A60/W	-	3120	2149	□	303736	✓
21	I	✓	70	4000	A60/W	-	2453	1836	■	304431	✓
21	I	✓	70	3000	A60/W	-	2278	1807	■	304428	✓
21	I	✓	70	4000	A60/W	-	2453	1836	■	304432	✓
21	I	✓	70	3000	A60/W	-	2278	1807	■	304429	✓
21	I	✓	70	4000	A60/W	-	2453	1836	□	304433	✓
21	I	✓	70	3000	A60/W	-	2278	1807	□	304430	✓



MIMIK 20 A60/W EM3P

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
21	I	-	70	4000	A60/W	-	2453	1836	■	304407	✓
21	I	-	70	3000	A60/W	-	2278	1807	■	304406	✓
21	I	-	70	4000	A60/W	-	2453	1836	■	304409	✓
21	I	-	70	3000	A60/W	-	2278	1807	■	304408	✓
21	I	-	70	4000	A60/W	-	2453	1836	□	304411	✓
21	I	-	70	3000	A60/W	-	2278	1807	□	304410	✓




Optional accessories


Complete unit

1A+1B = please order 2 codes


COMPONENTS	
A	luminaire
B	customising ring



DESCRIPTION	COLOR	PART NUMBER	UKCA
MIMIK FLAT M			
FLAT M Customising ring / Facade Accessory	■	310440	✓
FLAT M Customising ring / Facade Accessory	■	310441	✓
FLAT M Customising ring / Facade Accessory	□	310450	✓
MIMIK FLAT B			
FLAT B Customising ring / Facade Accessory	■	310442	✓
FLAT B Customising ring / Facade Accessory	■	310443	✓
FLAT B Customising ring / Facade Accessory	□	310451	✓
MIMIK CP/T2 - CP/T3 - A6o/W			
Customising ring / Facade Accessory	■	310444	✓
Customising ring / Facade Accessory	■	310445	✓
Customising ring / Facade Accessory	□	310449	✓



MIMIK 30




Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (MIMIK FLAT versions)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside (MIMIK models)
- MIMIK models are equipped with high-transmittance polycarbonate optics with different light distributions to meet a large variety of lighting schemes
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Stainless steel locking hardware
- Openable and maintainable luminaire (future-proof)




Adigeo Shopping Centre - Verona - Italy




MIMIK 10



MIMIK 10 POST




MIMIK 30
FLAT









MIMIK 30

Identifying and classifying our optics



MIMIK 30 FLAT







IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18.5	I	-	80	4000	A/W	-	2736	1803		303798	✓
18.5	I	-	80	3000	A/W	-	2644	1764		303800	✓
18.5	I	-	80	4000	A/W	-	2736	1803		303799	✓
18.5	I	-	80	3000	A/W	-	2644	1764		303801	✓
18.5	I	-	80	4000	A/W	-	2736	1803		303843	✓
18.5	I	-	80	3000	A/W	-	2644	1764		303844	✓



MIMIK 30 CP/T2







IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	✓	70	4000	CP/T2	-	4480	2700		303802	✓
30	I	✓	70	3000	CP/T2	-	4160	2506		303804	✓
30	I	✓	70	4000	CP/T2	-	4480	2700		303803	✓
30	I	✓	70	3000	CP/T2	-	4160	2506		303805	✓
30	I	✓	70	4000	CP/T2	-	4480	2700		303845	✓
30	I	✓	70	3000	CP/T2	-	4160	2506		303846	✓



MIMIK 30 CP/T3







IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	✓	70	4000	CP/T3	-	4480	2755		303806	✓
30	I	✓	70	3000	CP/T3	-	4160	2558		303808	✓
30	I	✓	70	4000	CP/T3	-	4480	2755		303807	✓
30	I	✓	70	3000	CP/T3	-	4160	2558		303809	✓
30	I	✓	70	4000	CP/T3	-	4480	2755		303847	✓
30	I	✓	70	3000	CP/T3	-	4160	2558		303848	✓






MIMIK 30 A60/W


IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	✓	70	4000	A60/W	-	4480	2558		303810	✓
30	I	✓	70	3000	A60/W	-	4160	2373		303812	✓
30	I	✓	70	4000	A60/W	-	4480	2558		303811	✓
30	I	✓	70	3000	A60/W	-	4160	2373		303813	✓
30	I	✓	70	4000	A60/W	-	4480	2558		303849	✓
30	I	✓	70	3000	A60/W	-	4160	2373		303850	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
MIMIK FLAT			
FLAT Customising ring / Facade Accessory		310446	✓
FLAT Customising ring / Facade Accessory		310447	✓
FLAT Customising ring / Facade Accessory		310448	✓



310446





310447



310448

MIMIK 50




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information


Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- High-transparency polycarbonate optics
- Built-in driver
- Stainless steel locking hardware
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Ni-Cd 3,6 V, 4 Ah batteries, 24 hours recharge time
- Single (M) and dual (B) emission versions available
- Standard separate switch (DA) for individual upward and downward light emission (B versions)
- Double emission (B) DALI versions have two drivers. Dual ignition is possible by assigning and managing addresses within the DALI protocol
- DALI versions have an operating temperature up to -40°C
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Openable and maintainable luminaire (future-proof)



MIMIK 50


Identifying and classifying our optics



MIMIK 50 M A60/W

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
53	I	-	80	4000	A60/W	-	9000	5955	■	3104511	✓
53	I	-	80	3000	A60/W	-	8630	5598	■	3104510	✓
39	I	-	80	4000	A60/W	-	6920	4573	■	3104487	✓
39	I	-	80	3000	A60/W	-	6630	4299	■	3104486	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
53	I	-	80	4000	A60/W	-	9000	5955	■	3104515	✓
53	I	-	80	3000	A60/W	-	8630	5598	■	3104514	✓



MIMIK 50 M A60/W EM3P

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
53	I	-	80	4000	A60/W	-	9000	5955	■	3104519	✓
53	I	-	80	3000	A60/W	-	8630	5598	■	3104518	✓



MIMIK 50 B A60/W

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
53 + 53	I	-	80	4000	A60/W	-	18000	11834	■	3104523	✓
53 + 53	I	-	80	3000	A60/W	-	17260	11124	■	3104522	✓
39 + 39	I	-	80	4000	A60/W	-	13840	9142	■	3104499	✓
39 + 39	I	-	80	3000	A60/W	-	13260	8594	■	3104498	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
53 + 53	I	-	80	4000	A60/W	-	18000	11834	■	3104527	✓
53 + 53	I	-	80	3000	A60/W	-	17260	11124	■	3104526	✓



MIMIK 50 B A60/W EM3P

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
53 + 53	I	-	80	4000	A60/W	-	18000	11834	■	3104531	✓
53 + 53	I	-	80	3000	A60/W	-	17260	11124	■	3104530	✓



MIMIK 50 M CP/T2

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
53	I	-	80	4000	CP/T2	-	9000	6659	■	3104509	✓
53	I	-	80	3000	CP/T2	-	8630	6363	■	3104508	✓
39	I	-	80	4000	CP/T2	-	6920	5071	■	3104485	✓
39	I	-	80	3000	CP/T2	-	6630	4880	■	3104484	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
53	I	-	80	4000	CP/T2	-	9000	6659	■	3104513	✓
53	I	-	80	3000	CP/T2	-	8630	6363	■	3104512	✓



MIMIK 50 M CP/T2 EM3P

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
53	I	-	80	4000	CP/T2	-	9000	6659	■	3104517	✓
53	I	-	80	3000	CP/T2	-	8630	6363	■	3104516	✓



MIMIK 50 B CP/T2

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
53 + 53	I	-	80	4000	CP/T2	-	18000	13198	■	3104521	✓
53 + 53	I	-	80	3000	CP/T2	-	17260	12642	■	3104520	✓
39 + 39	I	-	80	4000	CP/T2	-	13840	10094	■	3104497	✓
39 + 39	I	-	80	3000	CP/T2	-	13260	9719	■	3104496	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
53 + 53	I	-	80	4000	CP/T2	-	18000	13198	■	3104525	✓
53 + 53	I	-	80	3000	CP/T2	-	17260	12642	■	3104524	✓




MIMIK 50 B CP/T2 EM3P

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz - emergency 3h											
53 + 53	I	-	80	4000	CP/T2	-	18000	13198	■	3104529	✓
53 + 53	I	-	80	3000	CP/T2	-	17260	12642	■	3104528	✓



AMON WALL




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:


- Extruded aluminium profile housing, powder-coated ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s)
- Coated die-cast aluminium trims hinged to the housing
- Built-in driver
- Aluminium heat sink
- Stainless steel locking hardware
- Coated die-cast aluminium bracket features simplified installation system (WALL models)
- Dimmable DALI options available. Consult factory



AMON MINI



AMON MAXI




AMON WALL

AMON WALL A/M

IP65 - IK08 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
27	I	-	80	4000	A15/M	-	3120	1810	■	306311	✓
27	I	-	80	4000	A30/M	-	3120	1787	■	306312	✓
27	I	-	80	3000	A15/M	-	2850	1667	■	306317	✓
27	I	-	80	3000	A30/M	-	2850	1644	■	306318	✓



AMON WALL B A/M

IP65 - IK08 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
54	I	-	80	4000	A15/M	-	6240	3622	■	306313	✓
54	I	-	80	4000	A30/M	-	6240	3575	■	306314	✓
54	I	-	80	3000	A15/M	-	5700	3334	■	306319	✓
54	I	-	80	3000	A30/M	-	5700	3288	■	306320	✓





AMON WALL B A/M+S/I

IP65 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
37	I	-	80	4000	A15/M	-	4160	2357	■	306315	✓
37	I	-	80	4000	A30/M	-	4160	2334	■	306316	✓
37	I	-	80	3000	A15/M	-	3800	2170	■	306321	✓
37	I	-	80	3000	A30/M	-	3800	2147	■	306322	✓



MASK+





- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Anti-ageing custom moulded silicone sealing gasket(s)
- Single (M) and dual (B) emission versions available
- Single emission models suitable for either upwards or downwards mounting (M options)
- Built-in driver
- Stainless steel locking hardware
- EM/1P are maintained emergency versions (1h)
- Dimmable DALI options available. Consult factory
- Design by ROBERTO FIORATO



MASK+ ROUND

MASK+

MASK+ M

IP65 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
12.5	I	-	80	4000	S/EW	-	1668	971	■	3100765	✓
12.5	I	-	80	3000	S/EW	-	1552	914	■	3100763	✓
12.5	I	-	80	4000	S/EW	-	1668	971	□	3100766	✓
12.5	I	-	80	3000	S/EW	-	1552	914	□	3100764	✓
Power LED - emergency 1h - 220-240 V 50/60 Hz											
12.5	I	-	80	4000	S/EW	-	1668	971	■	3101062	✓
12.5	I	-	80	3000	S/EW	-	1552	914	■	3101060	✓
12.5	I	-	80	4000	S/EW	-	1668	971	□	3101063	✓
12.5	I	-	80	3000	S/EW	-	1552	914	□	3101061	✓



MASK+ B

IP65 - IK06 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	-	80	4000	S/EW	-	3336	1879	■	3100769	✓
24	I	-	80	3000	S/EW	-	3104	1770	■	3100767	✓
24	I	-	80	4000	S/EW	-	3336	1879	□	3100770	✓
24	I	-	80	3000	S/EW	-	3104	1770	□	3100768	✓



MASK+ MINI




Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel locking hardware
- Single (M) and dual (B) emission versions available
- Single emission models suitable for either upwards or downwards mounting (M options)
- PIR versions have a motion sensor fitted into the ring, suitable for resistive and inductive load
- Sensor settings from 10 to 2000 lux
- Opening angle 120°
- Adjustable operation time (10 s to 7 min)
- Design by ROBERTO FIORATO



PIR



MASK+ ROUND




MASK+ MINI PIR

MASK+ MINI M

IP65 - IK05


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
8	I	-	80	4000	S/EW	-	733	340	■	3102527	✓
8	I	-	80	3000	S/EW	-	733	317	■	3101602	✓
8	I	-	80	4000	S/EW	-	733	340	□	3102528	✓
8	I	-	80	3000	S/EW	-	733	317	□	3101603	✓



MASK+ MINI M PIR

IP65 - IK05


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
8	I	-	80	4000	S/EW	-	733	340	■	3104648	✓
8	I	-	80	3000	S/EW	-	733	317	■	3101606	✓
8	I	-	80	4000	S/EW	-	733	340	□	3104649	✓
8	I	-	80	3000	S/EW	-	733	317	□	3101607	✓





MASK+ MINI B

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
16	I	-	80	4000	S/EW	-	1450	670	■	3102529	✓
16	I	-	80	3000	S/EW	-	1450	627	■	3101604	✓
16	I	-	80	4000	S/EW	-	1450	670	□	3102530	✓
16	I	-	80	3000	S/EW	-	1450	627	□	3101605	✓



QUASAR 10



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Secured diffuser in printed transparent flat glass
- Foam polymer sealing gasket
- Stainless steel locking hardware
- Built-in driver
- Openable and maintainable luminaire (future-proof)



Private house - Andalusia - Spain










QUASAR 10 CEILING




QUASAR 10

QUASAR 10 1WB








IP44 - IK02


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
3.5	I	✓	80	4000	R	-	230	122		303355	✓
3.5	I	✓	80	3000	R	-	150	100		303354	✓
3.5	I	✓	80	4000	R	-	230	122		303357	✓
3.5	I	✓	80	3000	R	-	150	100		303356	✓
3.5	I	✓	80	3000	R	-	150	100		30335690104	✓
3.5	I	✓	80	4000	R	-	230	122		303451	✓
3.5	I	✓	80	3000	R	-	150	100		303450	✓



QUASAR 10 2WB







IP44 - IK02


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	✓	80	4000	R	-	460	235		303361	✓
6	I	✓	80	3000	R	-	300	192		303360	✓
6	I	✓	80	4000	R	-	460	235		303363	✓
6	I	✓	80	3000	R	-	300	192		303362	✓
6	I	✓	80	3000	R	-	300	192		30336290102	✓
6	I	✓	80	4000	R	-	460	235		303453	✓
6	I	✓	80	3000	R	-	300	192		303452	✓



QUASAR 10 1NB+1WB







IP44 - IK02


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	✓	80	4000	R	-	460	141		303367	✓
6	I	✓	80	3000	R	-	300	113		303366	✓
6	I	✓	80	4000	R	-	460	141		303369	✓
6	I	✓	80	3000	R	-	300	113		303368	✓
6	I	✓	80	4000	R	-	460	141		303455	✓
6	I	✓	80	3000	R	-	300	113		303454	✓




QUASAR 10 4WB

IP44 - IK02

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10.5	I	✓	80	4000	R	-	920	402		303349	✓
10.5	I	✓	80	3000	R	-	600	329		303348	✓
10.5	I	✓	80	4000	R	-	920	402		303351	✓
10.5	I	✓	80	3000	R	-	600	329		303350	✓
10.5	I	✓	80	4000	R	-	920	402		303449	✓
10.5	I	✓	80	3000	R	-	600	329		303448	✓



QUASAR 20



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (TECH versions)
- Satin finish pure aluminium reflector (Al 99.98)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- Openable and maintainable luminaire (future-proof)
- Versions with dimmable 1-10 V or DALI drivers available. Consult factory




Parish complex - Varignano - Viareggio - Italy



M / B







TECH / DOUBLE TECH



QUASAR 20

QUASAR 20 M








IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
11	I	✓	80	4000	S/EW	-	1356	519		303541	✓
11	I	✓	80	3000	S/EW	-	1292	492		303542	✓
11	I	✓	80	4000	S/EW	-	1356	519		303539	✓
11	I	✓	80	3000	S/EW	-	1292	492		303540	✓
11	I	✓	80	4000	S/EW	-	1356	519		303537	✓
11	I	✓	80	3000	S/EW	-	1292	492		303538	✓



QUASAR 20 TECH







IP65 - IK07


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
11	I	✓	80	4000	A30/M	30°	1356	797		303535	✓
11	I	✓	80	3000	A30/M	30°	1292	758		303536	✓
11	I	✓	80	4000	A30/M	30°	1356	797		303533	✓
11	I	✓	80	3000	A30/M	30°	1292	758		303534	✓
11	I	✓	80	3000	A30/M	30°	1292	758		30353490107	✓
11	I	✓	80	4000	A30/M	30°	1356	797		303531	✓
11	I	✓	80	3000	A30/M	30°	1292	758		303532	✓



QUASAR 20 B








IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	S/EW	-	2712	985		303547	✓
20	I	✓	80	3000	S/EW	-	2584	930		303548	✓
20	I	✓	80	4000	S/EW	-	2712	985		303545	✓
20	I	✓	80	3000	S/EW	-	2584	930		303546	✓
20	I	✓	80	4000	S/EW	-	2712	985		303543	✓
20	I	✓	80	3000	S/EW	-	2584	930		303544	✓





QUASAR 20 DOUBLE TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	A30/M	-	2712	1475		304100	✓
20	I	✓	80	3000	A30/M	-	2584	1417		304097	✓
20	I	✓	80	4000	A30/M	-	2712	1475		304101	✓
20	I	✓	80	3000	A30/M	-	2584	1417		304098	✓
20	I	✓	80	3000	A30/M	-	2584	1417		30409890104	✓
20	I	✓	80	4000	A30/M	-	2712	1475		304099	✓
20	I	✓	80	3000	A30/M	-	2584	1417		304096	✓



QUASAR 30



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (TECH versions)
- Satin finish pure aluminium reflector (Al 99.98)
- Built-in driver
- Anti-ageing custom moulded silicone sealing gasket(s)
- EM/3P LED versions feature an additional LED that is used for emergency lighting
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- EM/3P LED versions are equipped with 3.6V 2Ah, Ni MH batteries
- Openable and maintainable luminaire (future-proof)
- Versions with dimmable 1-10 V or DALI drivers available. Consult factory




Hotel Bergmanns alm beer house - Reden - Germany




M / B



TECH / DOUBLE TECH



QUASAR 30 CEILING



QUASAR 30

QUASAR 30 M

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	S/EW	-	2712	995	■	303559	✓
20	I	✓	80	3000	S/EW	-	2584	936	■	303560	✓
20	I	✓	80	4000	S/EW	-	2712	995	■	303557	✓
20	I	✓	80	3000	S/EW	-	2584	936	■	303558	✓
20	I	✓	80	4000	S/EW	-	2712	995	□	303555	✓
20	I	✓	80	3000	S/EW	-	2584	936	□	303556	✓



QUASAR 30 TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	A30/M	30°	2712	1606	■	303553	✓
20	I	✓	80	3000	A30/M	30°	2584	1557	■	303554	✓
20	I	✓	80	4000	A30/M	30°	2712	1606	■	303551	✓
20	I	✓	80	3000	A30/M	30°	2584	1557	■	303552	✓
20	I	✓	80	3000	A30/M	30°	2584	1557	■	30355290105	✓
20	I	✓	80	4000	A30/M	30°	2712	1606	□	303549	✓
20	I	✓	80	3000	A30/M	30°	2584	1557	□	303550	✓



QUASAR 30 B

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	I	✓	80	4000	S/EW	-	4800	1148	■	303565	✓
32	I	✓	80	3000	S/EW	-	4572	1532	■	303566	✓
32	I	✓	80	4000	S/EW	-	4800	1615	■	303563	✓
32	I	✓	80	3000	S/EW	-	4572	1532	■	303564	✓
32	I	✓	80	4000	S/EW	-	4800	1615	□	303561	✓
32	I	✓	80	3000	S/EW	-	4572	1532	□	303562	✓



QUASAR 30 DOUBLE TECH

IP65 - IK07


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
32	I	✓	80	4000	A30/M	-	4800	2489	■	304106	✓
32	I	✓	80	3000	A30/M	-	4572	2427	■	304103	✓
32	I	✓	80	4000	A30/M	-	4800	2489	■	304107	✓
32	I	✓	80	3000	A30/M	-	4572	2427	■	304104	✓
32	I	✓	80	3000	A30/M	-	4572	2427	■	30410490102	✓
32	I	✓	80	4000	A30/M	-	4800	2489	□	304105	✓
32	I	✓	80	3000	A30/M	-	4572	2427	□	304102	✓



QUASAR 30 TECH EM/3P

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
20	I	-	80	4000	A30/M	-	2712	1606	■	304346	✓
20	I	-	80	3000	A30/M	-	2584	1557	■	304345	✓
20	I	-	80	4000	A30/M	-	2712	1606	■	304197	✓
20	I	-	80	3000	A30/M	-	2584	1557	■	304196	✓
20	I	-	80	4000	A30/M	-	2712	1606	□	304348	✓
20	I	-	80	3000	A30/M	-	2584	1557	□	304347	✓



QUASAR 60



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (TECH versions)
- Satin finish pure aluminium reflector (Al 99.98)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Openable and maintainable luminaire (future-proof)




Private villa - Sanlúcar de Barrameda - Cádiz - Spain



M / B



TECH / DOUBLE TECH




QUASAR 60

QUASAR 6o M

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100821	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100818	✓
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100822	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100819	✓
19	I	-	80	4000	A7/EW	-	2736	1655	□	3100823	✓
19	I	-	80	3000	A7/EW	-	2554	1631	□	3100820	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100833	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100830	✓
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100834	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100831	✓
19	I	-	80	4000	A7/EW	-	2736	1655	□	3100835	✓
19	I	-	80	3000	A7/EW	-	2554	1631	□	3100832	✓



QUASAR 6o M EM/3P

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100845	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100842	✓
19	I	-	80	4000	A7/EW	-	2736	1655	■	3100846	✓
19	I	-	80	3000	A7/EW	-	2554	1631	■	3100843	✓
19	I	-	80	4000	A7/EW	-	2736	1655	□	3100847	✓
19	I	-	80	3000	A7/EW	-	2554	1631	□	3100844	✓



QUASAR 6o B

IP65 - IK06


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
38	I	-	80	4000	A7/EW	-	5472	3250	■	3100857	✓
38	I	-	80	3000	A7/EW	-	5107	3204	■	3100854	✓
38	I	-	80	4000	A7/EW	-	5472	3250	■	3100858	✓
38	I	-	80	3000	A7/EW	-	5107	3204	■	3100855	✓
38	I	-	80	4000	A7/EW	-	5472	3250	□	3100859	✓
38	I	-	80	3000	A7/EW	-	5107	3204	□	3100856	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
38	I	-	80	4000	A7/EW	-	5472	3250	■	3100869	✓
38	I	-	80	3000	A7/EW	-	5107	3204	■	3100866	✓
38	I	-	80	4000	A7/EW	-	5472	3250	■	3100870	✓
38	I	-	80	3000	A7/EW	-	5107	3204	■	3100867	✓
38	I	-	80	4000	A7/EW	-	5472	3250	□	3100871	✓
38	I	-	80	3000	A7/EW	-	5107	3204	□	3100868	✓



QUASAR 6o TECH

IP65 - IK07


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	I	-	80	4000	A22/EW	-	2736	2078	■	3100815	✓
19	I	-	80	3000	A22/EW	-	2554	2050	■	3100812	✓
19	I	-	80	4000	A22/EW	-	2736	2078	■	3100816	✓
19	I	-	80	3000	A22/EW	-	2554	2050	■	3100813	✓
19	I	-	80	4000	A22/EW	-	2736	2078	□	3100817	✓
19	I	-	80	3000	A22/EW	-	2554	2050	□	3100814	✓




QUASAR 6o DOUBLE TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
38	I	-	80	4000	A22/EW	-	5472	4082	■	3100851	✓
38	I	-	80	3000	A22/EW	-	5107	4026	■	3100848	✓
38	I	-	80	4000	A22/EW	-	5472	4082	■	3100852	✓
38	I	-	80	3000	A22/EW	-	5107	4026	■	3100849	✓
38	I	-	80	4000	A22/EW	-	5472	4082	□	3100853	✓
38	I	-	80	3000	A22/EW	-	5107	4026	□	3100850	✓



SHIELD+ 1



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-efficiency metallized technopolymer reflector with protective surface treatment
- Anti-ageing custom moulded silicone sealing gasket(s)
- Field settable integral tri-level lumen/wattage packages proprietary DIP switch driver
- Static ON/OFF or dimmable DALI options available
- EXTREME options are suitable for extreme operating temp. conditions, -40°C
- Through-wiring designed
- Twilight models (C versions) complete with dusk sensor available. Consult factory



Commercial Building Warmteservice - Gouda - Netherlands



SHIELD+ 1

SHIELD+ 1 MULTIPOWER

IP66 - IK07

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
13							2080	1773			
19	I	-	80	4000	A/EW	-	2775	2364	■	3106354	✓
27							3605	3072			
13							2030	1621			
19	I	-	80	3000	A/EW	-	2700	2161	■	3106352	✓
27							3515	2808			




SHIELD+ 1 EXTREME-40°

IP66 - IK07

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	I	-	80	4000	A/EW	-	3605	3072	■	3106362	✓
27	I	-	80	3000	A/EW	-	3514	2808	■	3106360	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	I	-	80	4000	A/EW	-	3605	3072	■	3106358	✓
27	I	-	80	3000	A/EW	-	3514	2808	■	3106356	✓



SHIELD+ 2




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-efficiency metallized technopolymer reflector with protective surface treatment
- Anti-ageing custom moulded silicone sealing gasket(s)
- Static ON/OFF or dimmable DALI options available
- DALI versions have two drivers. Dual ignition is possible by assigning and managing addresses within the DALI protocol
- EXTREME options are suitable for extreme operating temp. conditions, -40°C
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Li-Fe Po4 3,2V 3.0 Ah batteries, 24 hours recharge time
- Through-wiring designed
- Twilight models (C versions) complete with dusk sensor available. Consult factory




SHIELD+ 2

SHIELD+ 2

IP66 - IK09


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
79	I	-	80	4000	A/EW	-	10552	7985	■	3106328	✓
79	I	-	80	3000	A/EW	-	10284	7261	■	3106326	✓
52	I	-	80	4000	A/EW	-	7210	6070	■	3106332	✓
52	I	-	80	3000	A/EW	-	7028	5518	■	3106330	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
52	I	-	80	4000	A/EW	-	7210	6070	■	3106340	✓
52	I	-	80	3000	A/EW	-	7028	5518	■	3106338	✓




SHIELD+ 2 EXTREME-40°

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
79	I	-	80	4000	A/EW	-	10552	7985	■	3106336	✓
79	I	-	80	3000	A/EW	-	10284	7261	■	3106334	✓



ELIA OL




Scan the QR-code for the latest information

- BK-RAL9005 / Black RAL9005 /
- WH-RAL9016 / White RAL9016 /

Die-cast aluminum fixture for wall mounting, ideal for indoor and outdoor architectural lighting such as: stairs, passageways or facades, quick and easy to install, with a clean and essential line:

- Designed in two different finishes (black and white), with double emission diffusing polycarbonate opal screen (top and down) to create a comfortable atmosphere, color temperatures of 3,000K, 4,000 K and 5,700 K and a color rendering index greater than 80
- It has been designed to withstand temperature variations from -20 °C to + 45 °C, water and dust penetration up to IP65 degree and shocks up to IK08 degree
- Light and handy, it is easy to install thanks also to the rear bracket for fixing, the quick-fit terminal placed in the back for the electrical wiring



ELIA OL


ELIA OL

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
8	I	-	80	4000	OPAL	-	-	650	■	GWF2100FR840	✓
8	I	-	80	3000	OPAL	-	-	650	■	GWF2100FR830	✓
8	I	-	80	4000	OPAL	-	-	650	□	GWF2110FR840	✓
8	I	-	80	3000	OPAL	-	-	650	□	GWF2110FR830	✓



ORION H




- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:



- Polyester powder coat finish, die-cast aluminium housing, in compact size
- Microprismatic, flat glass diffuser, silk-screened on the inside
- Aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Stainless steel locking hardware



ORION H



The decorative sleeve changes the luminous effect of the luminaire and is available as an accessory (to be ordered separately). Consult factory (custom RAL).




ORION POST

ORION H M

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	A/EW	-	742	363,36	■	3105448	✓
5	I	-	80	3000	A/EW	-	675	352,33	■	3105446	✓
5	I	-	80	2700	A/EW	-	640	309,4	■	3111193	✓
5	I	-	80	4000	A/EW	-	742	363,36	□	3105449	✓
5	I	-	80	3000	A/EW	-	675	352,33	□	3105447	✓



ORION H B


IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	A/EW	-	1485	845,26	■	3105452	✓
10	I	-	80	3000	A/EW	-	1350	792,35	■	3105450	✓
10	I	-	80	2700	A/EW	-	1280	783,33	■	3111194	✓
10	I	-	80	4000	A/EW	-	1485	845,26	□	3105453	✓
10	I	-	80	3000	A/EW	-	1350	792,35	□	3105451	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ORION			
Carter ORION H	■	3106290	✓
Carter ORION H	□	3106289	✓
Carter ORION H	■	3106291	✓




3106290



3106289




3106291



A

B



ORION V




Scan the QR-code for the latest information


- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:



- Polyester powder coat finish, die-cast aluminium housing, in compact size
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Stainless steel locking hardware



ORION V



The decorative sleeve changes the luminous effect of the luminaire and is available as an accessory (to be ordered separately). Consult factory (custom RAL).




ORION POST

ORION V M

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	S/EW	-	742	577,83	■	3105440	✓
5	I	-	80	3000	S/EW	-	675	538,82	■	3105438	✓
5	I	-	80	4000	S/EW	-	742	577,83	□	3105441	✓
5	I	-	80	3000	S/EW	-	675	538,82	□	3105439	✓



ORION V M NB

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	R	-	742	134,1	■	3118409	✓
5	I	-	80	3000	R	-	675	125,44	■	3118407	✓
5	I	-	80	4000	R	-	742	134,1	□	3118410	✓
5	I	-	80	3000	R	-	675	125,44	□	3118408	✓



ORION V B

IP65 - IK06


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
11	I	-	80	4000	S/EW	-	1484	1125,33	□	3105445	✓
10	I	-	80	4000	S/EW	-	1484	1125,33	■	3105444	✓
10	I	-	80	3000	S/EW	-	1350	1065,05	■	3105442	✓
10	I	-	80	3000	S/EW	-	1350	1065,05	□	3105443	✓



ORION V B NB


IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	R	-	1484	265,18	■	3118413	✓
10	I	-	80	3000	R	-	1350	242,69	■	3118411	✓
10	I	-	80	4000	R	-	1484	265,18	□	3118414	✓
10	I	-	80	3000	R	-	1350	242,69	□	3118412	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ORION V			
Carter ORION V	■	3106287	✓
Carter ORION V	□	3106286	✓
Carter ORION V	■	3106288	✓




3106287



3106286




3106288



Complete unit

1A+1B = please order 2 codes

COMPONENTS	
A	luminaire
B	customising carter



POLO+ 2





Scan the QR-code for the latest information


- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-coated
- Extra clear, toughened, flat glass diffuser, matt and silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Stainless steel locking hardware
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- POLO+2/I version includes on/off switch



POLO+ 2



POLO+2
I

POLO+ 2 A/EW

IP65 - IK05

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9,5	I	-	80	4000	A/EW	-	1485	535,21	■	304558	✓
9,5	I	-	80	3000	A/EW	-	1350	478,45	■	304557	✓
9,5	I	-	80	4000	A/EW	-	1485	535,21	□	304560	✓
9,5	I	-	80	3000	A/EW	-	1350	478,45	□	304559	✓



POLO+ 2/I A/EW

IP40 - IK05

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9,5	I	-	80	4000	A/EW	-	1485	535,21	■	304974	✓
9,5	I	-	80	3000	A/EW	-	1350	478,45	■	304973	✓
9,5	I	-	80	4000	A/EW	-	1485	535,21	□	304976	✓
9,5	I	-	80	3000	A/EW	-	1350	478,45	□	304975	✓



POLO+ 3





Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-coated
- Extra clear, toughened, flat glass diffuser, matt and silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Stainless steel locking hardware
- Glare control and upward light pollution laws compliant (0% ULOR rating)



POLO+ 3 A/EW

POLO+ 3 A/EW

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
15	I	-	80	4000	A/EW	-	2225	726,96	■	304564	✓
15	I	-	80	3000	A/EW	-	2025	687,3	■	304563	✓
15	I	-	80	4000	A/EW	-	2225	726,96	□	304566	✓
15	I	-	80	3000	A/EW	-	2025	687,3	□	304565	✓



MIMIK 10 POST



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Landscaping LED bollard, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened, glass diffuser, silk-screened on the inside
- Satin finish pure aluminium reflector (Al 99.98)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- Extruded aluminium pole polyester powder coat finish ISO 9227/19244 - ISO 9223 (C5)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Base plate included
- Metal sturdy bases for floor mounting are available as accessories (HU versions)
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- Openable and maintainable luminaire (future-proof)
- Dimmable DALI options available. Consult factory



A/I



CP/T3




MIMIK 10 POST
300

MIMIK 10 POST
600





MIMIK 10 POST
1000

Identifying and classifying our optics







MIMIK 10 POST 300

IP65 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	A/I	-	1075	915		304619	✓
10	I	-	80	3000	A/I	-	1006	745		304617	✓
10	I	-	80	4000	A/I	-	1075	915		304620	✓
10	I	-	80	3000	A/I	-	1006	745		304618	✓





MIMIK 10 POST 600

IP65 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	A/I	-	1075	915		304615	✓
10	I	-	80	3000	A/I	-	1006	745		304613	✓
10	I	-	80	4000	A/I	-	1075	915		304616	✓
10	I	-	80	3000	A/I	-	1006	745		304614	✓





MIMIK 10 POST 1000

IP65 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	CP/T3	-	1076	780		306555	✓
10	I	-	80	3000	CP/T3	-	1000	767		306554	✓
10	I	-	80	4000	CP/T3	-	1076	780		306553	✓
10	I	-	80	3000	CP/T3	-	1000	767		306552	✓

MIMIK 10 POST 1000 HU

IP65 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	CP/T3	-	1076	780		3112996	✓
10	I	-	80	3000	CP/T3	-	1000	767		3112995	✓
10	I	-	80	4000	CP/T3	-	1076	780		3112998	✓
10	I	-	80	3000	CP/T3	-	1000	767		3112997	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
MIMIK 10 POST			
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓



310496



Palm Beach Torreblanca - Málaga - Spain



INSERT+ ZERO POST




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured

Post mounted outdoor luminaire for general lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Anti-ageing custom moulded silicone sealing gasket(s)
- Extruded aluminium post with base plate, polyester powder coat finish
- Rapid spring-type installation
- No visible screws



INSERT+ ZERO POST 300


INSERT+ ZERO POST 300

IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/W	-	483	157	■	3118129	✓
4	I	-	80	3000	A/W	-	377	151	■	3118127	✓
4	I	-	80	2700	A/W	-	435	148	■	3118125	✓
4	I	-	80	4000	A/W	-	483	157	■	3118128	✓
4	I	-	80	3000	A/W	-	377	151	■	3118126	✓
4	I	-	80	2700	A/W	-	435	148	■	3118124	✓



INSERT+ 1 V POST




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured

Post mounted outdoor luminaire for general lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Extruded aluminium post with base plate, polyester powder coat finish
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Rapid spring-type installation
- No visible screws



INSERT+ 1 V POST 600

INSERT+ 1 V POST 600

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/EW	-	418	197	■	3118477	✓
4	I	-	80	3000	A/EW	-	377	184	■	3118475	✓
4	I	-	80	4000	A/EW	-	418	197	■	3118476	✓
4	I	-	80	3000	A/EW	-	377	184	■	3118474	✓



INSERT+ 2 V POST




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Post mounted outdoor luminaire for general lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Static ON/OFF or dimmable DALI options available
- Extruded aluminium post with base plate, polyester powder coat finish
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Rapid spring-type installation
- No visible screws



INSERT+ 2 V POST 750

INSERT+ 2 V POST 750

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634	■	3118211	✓
9	I	-	80	3000	A/EW	-	1197	592	■	3118209	✓
9	I	-	80	4000	A/EW	-	1318	634	■	3118210	✓
9	I	-	80	3000	A/EW	-	1197	592	■	3118208	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634	■	3118215	✓
9	I	-	80	3000	A/EW	-	1197	592	■	3118213	✓
9	I	-	80	4000	A/EW	-	1318	634	■	3118214	✓
9	I	-	80	3000	A/EW	-	1197	592	■	3118212	✓



ORION POST



Scan the QR-code for the latest information

■ AN-96 / Anthracite gray / Textured

Landscaping LED bollard, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Painted stainless steel sheet metal structure (ORION POST 260)
- Painted extruded aluminium pole (ORION POST 600)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Base plate included
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable



ORION H



ORION V



ORION POST 260

ORION POST 260

IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	A/M	-	742	101,93	■	3106842	✓
5	I	-	80	3000	A/M	-	675	95,05	■	3106841	✓



ELIA BL





■ BK-RAL9005 / Black RAL9005 /


Scan the QR-code for the latest information

Die-cast aluminum luminaire for ground mounting, ideal for bollard lighting in residential areas and passageways:

- Designed in two different sizes (500mm and 700mm) with opal diffusing polycarbonate diffuser with double high and low emission) to create a comfortable atmosphere, color temperatures 3,000K, 4,000K and 5,700K and a color rendering index greater than 80
- It has been designed to withstand temperature variations from -20 ° C to + 45 ° C, water and dust penetration up to IP65 degree and shocks up to IK08 degree
- ELIA BL is easy to install thanks to the ground anchoring system with 4 blocking plugs



ELIA BL
L1 700



ELIA BL
M1 500

ELIA BL L1 700

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
8	I	-	80	4000	OPAL	-	-	650	■	GWF2300PR840	✓
8	I	-	80	3000	OPAL	-	-	650	■	GWF2300PR830	✓



ELIA BL M1 500

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
8	I	-	80	4000	OPAL	-	-	650	■	GWF2300LR840	✓
8	I	-	80	3000	OPAL	-	-	650	■	GWF2300LR830	✓



PADO



Mitsui outlet park - Taichung - Taiwan




Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured

Landscaping LED bollard, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Adapter for posts Ø 42-45 mm made of polyester powder-coated die-cast aluminium
- Internally frosted glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Built-in driver
- Stainless steel locking hardware
- Polyester powder coat finish extruded aluminium post (H 600 mm) with base plate for the PADO 600 model
- Polyester powder coat finish extruded aluminium post (H 900 mm) with base plate for the PADO 900 model
- Polyester powder coat finish extruded aluminium post (H 1200 mm) with base plate for the PADO 1200 model
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- Suitable for installation on existing poles Ø 60 mm (PADO /PADO BASIC)
- Design by ALESSANDRO PEDRETTI




PADO 600




PADO 900






PADO 1200



PADO



PADO BASIC



PADO 600

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	S/EW	-	2061	1160	■	304086	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304084	✓
20	I	-	80	4000	S/EW	-	2061	1160	■	304087	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304085	✓

PADO 900

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	S/EW	-	2061	1160	■	304090	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304088	✓
20	I	-	80	4000	S/EW	-	2061	1160	■	304091	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304089	✓

PADO 1200

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	S/EW	-	2061	1160	■	306354	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	306352	✓
20	I	-	80	4000	S/EW	-	2061	1160	■	306355	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	306353	✓

PADO

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	4000	S/EW	-	2061	1160	■	304094	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304092	✓
20	I	-	80	4000	S/EW	-	2061	1160	■	304095	✓
20	I	-	80	3000	S/EW	-	1974	1080	■	304093	✓


PADO BASIC

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	S/EW	-	1564	872	■	306290	✓
9.5	I	-	80	3000	S/EW	-	1491	830	■	306289	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
PADO			
Pole top adaptor Ø 45 mm PADO	■	310481	✓
Pole top adaptor Ø 45mm PADO	■	310482	✓




310481
310482



Mitsui outlet park - Taichung - Taiwan



Q-LIGHT



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Scan the QR-code for the latest information

Landscaping LED bollard, comprising:





- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra pure polished aluminium reflector
- Clear UV-stabilised and impact-resistant technopolymer diffuser
- Die-cast aluminium housing and fixing plate for in-ground installation, painted
- Die-cast aluminium housing complete with two PG11 cable glands suitable for through wiring of Ø 5 mm to Ø 10 mm cables
- Stainless steel fixing screws and rods
- Extruded aluminium pole polyester powder coat finish ISO 9227/19244 - ISO 9223 (C5)
- Base plate included



Q-LIGHT

Q-LIGHT


IP65 - IK05

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	80	4000	S/W	-	2088	1151		306671	✓
14	I	-	80	3000	S/W	-	1944	1024		306670	✓
14	I	-	80	4000	S/W	-	2088	1151		306669	✓
14	I	-	80	3000	S/W	-	1944	1024		306668	✓





Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
Q-LIGHT			
Baseplate Q-series		310398	✓



310398

CRICKET+ 10 WALL




Scan the QR-code for the latest information

■ AN-96 / Anthracite gray / Textured

Series of wall recessed luminaires for indoor and outdoor ,comprising:

- Black painted anodised die-cast aluminium housing
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Matt, toughened, flat glass diffuser
- Die-cast aluminium cover painted prior chemical preparation of the surface
- Mains connection through waterproof connection system (WATER-STOP)
- Stainless steel locking hardware
- Stainless steel springs for quick connection to recessed box
- Technopolymer recess box to be ordered separately
- Complete with 1 m factory pre-wired cable H05RN-F 3G1 mm²
- All CRICKET + 10 luminaires can be installed in solid walls. The RGBW and TW versions can be installed in solid walls using the respective outer casing



CRICKET+ 10 WALL

CRICKET+ 10 WALL VISA A/EW


IP67 - IK08 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	80	4000	A/EW	-	475	83	■	3115667	✓
5	I	-	80	3000	A/EW	-	440	78	■	3115666	✓
5	I	-	80	2700	A/EW	-	440	68	■	3116656	✓


Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 10 WALL			
Recessed box CRICKET+ 10 MARINE		3109879	✓



3109879

INSERT+ ZERO





Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall recessed luminaire, for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- Recessed box (503) included
- The luminaire is suitable for through-wiring









INSERT+ ZERO

INSERT+ ZERO

IP65 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4.5	I	-	80	4000	A29/M	-	530	142		304111	✓
4.5	I	-	80	3000	A29/M	-	511	125		304110	✓
4.5	I	-	80	4000	A29/M	-	530	142		304113	✓
4.5	I	-	80	3000	A29/M	-	511	125		304112	✓
4.5	I	-	80	4000	A29/M	-	530	142		304109	✓
4.5	I	-	80	3000	A29/M	-	511	125		304108	✓


INSERT+ ZERO CLIP






Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

- Wall recessed luminaire, for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Inner satin toughened flat glass diffuser
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Stainless steel springs for quick connection to recessed box
 - Recessed box (503) included
 - No visible screws
 - The luminaire is suitable for through-wiring



Private villa - Verona - Italy



INSERT + ZERO CLIP


INSERT+ ZERO CLIP

IP65 - IK08



LUMINAIRE VOLTAGE (V)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4.5	I	-	80	3000	A/M	-	511	142		310064	✓
4.5	I	-	80	2700	A/M	-	511	152		3115405	✓
4.5	I	-	80	3000	A/M	-	511	142		310066	✓
4.5	I	-	80	2700	A/M	-	511	152		3111780	✓
4.5	I	-	80	3000	A/M	-	511	142		310062	✓
4.5	I	-	80	2700	A/M	-	511	152		3115406	✓




INSERT+ ZERO GLASS



Scan the QR-code for the latest information

WH-87 / White / Textured

- Wall recessed luminaire, for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Inner satin toughened flat glass diffuser
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Stainless steel springs for quick connection to recessed box
 - Recessed box (503) included
 - No visible screws
 - The luminaire is suitable for through-wiring
 - GLASS versions have a front diffuser in toughened and screen printed glass



INSERT+ ZERO GLASS


INSERT+ ZERO GLASS

IP65 - IK05



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4.5	I	-	80	3000	S/EW	-	511	78	<input type="checkbox"/>	3114950	✓
4.5	I	-	80	2700	S/EW	-	511	73	<input type="checkbox"/>	3114949	✓

INSERT+ ZERO SM




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Indoor and outdoor wall-mount luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Polyester powder coat finish, die-cast, aluminium base for wall mounting
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Rapid spring-type installation
- No visible screws



INSERT+ ZERO SM

INSERT+ ZERO SM

IP65 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/W	-	483	157	■	3118110	✓
4	I	-	80	3000	A/W	-	442	151	■	3118107	✓
4	I	-	80	2700	A/W	-	435	148	■	3118104	✓
4	I	-	80	4000	A/W	-	483	157	■	3118109	✓
4	I	-	80	3000	A/W	-	442	151	■	3118106	✓
4	I	-	80	2700	A/W	-	435	148	■	3118103	✓
4	I	-	80	4000	A/W	-	483	157	□	3118108	✓
4	I	-	80	3000	A/W	-	442	151	□	3118105	✓
4	I	-	80	2700	A/W	-	435	148	□	3118102	✓

INSERT+ ZERO SM GLASS





Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Indoor and outdoor wall-mount luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Polyester powder coat finish, die-cast, aluminium base for wall mounting
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- No visible screws
- Rapid spring-type installation
- GLASS versions have a front diffuser in toughened and screen printed glass



INSERT+ ZERO SM GLASS

INSERT+ ZERO SM GLASS

IP65 - IK05




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	S/EW	-	483	89	■	3118119	✓
4	I	-	80	3000	S/EW	-	442	81	■	3118116	✓
4	I	-	80	2700	S/EW	-	435	80	■	3118113	✓
4	I	-	80	4000	S/EW	-	483	89	■	3118118	✓
4	I	-	80	3000	S/EW	-	442	81	■	3118115	✓
4	I	-	80	2700	S/EW	-	435	80	■	3118112	✓
4	I	-	80	4000	S/EW	-	483	89	□	3118117	✓
4	I	-	80	3000	S/EW	-	442	81	□	3118114	✓
4	I	-	80	2700	S/EW	-	435	80	□	3118111	✓

INSERT+ 1/2



House in Albánchez - Almería - Spain




Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Series of wall recessed luminaires for indoor and outdoor ,comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Electrical connector for cables Ø 7 - Ø 12 mm
- Built-in driver
- Stainless steel locking hardware
- Recessed box to be ordered separately
- The recessed box removable cover features two integral spirit levels for installation ease
- Retrofit kit adapter allows INSERT+ 1/2 to be installed in existing INSERT 1/2 recess boxes available as accessory (ordered separately)
- Supplied with 0,2 m pre-wired H07RN-F cable
- IP-rated through wiring connectors for cables Ø 7 - Ø 10.5 mm and Ø 14 - Ø 17 mm available as accessories (INSERT+ 2 models)









INSERT+
1



INSERT+
2

INSERT+ 1







IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	-	80	4000	A37/M	-	850	275		304117	✓
6	I	-	80	3000	A37/M	-	825	250		304116	✓
6	I	-	80	4000	A37/M	-	850	275		304119	✓
6	I	-	80	3000	A37/M	-	825	250		304118	✓
6	I	-	80	4000	A37/M	-	850	275		304115	✓
6	I	-	80	3000	A37/M	-	825	250		304114	✓



INSERT+ 2

IP65 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	-	80	4000	A25/W	-	1410	553		304123	✓
10	I	-	80	3000	A25/W	-	1350	503		304122	✓
10	I	-	80	4000	A25/W	-	1410	553		304125	✓
10	I	-	80	3000	A25/W	-	1350	503		304124	✓
10	I	-	80	4000	A25/W	-	1410	553		304121	✓
10	I	-	80	3000	A25/W	-	1350	503		304120	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1			
Recessed box INSERT+ 1		310475	✓
INSERT+ 2			
Recessed box Insert + 2		310490	✓




310475




Complete unit

1A+1B = please order 2 codes

	COMPONENTS
A	luminaire
B	recessed fixing kit



310475




310490

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1			
Adaptor INSERT+ 1 (retrofit kit Insert 1)	□	310476	✓
Adaptor INSERT+ 1 (retrofit kit Insert 1)	■	310477	✓
Adaptor INSERT+ 1 (retrofit kit Insert 1)	■	310478	✓
INSERT+ 2			
Adaptor INSERT+ 2 (retrofit kit Insert 2)	□	310487	✓
Adaptador INSERT+ 2 (retrofit kit Insert 2)	■	310488	✓
Adaptor INSERT+ 2 (retrofit kit Insert 2)	■	310489	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓




310495
310496




Complete unit

1A+1C = please order 2 codes

	COMPONENTS
A	luminaire
C	adaptor




INSERT 1




INSERT 2




INSERT+ 1



INSERT+ 2



310476
340477
310478



310487
310488
310489

INSERT+ 1 MARINE



Scan the QR-code for the latest information


■ BR-10 / Natural brass / Glossy

Series of wall recessed luminaires for indoor and outdoor ,comprising:

- Inner satin toughened flat glass diffuser
- EPDM sealing gasket
- Die-cast polished brass ring ISO 9223 (CX)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Electrical connector for cables Ø 7 - Ø 12 mm
- Built-in driver
- Stainless steel locking hardware
- Recessed box to be ordered separately
- The recessed box removable cover features two integral spirit levels for installation ease
- Supplied with 0,2 m pre-wired H07RN-F cable
- Metals with natural finish surface may oxidise with age. To restore the original brightness use commercial metal polish
- Die-cast corrosion resistant aluminium housing



Palm Beach Torreblanca - Malaga - Spain



INSERT+ 1 MARINE

INSERT+ 1 MARINE

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	-	80	4000	A37/M	-	850	354	■	304792	✓
6	I	-	80	3000	A37/M	-	825	325	■	304791	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1 MARINE			
Recessed box INSERT+ 1		310475	✓



310475

INSERT+ 1/2 V




Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Series of wall recessed luminaires for indoor and outdoor ,comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel springs for quick connection to recessed box
- No visible screws
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Recessed box to be ordered separately
- The recessed box removable cover features two integral spirit levels for installation ease
- Available for thorough wiring as accessories. Connectors fit $\varnothing 7 - \varnothing 10,5$ mm and $\varnothing 14 - \varnothing 17$ mm cables









INSERT+
1 V



INSERT+
2 V













INSERT+ 1 V

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/EW	-	418	197		3118537	✓
4	I	-	80	3000	A/EW	-	377	184		3118534	✓
4	I	-	80	4000	A/EW	-	418	197		3118536	✓
4	I	-	80	3000	A/EW	-	377	184		3118445	✓
4	I	-	80	4000	A/EW	-	418	197		3118535	✓
4	I	-	80	3000	A/EW	-	377	184		3118444	✓

INSERT+ 2 V

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634		3118198	✓
9	I	-	80	3000	A/EW	-	1197	592		3118195	✓
9	I	-	80	4000	A/EW	-	1318	634		3118197	✓
9	I	-	80	3000	A/EW	-	1197	592		3118194	✓
9	I	-	80	4000	A/EW	-	1318	634		3118196	✓
9	I	-	80	3000	A/EW	-	1197	592		3118193	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634		3118204	✓
9	I	-	80	3000	A/EW	-	1197	592		3118201	✓
9	I	-	80	4000	A/EW	-	1318	634		3118203	✓
9	I	-	80	3000	A/EW	-	1197	592		3118200	✓
9	I	-	80	4000	A/EW	-	1318	634		3118202	✓
9	I	-	80	3000	A/EW	-	1197	592		3118199	✓

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1 V			
Recessed box INSERT+ 1		310475	✓
INSERT+ 2 V			
Recessed box Insert + 2		310490	✓



310475



310490


Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1/2 V			
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓



310495
310496

INSERT+ 1 V GLASS




Scan the QR-code for the latest information

WH-87 / White / Textured

Series of wall recessed luminaires for indoor and outdoor ,comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel springs for quick connection to recessed box
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- No visible screws
- Recessed box to be ordered separately
- The recessed box removable cover features two integral spirit levels for installation ease
- GLASS versions have a front diffuser in toughened and screen printed glass



INSERT+ 1 V GLASS

INSERT+ 1 V GLASS

IP65 - IK06

LUMINAIRE VOLTAGE (V)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	S/EW	-	418	98	<input type="checkbox"/>	3118541	✓
4	I	-	80	3000	S/EW	-	377	92	<input type="checkbox"/>	3118538	✓



Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 1 V GLASS			
Recessed box INSERT+ 1		310475	✓



310475

INSERT+ 1 V SM




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Indoor and outdoor wall-mount luminaire, comprising:







- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Polyester powder coat finish, die-cast, aluminium base for wall mounting
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Rapid spring-type installation
- No visible screws



INSERT+ 1 V SM

INSERT+ 1 V SM

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/EW	-	418	197		3118464	✓
4	I	-	80	3000	A/EW	-	377	184		3118461	✓
4	I	-	80	4000	A/EW	-	418	197		3118463	✓
4	I	-	80	3000	A/EW	-	377	184		3118460	✓
4	I	-	80	4000	A/EW	-	418	197		3118462	✓
4	I	-	80	3000	A/EW	-	377	184		3118459	✓




INSERT+ 1 V SM GLASS



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured







- Indoor and outdoor wall-mount luminaire, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Polyester powder coat finish, die-cast, aluminium base for wall mounting
 - Inner satin toughened flat glass diffuser
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
 - Rapid spring-type installation
 - No visible screws
 - GLASS versions have a front diffuser in toughened and screen printed glass



INSERT+ 1 V SM GLASS

INSERT+ 1 V SM GLASS

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	S/EW	-	418	98		3118470	✓
4	I	-	80	3000	S/EW	-	377	92		3118467	✓
4	I	-	80	4000	S/EW	-	418	98		3118469	✓
4	I	-	80	3000	S/EW	-	377	92		3118466	✓
4	I	-	80	4000	S/EW	-	418	98		3118468	✓
4	I	-	80	3000	S/EW	-	377	92		3118465	✓



INSERT+ 3



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite grey / Textured

Solid and hollow wall recessed luminaire, for indoor and outdoor, comprising :


- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear toughened flat glass diffuser (A26/W versions)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Electrical connector for cables Ø 7 - Ø 12 mm
- Built-in driver
- Stainless steel locking hardware
- Recessed box to be ordered separately
- Supplied with 0,5 m pre-wired H07RN-F cable
- Anti-tampering locking kit available as accessory
- Available for thorough wiring as accessories. Connectors fit Ø 7 - Ø 10,5 mm and Ø 14 - Ø 17 mm cables



INSERT+3 A/W




INSERT+3 A26/W




INSERT+ 3

Identifying and classifying our optics



A/W - 27W - 4000K
180° | 90° | 270°



A26/W - 26W - 4000K
180° | 90° | 270°

INSERT+ 3 A/W

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	I	-	80	4000	A/W	-	4140	1592	■	3100879	✓
27	I	-	80	3000	A/W	-	4020	1502	■	3100877	✓
27	I	-	80	4000	A/W	-	4140	1592	■	3100878	✓
27	I	-	80	3000	A/W	-	4020	1502	■	3100876	✓



INSERT+ 3 A26/W

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	70	4000	A26/W	-	3585	1399	■	3100875	✓
26	I	-	70	3000	A26/W	-	3450	1388	■	3100881	✓
26	I	-	70	4000	A26/W	-	3585	1399	■	3100882	✓
26	I	-	70	3000	A26/W	-	3450	1388	■	3100880	✓



Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+3			
Recessed box INSERT+3		3100883	✓



3100883

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
INSERT+ 3			
Stainless steel, anti-tamper locking screws		3100992	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓




3100992



310495
310496

NOTTURNO



■ GR-11 / Anodised grey / Matt


Scan the QR-code for the latest information

Series of linear wall LED luminaires for indoor and outdoor, comprising:

- Extruded anodised aluminium housing
- Toughened, glass diffuser, silk-screened on the inside
- Stainless steel AISI 304 end caps
- Aluminium heat sink
- For luminaire installation, please select the appropriate bracket (available as mandatory accessory)
- Static ON/OFF or dimmable DALI options available



Palace Maffei - Verona - Italy




NOTTURNO
500

NOTTURNO
1000

NOTTURNO
1500

Identifying and classifying our optics



NOTTURNO 500

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED												
20	III	-	80	4000	S/I	-	2016	1623	■	504	304899	✓
20	III	-	80	4000	S/M	-	2016	1609	■	504	304900	✓
20	III	-	80	4000	ELL	13°x36°	2016	1606	■	504	304901	✓
20	III	-	80	3000	S/I	-	2016	1623	■	504	304896	✓
20	III	-	80	3000	S/M	-	2016	1609	■	504	304897	✓
20	III	-	80	3000	ELL	13°x36°	2016	1606	■	504	304898	✓
Power LED DALI												
20	III	-	80	4000	S/I	12°	2016	1623	■	504	3107538	✓
20	III	-	80	4000	S/M	30°	2016	1609	■	504	3107539	✓
20	III	-	80	4000	ELL	13°x36°	2016	1606	■	504	3107540	✓
20	III	-	80	3000	S/I	12°	2016	1623	■	504	3107534	✓
20	III	-	80	3000	S/M	30°	2016	1609	■	504	3107535	✓
20	III	-	80	3000	ELL	13°x36°	2016	1606	■	504	3107536	✓



NOTTURNO 1000

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED												
38	III	-	80	4000	S/I	-	4032	3122	■	972	304911	✓
38	III	-	80	4000	S/M	-	4032	3095	■	972	304912	✓
38	III	-	80	4000	ELL	13°x36°	4032	3088	■	972	304913	✓
38	III	-	80	3000	S/I	-	4032	3122	■	972	304908	✓
38	III	-	80	3000	S/M	-	4032	3095	■	972	304909	✓
38	III	-	80	3000	ELL	13°x36°	4032	3088	■	972	304910	✓



NOTTURNO 1500



IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED												
54	III	-	80	4000	S/I	-	6064	4621	■	1440	304923	✓
54	III	-	80	4000	S/M	-	6064	4581	■	1440	304924	✓
54	III	-	80	4000	ELL	13°x36°	6064	4571	■	1440	304925	✓
54	III	-	80	3000	S/I	-	6064	4621	■	1440	304920	✓
54	III	-	80	3000	S/M	-	6064	4581	■	1440	304921	✓
54	III	-	80	3000	ELL	13°x36°	6064	4571	■	1440	304922	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
NOTTURNO			
Power Supply Unit L500		310542	✓
Power Supply Unit L1000/1500		310543	✓
NOTTURNO - DALI			
Power Supply Unit DALI IN L500		3107574	✓
Boitier d'alimentation DALI IN / OUT L500		3107575	✓




310542
3107574
3107575

310543

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
NOTTURNO			
Bracket NOTTURNO (nr. 2)	■	310523	✓
Bracket (nr. 2)	■	310524	✓
NOTTURNO Telescopic bracket (nr. 2)	■	310978	✓
NOTTURNO ground support bracket (nr. 2)	■	310981	✓



310523


310524

310978



310981

OMBRA



■ GR-11 / Anodised grey / Matt


Scan the QR-code for the latest information

Series of linear wall LED luminaires for indoor and outdoor, comprising:


- Extruded anodised aluminium housing
- Toughened, glass diffuser, silk-screened on the inside
- Stainless steel AISI 304 end caps
- Anti-ageing custom moulded silicone sealing gasket(s)
- Aluminium heat sink
- Stainless steel locking hardware
- For luminaire installation, please select the appropriate bracket (available as mandatory accessory)
- Built-in driver
- Static ON/OFF or dimmable DALI options available



Casa Bau - Tortosa - Spain



Identifying and classifying our optics



OMBRA 500

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
20	I	-	80	4000	S/I	-	2016	1623	■	504	304935	✓
20	I	-	80	4000	S/M	-	2016	1609	■	504	304936	✓
20	I	-	80	4000	ELL	-	2016	1606	■	504	304937	✓
20	I	-	80	3000	S/I	-	2016	1623	■	504	304932	✓
20	I	-	80	3000	S/M	-	2016	1609	■	504	304933	✓
20	I	-	80	3000	ELL	-	2016	1606	■	504	304934	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
20	I	-	80	4000	S/I	12°	2016	1623	■	504	3107544	✓
20	I	-	80	4000	S/M	30°	2016	1609	■	504	3107545	✓
20	I	-	80	4000	ELL	13°x36°	2016	1606	■	504	3107546	✓
20	I	-	80	3000	S/I	12°	2016	1623	■	504	3107541	✓
20	I	-	80	3000	S/M	30°	2016	1609	■	504	3107542	✓
20	I	-	80	3000	ELL	13°x36°	2016	1606	■	504	3107543	✓



OMBRA 500 CL

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
20	I	-	80	4000	S/I	-	2016	1623	■	504	305834	✓
20	I	-	80	4000	S/M	-	2016	1609	■	504	305835	✓
20	I	-	80	4000	ELL	-	2016	1606	■	504	305836	✓
20	I	-	80	3000	S/I	-	2016	1623	■	504	305831	✓
20	I	-	80	3000	S/M	-	2016	1609	■	504	305832	✓
20	I	-	80	3000	ELL	-	2016	1606	■	504	305833	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
20	I	-	80	4000	S/I	12°	2016	1623	■	504	3107550	✓
20	I	-	80	4000	S/M	30°	2016	1609	■	504	3107551	✓
20	I	-	80	4000	ELL	13°x36°	2016	1606	■	504	3107552	✓
20	I	-	80	3000	S/I	12°	2016	1623	■	504	3107547	✓
20	I	-	80	3000	S/M	30°	2016	1609	■	504	3107548	✓
20	I	-	80	3000	ELL	13°x36°	2016	1606	■	504	3107549	✓



OMBRA 1000

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
38	I	-	80	4000	S/I	-	4032	3122	■	972	304947	✓
38	I	-	80	4000	S/M	-	4032	3095	■	972	304948	✓
38	I	-	80	4000	ELL	-	4032	3088	■	972	304949	✓
38	I	-	80	3000	S/I	-	4032	3122	■	972	304944	✓
38	I	-	80	3000	S/M	-	4032	3095	■	972	304945	✓
38	I	-	80	3000	ELL	-	4032	3088	■	972	304946	✓



OMBRA 1500


IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
54	I	-	80	4000	S/I	-	6064	4621	■	1440	304959	✓
54	I	-	80	4000	S/M	-	6064	4581	■	1440	304960	✓
54	I	-	80	4000	ELL	-	6064	4571	■	1440	304961	✓
54	I	-	80	3000	S/I	-	6064	4621	■	1440	304956	✓
54	I	-	80	3000	S/M	-	6064	4581	■	1440	304957	✓
54	I	-	80	3000	ELL	-	6064	4571	■	1440	304958	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
OMBRA			
OMBRA bracket (nr. 2)	■	310522	✓
Bracket (nr. 2)	■	310524	✓
OMBRA telescopic bracket OMBRA (nr. 2)	■	310977	✓
OMBRA ground support bracket (nr. 2)	■	310979	✓



310522



310524



310977



310979

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
OMBRA			
Wire for continuous power supply 3x1.5 mm		310569	✓




310569



Maffei Palace - Verona - Italy

STRIP SQUARE+




■ GR-11 / Anodised grey / Matt

Scan the QR-code for the latest information

Series of linear wall LED luminaires for indoor and outdoor, comprising:

- Extruded anodised aluminium housing
- Toughened, glass diffuser, silk-screened on the inside
- Coated die-cast aluminium end caps
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel locking hardware
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Adjustable wall mounting bracket for directing the luminaire
- High heat-dissipating aluminium gear tray for increased inner components lifespan
- Built-in driver
- Static ON/OFF or dimmable DALI options available
- Light colour and brightness dimming adjustable via Tunable White control system
- Tunable White (TW) options for dynamic lighting schemes CCT transition from 2700K to 6500K - (DALI DT8)
- DMX signal generator for RGBW versions available (ordered separately)




STRIP SQUARE+
528

STRIP SQUARE+
780

STRIP SQUARE+
1032

STRIP SQUARE+
1284

Identifying and classifying our optics



STRIP SQUARE+ 528

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
14	II	-	80	4000	A18/M	-	2130	1468	■	528	3109278	✓
14	II	-	80	4000	C/I	-	2130	1519	■	528	3109272	✓
14	II	-	80	4000	ELL	15°x45°	2130	1478	■	528	3109274	✓
14	II	-	80	4000	ELL	40°x60°	2130	1478	■	528	3109276	✓
14	II	-	80	3000	A18/M	-	2000	1374	■	528	3109277	✓
14	II	-	80	3000	C/I	-	2000	1425	■	528	3109271	✓
14	II	-	80	3000	ELL	15°x45°	2000	1384	■	528	3109273	✓
14	II	-	80	3000	ELL	40°x60°	2000	1384	■	528	3109275	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
14	II	-	80	4000	A18/M	-	2130	1468	■	528	3109310	✓
14	II	-	80	4000	C/I	-	2130	1519	■	528	3109304	✓
14	II	-	80	4000	ELL	15°x45°	2130	1478	■	528	3109306	✓
14	II	-	80	4000	ELL	40°x60°	2130	1478	■	528	3109308	✓
14	II	-	80	3000	A18/M	-	2000	1374	■	528	3109309	✓
14	II	-	80	3000	C/I	-	2000	1425	■	528	3109303	✓
14	II	-	80	3000	ELL	15°x45°	2000	1384	■	528	3109305	✓
14	II	-	80	3000	ELL	40°x60°	2000	1384	■	528	3109307	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
16	II	-	80	tw 2700-6500	ELL	15°x45°	2216	1142	■	528	3109335	✓

STRIP SQUARE+ 528 RGBW

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
RGBW LED												
15	III	-	80	rgbw 2700	ELL	15°x45°	1456	855	■	528	3109339	✓

STRIP SQUARE+ 780

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
20.5	II	-	80	4000	A18/M	-	3200	2136	■	780	3109286	✓
20.5	II	-	80	4000	C/I	-	3200	2216	■	780	3109280	✓
20.5	II	-	80	4000	ELL	15°x45°	3200	2152	■	780	3109282	✓
20.5	II	-	80	4000	ELL	40°x60°	3200	2152	■	780	3109284	✓
20.5	II	-	80	3000	A18/M	-	3000	2001	■	780	3109285	✓
20.5	II	-	80	3000	C/I	-	3000	2075	■	780	3109279	✓
20.5	II	-	80	3000	ELL	15°x45°	3000	2015	■	780	3109281	✓
20.5	II	-	80	3000	ELL	40°x60°	3000	2015	■	780	3109283	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
20.5	II	-	80	4000	A18/M	-	3200	2136	■	780	3109318	✓
20.5	II	-	80	4000	C/I	-	3200	2216	■	780	3109312	✓
20.5	II	-	80	4000	ELL	15°x45°	3200	2152	■	780	3109314	✓
20.5	II	-	80	4000	ELL	40°x60°	3200	2152	■	780	3109316	✓
20.5	II	-	80	3000	A18/M	-	3000	2001	■	780	3109317	✓
20.5	II	-	80	3000	C/I	-	3000	2075	■	780	3109311	✓
20.5	II	-	80	3000	ELL	15°x45°	3000	2015	■	780	3109313	✓
20.5	II	-	80	3000	ELL	40°x60°	3000	2015	■	780	3109315	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
22	II	-	80	tw 2700-6500	ELL	15°x45°	3324	1655	■	780	3109336	✓

STRIP SQUARE+ 780 RGBW

IP66 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
RGBW LED												
21	III	-	80	rgbw 2700	ELL	15°x45°	2185	1174	■	780	3109340	✓

STRIP SQUARE+ 1032

IP66 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
26	II	-	80	4000	A18/M	-	4260	2841	■	1032	3109294	✓
26	II	-	80	4000	C/I	-	4260	2946	■	1032	3109288	✓
26	II	-	80	4000	ELL	15°x45°	4260	2861	■	1032	3109290	✓
26	II	-	80	4000	ELL	40°x60°	4260	2861	■	1032	3109292	✓
26	II	-	80	3000	A18/M	-	4000	2660	■	1032	3109293	✓
26	II	-	80	3000	C/I	-	4000	2759	■	1032	3109287	✓
26	II	-	80	3000	ELL	15°x45°	4000	2680	■	1032	3109289	✓
26	II	-	80	3000	ELL	40°x60°	4000	2680	■	1032	3109291	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
26	II	-	80	4000	A18/M	-	4260	2841	■	1032	3109326	✓
26	II	-	80	4000	C/I	-	4260	2946	■	1032	3109320	✓
26	II	-	80	4000	ELL	15°x45°	4260	2861	■	1032	3109322	✓
26	II	-	80	4000	ELL	40°x60°	4260	2861	■	1032	3109324	✓
26	II	-	80	3000	A18/M	-	4000	2660	■	1032	3109325	✓
26	II	-	80	3000	C/I	-	4000	2759	■	1032	3109319	✓
26	II	-	80	3000	ELL	15°x45°	4000	2680	■	1032	3109321	✓
26	II	-	80	3000	ELL	40°x60°	4000	2680	■	1032	3109323	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
28	II	-	80	tw 2700-6500	ELL	15°x45°	4432	2252	■	1032	3109337	✓



STRIP SQUARE+ 1032 RGBW

IP66 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
27	III	-	80	rgbw 2700	ELL	15°x45°	2913	1624	■	1032	3109341	✓



STRIP SQUARE+ 1284

IP66 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
33	II	-	80	4000	A18/M	-	5400	3549	■	1284	3109302	✓
33	II	-	80	4000	C/I	-	5400	3681	■	1284	3109296	✓
33	II	-	80	4000	ELL	15°x45°	5400	3575	■	1284	3109298	✓
33	II	-	80	4000	ELL	40°x60°	5400	3575	■	1284	3109300	✓
33	II	-	80	3000	A18/M	-	5000	3324	■	1284	3109301	✓
33	II	-	80	3000	C/I	-	5000	3447	■	1284	3109295	✓
33	II	-	80	3000	ELL	15°x45°	5000	3348	■	1284	3109297	✓
33	II	-	80	3000	ELL	40°x60°	5000	3348	■	1284	3109299	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
33	II	-	80	4000	A18/M	-	5400	3549	■	1284	3109334	✓
33	II	-	80	4000	C/I	-	5400	3681	■	1284	3109328	✓
33	II	-	80	4000	ELL	15°x45°	5400	3575	■	1284	3109330	✓
33	II	-	80	4000	ELL	40°x60°	5400	3575	■	1284	3109332	✓
33	II	-	80	3000	A18/M	-	5000	3324	■	1284	3109333	✓
33	II	-	80	3000	C/I	-	5000	3447	■	1284	3109327	✓
33	II	-	80	3000	ELL	15°x45°	5000	3348	■	1284	3109329	✓
33	II	-	80	3000	ELL	40°x60°	5000	3348	■	1284	3109331	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
35	II	-	80	tw 2700-6500	ELL	15°x45°	5540	2867	■	1284	3109338	✓



STRIP SQUARE+ 1284 RGBW

IP66 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
32	III	-	80	rgbw 2700	ELL	15°x45°	3209	1965	■	1284	3109342	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
STRIP SQUARE+ RGBW			
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310950




310951



3117844



3117845



3115612

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+			
Connector 4 way IP68		3114174	✓
Connection Kit Y 3-way Ø 7-10,5 mm IP68		310496	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓




3114174



310495
310496

TYK+ 10





■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information


LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- High-transparency polycarbonate optics
- Optics assembly specifically developed for architectural lighting: custom-made optics achieve targeted illumination with precisely controlled beams without chromatic aberration
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Tear-proof nickelled brass cable gland M16x1.5 for cables Ø 5 mm - Ø 10 mm
- Stainless steel locking hardware
- Stainless steel wall-mounting bracket
- Complete with 1 m factory pre-wired cable H05RN-F 3G1 mm²
- Integral graduated stainless steel goniometer for precise aimings
- The snoot accessory is compatible with narrow-beam (C/I) optics
- Built-in driver
- For ELL 35x65 / 65x35 versions consult factory
- The TYK+ 10 RM versions are in class III, with no output cable and to be solely feed with the power supply units available as accessories
- Dimmable DALI2 power supply units are available, IP66-rated waterproof in powder-coated die-cast aluminium box or on IP20-rated plate to be incorporated in waterproof electrical cabinets
- The electrical connection between the power supply units and the related floodlights to be made with a maximum cable length of 20 metres
- RGBW and Tunable White versions to be powered with SELV drivers 48V DC, available as accessories to be ordered separately. Colour management through DMX interface
- DMX signal generator for RGBW and Tunable White versions to be ordered separately



TYK+ 10

Identifying and classifying our optics



TYK+ 10 C/I

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
7	I	-	90	2700	C/I	10°	530	418,65	■	3107285	✓
7	I	-	80	4000	C/I	10°	700	560,17	■	3107283	✓
7	I	-	80	3000	C/I	10°	650	518,9	■	3107284	✓



TYK+ 10 C/M

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
7	I	-	90	2700	C/M	34°	530	447	■	3107288	✓
7	I	-	80	4000	C/M	34°	700	598,1	■	3107286	✓
7	I	-	80	3000	C/M	34°	650	554,04	■	3107287	✓



TYK+ 10 RGBW C/M

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
RGBW LED											
6	III	-	80	rgbw 4000	C/M	30°	196	170	■	3113654	✓



TYK+ 10 TW C/M

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
TunableWhite Power LED											
5	III	-	90	tw 2700-5700	C/M	30°	500	443	■	3113655	✓



TYK+ 10 C/IW

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
7	I	-	90	2700	C/IW	65°	530	437,49	■	3107291	✓
7	I	-	80	4000	C/IW	65°	700	585,37	■	3107289	✓
7	I	-	80	3000	C/IW	65°	650	542,29	■	3107290	✓



TYK+ 10 ELL

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
7	I	-	90	2700	ELL	70°x9°	530	354,19	■	3107297	✓
7	I	-	90	2700	ELL	9°x70°	530	354,19	■	3107294	✓
7	I	-	80	4000	ELL	70°x9°	700	473	■	3107295	✓
7	I	-	80	4000	ELL	9°x70°	700	473,9	■	3107292	✓
7	I	-	80	3000	ELL	70°x9°	650	439	■	3107296	✓
7	I	-	80	3000	ELL	9°x70°	650	439	■	3107293	✓



TYK+ 10 RM C/I

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
15	III	-	90	2700	C/I	10°	1030	625,56	■	3112337	✓
15	III	-	80	4000	C/I	10°	1240	837	■	3112335	✓
15	III	-	80	3000	C/I	10°	1180	735,36	■	3112336	✓



TYK+ 10 RM C/M

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
15	III	-	90	2700	C/M	34°	1030	667,92	■	3112340	✓
15	III	-	80	4000	C/M	34°	1240	893,67	■	3112338	✓
15	III	-	80	3000	C/M	34°	1180	827,86	■	3112339	✓



TYK+ 10 RM C/IW

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
15	III	-	90	2700	C/IW	65°	1030	653,7	■	3112343	✓
15	III	-	80	4000	C/IW	65°	1240	874,65	■	3112341	✓
15	III	-	80	3000	C/IW	65°	1180	810,24	■	3112342	✓



TYK+ 10 RM ELL

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
15	III	-	90	2700	ELL	70°x9°	1030	530,33	■	3112349	✓
15	III	-	90	2700	ELL	9°x70°	1030	529,23	■	3112346	✓
15	III	-	80	4000	ELL	70°x9°	1240	709,59	■	3112347	✓
15	III	-	80	4000	ELL	9°x70°	1240	708,11	■	3112344	✓
15	III	-	80	3000	ELL	70°x9°	1180	657,33	■	3112348	✓
15	III	-	80	3000	ELL	9°x70°	1180	655,96	■	3112345	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+10 RGBW / TYK+10 TW			
Driver - CV 100W - 48 V kit		310950	✓
Driver - CV 500W - 48 V kit		310951	✓
Controller DMX touch black		3117845	✓
Controller DMX touch white		3117844	✓
TYK+ 10			
USB key EcoEcco		3115612	✓
TYK+ 10 RM			
DRIVER UNIT 20 W 1A - 1CH - DALI		3112413	✓
Driver Box 20 W 1A - 1CH - DALI	■	3112468	✓



310950




310951



3117845




3117844



3112413




3115612




3112468

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+ 10 C/I			
Anti-glare snoot	■	3107463	✓
TYK+ 10			
Barndoors painted	■	3112969	✓
Extra rotation bracket +25°/-90°		3108556	✓
Ground spike	■	700191	✓



3107463



3112969



3108556



700191



Chorus Life - Bergamo - Italy

TYK+ 15



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium separate housing compartments to maximise heat dissipation between electronic components and the LEDs, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- High-transparency polycarbonate optics
- Optics assembly specifically developed for architectural lighting: custom-made optics achieve targeted illumination with precisely controlled beams without chromatic aberration
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Tear-proof nickelled brass cable gland M20x1.5 for cables Ø 10 mm- Ø 14 mm
- Stainless steel locking hardware
- Stainless steel wall-mounting bracket
- Integral graduated stainless steel goniometer for precise aimings
- The snoot accessory is compatible with narrow-beam (C/I) optics
- Static ON/OFF or dimmable DALI options available




Oscar's church - Stockholm - Sweden



TYK+ 15

Identifying and classifying our optics



TYK+ 15 C/I

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/I	10°	1824	1220	■	LTS1603FB927	✓
24	I	✓	80	4000	C/I	10°	2640	1715	■	LTS1603FB840	✓
24	I	✓	80	3000	C/I	10°	2400	1575	■	LTS1603FB830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/I	10°	1824	1220	■	LTS1603DB927	✓
24	I	✓	80	4000	C/I	10°	2640	1715	■	LTS1603DB840	✓
24	I	✓	80	3000	C/I	10°	2400	1575	■	LTS1603DB830	✓



TYK+ 15 C/M

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/M	34°	1824	1370	■	LTS1603FF927	✓
24	I	✓	80	4000	C/M	34°	2640	1940	■	LTS1603FF840	✓
24	I	✓	80	3000	C/M	34°	2400	1760	■	LTS1603FF830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/M	34°	1824	1370	■	LTS1603DF927	✓
24	I	✓	80	4000	C/M	34°	2640	1940	■	LTS1603DF840	✓
24	I	✓	80	3000	C/M	34°	2400	1760	■	LTS1603DF830	✓



TYK+ 15 C/IW

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/IW	65°	1824	1350	■	LTS1603FJ927	✓
24	I	✓	80	4000	C/IW	65°	2640	1895	■	LTS1603FJ840	✓
24	I	✓	80	3000	C/IW	65°	2400	1730	■	LTS1603FJ830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
24	I	✓	90	2700	C/IW	65°	1824	1350	■	LTS1603DJ927	✓
24	I	✓	80	4000	C/IW	65°	2640	1895	■	LTS1603DJ840	✓
24	I	✓	80	3000	C/IW	65°	2400	1730	■	LTS1603DJ830	✓



TYK+ 15 ELL



IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
24	I	✓	90	2700	ELL	35°x65°	1824	825	■	LTS1603FK927	✓
24	I	✓	80	4000	ELL	35°x65°	2640	1155	■	LTS1603FK840	✓
24	I	✓	80	3000	ELL	35°x65°	2400	1075	■	LTS1603FK830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
24	I	✓	90	2700	ELL	35°x65°	1824	825	■	LTS1603DK927	✓
24	I	✓	80	4000	ELL	35°x65°	2640	1155	■	LTS1603DK840	✓
24	I	✓	80	3000	ELL	35°x65°	2400	1075	■	LTS1603DK830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+ 15			
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 1 luminaire	■	14029094	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 2 opposed luminaires	■	14047194	✓
Gliding support made of painted aluminium for the installation on Ø 90 mm posts	■	14099696	✓
Gliding support made of painted aluminium for the installation on Ø 60 mm posts	■	14099896	✓
Two-axis rotation bracket for gliding support		3107473	✓
Ground spike	■	700191	✓
Extra rotation bracket +55°/-90°		LTS1A2533	✓
Barndoors painted	■	LTS1A3561	✓
Anti-glare snoot	■	LTS1A3571	✓



TYK+ 20



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium separate housing compartments to maximise heat dissipation between electronic components and the LEDs, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- High-transparency polycarbonate optics
- Optics assembly specifically developed for architectural lighting: custom-made optics achieve targeted illumination with precisely controlled beams without chromatic aberration
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Tear-proof nickelled brass cable gland M20x1.5 for cables Ø 10 mm - Ø 14 mm
- Driver integral surge protection up to 6 kV (DM)
- Stainless steel locking hardware
- Stainless steel wall-mounting bracket
- Integral graduated stainless steel goniometer for precise aimings
- The snoot accessory is compatible with narrow-beam (C/I) optics
- Static ON/OFF or dimmable DALI options available
- For ELL 65x35 / 9x70 / 70x9 versions consult factory
- The RGBW versions to be powered with 48V DC SELV drivers, available as accessories. Colour management through DMX interface
- DMX signal generator for RGBW versions available (ordered separately)




Oscar's church - Stockholm - Sweden



TYK+ 20

Identifying and classifying our optics



TYK+ 20 C/I

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	-	90	2700	C/I	10°	4390	3432	■	3107330	✓
50	II	-	80	4000	C/I	10°	5880	4593,08	■	3107328	✓
50	II	-	80	3000	C/I	10°	5440	4254,82	■	3107329	✓
35	II	-	90	2700	C/I	10°	3113	2469,08	■	3107300	✓
35	II	-	80	4000	C/I	10°	4165	3303,63	■	3107298	✓
35	II	-	80	3000	C/I	10°	3858	3060,34	■	3107299	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
50	II	-	90	2700	C/I	10°	4390	3432,79	■	3107345	✓
50	II	-	80	4000	C/I	10°	5880	4593,08	■	3107343	✓
50	II	-	80	3000	C/I	10°	5440	4254,82	■	3107344	✓
35	II	-	90	2700	C/I	10°	3113	2469,08	■	3107315	✓
35	II	-	80	4000	C/I	10°	4165	3303,63	■	3107313	✓
35	II	-	80	3000	C/I	10°	3858	3060,34	■	3107314	✓



TYK+ 20 C/M

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	-	90	2700	C/M	34°	4390	3760,08	■	3107333	✓
50	II	-	80	4000	C/M	34°	5880	5030,99	■	3107331	✓
50	II	-	80	3000	C/M	34°	5440	4660,49	■	3107332	✓
35	II	-	90	2700	C/M	34°	3113	2747,67	■	3107303	✓
35	II	-	80	4000	C/M	34°	4165	3676,39	■	3107301	✓
35	II	-	80	3000	C/M	34°	3858	3405,64	■	3107302	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
50	II	-	90	2700	C/M	34°	4390	3760,08	■	3107348	✓
50	II	-	80	4000	C/M	34°	5880	5030,99	■	3107346	✓
50	II	-	80	3000	C/M	34°	5440	4660,49	■	3107347	✓
35	II	-	90	2700	C/M	34°	3113	2747,67	■	3107318	✓
35	II	-	80	4000	C/M	34°	4165	3676,39	■	3107316	✓
35	II	-	80	3000	C/M	34°	3858	3405,64	■	3107317	✓



TYK+ 20 RGBW C/M

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
RGBW LED											
37	III	-	80	rgbw 4000	C/M	30°	1832	1477	■	3112196	✓



TYK+ 20 C/IW

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	-	90	2700	C/IW	65°	4390	3713,36	■	3107336	✓
50	II	-	80	4000	C/IW	65°	5880	4968,48	■	3107334	✓
50	II	-	80	3000	C/IW	65°	5440	4602,58	■	3107335	✓
35	II	-	90	2700	C/IW	65°	3113	2667,6	■	3107306	✓
35	II	-	80	4000	C/IW	65°	4165	3569,26	■	3107304	✓
35	II	-	80	3000	C/IW	65°	3858	3306,4	■	3107305	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
50	II	-	90	2700	C/IW	65°	4390	3713,36	■	3107351	✓
50	II	-	80	4000	C/IW	65°	5880	4968,48	■	3107349	✓
50	II	-	80	3000	C/IW	65°	5440	4602,58	■	3107350	✓
35	II	-	90	2700	C/IW	65°	3113	2667,6	■	3107321	✓
35	II	-	80	4000	C/IW	65°	4165	3569,26	■	3107319	✓
35	II	-	80	3000	C/IW	65°	3858	3306,4	■	3107320	✓



TYK+ 20 ELL

IP66 - IK07 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	-	90	2700	ELL	35°x65°	4390	2335,54	■	3107339	✓
50	II	-	80	4000	ELL	35°x65°	5880	3124,96	■	3107337	✓
50	II	-	80	3000	ELL	35°x65°	5440	2894,82	■	3107338	✓
35	II	-	90	2700	ELL	35°x65°	3113	1677,92	■	3107309	✓
35	II	-	80	4000	ELL	35°x65°	4165	2245,06	■	3107307	✓
35	II	-	80	3000	ELL	35°x65°	3858	2080,01	■	3107308	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
50	II	-	90	2700	ELL	35°x65°	4390	2335,54	■	3107354	✓
50	II	-	80	4000	ELL	35°x65°	5880	3124,96	■	3107352	✓
50	II	-	80	3000	ELL	35°x65°	5440	2894,82	■	3107353	✓
35	II	-	80	4000	ELL	35°x65°	4165	2245,05	■	3107322	✓
35	II	-	80	3000	ELL	35°x65°	3858	2080,01	■	3107323	✓
30	II	-	90	2700	ELL	35°x65°	3113	1677,91	■	3107324	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+ 20			
USB key EcoEcco		3115612	✓
TYK+ 20 RGBW			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+ 20			
Barndoors painted	■	3112970	✓
Anti-glare snoot	■	3107466	✓
Extra rotation bracket +55°/-90°		3108557	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 1 luminaire	■	14029094	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 2 opposed luminaires	■	14047194	✓
Two-axis rotation bracket for gliding support		3107473	✓
Gliding support made of painted aluminium for the installation on Ø 90 mm posts	■	14099696	✓
Gliding support made of painted aluminium for the installation on Ø 60 mm posts	■	14099896	✓



TYK+ 30




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

- LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium separate housing compartments to maximise heat dissipation between electronic components and the LEDs, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
 - Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
 - High-transparency polycarbonate optics
 - Optics assembly specifically developed for architectural lighting: custom-made optics achieve targeted illumination with precisely controlled beams without chromatic aberration
 - Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
 - Tear-proof nickelled brass cable gland M20x1.5 for cables Ø 10 mm - Ø 14 mm
 - Each luminaire is supplied with two IP 68 cable gland allowing a single or a through power connection
 - Driver integral surge protection up to 6 kV (DM)
 - Stainless steel locking hardware
 - Stainless steel wall-mounting bracket
 - Integral graduated stainless steel goniometer for precise aimings
 - The snoot accessory is compatible with narrow-beam (C/I) optics
 - Static ON/OFF or dimmable DALI options available
 - For ELL 65x35 / 9x70 / 70x9 versions consult factory




Oscar's church - Stockholm - Sweden



TYK+ 30

Identifying and classifying our optics



TYK+ 30 C/I

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
85	II	-	90	2700	C/I	10°	8630	6140,05	■	3107360	✓
85	II	-	80	4000	C/I	10°	10650	8215,4	■	3107358	✓
85	II	-	80	3000	C/I	10°	9980	7610,38	■	3107359	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
85	II	-	90	2700	C/I	10°	8630	6140,05	■	3107375	✓
85	II	-	80	4000	C/I	10°	10650	8215,4	■	3107373	✓
85	II	-	80	3000	C/I	10°	9980	7610,38	■	3107374	✓



TYK+ 30 C/M

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
85	II	-	90	2700	C/M	34°	8630	6568	■	3107363	✓
85	II	-	80	4000	C/M	34°	10650	8788,01	■	3107361	✓
85	II	-	80	3000	C/M	34°	9980	8140,81	■	3107362	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
85	II	-	90	2700	C/M	34°	8630	6568	■	3107378	✓
85	II	-	80	4000	C/M	34°	10650	8788,01	■	3107376	✓
85	II	-	80	3000	C/M	34°	9980	8140,81	■	3107377	✓



TYK+ 30 C/IW

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
85	II	-	90	2700	C/IW	65°	8630	6437,13	■	3107366	✓
85	II	-	80	4000	C/IW	65°	10650	8612,89	■	3107364	✓
85	II	-	80	3000	C/IW	65°	9980	7978,58	■	3107365	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
85	II	-	90	2700	C/IW	65°	8630	6437,13	■	3107381	✓
85	II	-	80	4000	C/IW	65°	10650	8612,89	■	3107379	✓
85	II	-	80	3000	C/IW	65°	9980	7978,58	■	3107380	✓



TYK+ 30 ELL




IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
85	II	-	90	2700	ELL	35°x65°	8630	4154,34	■	3107369	✓
85	II	-	80	4000	ELL	35°x65°	10650	5558,53	■	3107367	✓
85	II	-	80	3000	ELL	35°x65°	9980	5149,17	■	3107368	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
85	II	-	90	2700	ELL	35°x65°	8630	4154,34	■	3107384	✓
85	II	-	80	4000	ELL	35°x65°	10650	5558,53	■	3107382	✓
85	II	-	80	3000	ELL	35°x65°	9980	5149,17	■	3107383	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TYK+ 30 C/I			
Anti-glare snoot	■	3107469	✓
TYK+ 30			
Extra rotation bracket +55°/-90°		3108558	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 1 luminaire	■	14029094	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 2 opposed luminaires	■	14047194	✓
Two-axis rotation bracket for gliding support		3107473	✓
Gliding support made of painted aluminium for the installation on Ø 60 mm posts	■	14099896	✓
Gliding support made of painted aluminium for the installation on Ø 90 mm posts	■	14099696	✓





Dymaeon wall - Patras - Greece

FOCUS+ ZERO



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:


- Polyester powder coat finish, die-cast aluminium housing, in compact size
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Aluminium reflector
- Waterproof cable gland M16x1.5 for cables Ø 5- Ø 10 mm
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Stainless steel locking hardware
- Adjustable mounting bracket made of die-cast aluminium, painted
- Complete with 1 m factory pre-wired cable H05RN-F 3G1 mm²
- The FOCUS+ZERO KIT versions are complete with 3 metres cable H05RN-F 3G1 mm²




Private Villa - Verona - Italy



FOCUS+ 2 - FOCUS+ 3



FOCUS+ ZERO



FOCUS+ ZERO KIT

FOCUS+ ZERO S/EW

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	S/EW	-	1485	1106,61	■	304611	✓
9.5	I	-	80	3000	S/EW	-	1350	1106,61	■	304610	✓
5	I	-	80	2700	S/EW	-	640	516,77	■	311191	✓



FOCUS+ ZERO KIT S/EW

IP65 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	S/EW	-	1485	1009,33	■	305509	✓
9.5	I	-	80	3000	S/EW	-	1350	1009,33	■	305508	✓
5	I	-	80	2700	S/EW	-	640	516,77	■	311192	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FOCUS+ ZERO - FOCUS+ ZERO KIT			
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓




310495
310496



Chapel of the Holy Shroud - Turin - Italy

FOCUS+1



Scan the QR-code for the latest information


■ AN-96 / Anthracite gray / Textured

LED floodlight for indoor and outdoor, comprising:


- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Waterproof cable gland M16x1.5 for cables \varnothing 5- \varnothing 10 mm
- Versions with 1-10 V dimmable ballast available (FOCUS+ 1 / 2 / 3). Consult Factory
- Built-in driver
- Stainless steel locking hardware
- Adjustable mounting bracket made of die-cast aluminium, painted
- Technopolymer ground spike available for anchoring to the ground



Church of the blessed virgin Mary - Borgo Nuovo - Verona - Italy



FOCUS+ 2 - FOCUS+ 3



FOCUS+1

FOCUS+1 A/M

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	A/M	10°	1880	1308	■	305098	✓
18	I	✓	70	3000	A/M	10°	1680	1170	■	305097	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	A/M	10°	1880	1308	■	305110	✓
18	I	✓	70	3000	A/M	10°	1680	1170	■	305109	✓



FOCUS+1 A/W

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	A/W	55°	1880	1239	■	305100	✓
18	I	✓	70	3000	A/W	55°	1680	1108	■	305099	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	A/W	55°	1880	1239	■	305112	✓
18	I	✓	70	3000	A/W	55°	1680	1108	■	305111	✓



FOCUS+1 C/I

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/I	17°	1880	1395	■	305486	✓
18	I	✓	70	3000	C/I	17°	1680	1247	■	305485	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/I	17°	1880	1395	■	305102	✓
18	I	✓	70	3000	C/I	17°	1680	1247	■	305101	✓



FOCUS+1 C/M

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/M	34°	1880	1389	■	305488	✓
18	I	✓	70	3000	C/M	34°	1680	1242	■	305487	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/M	34°	1880	1389	■	305104	✓
18	I	✓	70	3000	C/M	34°	1680	1242	■	305103	✓



FOCUS+1 C/W

IP66 - IK06

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/W	56°	1880	1320	■	305490	✓
18	I	✓	70	3000	C/W	56°	1680	1180	■	305489	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	C/W	56°	1880	1320	■	305106	✓
18	I	✓	70	3000	C/W	56°	1680	1180	■	305105	✓



FOCUS+1 ELL

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
18	I	✓	70	4000	ELL	15°x40°	1880	1462	■	305096	✓
18	I	✓	70	3000	ELL	15°x40°	1680	1307	■	305095	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
18	I	✓	70	4000	ELL	15°x40°	1880	1462	■	305108	✓
18	I	✓	70	3000	ELL	15°x40°	1680	1307	■	305107	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FOCUS+ 1			
Ground spike	■	700191	✓



700191

FOCUS+2



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Adjustable mounting bracket made of die-cast aluminium, painted
- Stainless steel locking hardware
- Cable gland M20x1.5 for cables Ø 7- Ø 12 mm (FOCUS+ 2 / 3)
- Versions with 1-10 V dimmable ballast available (FOCUS+ 1 / 2 / 3). Consult Factory




Chapel of the holy shroud - Turin - Italy



FOCUS+2

Identifying and classifying our optics



FOCUS+2 A/M

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	A/M	10°	2820	2069	■	305170	✓
26	I	✓	70	3000	A/M	10°	2520	1853	■	305169	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	A/M	10°	2820	2069	■	305182	✓
26	I	✓	70	3000	A/M	10°	2520	1853	■	305181	✓



FOCUS+2 A/W

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	A/W	55°	2820	2074	■	305172	✓
26	I	✓	70	3000	A/W	55°	2520	1857	■	305171	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	A/W	55°	2820	2074	■	305184	✓
26	I	✓	70	3000	A/W	55°	2520	1857	■	305183	✓



FOCUS+2 C/I

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/I	17°	2820	2189	■	305162	✓
26	I	✓	70	3000	C/I	17°	2520	1960	■	305161	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/I	17°	2820	2189	■	305174	✓
26	I	✓	70	3000	C/I	17°	2520	1960	■	305173	✓



FOCUS+2 C/M

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/M	34°	2820	2181	■	305164	✓
26	I	✓	70	3000	C/M	34°	2520	1953	■	305163	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/M	34°	2820	2181	■	305176	✓
26	I	✓	70	3000	C/M	34°	2520	1953	■	305175	✓



FOCUS+2 C/W

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/W	56°	2820	2037	■	305166	✓
26	I	✓	70	3000	C/W	56°	2520	1824	■	305165	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	C/W	56°	2820	2037	■	305178	✓
26	I	✓	70	3000	C/W	56°	2520	1824	■	305177	✓



FOCUS+2 ELL


IP66 - IK09

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	✓	70	4000	ELL	15°x40°	2820	2292	■	305168	✓
26	I	✓	70	3000	ELL	15°x40°	2520	2052	■	305167	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	✓	70	4000	ELL	15°x40°	2820	2292	■	305180	✓
26	I	✓	70	3000	ELL	15°x40°	2520	2052	■	305179	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
FOCUS+2			
Gliding support made of painted aluminium for the installation on Ø 60 mm posts	■	14099896	✓
Gliding support made of painted aluminium for the installation on Ø 90 mm posts	■	14099696	✓
Fixing bracket	■	311043	✓



Complete unit
 1A+1B+1C = please order 3 codes

COMPONENTS
A luminaire
B fixing bracket
C gliding support





Titul residential building - Moscow - Russia

FOCUS+3



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Adjustable mounting bracket made of die-cast aluminium, painted
- Stainless steel locking hardware
- Cable gland M20x1.5 for cables Ø 7- Ø 12 mm (FOCUS+ 2 / 3)
- Versions with 1-10 V dimmable ballast available (FOCUS+ 1 / 2 / 3). Consult Factory




Chapel of the holy shroud - Turin - Italy



FOCUS+3

Identifying and classifying our optics



FOCUS+3 A/M

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	A/M	10°	5640	3807	■	305242	✓
49	I	-	70	3000	A/M	10°	5040	3409	■	305241	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	A/M	10°	5640	3807	■	305254	✓
49	I	-	70	3000	A/M	10°	5040	3409	■	305253	✓



FOCUS+3 A/W

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	A/W	55°	5640	3820	■	305244	✓
49	I	-	70	3000	A/W	55°	5040	3420	■	305243	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	A/W	55°	5640	3820	■	305256	✓
49	I	-	70	3000	A/W	55°	5040	3420	■	305255	✓



FOCUS+3 C/I

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	C/I	17°	5640	4199	■	305234	✓
49	I	-	70	3000	C/I	17°	5040	3760	■	305233	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	C/I	17°	5640	4199	■	305246	✓
49	I	-	70	3000	C/I	17°	5040	3760	■	305245	✓



FOCUS+3 C/M

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	C/M	34°	5640	4114	■	305236	✓
49	I	-	70	3000	C/M	34°	5040	3683	■	305235	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	C/M	34°	5640	4114	■	305248	✓
49	I	-	70	3000	C/M	34°	5040	3683	■	305247	✓



FOCUS+3 C/W

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	C/W	56°	5640	3852	■	305238	✓
49	I	-	70	3000	C/W	56°	5040	3449	■	305237	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	C/W	56°	5640	3852	■	305250	✓
49	I	-	70	3000	C/W	56°	5040	3449	■	305249	✓



FOCUS+3 ELL

IP66 - IK09

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
49	I	-	70	4000	ELL	15°x40°	5640	4428	■	305240	✓
49	I	-	70	3000	ELL	15°x40°	5040	3964	■	305239	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
49	I	-	70	4000	ELL	15°x40°	5640	4428	■	305252	✓
49	I	-	70	3000	ELL	15°x40°	5040	3964	■	305251	✓



Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
FOCUS+3			
Gliding support made of painted aluminium for the installation on Ø 60 mm posts	■	14099896	✓
Gliding support made of painted aluminium for the installation on Ø 90 mm posts	■	14099696	✓
Fixing bracket	■	311043	✓




14099896



14099696




311043



Complete unit

1A+1B+1C = please order 3 codes



COMPONENTS	
A	luminaire
B	fixing bracket
C	gliding support





Chorus Life - Bergamo - Italy

GROOVE 21



■ GR-11 / Anodised grey / Matt

Scan the QR-code for the latest information

Series of class III reduced depth in-ground luminaires, comprising:

- Extruded anodised aluminium housing
- IP-67-rated double resin coating - transparent in the lower part to protect the LED from mechanical stresses and to guarantee maximum luminous efficiency - satin finish in the visible part, even in joints proximity, to ensure a homogeneous light distribution over the entire emitting area
- Technopolymer external box for electrical connection suitable for Ø 6 - 9 mm rubber cables. This is connected to the appliance with a 25 cm cable. It allows the appliance to be installed and connected without having to open it
- External power supply 48V has to be ordered separately
- Through-wiring designed
- Two-part fitting, consisting of LED luminaire and stainless steel recess box with anti-deformation cover (included). Tool-free installation of the luminaire in the recess box
- Recessed box to be ordered separately
- RGBW and Tunable White versions to be powered with SELV drivers 48V DC, available as accessories to be ordered separately. Colour management through DMX interface
- DMX signal generator for RGBW and Tunable White versions to be ordered separately
- Continuous mounted options and many other configurations are available at www.light-performer.com
- Design by Artec Studio



CONFIGURATOR LIGHT-PERFORMER®
www.light-performer.com

GROOVE 21 500

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
9,5	III	-	90	rgbw 3000	S/EW	-	-	-	■	500	3106645	✓
8	III	-	90	tw 2800-4800	S/EW	-	-	-	■	500	3106636	✓
5	III	-	90	4000	S/EW	-	540	160	■	500	3106621	✓
5	III	-	90	3000	S/EW	-	520	160	■	500	3106620	✓



GROOVE 21 500 T

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
9,5	III	-	90	rgbw 3000	S/EW	-	-	-	■	500	3106643	✓
8	III	-	90	tw 2800-4800	S/EW	-	-	-	■	500	3106634	✓
5	III	-	90	4000	S/EW	-	540	160	■	500	3106617	✓
5	III	-	90	3000	S/EW	-	520	160	■	500	3106616	✓



GROOVE 21 500 X

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
9,5	III	-	90	rgbw 3000	S/EW	-	-	-	■	500	3106644	✓
8	III	-	90	tw 2800-4800	S/EW	-	-	-	■	500	3106635	✓
5	III	-	90	4000	S/EW	-	540	160	■	500	3106619	✓
5	III	-	90	3000	S/EW	-	520	160	■	500	3106618	✓



GROOVE 21 1000

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
19	III	-	90	rgbw 3000	S/EW	-	-	-	■	994	3106646	✓
16	III	-	90	tw 2800-4800	S/EW	-	-	-	■	994	3106637	✓
10	III	-	90	4000	S/EW	-	1080	330	■	994	3106623	✓
10	III	-	90	3000	S/EW	-	1040	330	■	994	3106622	✓



GROOVE 21 1500

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
28,5	III	-	90	rgbw 3000	S/EW	-	-	-	■	1488	3106647	✓
24	III	-	90	tw 2800-4800	S/EW	-	-	-	■	1488	3106638	✓
15	III	-	90	4000	S/EW	-	1620	505	■	1488	3106625	✓
15	III	-	90	3000	S/EW	-	1560	505	■	1488	3106624	✓



GROOVE 21 2000

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
38	III	-	90	rgbw 3000	S/EW	-	-	-	■	1982	3106648	✓
32	III	-	90	tw 2800-4800	S/EW	-	-	-	■	1982	3106639	✓
20	III	-	90	4000	S/EW	-	2160	655	■	1982	3106627	✓
20	III	-	90	3000	S/EW	-	2080	655	■	1982	3106626	✓



GROOVE 21 R500

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
15	III	-	90	rgbw 3000	S/EW	-	-	-	■	515	3106649	✓
12.5	III	-	90	tw 2800-4800	S/EW	-	-	-	■	515	3106640	✓
8	III	-	90	4000	S/EW	-	860	255	■	515	3106629	✓
8	III	-	90	3000	S/EW	-	830	255	■	515	3106628	✓



GROOVE 21 R1200

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
11.5	III	-	90	rgbw 3000	S/EW	-	-	-	■	596	3106650	✓
9.5	III	-	90	tw 2800-4800	S/EW	-	-	-	■	596	3106641	✓
6	III	-	90	4000	S/EW	-	650	200	■	596	3106631	✓
6	III	-	90	3000	S/EW	-	625	200	■	596	3106630	✓



GROOVE 21 R2000

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED												
19	III	-	90	rgbw 3000	S/EW	-	-	-	■	977	3106651	✓
16	III	-	90	tw 2800-4800	S/EW	-	-	-	■	977	3106642	✓
10	III	-	90	4000	S/EW	-	1080	300	■	977	3106633	✓
10	III	-	90	3000	S/EW	-	1040	300	■	977	3106632	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
GROOVE 21			
KIT CONTROLLER 48 V - DALI		3106660	✓
KIT CONTROLLER 48 V - DMX		3106661	✓
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓



3106660



3106661




310950




310951

Mandatory accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
GROOVE 21			
Shaped joint (n. 2)		3111705	✓
T-shaped joint (n. 2)		3111706	✓
Kit closing cap (n. 2)		3111707	✓
Kit closing cap (n. 2)		3106662	✓
GROOVE 21 1000			
Recessed fixing kit GROOVE 21 1000		3106653	✓
GROOVE 21 R500			
Recessed fixing kit GROOVE 21 500		3106656	✓
Please consult our technical department			
Recessed fixing kit GROOVE 21 500		3106652	✓
Recessed fixing kit GROOVE 21 1500		3106654	✓
Recessed fixing kit GROOVE 21 1500		3106655	✓
Recessed fixing kit GROOVE 21 R1200		3106657	✓
Recessed box GROOVE 21 500 T-X		3106659	✓




3111705




3111706



3111707




3106662




3106653
3106654
3106655



3106656
3106657



3106652



3106659

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GROOVE 21			
Two-component epoxy resin - 50 ml		3116962	✓
Injector gun - aspect ratios 1:1/2:1		3116961	✓



3116962



3116961

STEEL SQUARE



■ INOX / Stainless steel / Glossy




Scan the QR-code for the latest information

Series of reduced depth in-ground luminaires, comprising:


- Black painted anodised die-cast aluminium housing
- Extra-clear toughened flat glass cover thickness 12 mm
- Optic compartment separate from the power compartment for better heat control
- Anti-ageing custom moulded silicone sealing gasket(s)
- Precision-cast stainless steel trim
- Mains connection through waterproof connection system (WATER-STOP)
- Built-in driver
- Stainless steel locking hardware
- Recessed box to be ordered separately
- Technopolymer recessed box allows water drainage through the Water-Drain™ system. The recessed rough-in kit is also equipped with a removable cover, with two bubble levels inside for quick installation
- LED extruded profiles may be oriented independently (+/- 10°)




Restaurant burg landshut - Bernkastel-Kues - Germany



STEEL SQUARE
20 - 6 LED




STEEL SQUARE
28 - 18 LED




STEEL SQUARE
34 - 24 LED

Identifying and classifying our optics



01 - 26 W - 3000 K
180° — 0° | 90° — 270°



02 - 26 W - 3000 K
180° — 0° | 90° — 270°

STEEL SQUARE 20 - 6 LED I 8°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6.6	I	-	80	3000	C/I	8°	510	346		301463	✓



STEEL SQUARE 20 - 6 LED ELL 10°X45°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6.6	I	-	80	3000	ELL	10°x45°	510	278		301469	✓



STEEL SQUARE 28 - 18 LED I 8°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	3000	C/I	8°	1530	1056		301484	✓



STEEL SQUARE 28 - 18 LED ELL 10°X45°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	-	80	3000	ELL	10°x45°	1530	852		301490	✓



STEEL SQUARE 34 - 24 LED I 8°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	80	3000	C/I	8°	2040	1357		301503	✓



STEEL SQUARE 34 - 24 LED ELL 10°X45°

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	80	3000	ELL	10°x45°	2040	1087		301509	✓



Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STEEL SQUARE			
Steel Recessed Fixing Kit, Square 20		310369	✓
Steel Recessed Fixing Kit, Square 28		310374	✓
Steel Recessed Fixing Kit, Square 34		310379	✓



310369



310374




310379



Complete unit
1A+1B = please order 2 codes
components
A gear body
B recessed fixing kit

TRACCIA



Scan the QR-code for the latest information


■ GR-11 / Anodised grey / Matt

Series of reduced depth in-ground luminaires, comprising:

- Extruded anodised aluminium housing
- EPDM sealing gasket
- Technopolymer anti-glare grid
- Toughened, glass diffuser, silk-screened on the inside
- Through-wiring designed
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Built-in driver
- Stainless steel locking hardware
- Recessed box to be ordered separately
- High heat-dissipating aluminium gear tray for increased inner components lifespan
- Integral unique device for field adjustable beam orientation (0° - 30°)
- Stand-alone or seamless linear compositions (up to 80 m) mounting options
- Static ON/OFF or dimmable DALI options available
- TRIMLESS options available. Consult factory



Fisherman monument - Egmond aan Zee - Netherlands




TRACCIA
500

TRACCIA
1000

TRACCIA
1500

Identifying and classifying our optics



TRACCIA 500

IP67 - IK10 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
21	I	-	80	4000	S/I	12°	2000	1769	■	525	305311	✓
21	I	-	80	4000	S/M	30°	2000	1759	■	525	305312	✓
21	I	-	80	4000	ELL	13°x36°	2000	1573	■	525	305313	✓
21	I	-	80	3000	S/I	12°	1900	1530	■	525	305308	✓
21	I	-	80	3000	S/M	30°	1900	1522	■	525	305309	✓
21	I	-	80	3000	ELL	13°x36°	1900	1362	■	525	305310	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
21	I	-	80	4000	S/I	12°	2000	1769	■	525	3107556	✓
21	I	-	80	4000	S/M	30°	2000	1759	■	525	3107557	✓
21	I	-	80	4000	ELL	13°x36°	2000	1573	■	525	3107558	✓
21	I	-	80	3000	S/I	12°	1900	1530	■	525	3107553	✓
21	I	-	80	3000	S/M	30°	1900	1522	■	525	3107554	✓
21	I	-	80	3000	ELL	13°x36°	1900	1362	■	525	3107555	✓



TRACCIA 1000

IP67 - IK10 - 850 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
42	I	-	80	4000	S/I	12°	4000	3274	■	1025	305323	✓
42	I	-	80	4000	S/M	30°	4000	3257	■	1025	305324	✓
42	I	-	80	4000	ELL	13°x36°	4000	2906	■	1025	305325	✓
42	I	-	80	3000	S/I	12°	3800	2832	■	1025	305320	✓
42	I	-	80	3000	S/M	30°	3800	2817	■	1025	305321	✓
42	I	-	80	3000	ELL	13°x36°	3800	2513	■	1025	305322	✓



TRACCIA 1500


IP67 - IK10 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
63	I	-	80	4000	S/I	12°	5700	5197	■	1525	305335	✓
63	I	-	80	4000	S/M	30°	5700	5170	■	1525	305336	✓
63	I	-	80	4000	ELL	13°x36°	5700	4614	■	1525	305337	✓
63	I	-	80	3000	S/I	12°	5450	4496	■	1525	305332	✓
63	I	-	80	3000	S/M	30°	5450	4472	■	1525	305333	✓
63	I	-	80	3000	ELL	13°x36°	5450	3991	■	1525	305334	✓



Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TRACCIA			
Recessed fixing Kit Traccia L500		310525	✓
Recessed fixing Kit Traccia L1000		310526	✓
Recessed fixing Kit Traccia L1500		310527	✓



310525
310526
310527



Complete unit
1A+1B = please order 2 codes
components
A gear body
B recessed fixing kit

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
TRACCIA			
Wire for continuous power supply 3x1.5 mm		310569	✓




310569

CRICKET+ 10



Cantina Valetti - Bardolino - Italy




- AN-96 / Anthracite gray / Textured
- INOX / Stainless steel / Matt



Scan the QR-code for the latest information

Series of reduced depth in-ground luminaires, comprising:

- Black painted anodised die-cast aluminium housing
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Extra-clear toughened flat safety glass with acid-etched finish (C/EW versions)
- Die-cast aluminium trim powder-coated
- Closing ring in AISI 316 stainless steel with satin finish (stainless steel versions)
- Mains connection through waterproof connection system (WATER-STOP)
- Technopolymer recess box to be ordered separately
- Stainless steel locking hardware
- Floor mounted luminaires are usually subject to harsh conditions. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- RGBW and Tunable White versions to be powered with SELV drivers 48V DC, available as accessories to be ordered separately. Colour management through DMX interface
- DMX signal generator for RGBW and Tunable White versions to be ordered separately




CRICKET+ 10

CRICKET+ 10
(3109879)

CRICKET+ 10 RGBW
(3113571)

Identifying and classifying our optics



CRICKET+ 10 C/I

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/I	-	355	363	■	3111887	✓
5	I	-	90	2700	C/I	-	355	363	■	3111884	✓
5	I	-	80	4000	C/I	-	475	446	■	3109824	✓
5	I	-	80	3000	C/I	-	440	415	■	3109825	✓
5	I	-	80	4000	C/I	-	475	446	■	3109818	✓
5	I	-	80	3000	C/I	-	440	415	■	3109819	✓



CRICKET+ 10 C/M

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/M	-	355	355,5	■	3111886	✓
5	I	-	90	2700	C/M	-	355	355,5	■	3111883	✓
5	I	-	80	4000	C/M	-	475	436	■	3109822	✓
5	I	-	80	3000	C/M	-	440	406	■	3109823	✓
5	I	-	80	4000	C/M	-	475	436	■	3109816	✓
5	I	-	80	3000	C/M	-	440	406	■	3109817	✓



CRICKET+ 10 RGBW C/M

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
RGBW LED											
3.5	III	-	80	rgbw 4000	C/M	30°	130	100	■	3112274	✓
3.5	III	-	80	rgbw 4000	C/M	30°	130	100	■	3112273	✓



CRICKET+ 10 TW C/M

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
TunableWhite Power LED											
6	III	-	80	tw 2700-5700	C/M	30°	440	310	■	3112277	✓
6	III	-	80	tw 2700-5700	C/M	30°	440	310	■	3112276	✓



CRICKET+ 10 C/EW

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/EW	-	355	106	■	3111885	✓
5	I	-	90	2700	C/EW	-	355	106	■	3111882	✓
5	I	-	80	4000	C/EW	-	475	278	■	3109820	✓
5	I	-	80	3000	C/EW	-	440	130	■	3109821	✓
5	I	-	80	4000	C/EW	-	475	142	■	3109814	✓
5	I	-	80	3000	C/EW	-	440	130	■	3109815	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 10 RGBW / CRICKET+ 10 TW			
Driver - CV 500 W - 48 V kit		310951	✓
Driver - CV 100 W - 48 V kit		310950	✓
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310951




310950



3117844




3117845




3115612

Mandatory accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 10			
Recessed box CRICKET+ 10		3109879	✓
CRICKET+ 10 RGBW			
Recessed box CRICKET+ 10 RGBW/TW		3113571	✓



3109879




3113571



Cantina Valetti - Bardolino - Italy

CRICKET+ 10 MARINE




■ BR-10 / Natural brass / Glossy



Scan the QR-code for the latest information


Series of reduced depth in-ground luminaires, comprising:

- Black painted anodised die-cast aluminium housing
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Extra-clear toughened flat safety glass with acid-etched finish (C/EW versions)
- Closing ring in marine brass with polished finish ISO 9223 (CX)
- Mains connection through waterproof connection system (WATER-STOP)
- Technopolymer recess box to be ordered separately
- Stainless steel locking hardware
- Floor mounted luminaires are usually subject to harsh conditions. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- RGBW and Tunable White versions to be powered with SELV drivers 48V DC, available as accessories to be ordered separately. Colour management through DMX interface
- DMX signal generator for RGBW and Tunable White versions to be ordered separately



CRICKET+ 10 MARINE CRICKET+ 10 MARINE (3109879) CRICKET+ 10 MARINE RGBW / TW (3113571)

Identifying and classifying our optics



CRICKET+ 10 C/I MARINE

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/I	-	355	363	☑	3111890	✓
5	I	-	80	4000	C/I	-	475	446	☑	3109830	✓
5	I	-	80	3000	C/I	-	440	415	☑	3109831	✓



CRICKET+ 10 C/M MARINE

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/M	-	355	355,5	☑	3111889	✓
5	I	-	80	4000	C/M	-	475	436	☑	3109828	✓
5	I	-	80	3000	C/M	-	440	406	☑	3109829	✓



CRICKET+ 10 RGBW C/M MARINE

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
RGBW LED											
3.5	III	-	80	rgbw 4000	C/M	30°	130	100	☑	3112275	✓



CRICKET+ 10 TW C/M MARINE

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
TunableWhite Power LED											
6	III	-	80	tw 2700-5700	C/M	30°	440	310	☑	3112282	✓



CRICKET+ 10 C/EW MARINE

IP67 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
5	I	-	90	2700	C/EW	-	355	106	☑	3111888	✓
5	I	-	80	4000	C/EW	-	475	142	☑	3109826	✓
5	I	-	80	3000	C/EW	-	440	132	☑	3109827	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 10 MARINE RGBW / CRICKET+ 10 MARINE TW			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310950




310951



3117844




3117845




3115612

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 10 MARINE			
Recessed box CRICKET+ 10		3109879	✓
CRICKET+ 10 MARINE RGBW / CRICKET+ 10 MARINE TW			
Recessed box CRICKET+ 10 RGBW/TW		3113571	✓



3109879




3113571

CRICKET+ 15



Hotel Don Carlos - Marbella - Spain





- AN-96 / Anthracite gray / Textured
- INOX / Stainless steel / Matt

Scan the QR-code for the latest information

Series of reduced depth in-ground luminaires, comprising:


- Black painted anodised die-cast aluminium housing
- Aluminium heat sink
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Die-cast aluminium trim powder-coated
- Die-cast aluminium trim, powder-coated, covered with AISI 316 stainless steel (stainless steel options)
- Mains connection through waterproof connection system (WATER-STOP)
- Technopolymer recessed box with reinforcing bars for driveability and integral WATER-DRAIN system available as accessory (ordered separately)
- Stainless steel locking hardware
- Floor mounted luminaires are usually subject to harsh conditions. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas



CRICKET+ 15

CRICKET+ 15
(311136)

Identifying and classifying our optics



CRICKET+ 15 A/M

IP67 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	90	2700	A5/M	-	1065	588	■	3111894	✓
14	I	-	90	2700	A5/M	-	1065	588	■	3111891	✓
14	I	-	80	4000	A5/M	-	1403	717	■	3108365	✓
14	I	-	80	3000	A5/M	-	1300	671	■	3108366	✓
14	I	-	80	4000	A5/M	-	1403	717	■	3108359	✓
14	I	-	80	3000	A5/M	-	1300	671	■	3108360	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	I	-	90	2700	A5/M	-	1065	588	■	3118704	✓
14	I	-	90	2700	A5/M	-	1065	588	■	3118701	✓
14	I	-	80	4000	A5/M	-	1403	717	■	3118695	✓
14	I	-	80	3000	A5/M	-	1300	671	■	3118696	✓
14	I	-	80	4000	A5/M	-	1403	717	■	3118689	✓
14	I	-	80	3000	A5/M	-	1300	671	■	3118690	✓



CRICKET+ 15 C/I

IP67 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	90	2700	C/I	-	1065	1000,8	■	3111895	✓
14	I	-	90	2700	C/I	-	1065	1000,8	■	3111892	✓
14	I	-	80	4000	C/I	-	1403	1069	■	3108369	✓
14	I	-	80	3000	C/I	-	1300	1000	■	3108370	✓
14	I	-	80	4000	C/I	-	1403	1069	■	3108363	✓
14	I	-	80	3000	C/I	-	1300	1000	■	3108364	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	I	-	90	2700	C/I	-	1065	1000,8	■	3118705	✓
14	I	-	90	2700	C/I	-	1065	1000,8	■	3118702	✓
14	I	-	80	4000	C/I	-	1403	1069	■	3118699	✓
14	I	-	80	3000	C/I	-	1300	1000	■	3118700	✓
14	I	-	80	4000	C/I	-	1403	1069	■	3118693	✓
14	I	-	80	3000	C/I	-	1300	1000	■	3118694	✓



CRICKET+ 15 C/M


IP67 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
14	I	-	90	2700	C/M	-	1065	986	■	3111896	✓
14	I	-	90	2700	C/M	-	1065	986	■	3111893	✓
14	I	-	80	4000	C/M	-	1403	1203	■	3108367	✓
14	I	-	80	3000	C/M	-	1300	1125	■	3108368	✓
14	I	-	80	4000	C/M	-	1403	1203	■	3108361	✓
14	I	-	80	3000	C/M	-	1300	1125	■	3108362	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
14	I	-	90	2700	C/M	-	1065	986	■	3118706	✓
14	I	-	90	2700	C/M	-	1065	986	■	3118703	✓
14	I	-	80	4000	C/M	-	1403	1203	■	3118697	✓
14	I	-	80	3000	C/M	-	1403	1125	■	3118698	✓
14	I	-	80	4000	C/M	-	1403	1203	■	3118691	✓
14	I	-	80	3000	C/M	-	1300	1125	■	3118692	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 15			
Recessed fixing kit		3111136	✓



3111136

CRICKET+ 20




- AN-96 / Anthracite gray / Textured
- INOX / Stainless steel / Matt


Scan the QR-code for the latest information

Series of reduced depth in-ground luminaires, comprising:

- Black painted anodised die-cast aluminium housing
- High-transparency polycarbonate optics
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Die-cast aluminium trim powder-coated
- Die-cast aluminium trim, powder-coated, covered with AISI 316 stainless steel (stainless steel options)
- Mains connection through waterproof connection system (WATER-STOP)
- Stainless steel locking hardware
- Technopolymer recess box to be ordered separately
- Floor mounted luminaires are usually subject to harsh conditions. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- Static ON/OFF or dimmable DALI options available
- For more RGBW options consult factory
- The RGBW versions to be powered with 48V DC SELV drivers, available as accessories. Colour management through DMX interface
- DMX signal generator for RGBW versions available (ordered separately)




CRICKET+ 20



CRICKET+ 20
(3111135)

Identifying and classifying our optics



CRICKET+ 20 A/M

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	90	2700	A5/M	-	3195	1570	■	3111900	✓
26	I	-	90	2700	A5/M	-	3195	1570	■	3111897	✓
26	I	-	80	4000	A5/M	-	2940	1916	■	3108377	✓
26	I	-	80	3000	A5/M	-	2724	1793	■	3108378	✓
26	I	-	80	4000	A5/M	-	2940	1916	■	3108371	✓
26	I	-	80	3000	A5/M	-	2724	1793	■	3108372	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	-	90	2700	A5/M	-	3195	1570	■	3111906	✓
26	I	-	90	2700	A5/M	-	3195	1570	■	3111903	✓
26	I	-	80	4000	A5/M	-	2940	1916	■	3108389	✓
26	I	-	80	3000	A5/M	-	2724	1793	■	3108390	✓
26	I	-	80	4000	A5/M	-	2940	1916	■	3108383	✓
26	I	-	80	3000	A5/M	-	2724	1793	■	3108384	✓



CRICKET+ 20 C/I

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	90	2700	C/I	-	3195	1907	■	3111901	✓
26	I	-	90	2700	C/I	-	3195	1907	■	3111898	✓
26	I	-	80	4000	C/I	-	2940	2326	■	3108381	✓
26	I	-	80	3000	C/I	-	2724	2177	■	3108382	✓
26	I	-	80	4000	C/I	-	2940	2326	■	3108375	✓
26	I	-	80	3000	C/I	-	2724	2177	■	3108376	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	-	90	2700	C/I	-	3195	1907	■	3111907	✓
26	I	-	90	2700	C/I	-	3195	1907	■	3111904	✓
26	I	-	80	4000	C/I	-	2940	2326	■	3108393	✓
26	I	-	80	3000	C/I	-	2724	2177	■	3108394	✓
26	I	-	80	4000	C/I	-	2940	2326	■	3108387	✓
26	I	-	80	3000	C/I	-	2724	2177	■	3108388	✓



CRICKET+ 20 C/M

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
26	I	-	90	2700	C/M	-	3195	2078	■	3111902	✓
26	I	-	90	2700	C/M	-	3195	2078	■	3111899	✓
26	I	-	80	4000	C/M	-	2940	2536	■	3108379	✓
26	I	-	80	3000	C/M	-	2794	2373	■	3108380	✓
26	I	-	80	4000	C/M	-	2940	2536	■	3108373	✓
26	I	-	80	3000	C/M	-	2794	2373	■	3108374	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
26	I	-	90	2700	C/M	-	3195	2078	■	3111908	✓
26	I	-	90	2700	C/M	-	3195	2078	■	3111905	✓
26	I	-	80	4000	C/M	-	2940	2536	■	3108391	✓
26	I	-	80	3000	C/M	-	2794	2373	■	3108392	✓
26	I	-	80	4000	C/M	-	2940	2536	■	3108385	✓
26	I	-	80	3000	C/M	-	2794	2373	■	3108386	✓



CRICKET+ 20 RGBW C/M

IP67 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
RGBW LED											
16.5	III	-	80	rgbw 4000	C/M	30°	1150	538	■	3112199	✓
16.5	III	-	80	rgbw 4000	C/M	30°	1150	538	■	3112198	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 20 RGBW			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310950



310951



3117844




3117845



3115612

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
CRICKET+ 20			
Recessed fixing kit		3111135	✓



3111135



St. Sauveur-le-Vicomte Castle - France

STRIP SQUARE+ INGROUND



■ GR-11 / Anodised grey / Matt


Scan the QR-code for the latest information

Series of reduced depth in-ground luminaires, comprising:

- Extruded anodised aluminium housing
- Toughened, glass diffuser, silk-screened on the inside
- Coated die-cast aluminium end caps
- Anti-ageing custom moulded silicone sealing gasket(s)
- Complete with IP-rated through wiring connection box (WATER-STOP) for cables Ø 5 mm to Ø 13 mm
- High heat-dissipating aluminium gear tray for increased inner components lifespan
- Built-in driver
- Static ON/OFF or dimmable DALI options available
- Light colour and brightness dimming adjustable via Tunable White control system
- Tunable White (TW) options for dynamic lighting schemes CCT transition from 2700K to 6500K - (DALI DT8)
- DMX signal generator for RGBW versions available (ordered separately)
- Stainless steel springs for fixing the luminaire to the outer housing
- Recessed box to be ordered separately
- Through-wiring designed



Restaurant burg landshut - Bernkastel-Kues - Germany




STRIP SQUARE+ INGROUND
550

STRIP SQUARE+ INGROUND
800

STRIP SQUARE+ INGROUND
1050

STRIP SQUARE+ INGROUND
1300

Identifying and classifying our optics



STRIP SQUARE+ INGROUND 550

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
14	I	-	80	4000	A18/M	-	2130	1468	■	550	3109356	✓
14	I	-	80	4000	C/I	-	2130	1519	■	550	3109350	✓
14	I	-	80	4000	ELL	15°x45°	2130	1478	■	550	3109352	✓
14	I	-	80	4000	ELL	40°x60°	2130	1478	■	550	3109354	✓
14	I	-	80	3000	A18/M	-	2000	1374	■	550	3109355	✓
14	I	-	80	3000	C/I	-	2000	1425	■	550	3109349	✓
14	I	-	80	3000	ELL	15°x45°	2000	1384	■	550	3109351	✓
14	I	-	80	3000	ELL	40°x60°	2000	1384	■	550	3109353	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
14	I	-	80	4000	A18/M	-	2130	1468	■	550	3109388	✓
14	I	-	80	4000	C/I	-	2130	1519	■	550	3109382	✓
14	I	-	80	4000	ELL	15°x45°	2130	1478	■	550	3109384	✓
14	I	-	80	4000	ELL	40°x60°	2130	1478	■	550	3109386	✓
14	I	-	80	3000	A18/M	-	2000	1374	■	550	3109387	✓
14	I	-	80	3000	C/I	-	2000	1425	■	550	3109381	✓
14	I	-	80	3000	ELL	15°x45°	2000	1384	■	550	3109383	✓
14	I	-	80	3000	ELL	40°x60°	2000	1384	■	550	3109385	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
16	I	-	80	tw 2700-6500	ELL	15°x45°	2216	1142	■	550	3109413	✓

STRIP SQUARE+ INGROUND 550 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
15	III	-	80	rgbw 2700	ELL	15°x45°	1456	855	■	550	3109417	✓

STRIP SQUARE+ INGROUND 800

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
20.5	I	-	80	4000	A18/M	-	3200	2136	■	802	3109364	✓
20.5	I	-	80	4000	C/I	-	3200	2216	■	802	3109358	✓
20.5	I	-	80	4000	ELL	15°x45°	3200	2152	■	802	3109360	✓
20.5	I	-	80	4000	ELL	40°x60°	3200	2152	■	802	3109362	✓
20.5	I	-	80	3000	A18/M	-	3000	2001	■	802	3109363	✓
20.5	I	-	80	3000	C/I	-	3000	2075	■	802	3109357	✓
20.5	I	-	80	3000	ELL	15°x45°	3000	2015	■	802	3109359	✓
20.5	I	-	80	3000	ELL	40°x60°	3000	2015	■	802	3109361	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
20.5	I	-	80	4000	A18/M	-	3200	2136	■	802	3109396	✓
20.5	I	-	80	4000	C/I	-	3200	2216	■	802	3109390	✓
20.5	I	-	80	4000	ELL	15°x45°	3200	2152	■	802	3109392	✓
20.5	I	-	80	4000	ELL	40°x60°	3200	2152	■	802	3109394	✓
20.5	I	-	80	3000	A18/M	-	3000	2001	■	802	3109395	✓
20.5	I	-	80	3000	C/I	-	3000	2075	■	802	3109389	✓
20.5	I	-	80	3000	ELL	15°x45°	3000	2015	■	802	3109391	✓
20.5	I	-	80	3000	ELL	40°x60°	3000	2015	■	802	3109393	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
22	I	-	80	tw 2700-6500	ELL	15°x45°	3324	1655	■	802	3109414	✓


















STRIP SQUARE+ INGROUND 800 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
21	III	-	80	rgbw 2700	ELL	15°x45°	2185	1174	■	802	3109418	✓


STRIP SQUARE+ INGROUND 1050

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
26	I	-	80	4000	A18/M	-	4260	2841		1054	3109372	✓
26	I	-	80	4000	C/I	-	4260	2946		1054	3109366	✓
26	I	-	80	4000	ELL	15°x45°	4260	2861		1054	3109368	✓
26	I	-	80	4000	ELL	40°x60°	4260	2861		1054	3109370	✓
26	I	-	80	3000	A18/M	-	4000	2660		1054	3109371	✓
26	I	-	80	3000	C/I	-	4000	2759		1054	3109365	✓
26	I	-	80	3000	ELL	15°x45°	4000	2680		1054	3109367	✓
26	I	-	80	3000	ELL	40°x60°	4000	2680		1054	3109369	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
26	I	-	80	4000	A18/M	-	4260	2841		1054	3109404	✓
26	I	-	80	4000	C/I	-	4260	2946		1054	3109398	✓
26	I	-	80	4000	ELL	15°x45°	4260	2861		1054	3109400	✓
26	I	-	80	4000	ELL	40°x60°	4260	2861		1054	3109402	✓
26	I	-	80	3000	A18/M	-	4000	2660		1054	3109403	✓
26	I	-	80	3000	C/I	-	4000	2759		1054	3109397	✓
26	I	-	80	3000	ELL	15°x45°	4000	2680		1054	3109399	✓
26	I	-	80	3000	ELL	40°x60°	4000	2680		1054	3109401	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
28	I	-	80	tw 2700-6500	ELL	15°x45°	4432	2252		1054	3109415	✓


















STRIP SQUARE+ INGROUND 1050 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
27	III	-	80	rgbw 2700	ELL	15°x45°	2913	1624		1054	3109419	✓


STRIP SQUARE+ INGROUND 1300

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
33	I	-	80	4000	A18/M	-	5400	3549		1306	3109380	✓
33	I	-	80	4000	C/I	-	5400	3681		1306	3109374	✓
33	I	-	80	4000	ELL	15°x45°	5400	3575		1306	3109376	✓
33	I	-	80	4000	ELL	40°x60°	5400	3575		1306	3109378	✓
33	I	-	80	3000	A18/M	-	5000	3324		1306	3109379	✓
33	I	-	80	3000	C/I	-	5000	3447		1306	3109373	✓
33	I	-	80	3000	ELL	15°x45°	5000	3348		1306	3109375	✓
33	I	-	80	3000	ELL	40°x60°	5000	3348		1306	3109377	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
33	I	-	80	4000	A18/M	-	5400	3549		1306	3109412	✓
33	I	-	80	4000	C/I	-	5400	3681		1306	3109406	✓
33	I	-	80	4000	ELL	15°x45°	5400	3575		1306	3109408	✓
33	I	-	80	4000	ELL	40°x60°	5400	3575		1306	3109410	✓
33	I	-	80	3000	A18/M	-	5000	3324		1306	3109411	✓
33	I	-	80	3000	C/I	-	5000	3447		1306	3109405	✓
33	I	-	80	3000	ELL	15°x45°	5000	3348		1306	3109407	✓
33	I	-	80	3000	ELL	40°x60°	5000	3348		1306	3109409	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
35	I	-	80	tw 2700-6500	ELL	15°x45°	5540	2867		1306	3109416	✓

STRIP SQUARE+ INGROUND 1300 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
32	III	-	80	rgbw 2700	ELL	15°x45°	3209	1965		1306	3109420	✓

Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
STRIP SQUARE+ INGROUND RGBW			
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310950

310951

3117844



3117845

3115612

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND			
Recessed fixing kit L 590 mm		310422	✓
Recessed fixing kit L 842 mm		310423	✓
Recessed fixing kit L 1094 mm		310424	✓
Recessed fixing kit L 1346 mm		310425	✓



310422

310423

310424

310425



Complete unit
1A+1B = please order 2 codes

	components
A	gear body
B	recessed fixing kit

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND RGBW			
Box for RGBW continuous row		3109576	✓




3109576


LASER+



Arena di Verona - European Volley Championship 2023 - Verona - Italy





■ GR-94 / Metallic grey / Textured




Scan the QR-code for the latest information

High-powered LED floodlight for indoor and outdoor, comprising:


- Die-cast aluminium bearing structure polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- UV and heat stabilised, technopolymer diffuser with integral custom moulded optics
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- High-efficiency die-cast aluminium heat sink
- Die-cast aluminium electrical connection box polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5)
- Light beam obtained by the combination of multiple LED modules
- Stainless steel locking hardware
- Die-cast aluminium bracket, polyester powder coat prior surface chemical conversion
- Electrical connection through a 1.5-meter piece of H07RN-F 7G1.5 cable, allowing the electrical connection without opening the luminaire body. The electrical connection, with the cable coming from the power supply unit, must be made using a suitable waterproof system (e.g. junction box) with at least IP66 protection rating.
- Galvanised powder-coated steel bracket (LASER+ 10)
- All LASER+ power consumption includes power unit losses
- Integral graduated goniometer for aiming purposes
- Tiltable optics assemblies $\pm 20^\circ$ (upper and lower body for LASER+30, the lower one for LASER+20) for punctual aiming and field settings
- For LASER+ 20/30 models use only the power supply units available as accessories (ordered separately)
- IP66-rated power control gears available in DALI and DMX-RDM. Maximum distance of 100 m cable length between control gear and luminaire
- Correctly match the floodlight with the control gear. Pay attention to the models and the number of connection channels: two (2CH) and three (3CH)
- All the power supply units are protected against mains surges of up to 10 kV (CM/DM)
- Integral control gearbox, placed in a powder-coated, sheet metal compartment. Mains connection trough M25x1.5 anti-tearing cable gland in polyamide box, for cables $\varnothing 9 - \varnothing 16$ mm (LASER+ 10 models)
- Integral DALI or DMX 512-RDM drivers depending on models (LASER+ 10)
- The LASER+ 10 versions are complete with additional surge protection device (SPD) up to 10 kV (CM/DM)
- Replaceable LED modules (future-proof) can be upgraded to prolong service life by qualified users, only
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For up lighting installation, consult factory
- Design by GIORGIO LODI



LASER+
10



LASER+
20



LASER+
30

LASER+ 10 A/I

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	A30/I	30°	61600	-	■	3119467	✓
542	I	✓	80	5700	A30/I	30°	79100	-	■	3119466	✓
542	I	✓	70	5700	A30/I	30°	86700	-	■	3119465	✓
542	I	✓	70	4000	A30/I	30°	90500	-	■	3119468	✓
Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz											
542	I	✓	90	5700	A30/I	30°	61600	-	■	3119483	✓
542	I	✓	80	5700	A30/I	30°	79100	-	■	3119482	✓
542	I	✓	70	5700	A30/I	30°	86700	-	■	3119481	✓
542	I	✓	70	4000	A30/I	30°	90500	-	■	3119484	✓



LASER+ 10 A/M

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	A50/M	50°	61600	-	■	3107713	✓
542	I	✓	90	5700	A60/M	60°	61600	-	■	3107717	✓
542	I	✓	80	5700	A50/M	50°	79100	-	■	3107712	✓
542	I	✓	80	5700	A60/M	60°	79100	-	■	3107716	✓
542	I	✓	70	5700	A50/M	50°	86700	-	■	3107711	✓
542	I	✓	70	5700	A60/M	60°	86700	-	■	3107715	✓
542	I	✓	70	4000	A50/M	50°	90500	-	■	3107714	✓
542	I	✓	70	4000	A60/M	60°	90500	-	■	3107718	✓
Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz											
542	I	✓	90	5700	A50/M	50°	61600	-	■	3113338	✓
542	I	✓	90	5700	A60/M	60°	61600	-	■	3113342	✓
542	I	✓	80	5700	A50/M	50°	79100	-	■	3113337	✓
542	I	✓	80	5700	A60/M	60°	79100	-	■	3113341	✓
542	I	✓	70	5700	A50/M	50°	86700	-	■	3113336	✓
542	I	✓	70	5700	A60/M	60°	86700	-	■	3113340	✓
542	I	✓	70	4000	A50/M	50°	90500	-	■	3113339	✓
542	I	✓	70	4000	A60/M	60°	90500	-	■	3113343	✓



LASER+ 10 C/I

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	C/I	10°	61600	-	■	3107689	✓
542	I	✓	90	5700	C/I	13°	61600	-	■	3107693	✓
542	I	✓	90	5700	C/I	16°	61600	-	■	3107697	✓
542	I	✓	80	5700	C/I	10°	79100	-	■	3107688	✓
542	I	✓	80	5700	C/I	13°	79100	-	■	3107692	✓
542	I	✓	80	5700	C/I	16°	79100	-	■	3107696	✓
542	I	✓	70	5700	C/I	10°	86700	-	■	3107687	✓
542	I	✓	70	5700	C/I	13°	86700	-	■	3107691	✓
542	I	✓	70	5700	C/I	16°	86700	-	■	3107695	✓
542	I	✓	70	4000	C/I	10°	90500	-	■	3107690	✓
542	I	✓	70	4000	C/I	13°	90500	-	■	3107694	✓
542	I	✓	70	4000	C/I	16°	90500	-	■	3107698	✓

Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz

542	I	✓	90	5700	C/I	10°	61600	-	■	3113314	✓
542	I	✓	90	5700	C/I	13°	61600	-	■	3113318	✓
542	I	✓	90	5700	C/I	16°	61600	-	■	3113322	✓
542	I	✓	80	5700	C/I	10°	79100	-	■	3113313	✓
542	I	✓	80	5700	C/I	13°	79100	-	■	3113317	✓
542	I	✓	80	5700	C/I	16°	79100	-	■	3113321	✓
542	I	✓	70	5700	C/I	10°	86700	-	■	3113312	✓
542	I	✓	70	5700	C/I	13°	86700	-	■	3113316	✓
542	I	✓	70	5700	C/I	16°	86700	-	■	3113320	✓
542	I	✓	70	4000	C/I	10°	90500	-	■	3113315	✓
542	I	✓	70	4000	C/I	13°	90500	-	■	3113319	✓
542	I	✓	70	4000	C/I	16°	90500	-	■	3113323	✓

LASER+ 10 ELL

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	ELL	10°x25°	61600	-	■	3107701	✓
542	I	✓	90	5700	ELL	15°x34°	61600	-	■	3107705	✓
542	I	✓	90	5700	ELL	30°x45°	61600	-	■	3107709	✓
542	I	✓	80	5700	ELL	10°x25°	79100	-	■	3107700	✓
542	I	✓	80	5700	ELL	15°x34°	79100	-	■	3107704	✓
542	I	✓	80	5700	ELL	30°x45°	79100	-	■	3107708	✓
542	I	✓	70	5700	ELL	10°x25°	86700	-	■	3107699	✓
542	I	✓	70	5700	ELL	15°x34°	86700	-	■	3107703	✓
542	I	✓	70	5700	ELL	30°x45°	86700	-	■	3107707	✓
542	I	✓	70	4000	ELL	10°x25°	90500	-	■	3107702	✓
542	I	✓	70	4000	ELL	15°x34°	90500	-	■	3107706	✓
542	I	✓	70	4000	ELL	30°x45°	90500	-	■	3107710	✓

Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz

542	I	✓	90	5700	ELL	10°x25°	61600	-	■	3113326	✓
542	I	✓	90	5700	ELL	15°x34°	61600	-	■	3113330	✓
542	I	✓	90	5700	ELL	30°x45°	61600	-	■	3113334	✓
542	I	✓	80	5700	ELL	10°x25°	79100	-	■	3113325	✓
542	I	✓	80	5700	ELL	15°x34°	79100	-	■	3113329	✓
542	I	✓	80	5700	ELL	30°x45°	79100	-	■	3113333	✓
542	I	✓	70	5700	ELL	10°x25°	86700	-	■	3113324	✓
542	I	✓	70	5700	ELL	15°x34°	86700	-	■	3113328	✓
542	I	✓	70	5700	ELL	30°x45°	86700	-	■	3113332	✓
542	I	✓	70	4000	ELL	10°x25°	90500	-	■	3113327	✓
542	I	✓	70	4000	ELL	15°x34°	90500	-	■	3113331	✓
542	I	✓	70	4000	ELL	30°x45°	90500	-	■	3113335	✓

LASER+ 20 A/I

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	A30/I	30°	120500	-	■	3119463	✓
1060	I	✓	80	5700	A30/I	30°	154700	-	■	3119462	✓
1060	I	✓	70	5700	A30/I	30°	169600	-	■	3119461	✓
1060	I	✓	70	4000	A30/I	30°	177000	-	■	3119464	✓



LASER+ 20 A/M

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	A50/M	50°	120500	-	■	3107681	✓
1060	I	✓	90	5700	A60/M	60°	120500	-	■	3107685	✓
1060	I	✓	80	5700	A50/M	50°	154700	-	■	3107680	✓
1060	I	✓	80	5700	A60/M	60°	154700	-	■	3107684	✓
1060	I	✓	70	5700	A50/M	50°	169600	-	■	3107679	✓
1060	I	✓	70	5700	A60/M	60°	169600	-	■	3107683	✓
1053	I	✓	70	4000	A50/M	50°	177000	-	■	3107682	✓
1053	I	✓	70	4000	A60/M	60°	177000	-	■	3107686	✓



LASER+ 20 C/I

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	C/I	10°	120500	-	■	3107657	✓
1060	I	✓	90	5700	C/I	13°	120500	-	■	3107661	✓
1060	I	✓	90	5700	C/I	16°	120500	-	■	3107665	✓
1060	I	✓	80	5700	C/I	10°	154700	-	■	3107656	✓
1060	I	✓	80	5700	C/I	13°	154700	-	■	3107660	✓
1060	I	✓	80	5700	C/I	16°	154700	-	■	3107664	✓
1060	I	✓	70	5700	C/I	10°	169600	-	■	3107655	✓
1060	I	✓	70	5700	C/I	13°	169600	-	■	3107659	✓
1060	I	✓	70	5700	C/I	16°	169600	-	■	3107663	✓
1053	I	✓	70	4000	C/I	10°	177000	-	■	3107658	✓
1053	I	✓	70	4000	C/I	13°	177000	-	■	3107662	✓
1053	I	✓	70	4000	C/I	16°	177000	-	■	3107666	✓



LASER+ 20 ELL

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	ELL	10°x25°	120500	-	■	3107669	✓
1060	I	✓	90	5700	ELL	15°x34°	120500	-	■	3107673	✓
1060	I	✓	90	5700	ELL	30°x45°	120500	-	■	3107677	✓
1060	I	✓	80	5700	ELL	10°x25°	154700	-	■	3107668	✓
1060	I	✓	80	5700	ELL	15°x34°	154700	-	■	3107672	✓
1060	I	✓	80	5700	ELL	30°x45°	154700	-	■	3107676	✓
1060	I	✓	70	5700	ELL	10°x25°	169600	-	■	3107667	✓
1060	I	✓	70	5700	ELL	15°x34°	169600	-	■	3107671	✓
1060	I	✓	70	5700	ELL	30°x45°	169600	-	■	3107675	✓
1053	I	✓	70	4000	ELL	10°x25°	177000	-	■	3107670	✓
1053	I	✓	70	4000	ELL	15°x34°	177000	-	■	3107674	✓
1053	I	✓	70	4000	ELL	30°x45°	177000	-	■	3107678	✓



LASER+ 30 A/I

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	A30/I	30°	181000	-	■	3119459	✓
1592	I	✓	80	5700	A30/I	30°	232400	-	■	3119458	✓
1592	I	✓	70	5700	A30/I	30°	254700	-	■	3119457	✓
1592	I	✓	70	4000	A30/I	30°	265800	-	■	3119460	✓



LASER+ 30 A/M

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	A50/M	50°	181000	-	■	3107649	✓
1592	I	✓	90	5700	A60/M	60°	181000	-	■	3107653	✓
1592	I	✓	80	5700	A50/M	50°	232400	-	■	3107648	✓
1592	I	✓	80	5700	A60/M	60°	232400	-	■	3107652	✓
1592	I	✓	70	5700	A50/M	50°	254700	-	■	3107647	✓
1592	I	✓	70	5700	A60/M	60°	254700	-	■	3107651	✓
1580	I	✓	70	4000	A50/M	50°	265800	-	■	3107650	✓
1580	I	✓	70	4000	A60/M	60°	265800	-	■	3107654	✓



LASER+ 30 C/I

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	C/I	10°	181000	-	■	3107625	✓
1592	I	✓	90	5700	C/I	13°	181000	-	■	3107629	✓
1592	I	✓	90	5700	C/I	16°	181000	-	■	3107633	✓
1592	I	✓	80	5700	C/I	10°	232400	-	■	3107624	✓
1592	I	✓	80	5700	C/I	13°	232400	-	■	3107628	✓
1592	I	✓	80	5700	C/I	16°	232400	-	■	3107632	✓
1592	I	✓	70	5700	C/I	10°	254700	-	■	3107623	✓
1592	I	✓	70	5700	C/I	13°	254700	-	■	3107627	✓
1592	I	✓	70	5700	C/I	16°	254700	-	■	3107631	✓
1580	I	✓	70	4000	C/I	10°	265800	-	■	3107626	✓
1580	I	✓	70	4000	C/I	13°	265800	-	■	3107630	✓
1580	I	✓	70	4000	C/I	16°	265800	-	■	3107634	✓




LASER+ 30 ELL


IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	ELL	10°x25°	181000	-	■	3107637	✓
1592	I	✓	90	5700	ELL	15°x34°	181000	-	■	3107641	✓
1592	I	✓	90	5700	ELL	30°x45°	181000	-	■	3107645	✓
1592	I	✓	80	5700	ELL	10°x25°	232400	-	■	3107636	✓
1592	I	✓	80	5700	ELL	15°x34°	232400	-	■	3107640	✓
1592	I	✓	80	5700	ELL	30°x45°	232400	-	■	3107644	✓
1592	I	✓	70	5700	ELL	10°x25°	254700	-	■	3107635	✓
1592	I	✓	70	5700	ELL	15°x34°	254700	-	■	3107639	✓
1592	I	✓	70	5700	ELL	30°x45°	254700	-	■	3107643	✓
1580	I	✓	70	4000	ELL	10°x25°	265800	-	■	3107638	✓
1580	I	✓	70	4000	ELL	15°x34°	265800	-	■	3107642	✓
1580	I	✓	70	4000	ELL	30°x45°	265800	-	■	3107646	✓






UP LIGHT POSITION




LENS :

C10	OK ✓
C13	OK ✓
C16	OK ✓
ELL10x25	OK ✓
ELL15x34	OK ✓
ELL30x45	OK ✓
A30	OK ✓
A50	OK ✓
A60	OK ✓



LENS :

C10	NO
C13	NO
C16	NO
ELL10x25	NO
ELL15x34	NO
ELL30x45	NO
A30	NO
A50	NO
A60	NO



LENS :

C10	NO
C13	OK ✓
C16	OK ✓
ELL10x25	OK ✓
ELL15x34	OK ✓
ELL30x45	OK ✓
A30	NO
A50	NO
A60	NO

For UP LIGHT installation, consult factory

UP LIGHT-AMBIENT TEMPERATURES

FITTING	CORRENT DRIVER	MODULE 740	MODULES 757-857-957	Ta
LASER+ 20 / DRIVER 1000 W	1400 mA	1053 W	1060 W	35 °C
LASER+ 20 / DRIVER 1000 W	1200 mA	899 W	917 W	40 °C
LASER+ 20 / DRIVER 1000 W	1050 mA	780 W	780 W	45 °C
LASER+ 20 / DRIVER 1000 W	850 mA	628 W	628 W	50 °C
LASER+ 30 / DRIVER 1500 W	1400 mA	1580 W	1592 W	35 °C
LASER+ 30 / DRIVER 1500 W	1200 mA	1349 W	1366 W	40 °C
LASER+ 30 / DRIVER 1500 W	1050 mA	1171 W	1171 W	45 °C
LASER+ 30 / DRIVER 1500 W	850 mA	941 W	941 W	50 °C


Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 20			
Driver box 1000 - 1,4 A - 2 CH - DALI		3109423	✓
Driver box 1000 - 1,4 A - 2 CH - DMX		3109424	✓
LASER+ 30			
Driver box 1500 - 1,4 A - 3 CH - DALI		3109421	✓
Driver box 1500 - 1,4 A - 3 CH - DMX		3109422	✓




3109421
3109422
3109423
3109424

Complete unit	
1A+1B = please order 2 codes	
COMPONENTS	
A	luminaire
B	drivers box



Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 10			
Louvre LASER+ 10 - 5°	■	3109551	✓
Louvre LASER+ 10 - 10°	■	3115076	✓
LASER+ 20			
Louvre LASER+ 20 - 5°	■	3115077	✓
Louvre LASER+ 20 - 10°	■	3115078	✓
LASER+ 30			
Louvre LASER+ 30 - 5°	■	3115079	✓
Louvre LASER+ 30 - 10°	■	3115080	✓
LASER+			
Pointer support		3109552	✓
Pointer support		3116553	✓
Brackets supports for driver		3117476	✓





Arena di Verona - European Volley Championship 2023 - Verona - Italy

LASER+ 10 EXTREME RM




Scan the QR-code for the latest information

■ GR-94 / Metallic grey / Textured

High-powered LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium bearing structure polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- UV and heat stabilised, technopolymer diffuser with integral custom moulded optics
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Ultra-high efficiency anodised extruded aluminium heat sink
- The superior heat dissipation provided by the extruded aluminium heat sink allows a maximum luminaire operating temperature of 50°C, without dimming down the system
- Technopolymer electrical connection box
- M20x1.5 cable gland for cables Ø10-Ø14 mm
- Light beam obtained by the combination of multiple LED modules
- Stainless steel locking hardware
- Galvanised powder-coated steel bracket
- All LASER+ power consumption includes power unit losses
- Integral graduated goniometer for aiming purposes
- For LASER+ 20/30 models use only the power supply units available as accessories (ordered separately)
- IP66-rated watertight power supply units with DALI or DMX-RDM dimming, with one channel (1CH - for one projector), two channels (1 + 1CH - for two projectors) and three channels (1 + 1 + 1CH - for three projectors) are available as an accessory. Maximum distance of 100 m cable length between the units and the luminaire (50 m for 1CH units)
- For the electrical connection between the two and three-channel power supply units and the projectors, use the watertight junction box available as an accessory
- Power supply units can be addressed separately for independent lighting management of each projector. Therefore, for the two and three-channel units, two and three dimming addresses will be needed respectively
- The power supply groups are made up of drivers with protection against mains power surges of up to 10 kV (CM/DM)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For up lighting installation, consult factory
- Design by GIORGIO LODI



LASER+ 10 EXTREME

LASER+ 10 EXTREME A/I RM

IP66 - IK09 - 750 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
542	I	-	90	5700	A30/I	30°	61600	-	■	3119491	✓
542	I	-	80	5700	A30/I	30°	79100	-	■	3119490	✓
542	I	-	70	5700	A30/I	30°	86700	-	■	3119489	✓
542	I	-	70	4000	A30/I	30°	90500	-	■	3119492	✓

LASER+ 10 EXTREME A/M RM

IP66 - IK09 - 750 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
542	I	-	90	5700	A50/M	50°	61600	-	■	3116877	✓
542	I	-	90	5700	A60/M	60°	61600	-	■	3116881	✓
542	I	-	80	5700	A50/M	50°	79100	-	■	3116876	✓
542	I	-	80	5700	A60/M	60°	79100	-	■	3116880	✓
542	I	-	70	5700	A50/M	50°	86700	-	■	3116875	✓
542	I	-	70	5700	A60/M	60°	86700	-	■	3116879	✓
542	I	-	70	4000	A50/M	50°	90500	-	■	3116878	✓
542	I	-	70	4000	A60/M	60°	90500	-	■	3116882	✓

LASER+ 10 EXTREME C/I RM

IP66 - IK08 - 750 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
542	I	-	90	5700	C/I	10°	61600	-	■	3116849	✓
542	I	-	90	5700	C/I	13°	61600	-	■	3116853	✓
542	I	-	90	5700	C/I	16°	61600	-	■	3116857	✓
542	I	-	80	5700	C/I	10°	79100	-	■	3116848	✓
542	I	-	80	5700	C/I	13°	79100	-	■	3116852	✓
542	I	-	80	5700	C/I	16°	79100	-	■	3116856	✓
542	I	-	70	5700	C/I	10°	86700	-	■	3116847	✓
542	I	-	70	5700	C/I	13°	86700	-	■	3116851	✓
542	I	-	70	5700	C/I	16°	86700	-	■	3116855	✓
542	I	-	70	4000	C/I	10°	90500	-	■	3116850	✓
542	I	-	70	4000	C/I	13°	90500	-	■	3116854	✓
542	I	-	70	4000	C/I	16°	90500	-	■	3116858	✓

LASER+ 10 EXTREME ELL RM

IP66 - IK08 - 750 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
542	I	-	90	5700	ELL	10°x25°	61600	-	■	3116861	✓
542	I	-	90	5700	ELL	15°x34°	61600	-	■	3116865	✓
542	I	-	90	5700	ELL	30°x45°	61600	-	■	3116869	✓
542	I	-	80	5700	ELL	10°x25°	79100	-	■	3116860	✓
542	I	-	80	5700	ELL	15°x34°	79100	-	■	3116864	✓
542	I	-	80	5700	ELL	30°x45°	79100	-	■	3116868	✓
542	I	-	70	5700	ELL	10°x25°	86700	-	■	3116859	✓
542	I	-	70	5700	ELL	15°x34°	86700	-	■	3116863	✓
542	I	-	70	5700	ELL	30°x45°	86700	-	■	3116867	✓
542	I	-	70	4000	ELL	10°x25°	90500	-	■	3116862	✓
542	I	-	70	4000	ELL	15°x34°	90500	-	■	3116866	✓
542	I	-	70	4000	ELL	30°x45°	90500	-	■	3116870	✓

Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 10 EXTREME			
DRIVER BOX 600 W - 1,4 A - 1 CH - DALI		3116294	✓
DRIVER BOX 600 W - 1,4 A - 1 CH - DMX		3116295	✓
DRIVER BOX 1000 W - 1,4 A - 1+1 CH - DALI		3116296	✓
DRIVER BOX 1000 W - 1,4 A - 1+1 CH - DMX		3116297	✓
DRIVER BOX 1500 W - 1,4 A - 1+1+1 CH - DALI		3116298	✓
DRIVER BOX 1500 W - 1,4 A - 1+1+1 CH - DMX		3116299	✓




3116294
3116295




3116296
3116297
3116298
3116299

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 10 EXTREME RM			
Louvre LASER+ 10 - 5°	■	3109551	✓
Louvre LASER+ 10 - 10°	■	3115076	✓
Pointer support		3109552	✓
Connection Kit Y 2-3-way		3116044	✓



3109551



3115076




3109552



3116044

LASER+ EXTREME





■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

High-powered LED floodlight for indoor and outdoor, comprising:


- Die-cast aluminium bearing structure polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- UV and heat stabilised, technopolymer diffuser with integral custom moulded optics
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Ultra-high efficiency anodised extruded aluminium heat sink
- The superior heat dissipation provided by the extruded aluminium heat sink allows a maximum luminaire operating temperature of 50°C, without dimming down the system
- Galvanised powder-coated steel bracket (LASER+ 10)
- Die-cast aluminium electrical connection box polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5)
- Electrical connection through a 1.5-meter piece of H07RN-F 7G1.5 cable, allowing the electrical connection without opening the luminaire body. The electrical connection, with the cable coming from the power supply unit, must be made using a suitable waterproof system (e.g. junction box) with at least IP66 protection rating.
- Light beam obtained by the combination of multiple LED modules
- Die-cast aluminium bracket, polyester powder coat prior surface chemical conversion
- Stainless steel locking hardware
- All LASER+ power consumption includes power unit losses
- Integral graduated goniometer for aiming purposes
- For LASER+ 20/30 models use only the power supply units available as accessories (ordered separately)
- IP66-rated power control gears available in DALI and DMX-RDM. Maximum distance of 100 m cable length between control gear and luminaire
- Correctly match the floodlight with the control gear. Pay attention to the models and the number of connection channels: two (2CH) and three (3CH)
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Integral control gearbox, placed in a powder-coated, sheet metal compartment. Mains connection trough M25x1.5 anti-tearing cable gland in polyamide box, for cables Ø 9 - Ø 16 mm (LASER+ 10 models)
- Integral DALI or DMX 512-RDM drivers depending on models (LASER+ 10)
- The LASER+ 10 versions are complete with additional surge protection device (SPD) up to 10 kV (CM/DM)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For up lighting installation, consult factory
- Design by GIORGIO LODI



LASER+
10 EXTREME



LASER+
20 EXTREME



LASER+
30 EXTREME

LASER+ 10 EXTREME A/I

IP66 - IK09 - 960 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	A30/I	30°	61600	-	■	3119479	✓
542	I	✓	80	5700	A30/I	30°	79100	-	■	3119478	✓
542	I	✓	70	5700	A30/I	30°	86700	-	■	3119477	✓
542	I	✓	70	4000	A30/I	30°	90500	-	■	3119480	✓
Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz											
542	I	✓	90	5700	A30/I	30°	61600	-	■	3119487	✓
542	I	✓	80	5700	A30/I	30°	79100	-	■	3119486	✓
542	I	✓	70	5700	A30/I	30°	86700	-	■	3119485	✓
542	I	✓	70	4000	A30/I	30°	90500	-	■	3119488	✓

LASER+ 10 EXTREME A/M

IP66 - IK09 - 960 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	A50/M	50°	61600	-	■	3107809	✓
542	I	✓	90	5700	A60/M	60°	61600	-	■	3107813	✓
542	I	✓	80	5700	A50/M	50°	79100	-	■	3107808	✓
542	I	✓	80	5700	A60/M	60°	79100	-	■	3107812	✓
542	I	✓	70	5700	A50/M	50°	86700	-	■	3107807	✓
542	I	✓	70	5700	A60/M	60°	86700	-	■	3107811	✓
542	I	✓	70	4000	A50/M	50°	90500	-	■	3107810	✓
542	I	✓	70	4000	A60/M	60°	90500	-	■	3107814	✓
Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz											
542	I	✓	90	5700	A50/M	50°	61600	-	■	3113374	✓
542	I	✓	90	5700	A60/M	60°	61600	-	■	3113378	✓
542	I	✓	80	5700	A50/M	50°	79100	-	■	3113373	✓
542	I	✓	80	5700	A60/M	60°	79100	-	■	3113377	✓
542	I	✓	70	5700	A50/M	50°	86700	-	■	3113372	✓
542	I	✓	70	5700	A60/M	60°	86700	-	■	3113376	✓
542	I	✓	70	4000	A50/M	50°	90500	-	■	3113375	✓
542	I	✓	70	4000	A60/M	60°	90500	-	■	3113379	✓

LASER+ 10 EXTREME C/I

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	C/I	10°	61600	-	■	3107785	✓
542	I	✓	90	5700	C/I	13°	61600	-	■	3107789	✓
542	I	✓	90	5700	C/I	16°	61600	-	■	3107793	✓
542	I	✓	80	5700	C/I	10°	79100	-	■	3107784	✓
542	I	✓	80	5700	C/I	13°	79100	-	■	3107788	✓
542	I	✓	80	5700	C/I	16°	79100	-	■	3107792	✓
542	I	✓	70	5700	C/I	10°	86700	-	■	3107783	✓
542	I	✓	70	5700	C/I	13°	86700	-	■	3107787	✓
542	I	✓	70	5700	C/I	16°	86700	-	■	3107791	✓
542	I	✓	70	4000	C/I	10°	90500	-	■	3107786	✓
542	I	✓	70	4000	C/I	13°	90500	-	■	3107790	✓
542	I	✓	70	4000	C/I	16°	90500	-	■	3107794	✓

Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz

542	I	✓	90	5700	C/I	10°	61600	-	■	3113350	✓
542	I	✓	90	5700	C/I	13°	61600	-	■	3113354	✓
542	I	✓	90	5700	C/I	16°	61600	-	■	3113358	✓
542	I	✓	80	5700	C/I	10°	79100	-	■	3113349	✓
542	I	✓	80	5700	C/I	13°	79100	-	■	3113353	✓
542	I	✓	80	5700	C/I	16°	79100	-	■	3113357	✓
542	I	✓	70	5700	C/I	10°	86700	-	■	3113348	✓
542	I	✓	70	5700	C/I	13°	86700	-	■	3113352	✓
542	I	✓	70	5700	C/I	16°	86700	-	■	3113356	✓
542	I	✓	70	4000	C/I	10°	90500	-	■	3113351	✓
542	I	✓	70	4000	C/I	13°	90500	-	■	3113355	✓
542	I	✓	70	4000	C/I	16°	90500	-	■	3113359	✓

LASER+ 10 EXTREME ELL

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
542	I	✓	90	5700	ELL	10°x25°	61600	-	■	3107797	✓
542	I	✓	90	5700	ELL	15°x34°	61600	-	■	3107801	✓
542	I	✓	90	5700	ELL	30°x45°	61600	-	■	3107805	✓
542	I	✓	80	5700	ELL	10°x25°	79100	-	■	3107796	✓
542	I	✓	80	5700	ELL	15°x34°	79100	-	■	3107800	✓
542	I	✓	80	5700	ELL	30°x45°	79100	-	■	3107804	✓
542	I	✓	70	5700	ELL	10°x25°	86700	-	■	3107795	✓
542	I	✓	70	5700	ELL	15°x34°	86700	-	■	3107799	✓
542	I	✓	70	5700	ELL	30°x45°	86700	-	■	3107803	✓
542	I	✓	70	4000	ELL	10°x25°	90500	-	■	3107798	✓
542	I	✓	70	4000	ELL	15°x34°	90500	-	■	3107802	✓
542	I	✓	70	4000	ELL	30°x45°	90500	-	■	3107806	✓

Power LED - dimmable DMX-RDM 220-240 V 50/60 Hz

542	I	✓	90	5700	ELL	10°x25°	61600	-	■	3113362	✓
542	I	✓	90	5700	ELL	15°x34°	61600	-	■	3113366	✓
542	I	✓	90	5700	ELL	30°x45°	61600	-	■	3113370	✓
542	I	✓	80	5700	ELL	10°x25°	79100	-	■	3113361	✓
542	I	✓	80	5700	ELL	15°x34°	79100	-	■	3113365	✓
542	I	✓	80	5700	ELL	30°x45°	79100	-	■	3113369	✓
542	I	✓	70	5700	ELL	10°x25°	86700	-	■	3113360	✓
542	I	✓	70	5700	ELL	15°x34°	86700	-	■	3113364	✓
542	I	✓	70	5700	ELL	30°x45°	86700	-	■	3113368	✓
542	I	✓	70	4000	ELL	10°x25°	90500	-	■	3113363	✓
542	I	✓	70	4000	ELL	15°x34°	90500	-	■	3113367	✓
542	I	✓	70	4000	ELL	30°x45°	90500	-	■	3113371	✓

LASER+ 20 EXTREME A/I

IP66 - IK09 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	A30/I	30°	120500	-	■	3119475	✓
1060	I	✓	80	5700	A30/I	30°	154700	-	■	3119474	✓
1060	I	✓	70	5700	A30/I	30°	169600	-	■	3119473	✓
1060	I	✓	70	4000	A30/I	30°	177000	-	■	3119476	✓

LASER+ 20 EXTREME A/M

IP66 - IK09 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	A50/M	50°	120500	-	■	3107777	✓
1060	I	✓	90	5700	A60/M	60°	120500	-	■	3107781	✓
1060	I	✓	80	5700	A50/M	50°	154700	-	■	3107776	✓
1060	I	✓	80	5700	A60/M	60°	154700	-	■	3107780	✓
1060	I	✓	70	5700	A50/M	50°	169600	-	■	3107775	✓
1060	I	✓	70	5700	A60/M	60°	169600	-	■	3107779	✓
1053	I	✓	70	4000	A50/M	50°	177000	-	■	3107778	✓
1053	I	✓	70	4000	A60/M	60°	177000	-	■	3107782	✓

LASER+ 20 EXTREME C/I

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	C/I	10°	120500	-	■	3107753	✓
1060	I	✓	90	5700	C/I	13°	120500	-	■	3107757	✓
1060	I	✓	90	5700	C/I	16°	120500	-	■	3107761	✓
1060	I	✓	80	5700	C/I	10°	154700	-	■	3107752	✓
1060	I	✓	80	5700	C/I	13°	154700	-	■	3107756	✓
1060	I	✓	80	5700	C/I	16°	154700	-	■	3107760	✓
1060	I	✓	70	5700	C/I	10°	169600	-	■	3107751	✓
1060	I	✓	70	5700	C/I	13°	169600	-	■	3107755	✓
1060	I	✓	70	5700	C/I	16°	169600	-	■	3107759	✓
1053	I	✓	70	4000	C/I	10°	177000	-	■	3107754	✓
1053	I	✓	70	4000	C/I	13°	177000	-	■	3107758	✓
1053	I	✓	70	4000	C/I	16°	177000	-	■	3107762	✓

LASER+ 20 EXTREME ELL

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
1060	I	✓	90	5700	ELL	10°x25°	120500	-	■	3107765	✓
1060	I	✓	90	5700	ELL	15°x34°	120500	-	■	3107769	✓
1060	I	✓	90	5700	ELL	30°x45°	120500	-	■	3107773	✓
1060	I	✓	80	5700	ELL	10°x25°	154700	-	■	3107764	✓
1060	I	✓	80	5700	ELL	15°x34°	154700	-	■	3107768	✓
1060	I	✓	80	5700	ELL	30°x45°	154700	-	■	3107772	✓
1060	I	✓	70	5700	ELL	10°x25°	169600	-	■	3107763	✓
1060	I	✓	70	5700	ELL	15°x34°	169600	-	■	3107767	✓
1060	I	✓	70	5700	ELL	30°x45°	169600	-	■	3107771	✓
1053	I	✓	70	4000	ELL	10°x25°	177000	-	■	3107766	✓
1053	I	✓	70	4000	ELL	15°x34°	177000	-	■	3107770	✓
1053	I	✓	70	4000	ELL	30°x45°	177000	-	■	3107774	✓

LASER+ 30 EXTREME A/I

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	A30/I	30°	181000	-	■	3119471	✓
1592	I	✓	80	5700	A30/I	30°	232400	-	■	3119470	✓
1592	I	✓	70	5700	A30/I	30°	254700	-	■	3119469	✓
1592	I	✓	70	4000	A30/I	30°	265800	-	■	3119472	✓



LASER+ 30 EXTREME A/M

IP66 - IK09 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	A50/M	50°	181000	-	■	3107745	✓
1592	I	✓	90	5700	A60/M	60°	181000	-	■	3107749	✓
1592	I	✓	80	5700	A50/M	50°	232400	-	■	3107744	✓
1592	I	✓	80	5700	A60/M	60°	232400	-	■	3107748	✓
1592	I	✓	70	5700	A50/M	50°	254700	-	■	3107743	✓
1592	I	✓	70	5700	A60/M	60°	254700	-	■	3107747	✓
1580	I	✓	70	4000	A50/M	50°	265800	-	■	3107746	✓
1580	I	✓	70	4000	A60/M	60°	265800	-	■	3107750	✓



LASER+ 30 EXTREME C/I

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	C/I	10°	181000	-	■	3107721	✓
1592	I	✓	90	5700	C/I	13°	181000	-	■	3107725	✓
1592	I	✓	90	5700	C/I	16°	181000	-	■	3107729	✓
1592	I	✓	80	5700	C/I	10°	232400	-	■	3107720	✓
1592	I	✓	80	5700	C/I	13°	232400	-	■	3107724	✓
1592	I	✓	80	5700	C/I	16°	232400	-	■	3107728	✓
1592	I	✓	70	5700	C/I	10°	254700	-	■	3107719	✓
1592	I	✓	70	5700	C/I	13°	254700	-	■	3107723	✓
1592	I	✓	70	5700	C/I	16°	254700	-	■	3107727	✓
1580	I	✓	70	4000	C/I	10°	265800	-	■	3107722	✓
1580	I	✓	70	4000	C/I	13°	265800	-	■	3107726	✓
1580	I	✓	70	4000	C/I	16°	265800	-	■	3107730	✓




LASER+ 30 EXTREME ELL


IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1592	I	✓	90	5700	ELL	10°x25°	181000	-	■	3107733	✓
1592	I	✓	90	5700	ELL	15°x34°	181000	-	■	3107737	✓
1592	I	✓	90	5700	ELL	30°x45°	181000	-	■	3107741	✓
1592	I	✓	80	5700	ELL	10°x25°	232400	-	■	3107732	✓
1592	I	✓	80	5700	ELL	15°x34°	232400	-	■	3107736	✓
1592	I	✓	80	5700	ELL	30°x45°	232400	-	■	3107740	✓
1592	I	✓	70	5700	ELL	10°x25°	254700	-	■	3107731	✓
1592	I	✓	70	5700	ELL	15°x34°	254700	-	■	3107735	✓
1592	I	✓	70	5700	ELL	30°x45°	254700	-	■	3107739	✓
1580	I	✓	70	4000	ELL	10°x25°	265800	-	■	3107734	✓
1580	I	✓	70	4000	ELL	15°x34°	265800	-	■	3107738	✓
1580	I	✓	70	4000	ELL	30°x45°	265800	-	■	3107742	✓






UP LIGHT POSITION




LENS :

C10	OK ✓
C13	OK ✓
C16	OK ✓
ELL10x25	OK ✓
ELL15x34	OK ✓
ELL30x45	OK ✓
A30	OK ✓
A50	OK ✓
A60	OK ✓



LENS :

C10	NO
C13	NO
C16	NO
ELL10x25	NO
ELL15x34	NO
ELL30x45	NO
A30	NO
A50	NO
A60	NO



LENS :

C10	NO
C13	OK ✓
C16	OK ✓
ELL10x25	OK ✓
ELL15x34	OK ✓
ELL30x45	OK ✓
A30	NO
A50	NO
A60	NO

For UP LIGHT installation, consult factory

UP LIGHT-AMBIENT TEMPERATURES

FITTING	CORRENT DRIVER	MODULE 740	MODULES 757-857-957	Ta
LASER+ 20 / DRIVER 1000 W	1400 mA	1053 W	1060 W	35 °C
LASER+ 20 / DRIVER 1000 W	1200 mA	899 W	917 W	40 °C
LASER+ 20 / DRIVER 1000 W	1050 mA	780 W	780 W	45 °C
LASER+ 20 / DRIVER 1000 W	850 mA	628 W	628 W	50 °C
LASER+ 30 / DRIVER 1500 W	1400 mA	1580 W	1592 W	35 °C
LASER+ 30 / DRIVER 1500 W	1200 mA	1349 W	1366 W	40 °C
LASER+ 30 / DRIVER 1500 W	1050 mA	1171 W	1171 W	45 °C
LASER+ 30 / DRIVER 1500 W	850 mA	941 W	941 W	50 °C


Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 20 EXTREME			
Driver box 1000 - 1,4 A - 2 CH - DALI		3109423	✓
Driver box 1000 - 1,4 A - 2 CH - DMX		3109424	✓
LASER+ 30 EXTREME			
Driver box 1500 - 1,4 A - 3 CH - DALI		3109421	✓
Driver box 1500 - 1,4 A - 3 CH - DMX		3109422	✓




3109421
3109422
3109423
3109424

Complete unit		1A+1B = please order 2 codes	
COMPONENTS			
A	luminaire		
B	drivers box		



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
LASER+ 10 EXTREME			
Louvre LASER+ 10 - 5°	■	3109551	✓
Louvre LASER+ 10 - 10°	■	3115076	✓
LASER+ 20 EXTREME			
Louvre LASER+ 20 - 5°	■	3115077	✓
Louvre LASER+ 20 - 10°	■	3115078	✓
LASER+ 30 EXTREME			
Louvre LASER+ 30 - 5°	■	3115079	✓
Louvre LASER+ 30 - 10°	■	3115080	✓
LASER+ EXTREME			
Brackets supports for driver		3117476	✓
LASER+ EXTREME A			
Pointer support		3116553	✓
LASER+ EXTREME ELL / C			
Pointer support		3109552	✓



SMART [PRO] 2.0 1M



■ Graphite grey / Graphite grey /


Scan the QR-code for the latest information

Medium power outdoor and indoor LED projector, suitable for lighting sports areas and facilities

- The body is produced in aluminium die casting EN AB 46100, with integrated passive heat sink, powder coated polyester with trivalent passivation
- Available with nine different types of optics, three types of Colour Temperature (3,000K/4,000K/5,700K) and two different types of Chromatic Yield Index (CRI>70, CRI>80)
- Metal core PCB with CSP LED
- Available with integrated 1-10V or DALI driver
- Designed to withstand surges up to 5 kV (RCCB mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66 protection and impacts up to IK08
- Insulation class I or II
- Electrical connection via IP68 connector for 1.5mm² cables
- Reflector made of metallic HT PC or anodised and polished aluminium
- Hardened front glass with 4mm thickness, anti-ageing silicone seals and A2 stainless steel exterior screws
- Equipped with a venting and anti-condensation valve
- It can be installed on the wall, ceiling or ground thanks to the polyester powder coated galvanised steel bracket, with trivalent passivation, equipped with adjustable goniometric scale and supplied in kit




Monte Bondone - Trento - Italy



SMART [PRO] 2.0
1M

Identifying and classifying our optics



SMART [PRO] 2.0 1M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
165	I	✓	80	5700	S1	Wide	-	19200	■	GWP2185AS	✓
165	I	✓	80	5700	S2	Medium	-	19900	■	GWP2185BS	✓
165	I	✓	80	4000	S1	Wide	-	19200	■	GWP2184AS	✓
165	I	✓	80	4000	S2	Medium	-	19900	■	GWP2184BS	✓
165	I	✓	70	5700	S1	Wide	-	20600	■	GWP2175AS	✓
165	I	✓	70	5700	S2	Medium	-	21300	■	GWP2175BS	✓
165	I	✓	70	4000	S1	Wide	-	20600	■	GWP2174AS	✓
165	I	✓	70	4000	S2	Medium	-	21300	■	GWP2174BS	✓
165	I	✓	70	3000	S1	Wide	-	19200	■	GWP2173AS	✓
165	I	✓	70	3000	S2	Medium	-	19900	■	GWP2173BS	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
165	II	✓	80	4000	S1	Wide	-	19200	■	GWP2184AB	✓
165	II	✓	80	4000	S2	Medium	-	19900	■	GWP2184BB	✓
165	II	✓	80	3000	S1	Wide	-	17900	■	GWP2183AB	✓
165	II	✓	80	3000	S2	Medium	-	18500	■	GWP2183BB	✓
165	II	✓	70	5700	S1	Wide	-	20600	■	GWP2175AB	✓
165	II	✓	70	5700	S2	Medium	-	21300	■	GWP2175BB	✓
165	II	✓	70	4000	S1	Wide	-	20600	■	GWP2174AB	✓
165	II	✓	70	4000	S2	Medium	-	21300	■	GWP2174BB	✓
165	II	✓	70	3000	S1	Wide	-	19200	■	GWP2173AB	✓
165	II	✓	70	3000	S2	Medium	-	19900	■	GWP2173BB	✓
165	I	✓	80	5700	S1	Wide	-	19200	■	GWP2185AD	✓
165	I	✓	80	5700	S2	Medium	-	19900	■	GWP2185BD	✓
165	I	✓	80	4000	S1	Wide	-	19200	■	GWP2184AD	✓
165	I	✓	80	4000	S2	Medium	-	19900	■	GWP2184BD	✓
165	I	✓	70	5700	S1	Wide	-	20600	■	GWP2175AD	✓
165	I	✓	70	5700	S2	Medium	-	21300	■	GWP2175BD	✓
165	I	✓	70	4000	S1	Wide	-	20600	■	GWP2174AD	✓
165	I	✓	70	4000	S2	Medium	-	21300	■	GWP2174BD	✓
165	I	✓	70	3000	S1	Wide	-	19200	■	GWP2173AD	✓
165	I	✓	70	3000	S2	Medium	-	19900	■	GWP2173BD	✓

SMART [PRO] 2.0 1M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
165	I	✓	80	5700	A1	Wide	-	18300	■	GWP2185CS	✓
165	I	✓	80	5700	A3	Narrow	-	20700	■	GWP2185NS	✓
165	I	✓	80	4000	A1	Wide	-	18300	■	GWP2184CS	✓
165	I	✓	80	4000	A3	Narrow	-	20700	■	GWP2184NS	✓
165	I	✓	70	5700	A1	Wide	-	19600	■	GWP2175CS	✓
165	I	✓	70	5700	A3	Narrow	-	22100	■	GWP2175NS	✓
165	I	✓	70	4000	A1	Wide	-	19600	■	GWP2174CS	✓
165	I	✓	70	4000	A3	Narrow	-	22100	■	GWP2174NS	✓
165	I	✓	70	3000	A1	Wide	-	18300	■	GWP2173CS	✓
165	I	✓	70	3000	A3	Narrow	-	20700	■	GWP2173NS	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
165	II	✓	80	4000	A1	Wide	-	18300	■	GWP2184CB	✓
165	II	✓	80	4000	A3	Narrow	-	20700	■	GWP2184NB	✓
165	II	✓	80	3000	A1	Wide	-	17000	■	GWP2183CB	✓
165	II	✓	80	3000	A3	Narrow	-	19200	■	GWP2183NB	✓
165	II	✓	70	5700	A1	Wide	-	19600	■	GWP2175CB	✓
165	II	✓	70	5700	A3	Narrow	-	22100	■	GWP2175NB	✓
165	II	✓	70	4000	A1	Wide	-	19600	■	GWP2174CB	✓
165	II	✓	70	4000	A3	Narrow	-	22100	■	GWP2174NB	✓
165	II	✓	70	3000	A1	Wide	-	18300	■	GWP2173CB	✓
165	II	✓	70	3000	A3	Narrow	-	20700	■	GWP2173NB	✓
165	I	✓	80	5700	A1	Wide	-	18300	■	GWP2185CD	✓
165	I	✓	80	5700	A3	Narrow	-	20700	■	GWP2185ND	✓
165	I	✓	80	4000	A1	Wide	-	18300	■	GWP2184CD	✓
165	I	✓	80	4000	A3	Narrow	-	20700	■	GWP2184ND	✓
165	I	✓	70	5700	A1	Wide	-	19600	■	GWP2175CD	✓
165	I	✓	70	5700	A3	Narrow	-	22100	■	GWP2175ND	✓
165	I	✓	70	4000	A1	Wide	-	19600	■	GWP2174CD	✓
165	I	✓	70	4000	A3	Narrow	-	22100	■	GWP2174ND	✓
165	I	✓	70	3000	A1	Wide	-	18300	■	GWP2173CD	✓
165	I	✓	70	3000	A3	Narrow	-	20700	■	GWP2173ND	✓



SMART [PRO] 2.0 1M CIRCULAR

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
165	I	✓	80	5700	C4	15°	-	19600	■	GWP2185GS	✓
165	I	✓	80	5700	C3	20°	-	19600	■	GWP2185HS	✓
165	I	✓	80	5700	C2	25°	-	19200	■	GWP2185LS	✓
165	I	✓	80	5700	C1	30°	-	19000	■	GWP2185MS	✓
165	I	✓	80	4000	C4	15°	-	19600	■	GWP2184GS	✓
165	I	✓	80	4000	C3	20°	-	19600	■	GWP2184HS	✓
165	I	✓	80	4000	C2	25°	-	19200	■	GWP2184LS	✓
165	I	✓	80	4000	C1	30°	-	19000	■	GWP2184MS	✓
165	I	✓	70	5700	C4	15°	-	21000	■	GWP2175GS	✓
165	I	✓	70	5700	C3	20°	-	21000	■	GWP2175HS	✓
165	I	✓	70	5700	C2	25°	-	20500	■	GWP2175LS	✓
165	I	✓	70	5700	C1	30°	-	20400	■	GWP2175MS	✓
165	I	✓	70	4000	C4	15°	-	21000	■	GWP2174GS	✓
165	I	✓	70	4000	C3	20°	-	21000	■	GWP2174HS	✓
165	I	✓	70	4000	C2	25°	-	20500	■	GWP2174LS	✓
165	I	✓	70	4000	C1	30°	-	20400	■	GWP2174MS	✓
165	I	✓	70	3000	C4	15°	-	19600	■	GWP2173GS	✓
165	I	✓	70	3000	C3	20°	-	19600	■	GWP2173HS	✓
165	I	✓	70	3000	C2	25°	-	19200	■	GWP2173LS	✓
165	I	✓	70	3000	C1	30°	-	19000	■	GWP2173MS	✓



Power LED dimmable DALI - 220-240 V 50/60 Hz

165	II	✓	80	4000	C4	15°	-	19600	■	GWP2184GB	✓
165	II	✓	80	4000	C3	20°	-	19600	■	GWP2184HB	✓
165	II	✓	80	4000	C2	25°	-	19200	■	GWP2184LB	✓
165	II	✓	80	4000	C1	30°	-	19000	■	GWP2184MB	✓
165	II	✓	80	3000	C4	15°	-	18200	■	GWP2183GB	✓
165	II	✓	80	3000	C3	20°	-	18200	■	GWP2183HB	✓
165	II	✓	80	3000	C2	25°	-	17800	■	GWP2183LB	✓
165	II	✓	80	3000	C1	30°	-	17600	■	GWP2183MB	✓
165	II	✓	70	5700	C4	15°	-	21000	■	GWP2175GB	✓
165	II	✓	70	5700	C3	20°	-	21000	■	GWP2175HB	✓
165	II	✓	70	5700	C2	25°	-	20500	■	GWP2175LB	✓
165	II	✓	70	5700	C1	30°	-	20400	■	GWP2175MB	✓
165	II	✓	70	4000	C4	15°	-	21000	■	GWP2174GB	✓
165	II	✓	70	4000	C3	20°	-	21000	■	GWP2174HB	✓
165	II	✓	70	4000	C2	25°	-	20500	■	GWP2174LB	✓
165	II	✓	70	4000	C1	30°	-	20400	■	GWP2174MB	✓
165	II	✓	70	3000	C4	15°	-	19600	■	GWP2173GB	✓
165	II	✓	70	3000	C3	20°	-	19600	■	GWP2173HB	✓
165	II	✓	70	3000	C2	25°	-	19200	■	GWP2173LB	✓
165	II	✓	70	3000	C1	30°	-	19000	■	GWP2173MB	✓
165	I	✓	80	5700	C4	15°	-	19600	■	GWP2185GD	✓
165	I	✓	80	5700	C3	20°	-	19600	■	GWP2185HD	✓
165	I	✓	80	5700	C2	25°	-	19200	■	GWP2185LD	✓
165	I	✓	80	5700	C1	30°	-	19000	■	GWP2185MD	✓
165	I	✓	80	4000	C4	15°	-	19600	■	GWP2184GD	✓
165	I	✓	80	4000	C3	20°	-	19600	■	GWP2184HD	✓
165	I	✓	80	4000	C2	25°	-	19200	■	GWP2184LD	✓
165	I	✓	80	4000	C1	30°	-	19000	■	GWP2184MD	✓
165	I	✓	70	5700	C4	15°	-	21000	■	GWP2175GD	✓
165	I	✓	70	5700	C3	20°	-	21000	■	GWP2175HD	✓
165	I	✓	70	5700	C2	25°	-	20500	■	GWP2175LD	✓
165	I	✓	70	5700	C1	30°	-	20400	■	GWP2175MD	✓
165	I	✓	70	4000	C4	15°	-	21000	■	GWP2174GD	✓
165	I	✓	70	4000	C3	20°	-	21000	■	GWP2174HD	✓
165	I	✓	70	4000	C2	25°	-	20500	■	GWP2174LD	✓
165	I	✓	70	4000	C1	30°	-	20400	■	GWP2174MD	✓
165	I	✓	70	3000	C4	15°	-	19600	■	GWP2173GD	✓
165	I	✓	70	3000	C3	20°	-	19600	■	GWP2173HD	✓
165	I	✓	70	3000	C2	25°	-	19200	■	GWP2173LD	✓
165	I	✓	70	3000	C1	30°	-	19000	■	GWP2173MD	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 1M			
Connector GW Connect 3 poles (for indoor use only)		GWP20110	✓
Connector GW Connect 4 poles (for indoor use only)		GWP20111	✓
Connector GW Connect 5 poles (for indoor use only)		GWP20112	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓

SMART [PRO] 2.0 2M



■ Graphite grey / Graphite grey /


Scan the QR-code for the latest information

Medium power outdoor and indoor LED projector, suitable for lighting sports areas and facilities

- The body is produced in aluminium die casting EN AB 46100, with integrated passive heat sink, powder coated polyester with trivalent passivation
- Available with nine different types of optics, three types of Colour Temperature (3,000K/4,000K/5,700K) and two different types of Chromatic Yield Index (CRI>70, CRI>80)
- Metal core PCB with CSP LED
- Available with integrated 1-10V or DALI driver
- Designed to withstand surges up to 5 kV (RCCB mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66 protection and impacts up to IK08
- Insulation class I or II
- Electrical connection via IP68 connector for 1.5mm² cables
- Reflector made of metallic HT PC or anodised and polished aluminium
- Hardened front glass with 4mm thickness, anti-ageing silicone seals and A2 stainless steel exterior screws
- Equipped with a venting and anti-condensation valve
- It can be installed on the wall, ceiling or ground thanks to the polyester powder coated galvanised steel bracket, with trivalent passivation, equipped with adjustable goniometric scale and supplied in kit




BMX Olympic - Verona - Italy



SMART [PRO] 2.0
2M

Identifying and classifying our optics



SMART [PRO] 2.0 2M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
330	I	✓	80	5700	S1	Wide	-	38500	■	GWP2285AS	✓
330	I	✓	80	5700	S2	Medium	-	39800	■	GWP2285BS	✓
330	I	✓	80	4000	S1	Wide	-	38500	■	GWP2284AS	✓
330	I	✓	80	4000	S2	Medium	-	39800	■	GWP2284BS	✓
330	I	✓	70	5700	S1	Wide	-	41200	■	GWP2275AS	✓
330	I	✓	70	5700	S2	Medium	-	42700	■	GWP2275BS	✓
330	I	✓	70	4000	S1	Wide	-	41200	■	GWP2274AS	✓
330	I	✓	70	4000	S2	Medium	-	42700	■	GWP2274BS	✓
330	I	✓	70	3000	S1	Wide	-	38500	■	GWP2273AS	✓
330	I	✓	70	3000	S2	Medium	-	39800	■	GWP2273BS	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
330	II	✓	80	4000	S1	Wide	-	38500	■	GWP2284AB	✓
330	II	✓	80	4000	S2	Medium	-	39800	■	GWP2284BB	✓
330	II	✓	80	3000	S1	Wide	-	35700	■	GWP2283AB	✓
330	II	✓	80	3000	S2	Medium	-	37000	■	GWP2283BB	✓
330	II	✓	70	5700	S1	Wide	-	41200	■	GWP2275AB	✓
330	II	✓	70	5700	S2	Medium	-	42700	■	GWP2275BB	✓
330	II	✓	70	4000	S1	Wide	-	41200	■	GWP2274AB	✓
330	II	✓	70	4000	S2	Medium	-	42700	■	GWP2274BB	✓
330	II	✓	70	3000	S1	Wide	-	38500	■	GWP2273AB	✓
330	II	✓	70	3000	S2	Medium	-	39800	■	GWP2273BB	✓
330	I	✓	80	5700	S1	Wide	-	38500	■	GWP2285AD	✓
330	I	✓	80	5700	S2	Medium	-	39800	■	GWP2285BD	✓
330	I	✓	80	4000	S1	Wide	-	38500	■	GWP2284AD	✓
330	I	✓	80	4000	S2	Medium	-	39800	■	GWP2284BD	✓
330	I	✓	70	5700	S1	Wide	-	41200	■	GWP2275AD	✓
330	I	✓	70	5700	S2	Medium	-	42700	■	GWP2275BD	✓
330	I	✓	70	4000	S1	Wide	-	41200	■	GWP2274AD	✓
330	I	✓	70	4000	S2	Medium	-	42700	■	GWP2274BD	✓
330	I	✓	70	3000	S1	Wide	-	38500	■	GWP2273AD	✓
330	I	✓	70	3000	S2	Medium	-	39800	■	GWP2273BD	✓

SMART [PRO] 2.0 2M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
330	I	✓	80	5700	A1	Wide	-	36600	■	GWP2285CS	✓
330	I	✓	80	5700	A3	Narrow	-	41300	■	GWP2285NS	✓
330	I	✓	80	4000	A1	Wide	-	36600	■	GWP2284CS	✓
330	I	✓	80	4000	A3	Narrow	-	41300	■	GWP2284NS	✓
330	I	✓	70	5700	A1	Wide	-	39200	■	GWP2275CS	✓
330	I	✓	70	5700	A3	Narrow	-	44300	■	GWP2275NS	✓
330	I	✓	70	4000	A1	Wide	-	39200	■	GWP2274CS	✓
330	I	✓	70	4000	A3	Narrow	-	44300	■	GWP2274NS	✓
330	I	✓	70	3000	A1	Wide	-	36600	■	GWP2273CS	✓
330	I	✓	70	3000	A3	Narrow	-	41300	■	GWP2273NS	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
330	II	✓	80	4000	A1	Wide	-	36600	■	GWP2284CB	✓
330	II	✓	80	4000	A3	Narrow	-	41300	■	GWP2284NB	✓
330	II	✓	80	3000	A1	Wide	-	34000	■	GWP2283CB	✓
330	II	✓	80	3000	A3	Narrow	-	38400	■	GWP2283NB	✓
330	II	✓	70	5700	A1	Wide	-	39200	■	GWP2275CB	✓
330	II	✓	70	5700	A3	Narrow	-	44300	■	GWP2275NB	✓
330	II	✓	70	4000	A1	Wide	-	39200	■	GWP2274CB	✓
330	II	✓	70	4000	A3	Narrow	-	44300	■	GWP2274NB	✓
330	II	✓	70	3000	A1	Wide	-	36600	■	GWP2273CB	✓
330	II	✓	70	3000	A3	Narrow	-	41300	■	GWP2273NB	✓
330	I	✓	80	5700	A1	Wide	-	36600	■	GWP2285CD	✓
330	I	✓	80	5700	A3	Narrow	-	41300	■	GWP2285ND	✓
330	I	✓	80	4000	A1	Wide	-	36600	■	GWP2284CD	✓
330	I	✓	80	4000	A3	Narrow	-	41300	■	GWP2284ND	✓
330	I	✓	70	5700	A1	Wide	-	39200	■	GWP2275CD	✓
330	I	✓	70	5700	A3	Narrow	-	44300	■	GWP2275ND	✓
330	I	✓	70	4000	A1	Wide	-	39200	■	GWP2274CD	✓
330	I	✓	70	4000	A3	Narrow	-	44300	■	GWP2274ND	✓
330	I	✓	70	3000	A1	Wide	-	36600	■	GWP2273CD	✓
330	I	✓	70	3000	A3	Narrow	-	41300	■	GWP2273ND	✓



SMART [PRO] 2.0 2M CIRCULAR

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
330	I	✓	80	5700	C4	15°	-	39200	■	GWP2285GS	✓
330	I	✓	80	5700	C3	20°	-	39200	■	GWP2285HS	✓
330	I	✓	80	5700	C2	25°	-	38300	■	GWP2285LS	✓
330	I	✓	80	5700	C1	30°	-	38000	■	GWP2285MS	✓
330	I	✓	80	4000	C4	15°	-	39200	■	GWP2284GS	✓
330	I	✓	80	4000	C3	20°	-	39200	■	GWP2284HS	✓
330	I	✓	80	4000	C2	25°	-	38300	■	GWP2284LS	✓
330	I	✓	80	4000	C1	30°	-	38000	■	GWP2284MS	✓
330	I	✓	70	5700	C4	15°	-	42000	■	GWP2275GS	✓
330	I	✓	70	5700	C3	20°	-	42000	■	GWP2275HS	✓
330	I	✓	70	5700	C2	25°	-	41000	■	GWP2275LS	✓
330	I	✓	70	5700	C1	30°	-	40700	■	GWP2275MS	✓
330	I	✓	70	4000	C4	15°	-	42000	■	GWP2274GS	✓
330	I	✓	70	4000	C3	20°	-	42000	■	GWP2274HS	✓
330	I	✓	70	4000	C2	25°	-	41000	■	GWP2274LS	✓
330	I	✓	70	4000	C1	30°	-	40700	■	GWP2274MS	✓
330	I	✓	70	3000	C4	15°	-	39200	■	GWP2273GS	✓
330	I	✓	70	3000	C3	20°	-	39200	■	GWP2273HS	✓
330	I	✓	70	3000	C2	25°	-	38300	■	GWP2273LS	✓
330	I	✓	70	3000	C1	30°	-	38000	■	GWP2273MS	✓



Power LED dimmable DALI - 220-240 V 50/60 Hz

330	II	✓	80	4000	C4	15°	-	39200	■	GWP2284GB	✓
330	II	✓	80	4000	C3	20°	-	39200	■	GWP2284HB	✓
330	II	✓	80	4000	C2	25°	-	38300	■	GWP2284LB	✓
330	II	✓	80	4000	C1	30°	-	38000	■	GWP2284MB	✓
330	II	✓	80	3000	C4	15°	-	36400	■	GWP2283GB	✓
330	II	✓	80	3000	C3	20°	-	36400	■	GWP2283HB	✓
330	II	✓	80	3000	C2	25°	-	35600	■	GWP2283LB	✓
330	II	✓	80	3000	C1	30°	-	35300	■	GWP2283MB	✓
330	II	✓	70	5700	C4	15°	-	42000	■	GWP2275GB	✓
330	II	✓	70	5700	C3	20°	-	42000	■	GWP2275HB	✓
330	II	✓	70	5700	C2	25°	-	41000	■	GWP2275LB	✓
330	II	✓	70	5700	C1	30°	-	40700	■	GWP2275MB	✓
330	II	✓	70	4000	C4	15°	-	42000	■	GWP2274GB	✓
330	II	✓	70	4000	C3	20°	-	42000	■	GWP2274HB	✓
330	II	✓	70	4000	C2	25°	-	41000	■	GWP2274LB	✓
330	II	✓	70	4000	C1	30°	-	40700	■	GWP2274MB	✓
330	II	✓	70	3000	C4	15°	-	39200	■	GWP2273GB	✓
330	II	✓	70	3000	C3	20°	-	39200	■	GWP2273HB	✓
330	II	✓	70	3000	C2	25°	-	38300	■	GWP2273LB	✓
330	II	✓	70	3000	C1	30°	-	38000	■	GWP2273MB	✓
330	I	✓	80	5700	C4	15°	-	39200	■	GWP2285GD	✓
330	I	✓	80	5700	C3	20°	-	39200	■	GWP2285HD	✓
330	I	✓	80	5700	C2	25°	-	38300	■	GWP2285LD	✓
330	I	✓	80	5700	C1	30°	-	38000	■	GWP2285MD	✓
330	I	✓	80	4000	C4	15°	-	39200	■	GWP2284GD	✓
330	I	✓	80	4000	C3	20°	-	39200	■	GWP2284HD	✓
330	I	✓	80	4000	C2	25°	-	38300	■	GWP2284LD	✓
330	I	✓	80	4000	C1	30°	-	38000	■	GWP2284MD	✓
330	I	✓	70	5700	C4	15°	-	42000	■	GWP2275GD	✓
330	I	✓	70	5700	C3	20°	-	42000	■	GWP2275HD	✓
330	I	✓	70	5700	C2	25°	-	41000	■	GWP2275LD	✓
330	I	✓	70	5700	C1	30°	-	40700	■	GWP2275MD	✓
330	I	✓	70	4000	C4	15°	-	42000	■	GWP2274GD	✓
330	I	✓	70	4000	C3	20°	-	42000	■	GWP2274HD	✓
330	I	✓	70	4000	C2	25°	-	41000	■	GWP2274LD	✓
330	I	✓	70	4000	C1	30°	-	40700	■	GWP2274MD	✓
330	I	✓	70	3000	C4	15°	-	39200	■	GWP2273GD	✓
330	I	✓	70	3000	C3	20°	-	39200	■	GWP2273HD	✓
330	I	✓	70	3000	C2	25°	-	38300	■	GWP2273LD	✓
330	I	✓	70	3000	C1	30°	-	38000	■	GWP2273MD	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 2M			
Replacement glass		GWP2903	✓
Red Dot pointer support		GWP2904	✓
Anti-glare louvre		GWP2905	✓
Connector GW Connect 3 poles (for indoor use only)		GWP20110	✓
Connector GW Connect 4 poles (for indoor use only)		GWP20111	✓
Connector GW Connect 5 poles (for indoor use only)		GWP20112	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓



GWP2905



BMX Olympic - Verona - Italy

SMART [PRO] 2.0 2+2M



Scan the QR-code for the latest information


■ Graphite grey / Graphite grey /

High power outdoor and indoor LED projector, suitable for lighting large areas and sports facilities

- The body is fabricated in aluminium die casting EN AB 46100, with integrated passive heat sink, powder coated polyester with trivalent passivation
- Available with nine different types of optics, three types of Colour Temperature (3,000/4,000K/5,700K) and three different types of Chromatic Yield Index (CRI>70, CRI>80, CRI>90)
- Metal core PCB with CSP LED
- Remote power supply unit supplied separately (1-10V , DALI or DMX)
- Designed to withstand surges up to 5 kV (RCCB mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66 degree of protection and impacts up to IK08 grade
- Insulation class I
- Electrical connection via IP68 connector for 1.5mm² cables
- Reflector made of metallic HT PC or anodised and polished aluminium
- Hardened front glass with 4mm thickness, anti-ageing silicone seals and A2 stainless steel exterior screws
- Plastic venting and anti-condensation device
- It can be installed on the wall, ceiling or ground thanks to the polyester powder coated galvanised steel bracket, with trivalent passivation, equipped with adjustable goniometric scale and supplied in kit




Albinoleffe stadium - Zanica - Italy



SMART [PRO] 2.0
2+2M

Identifying and classifying our optics



SMART [PRO] 2.0 2+2M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
660	I	✓	90	5700	S1	Wide	-	65900	■	GWP2495AS	✓
660	I	✓	90	5700	S2	Medium	-	68300	■	GWP2495BS	✓
660	I	✓	80	5700	S1	Wide	-	76900	■	GWP2485AS	✓
660	I	✓	80	5700	S2	Medium	-	79700	■	GWP2485BS	✓
660	I	✓	80	4000	S1	Wide	-	76900	■	GWP2484AS	✓
660	I	✓	80	4000	S2	Medium	-	79700	■	GWP2484BS	✓
660	I	✓	70	5700	S1	Wide	-	82400	■	GWP2475AS	✓
660	I	✓	70	5700	S2	Medium	-	85400	■	GWP2475BS	✓
660	I	✓	70	4000	S1	Wide	-	82400	■	GWP2474AS	✓
660	I	✓	70	4000	S2	Medium	-	85400	■	GWP2474BS	✓
660	I	✓	70	3000	S1	Wide	-	76900	■	GWP2473AS	✓
660	I	✓	70	3000	S2	Medium	-	79700	■	GWP2473BS	✓



SMART [PRO] 2.0 2+2M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
660	I	✓	90	5700	A1	Wide	-	62800	■	GWP2495CS	✓
660	I	✓	90	5700	A3	Narrow	-	70800	■	GWP2495NS	✓
660	I	✓	80	5700	A1	Wide	-	73200	■	GWP2485CS	✓
660	I	✓	80	5700	A3	Narrow	-	82600	■	GWP2485NS	✓
660	I	✓	80	4000	A1	Wide	-	73200	■	GWP2484CS	✓
660	I	✓	80	4000	A3	Narrow	-	82600	■	GWP2484NS	✓
660	I	✓	70	5700	A1	Wide	-	78500	■	GWP2475CS	✓
660	I	✓	70	5700	A3	Narrow	-	88500	■	GWP2475NS	✓
660	I	✓	70	4000	A1	Wide	-	78500	■	GWP2474CS	✓
660	I	✓	70	4000	A3	Narrow	-	88500	■	GWP2474NS	✓
660	I	✓	70	3000	A1	Wide	-	73200	■	GWP2473CS	✓
660	I	✓	70	3000	A3	Narrow	-	82600	■	GWP2473NS	✓



SMART [PRO] 2.0 2+2M CIRCULAR

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
660	I	✓	90	5700	C4	15°	-	67200	■	GWP2495GS	✓
660	I	✓	90	5700	C3	20°	-	67100	■	GWP2495HS	✓
660	I	✓	90	5700	C2	25°	-	65700	■	GWP2495LS	✓
660	I	✓	90	5700	C1	30°	-	65100	■	GWP2495MS	✓
660	I	✓	80	5700	C4	15°	-	78400	■	GWP2485GS	✓
660	I	✓	80	5700	C3	20°	-	78300	■	GWP2485HS	✓
660	I	✓	80	5700	C2	25°	-	76600	■	GWP2485LS	✓
660	I	✓	80	5700	C1	30°	-	76000	■	GWP2485MS	✓
660	I	✓	80	4000	C4	15°	-	78400	■	GWP2484GS	✓
660	I	✓	80	4000	C3	20°	-	78300	■	GWP2484HS	✓
660	I	✓	80	4000	C2	25°	-	76600	■	GWP2484LS	✓
660	I	✓	80	4000	C1	30°	-	76000	■	GWP2484MS	✓
660	I	✓	70	5700	C4	15°	-	84000	■	GWP2475GS	✓
660	I	✓	70	5700	C3	20°	-	83900	■	GWP2475HS	✓
660	I	✓	70	5700	C2	25°	-	82100	■	GWP2475LS	✓
660	I	✓	70	5700	C1	30°	-	81400	■	GWP2475MS	✓
660	I	✓	70	4000	C4	15°	-	84000	■	GWP2474GS	✓
660	I	✓	70	4000	C3	20°	-	83900	■	GWP2474HS	✓
660	I	✓	70	4000	C2	25°	-	82100	■	GWP2474LS	✓
660	I	✓	70	4000	C1	30°	-	81400	■	GWP2474MS	✓
660	I	✓	70	3000	C4	15°	-	78400	■	GWP2473GS	✓
660	I	✓	70	3000	C3	20°	-	78300	■	GWP2473HS	✓
660	I	✓	70	3000	C2	25°	-	76600	■	GWP2473LS	✓
660	I	✓	70	3000	C1	30°	-	76000	■	GWP2473MS	✓




Control gear


DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 2+2M			
Power supply unit connection kit		GWP2909	✓
Power supply unit 1-10 V 220-240 V		GWP2901	✓
Power supply unit DALI 220-400 V		GWP2910	✓
Power supply unit DMX 220-400 V		GWP2911	✓



GWP2909



GWP2901



**GWP2910
GWP2911**

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 2+2M			
Replacement glass		GWP2903	✓
Red Dot pointer support		GWP2904	✓
Anti-glare louvre		GWP2905	✓
Connector GW Connect 7 poles		GWP30008	✓
Support bracket		GWP2912	✓
Power supply unit mounting bracket		GWP2913	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓



GWP2905



Albinoleffe stadium - Zanica - Italy

SMART [PRO] 2.0 3X2M




Scan the QR-code for the latest information


■ Graphite grey / Graphite grey /

High-power outdoor and indoor LED projector, suitable for lighting large areas and sports facilities

- The body is fabricated in aluminium die casting EN AB 46100, with integrated passive heat dissipation, powder-coated polyester paint with trivalent passivation
- Available with nine different types of optics, three types of Colour Temperature (3,000/4,000K/5,700K) and three different types of Color Rendering Index (CRI>70, CRI>80, CRI>90)
- PCB metal core with CSP LED
- Remote power supply unit in DALI or DMX options, multiple electrical connection kits, supplied separately
- Designed to withstand surges up to 5 kV (RCCB mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66 protection grade and shockproof up to IK08 grade
- Insulation class I
- Electrical connection via IP68 connector for 1.5mm² cables
- Reflector made of metallic HT PC or anodised and polished aluminium
- Hardened front glass with 4mm thickness, anti-ageing silicone seals and A2 stainless steel exterior screws
- Fixing screws with GEOMET® treatment
- Equipped with a venting and anti-condensation valve
- It can be installed on the wall, ceiling or ground thanks to the polyester powder coated galvanised steel bracket with trivalent passivation, equipped with adjustable goniometric scale and supplied in a kit




Velodrome Maspes-Vigorelli - Milan - Italy



SMART [PRO] 2.0
3x2M

Identifying and classifying our optics



SMART [PRO] 2.0 3X2M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
970	I	✓	90	5700	S1	Wide	-	98900	■	GWP2630AA957	✓
970	I	✓	90	5700	S2	Medium	-	102400	■	GWP2630AB957	✓
970	I	✓	80	5700	S1	Wide	-	115400	■	GWP2630AA857	✓
970	I	✓	80	5700	S2	Medium	-	119500	■	GWP2630AB857	✓
970	I	✓	80	4000	S1	Wide	-	115400	■	GWP2630AA840	✓
970	I	✓	80	4000	S2	Medium	-	119500	■	GWP2630AB840	✓
970	I	✓	70	5700	S1	Wide	-	123600	■	GWP2630AA757	✓
970	I	✓	70	5700	S2	Medium	-	128100	■	GWP2630AB757	✓
970	I	✓	70	4000	S1	Wide	-	123600	■	GWP2630AA740	✓
970	I	✓	70	4000	S2	Medium	-	128100	■	GWP2630AB740	✓
970	I	✓	70	3000	S1	Wide	-	115400	■	GWP2630AA730	✓
970	I	✓	70	3000	S2	Medium	-	119500	■	GWP2630AB730	✓



SMART [PRO] 2.0 3X2M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
970	I	✓	90	5700	A1	Wide	-	94200	■	GWP2630AC957	✓
970	I	✓	90	5700	A3	Narrow	-	106200	■	GWP2630AN957	✓
970	I	✓	80	5700	A1	Wide	-	109800	■	GWP2630AC857	✓
970	I	✓	80	5700	A3	Narrow	-	123900	■	GWP2630AN857	✓
970	I	✓	80	4000	A1	Wide	-	109800	■	GWP2630AC840	✓
970	I	✓	80	4000	A3	Narrow	-	123900	■	GWP2630AN840	✓
970	I	✓	70	5700	A1	Wide	-	117700	■	GWP2630AC757	✓
970	I	✓	70	5700	A3	Narrow	-	132800	■	GWP2630AN757	✓
970	I	✓	70	4000	A1	Wide	-	117700	■	GWP2630AC740	✓
970	I	✓	70	4000	A3	Narrow	-	132800	■	GWP2630AN740	✓
970	I	✓	70	3000	A1	Wide	-	109800	■	GWP2630AC730	✓
970	I	✓	70	3000	A3	Narrow	-	123900	■	GWP2630AN730	✓



SMART [PRO] 2.0 3X2M CIRCULAR


IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
970	I	✓	90	5700	C4	15°	-	100700	■	GWP2630AG957	✓
970	I	✓	90	5700	C3	20°	-	100700	■	GWP2630AH957	✓
970	I	✓	90	5700	C2	25°	-	98500	■	GWP2630AL957	✓
970	I	✓	90	5700	C1	30°	-	97700	■	GWP2630AM957	✓
970	I	✓	80	5700	C4	15°	-	117500	■	GWP2630AG857	✓
970	I	✓	80	5700	C3	20°	-	117500	■	GWP2630AH857	✓
970	I	✓	80	5700	C2	25°	-	114900	■	GWP2630AL857	✓
970	I	✓	80	5700	C1	30°	-	114000	■	GWP2630AM857	✓
970	I	✓	80	4000	C4	15°	-	117500	■	GWP2630AG840	✓
970	I	✓	80	4000	C3	20°	-	117500	■	GWP2630AH840	✓
970	I	✓	80	4000	C2	25°	-	114900	■	GWP2630AL840	✓
970	I	✓	80	4000	C1	30°	-	114000	■	GWP2630AM840	✓
970	I	✓	70	5700	C4	15°	-	125900	■	GWP2630AG757	✓
970	I	✓	70	5700	C3	20°	-	125900	■	GWP2630AH757	✓
970	I	✓	70	5700	C2	25°	-	123100	■	GWP2630AL757	✓
970	I	✓	70	5700	C1	30°	-	122100	■	GWP2630AM757	✓
970	I	✓	70	4000	C4	15°	-	125900	■	GWP2630AG740	✓
970	I	✓	70	4000	C3	20°	-	125900	■	GWP2630AH740	✓
970	I	✓	70	4000	C2	25°	-	123100	■	GWP2630AL740	✓
970	I	✓	70	4000	C1	30°	-	122100	■	GWP2630AM740	✓
970	I	✓	70	3000	C4	15°	-	117500	■	GWP2630AG730	✓
970	I	✓	70	3000	C3	20°	-	117500	■	GWP2630AH730	✓
970	I	✓	70	3000	C2	25°	-	114900	■	GWP2630AL730	✓
970	I	✓	70	3000	C1	30°	-	114000	■	GWP2630AM730	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 3X2M			
Power supply unit DALI 220-400 V		GWP20031	✓
Power supply unit DMX 220-400 V		GWP20032	✓




GWP20031
GWP20032

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PRO] 2.0 3X2M			
Replacement glass		GWP2903	✓
Red Dot pointer support		GWP2904	✓
Anti-glare louvre		GWP2905	✓
Connector GW Connect 12 poles		GWP20004	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
Power supply unit mounting bracket		GWP20006	✓
H07RN-F 12x1,5 mm2 cable - skein 50 m		GWP20005	✓




GWP2905



GWP20006

SPATIUM PRO 1M




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information


High-power outdoor LED floodlight suitable for the lighting of outdoor areas such as industrial perimeter areas, pedestrian areas and car parks

- The floodlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated 'self-cleaning' heat dissipation system
- The bracket is made in galvanised steel fixed to the module via screws
- The floodlight is available in the following colour temperatures 3,000K, 4,000K or 5,700K and colour rendering CRI>70 (SDCM 5 Step), CRI>80 (SDCM 3 Step)
- The range also includes 4 types of optics: circular 40°, symmetrical/elliptical optic, and 2 asymmetric optics
- The power supply unit, available in the DALI version can be oriented to optimise the heat dissipation depending on the orientation of the motor
- The floodlight is completed with an external power supply unit fixed to the back of the heatsink
- It is protected from surges up to 6 kV in differential mode and 10 kV in common mode
- The T.I.R.Ex.optic system developed by GEWISS with lenses in PMMA HT (high-transparency), gives complete control over the light beam, allowing for great flexibility for any project design, with high qualitative and quantitative performance
- Equipped with a venting and anti-condensation valve
- The orientation system is enabled by the goniometer integrated into the bracket, which facilitates the pointing phases during installation



SPATIUM PRO 1M

Identifying and classifying our optics



SPATIUM PRO 1M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable DALI - 220-240 V 50/60 Hz											
400	I	✓	80	5700	C1	40°	-	42000	■	GWP3133DF857	✓
400	I	✓	80	5700	ELL	30°x80°	-	40000	■	GWP3133DA857	✓
400	I	✓	80	4000	C1	40°	-	42000	■	GWP3133DF840	✓
400	I	✓	80	4000	ELL	30°x80°	-	40000	■	GWP3133DA840	✓
400	I	✓	80	3000	C1	40°	-	41000	■	GWP3133DF830	✓
400	I	✓	80	3000	ELL	30°x80°	-	38500	■	GWP3133DA830	✓
400	I	✓	70	5700	C1	40°	-	49000	■	GWP3133DF757	✓
400	I	✓	70	5700	ELL	30°x80°	-	46500	■	GWP3133DA757	✓
400	I	✓	70	4000	C1	40°	-	49000	■	GWP3133DF740	✓
400	I	✓	70	4000	ELL	30°x80°	-	46500	■	GWP3133DA740	✓
400	I	✓	70	3000	C1	40°	-	46000	■	GWP3133DF730	✓
400	I	✓	70	3000	ELL	30°x80°	-	43500	■	GWP3133DA730	✓

SPATIUM PRO 1M ASYMMETRIC

IP66 - IK08




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable DALI - 220-240 V 50/60 Hz											
400	I	✓	80	5700	A1	45°	-	40000	■	GWP3133DB857	✓
400	I	✓	80	5700	A2	60°	-	36500	■	GWP3133DC857	✓
400	I	✓	80	4000	A1	45°	-	40000	■	GWP3133DB840	✓
400	I	✓	80	4000	A2	60°	-	36500	■	GWP3133DC840	✓
400	I	✓	80	3000	A1	45°	-	39000	■	GWP3133DB830	✓
400	I	✓	80	3000	A2	60°	-	35500	■	GWP3133DC830	✓
400	I	✓	70	5700	A1	45°	-	46000	■	GWP3133DB757	✓
400	I	✓	70	5700	A2	60°	-	42500	■	GWP3133DC757	✓
400	I	✓	70	4000	A1	45°	-	46000	■	GWP3133DB740	✓
400	I	✓	70	4000	A2	60°	-	42500	■	GWP3133DC740	✓
400	I	✓	70	3000	A1	45°	-	44000	■	GWP3133DB730	✓
400	I	✓	70	3000	A2	60°	-	40000	■	GWP3133DC730	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPATIUM PRO 1M			
Red Dot pointer support		GWP30004	✓
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
SPATIUM PRO 1M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓
SPATIUM PRO 1M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓



GWP30004





GWP30002



GWP30003

SPATIUM PRO 2M




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information


High-power outdoor LED floodlight, suitable for lighting large areas and industrial zones

- The blocks are misaligned to allow for better thermal dissipation and increased system efficiency and longevity
- The floodlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated 'self-cleaning' heat dissipation system
- The floodlight is available in the following colour temperatures 3,000K, 4,000K or 5,700K and colour rendering CRI>70 (SDCM 5 Step), CRI>80 (SDCM 3 Step)
- The range also includes 4 types of optics: circular 40°, symmetrical/elliptical optic, and 2 asymmetric optics
- The system includes an external power supply unit installed on the bracket or remote in the DALI version
- The Power supply unit is for single-phase electric networks, protected from surges up to 6 kV in differential mode and 10 kV in common mode
- The T.I.R.Ex.optic system developed by GEWISS with lenses in PMMA HT (high-transparency), gives complete control over the light beam, allowing for great flexibility for any project design, with high qualitative and quantitative performance
- It consists of 2 modules, each with a bleed and anti-condensation valve, protected from accidental impact
- The rotation system between the brackets and optic modules is of a truncated-conical aluminium type, with an integrated goniometer in the bracket for easy control of orientation, and screw and grub screw fastening, which guarantees the secure fixing of each individual module over time



SPATIUM PRO 2M

Identifying and classifying our optics



SPATIUM PRO 2M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
800	I	✓	80	5700	C1	40°	-	84000	■	GWP3233AF857	✓
800	I	✓	80	5700	ELL	30°x80°	-	80000	■	GWP3233AA857	✓
800	I	✓	80	4000	C1	40°	-	84000	■	GWP3233AF840	✓
800	I	✓	80	4000	ELL	30°x80°	-	80000	■	GWP3233AA840	✓
800	I	✓	80	3000	C1	40°	-	82000	■	GWP3233AF830	✓
800	I	✓	80	3000	ELL	30°x80°	-	77000	■	GWP3233AA830	✓
800	I	✓	70	5700	C1	40°	-	98000	■	GWP3233AF757	✓
800	I	✓	70	5700	ELL	30°x80°	-	93000	■	GWP3233AA757	✓
800	I	✓	70	4000	C1	40°	-	98000	■	GWP3233AF740	✓
800	I	✓	70	4000	ELL	30°x80°	-	93000	■	GWP3233AA740	✓
800	I	✓	70	3000	C1	40°	-	92000	■	GWP3233AF730	✓
800	I	✓	70	3000	ELL	30°x80°	-	87000	■	GWP3233AA730	✓

SPATIUM PRO 2M ASYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
800	I	✓	80	5700	A1	45°	-	80000	■	GWP3233AB857	✓
800	I	✓	80	5700	A2	60°	-	73000	■	GWP3233AC857	✓
800	I	✓	80	4000	A1	45°	-	80000	■	GWP3233AB840	✓
800	I	✓	80	4000	A2	60°	-	73000	■	GWP3233AC840	✓
800	I	✓	80	3000	A1	45°	-	78000	■	GWP3233AB830	✓
800	I	✓	80	3000	A2	60°	-	71000	■	GWP3233AC830	✓
800	I	✓	70	5700	A1	45°	-	92000	■	GWP3233AB757	✓
800	I	✓	70	5700	A2	60°	-	85000	■	GWP3233AC757	✓
800	I	✓	70	4000	A1	45°	-	92000	■	GWP3233AB740	✓
800	I	✓	70	4000	A2	60°	-	85000	■	GWP3233AC740	✓
800	I	✓	70	3000	A1	45°	-	88000	■	GWP3233AB730	✓
800	I	✓	70	3000	A2	60°	-	80000	■	GWP3233AC730	✓

Control gear


DESCRIPTION	COLOR	PART NUMBER	UKCA
SPATIUM PRO 2M			
Single driver 0-10 V 220-240 V		GWP30018	✓
Single driver DALI 220-240 V		GWP30016	✓
Driver box 0-10 V 220-240 V		GWP30026	✓
Driver box DALI 220-240 V		GWP30024	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 2M			
Red Dot pointer support		GWP30004	✓
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
Connector GW Connect 7 poles		GWP30008	✓
Power supply unit mounting bracket		GWP30007	✓
Connection kit for 2 single drivers		GWP30027	✓
STADIUM PRO 2M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓
STADIUM PRO 2M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓




GWP30004



GWP30002






GWP30003



GWP30007

SPATIUM PRO 3M




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information


High-power LED floodlight for outdoor lighting in large areas, such as car parks, ports, large industrial areas, airports and inland terminals

- The blocks are offset to allow better heat dissipation and increase the efficiency and lifespan of the system
- The spotlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated "self-cleaning" heat dissipation system
- The floodlight is available in 3,000K, 4,000K or 5,700K colour temperatures and CRI>70 (5-Step SDCM) or CRI>80 (3-Step SDCM) colour rendering
- The range also includes 4 types of optics: 40° circular, a symmetrical/elliptical optic and 2 asymmetrical optics
- The system's external power supply unit is fixed to the edge of the bracket or remote, in the DALI version
- The power supply is for single-phase electrical grids, it is immune to surges of up to 6 kV in RCCB mode and 10 kV in common mode
- The T.I.R.Ex optical system developed by GEWISS, with high transparency PMMA HT lenses, gives total control over the light beam, providing wide flexibility in the design environment, with high qualitative and quantitative performance
- It consists of three modules, each with a ventilation and anti-condensation valve, protected from accidental impacts
- The rotation device between the bracket and the optical modules is an aluminium truncated cone-shaped system with a goniometer built into the bracket for easy orientation control and fixing with bolts and grub screws to ensure the stability of each individual module over time



SPATIUM PRO 3M

Identifying and classifying our optics



SPATIUM PRO 3M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1200	I	✓	80	5700	C1	40°	-	127000	■	GWP3333AF857	✓
1200	I	✓	80	5700	ELL	30°x80°	-	121000	■	GWP3333AA857	✓
1200	I	✓	80	4000	C1	40°	-	127000	■	GWP3333AF840	✓
1200	I	✓	80	4000	ELL	30°x80°	-	121000	■	GWP3333AA840	✓
1200	I	✓	80	3000	C1	40°	-	123000	■	GWP3333AF830	✓
1200	I	✓	80	3000	ELL	30°x80°	-	116000	■	GWP3333AA830	✓
1200	I	✓	70	5700	C1	40°	-	147000	■	GWP3333AF757	✓
1200	I	✓	70	5700	ELL	30°x80°	-	139500	■	GWP3333AA757	✓
1200	I	✓	70	4000	C1	40°	-	147000	■	GWP3333AF740	✓
1200	I	✓	70	4000	ELL	30°x80°	-	139500	■	GWP3333AA740	✓
1200	I	✓	70	3000	C1	40°	-	138000	■	GWP3333AF730	✓
1200	I	✓	70	3000	ELL	30°x80°	-	131000	■	GWP3333AA730	✓



SPATIUM PRO 3M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1200	I	✓	80	5700	A1	45°	-	119000	■	GWP3333AB857	✓
1200	I	✓	80	5700	A2	60°	-	110000	■	GWP3333AC857	✓
1200	I	✓	80	4000	A1	45°	-	119000	■	GWP3333AB840	✓
1200	I	✓	80	4000	A2	60°	-	110000	■	GWP3333AC840	✓
1200	I	✓	80	3000	A1	45°	-	115000	■	GWP3333AB830	✓
1200	I	✓	80	3000	A2	60°	-	106000	■	GWP3333AC830	✓
1200	I	✓	70	5700	A1	45°	-	138000	■	GWP3333AB757	✓
1200	I	✓	70	5700	A2	60°	-	127500	■	GWP3333AC757	✓
1200	I	✓	70	4000	A1	45°	-	138000	■	GWP3333AB740	✓
1200	I	✓	70	4000	A2	60°	-	127500	■	GWP3333AC740	✓
1200	I	✓	70	3000	A1	45°	-	130000	■	GWP3333AB730	✓
1200	I	✓	70	3000	A2	60°	-	120000	■	GWP3333AC730	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPATIUM PRO 3M			
Single driver 0-10 V 220-240 V		GWP30018	✓
Single driver DALI 220-240 V		GWP30016	✓
Driver box 0-10 V 220-240 V		GWP30036	✓
Driver box DALI 220-240 V		GWP30034	✓




GWP30034

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPATIUM PRO 3M			
Red Dot pointer support		GWP30004	✓
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
Power supply unit mounting bracket		GWP30005	✓
Connection kit for 3 single drivers		GWP30037	✓
SPATIUM PRO 3M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓
SPATIUM PRO 3M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓




GWP30004



GWP30002




GWP30003



GWP30005

SQUARE PRO



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

High-powered LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in electrical connection box with aluminium cover
- Waterproof M25x1.5 cable gland for cables Ø 10 - Ø 16 mm
- Light beam obtained by the combination of multiple LED modules
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Stainless steel locking hardware
- Galvanised powder-coated steel bracket
- Integral graduated goniometer for aiming purposes
- All SQUARE PRO power consumption includes power unit losses
- SQUARE PRO 4CH versions are not compatible with protective glass
- To connect the SQUARE PRO use the control gears supplied as accessories only
- ON-OFF, dimmable DALI and DMX-RDM control gears can be housed in IP66-rated boxes or on IP20-rated metal plates (for electrical panels). The electrical connection between control gear and floodlight must take place with a maximum cable length distance of 50 m
- Correctly match the floodlight with the control gear. Pay attention to the models and the number of connections: two (2CH), three (3CH) or four (4CH) channels
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) for every driver unit/box




Palaleonessa - Brescia - Italy



SQUARE PRO

Identifying and classifying our optics



SQUARE PRO 64/2 A/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
558	I	-	70	5700	A65/I	-	91023	77091	■	3119511	✓
558	I	-	70	4000	A65/I	-	91994	77913	■	3119510	✓



SQUARE PRO 96/3 A/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
835	I	-	70	5700	A65/I	-	136534	112178	■	3119521	✓
835	I	-	70	4000	A65/I	-	137991	114689	■	3119520	✓



SQUARE PRO 96/4 A/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 4CH											
1118	I	-	70	5700	A65/I	-	162006	134650	■	3119531	✓
1118	I	-	70	4000	A65/I	-	165633	137664	■	3119530	✓



SQUARE PRO 64/2 A/M

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
558	I	-	70	5700	A45/M	-	91023	80295	■	3119513	✓
558	I	-	70	4000	A45/M	-	91994	80929	■	3119512	✓



SQUARE PRO 96/3 A/M

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
835	I	-	70	5700	A45/M	-	136534	117402	■	3119523	✓
835	I	-	70	4000	A45/M	-	137991	119577	■	3119522	✓



SQUARE PRO 96/4 A/M

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 4CH											
1118	I	-	70	5700	A45/M	-	162006	141721	■	3119533	✓
1118	I	-	70	4000	A45/M	-	165633	144347	■	3119532	✓



SQUARE PRO 64/2 C/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
558	I	-	70	5700	C/I	-	91023	82765	■	3119515	✓
558	I	-	70	4000	C/I	-	91994	83824	■	3119514	✓



SQUARE PRO 96/3 C/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
835	I	-	70	5700	C/I	-	136534	120900	■	3119525	✓
835	I	-	70	4000	C/I	-	137991	123018	■	3119524	✓



SQUARE PRO 96/4 C/I

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 4CH											
1118	I	-	70	5700	C/I	-	162006	145692	■	3119535	✓
1118	I	-	70	4000	C/I	-	165633	148250	■	3119534	✓



SQUARE PRO 64/2 ELL

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
558	I	-	70	5700	ELL	15°x30°	91023	80511	■	3119517	✓
558	I	-	70	5700	ELL	30°x40°	91023	75843	■	3119519	✓
558	I	-	70	4000	ELL	15°x30°	91994	81313	■	3119516	✓
558	I	-	70	4000	ELL	30°x40°	91994	76952	■	3119518	✓



SQUARE PRO 96/3 ELL

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
835	I	-	70	5700	ELL	15°x30°	136534	117204	■	3119527	✓
835	I	-	70	5700	ELL	30°x40°	136534	110831	■	3119529	✓
835	I	-	70	4000	ELL	15°x30°	137991	119018	■	3119526	✓
835	I	-	70	4000	ELL	30°x40°	137991	112588	■	3119528	✓



SQUARE PRO 96/4 ELL


IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 4CH											
1118	I	-	70	5700	ELL	15°x30°	162006	141966	■	3119537	✓
1118	I	-	70	5700	ELL	30°x40°	162006	133654	■	3119539	✓
1118	I	-	70	4000	ELL	15°x30°	165633	144164	■	3119536	✓
1118	I	-	70	4000	ELL	30°x40°	165633	135779	■	3119538	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SQUARE PRO			
Protective grid SQUARE PRO		14474201	✓
SQUARE PRO (max 840 W)			
Protective glass SQUARE PRO (max 840 W)		14474494	✓



Control gear



Complete unit
1A+1B = please order 2 codes

COMPONENTS	
A	luminaire
B	drivers box



Complete unit
1A+1B = please order 2 codes


COMPONENTS	
A	luminaire
C	drivers unit

2 CH		
A	B	C
SQUARE PRO	IP66	IP20
SQUARE PRO 64/2 - A/I - A/M - C/I - ELL		
220-240 V 50/60 Hz		
ON-OFF	14473894	14473401
DALI	14473994	-
DMX	3119981	3120127

3 CH		
A	B	C
SQUARE PRO	IP66	IP20
SQUARE PRO 96/3 - A/I - A/M - C/I - ELL		
220-240 V 50/60 Hz		
ON-OFF	14474094	14473601
DALI	14474194	-
DMX	3119980	3120126

4 CH		
A	B	C
SQUARE PRO	IP66	IP20
SQUARE PRO 96/4 - A/I - A/M - C/I - ELL		
220-240 V 50/60 Hz		
ON-OFF	14476094	14475901
DALI	310988	-
DMX	3119979	3120125


DESCRIPTION	COLOR	PART NUMBER	UKCA
Drivers box IP66 - SQUARE PRO 64/2 - A/I - A/M - C/I - ELL			
Drivers box 600 W - 1.4A - 2CH - 220-240 V 50/60 Hz	■	14473894	✓
Drivers box 600 W - 1.4A - 2CH - DALI - 220-240 V 50/60 Hz	■	14473994	✓
DRIVER BOX 600 W 1,4 A - 2CH - DMX 220-240 V	■	3119981	✓
Drivers unit IP20 - SQUARE PRO 64/2 - A/I - A/M - C/I - ELL			
Drivers unit 600 W - 1.4A - 2CH - 220-240 V 50/60 Hz		14473401	✓
DRIVER UNIT 600 W 1,4 A - 2CH - DMX 220-240 V		3120127	✓
Drivers box IP66 - SQUARE PRO 96/3 - A/I - A/M - C/I - ELL			
Drivers box 900 W - 1.4A - 3CH - 220-240 V 50/60 Hz	■	14474094	✓
Drivers box 900 W - 1.4A - 3CH - DALI 220-240 V 50/60 Hz	■	14474194	✓
DRIVER BOX 900 W 1,4 A - 3CH - DMX 220-240 V	■	3119980	✓
Drivers unit IP20 - SQUARE PRO 96/3 - A/I - A/M - C/I - ELL			
Drivers unit 900 W - 1.4A - 3CH - 220-240 V 50/60 Hz		14473601	✓
DRIVER UNIT 900 W 1,4 A - 3CH - DMX 220-240 V		3120126	✓
Drivers box IP66 - SQUARE PRO 96/4 - A/I - A/M - C/I - ELL			
Drivers box 1100 W - 1.8A - 4CH - 220-240 V 50/60 Hz	■	14476094	✓
Drivers box 1100 W - 1.8A - 4CH - DALI - 220-240 V 50/60 Hz	■	310988	✓
DRIVER BOX 1100 W 1,8 A - 4CH - DMX 220-240 V	■	3119979	✓
Drivers unit IP20 - SQUARE PRO 96/4 - A/I - A/M - C/I - ELL			
Drivers unit 1100 W - 1.8A - 4CH - 220-240 V 50/60 Hz		14475901	✓
DRIVER UNIT 1100 W 1,8 A - 4CH - DMX 220-240 V		3120125	✓





Mangin Beaulieu Sports Complex - Nantes - France

SQUARE PRO GLASS



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

High-powered LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- High-efficiency aluminised technopolymer reflector with protective surface treatment (C/I versions)
- Foam silicone sealing gaskets directly applied on glass without joints
- Built-in electrical connection box with aluminium cover
- Connection box including anti-ageing silicone sealing gasket
- Waterproof M25x1.5 cable gland for cables Ø 10 - Ø 16 mm
- Light beam obtained by the combination of multiple LED modules
- Glass locking fasteners powder-coated stainless-steel
- Stainless steel locking hardware
- Galvanised powder-coated steel bracket
- Integral graduated goniometer for aiming purposes
- All SQUARE PRO power consumption includes power unit losses
- Correctly match the floodlight with the control gear. Pay attention to the models and the number of connection channels: two (2CH) and three (3CH)
- IP66-rated waterproof boxes or IP20-rated metal plates (to be incorporated into third-party electrical panels) DALI and 1-10V power supply options available. Maximum distance of 50 m cable length between control gear and luminaire
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) for every driver unit/box
- The 4000 K and 3000 K LED versions are CRI ≥ 70. Consult factory for other colour temperatures (CCT) and colour renderings index (CRI)




Mangin Beaulieu sports complex - Nantes - France



SQUARE PRO GLASS

Identifying and classifying our optics



SQUARE PRO GLASS 710/3 S/W

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
710	I	-	70	4000	S/W	-	113616	99343	■	3104803	✓
710	I	-	70	3000	S/W	-	108000	94845	■	3104804	✓



SQUARE PRO GLASS 470/2 S/W

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
470	I	-	70	4000	S/W	-	75744	65762	■	3104807	✓
470	I	-	70	3000	S/W	-	72000	62784	■	3104808	✓



SQUARE PRO GLASS 710/3 A50/W

IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
710	I	-	70	4000	A50/W	-	113616	102827	■	3104801	✓
710	I	-	70	3000	A50/W	-	108000	98172	■	3104802	✓



SQUARE PRO GLASS 470/2 A50/W


IP66 - IK07 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
470	I	-	70	4000	A50/W	-	75744	68068	■	3104805	✓
470	I	-	70	3000	A50/W	-	72000	64987	■	3104806	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SQUARE PRO GLASS A50/W			
Louvre SQUARE PRO GLASS A50/W	■	3105479	✓




3105479

Control gear






Complete unit
1A+1B = please order 2 codes




COMPONENTS	
A	luminaire
B	drivers box




Complete unit
1A+1C = please order 2 codes

COMPONENTS	
A	luminaire
C	drivers unit


2 CH		
		
A SQUARE PRO GLASS	B IP66	C IP20
SQUARE PRO GLASS 470/2 - S/W - A50/W		
220-240 V 50/60 Hz		
DALI	3104828	3104830

3 CH		
		
A SQUARE PRO GLASS	B IP66	C IP20
SQUARE PRO GLASS 710/3 S/W - A50/W		
220-240 V 50/60 Hz		
DALI	3104813	3104829

DESCRIPTION	COLOR	PART NUMBER	UKCA
Drivers box IP66 - SQUARE PRO GLASS 470/2 - S/W - A50/W			
Drivers box 470 W - 1.1A - 2CH - DALI - 220-240 V 50/60 Hz	■	3104828	✓
Drivers unit IP20 - SQUARE PRO GLASS 470/2 - S/W - A50/W			
Drivers unit 470 W - 1.1A - 2CH - DALI - 220-240 V 50/60 Hz		3104830	✓
Drivers box IP66 - SQUARE PRO GLASS 710/3 - S/W - A50/W			
Drivers box 750 W - 1.1A - 3CH - DALI 220-240 V 50/60 Hz	■	3104813	✓
Drivers unit IP20 - SQUARE PRO GLASS 710/3 - S/W - A50/W			
Drivers unit 750 W - 1.1A - 3CH - DALI 220-240 V 50/60 Hz		3104829	✓



STADIUM PRO 1M



■ Graphite grey / Graphite grey /


Scan the QR-code for the latest information

High-power LED floodlight, with high-emittance LES (light emitting surface), suitable for lighting small or medium-sized sporting facilities

- The floodlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated 'self-cleaning' heat dissipation system
- The floodlight is available in the following colour temperatures 4,000K or 5,700K and colour rendering CRI>70, CRI>80 o CRI>90 (TLCI>80)
- The range offers 6 types of circular optics, from 8° up to 40°, 1 symmetrical/elliptical optic and 2 asymmetric optics
- The powers supply unit available in DALI or DMX-RDM versions acan be oriented to optimise the heat dispersion depending on the orientation of the motor
- The floodlight is completed with the power supply unit fixed onto the back of the heat sink
- It is protected from surges up to 6 kV in differential mode and 10 kV in common mode
- The T.I.R.Ex.optic system developed by GEWISS with lenses in PMMA HT (high-transparency), gives complete control over the light beam, allowing for great flexibility in any project design, with high qualitative and quantitative performance
- With a bleed and anti-condensation valve, protected from accidental impact
- The orientation system is enabled by the goniometer integrated into the bracket, which facilitates the pointing phases during installation




Velodrome Maspes-Vigorelli - Milan - Italy



STADIUM PRO
1M

STADIUM PRO
1M RM

Identifying and classifying our optics



STADIUM PRO 1M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable DALI - 220-240 V 50/60 Hz											
480	I	✓	90	5700	C6	8°	-	39500	■	GWP3131DN957	✓
480	I	✓	90	5700	C5	10°	-	43000	■	GWP3131DM957	✓
480	I	✓	90	5700	C4	15°	-	43000	■	GWP3131DL957	✓
480	I	✓	90	5700	C3	20°	-	41500	■	GWP3131DH957	✓
480	I	✓	90	5700	C2	30°	-	41500	■	GWP3131DG957	✓
480	I	✓	90	5700	C1	40°	-	39500	■	GWP3131DF957	✓
480	I	✓	90	5700	ELL	20°x80°	-	39500	■	GWP3131DA957	✓
480	I	✓	80	5700	C6	8°	-	46000	■	GWP3131DN857	✓
480	I	✓	80	5700	C5	10°	-	50500	■	GWP3131DM857	✓
480	I	✓	80	5700	C4	15°	-	50500	■	GWP3131DL857	✓
480	I	✓	80	5700	C3	20°	-	49000	■	GWP3131DH857	✓
480	I	✓	80	5700	C2	30°	-	49000	■	GWP3131DG857	✓
480	I	✓	80	5700	C1	40°	-	46000	■	GWP3131DF857	✓
480	I	✓	80	5700	ELL	20°x80°	-	46000	■	GWP3131DA857	✓
480	I	✓	80	4000	C6	8°	-	46000	■	GWP3131DN840	✓
480	I	✓	80	4000	C5	10°	-	50500	■	GWP3131DM840	✓
480	I	✓	80	4000	C4	15°	-	50500	■	GWP3131DL840	✓
480	I	✓	80	4000	C3	20°	-	49000	■	GWP3131DH840	✓
480	I	✓	80	4000	C2	30°	-	49000	■	GWP3131DG840	✓
480	I	✓	80	4000	C1	40°	-	46000	■	GWP3131DF840	✓
480	I	✓	80	4000	ELL	20°x80°	-	46000	■	GWP3131DA840	✓
480	I	✓	70	5700	C6	8°	-	53500	■	GWP3131DN757	✓
480	I	✓	70	5700	C5	10°	-	58500	■	GWP3131DM757	✓
480	I	✓	70	5700	C4	15°	-	58500	■	GWP3131DL757	✓
480	I	✓	70	5700	C3	20°	-	56500	■	GWP3131DH757	✓
480	I	✓	70	5700	C2	30°	-	56500	■	GWP3131DG757	✓
480	I	✓	70	5700	C1	40°	-	53500	■	GWP3131DF757	✓
480	I	✓	70	5700	ELL	20°x80°	-	53500	■	GWP3131DA757	✓
480	I	✓	70	4000	C6	8°	-	53500	■	GWP3131DN740	✓
480	I	✓	70	4000	C5	10°	-	58500	■	GWP3131DM740	✓
480	I	✓	70	4000	C4	15°	-	58500	■	GWP3131DL740	✓
480	I	✓	70	4000	C3	20°	-	56500	■	GWP3131DH740	✓
480	I	✓	70	4000	C2	30°	-	56500	■	GWP3131DG740	✓
480	I	✓	70	4000	C1	40°	-	53500	■	GWP3131DF740	✓
480	I	✓	70	4000	ELL	20°x80°	-	53500	■	GWP3131DA740	✓

STADIUM PRO 1M ASYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable DALI - 220-240 V 50/60 Hz											
480	I	✓	90	5700	A1	45°	-	38000	■	GWP3131DB957	✓
480	I	✓	90	5700	A2	60°	-	37000	■	GWP3131DC957	✓
480	I	✓	80	5700	A1	45°	-	44500	■	GWP3131DB857	✓
480	I	✓	80	5700	A2	60°	-	43000	■	GWP3131DC857	✓
480	I	✓	80	4000	A1	45°	-	44500	■	GWP3131DB840	✓
480	I	✓	80	4000	A2	60°	-	43000	■	GWP3131DC840	✓
480	I	✓	70	5700	A1	45°	-	51000	■	GWP3131DB757	✓
480	I	✓	70	5700	A2	60°	-	49500	■	GWP3131DC757	✓
480	I	✓	70	4000	A1	45°	-	51000	■	GWP3131DB740	✓
480	I	✓	70	4000	A2	60°	-	49500	■	GWP3131DC740	✓

STADIUM PRO 1M RM SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
480	I	✓	90	5700	C6	8°	-	39500	■	GWP3131AN957	✓
480	I	✓	90	5700	C5	10°	-	43000	■	GWP3131AM957	✓
480	I	✓	90	5700	C4	15°	-	43000	■	GWP3131AL957	✓
480	I	✓	90	5700	C3	20°	-	41500	■	GWP3131AH957	✓
480	I	✓	90	5700	C2	30°	-	41500	■	GWP3131AG957	✓
480	I	✓	90	5700	C1	40°	-	39500	■	GWP3131AF957	✓
480	I	✓	90	5700	ELL	20°x80°	-	39500	■	GWP3131AA957	✓
480	I	✓	80	5700	C6	8°	-	46000	■	GWP3131AN857	✓
480	I	✓	80	5700	C5	10°	-	50500	■	GWP3131AM857	✓
480	I	✓	80	5700	C4	15°	-	50500	■	GWP3131AL857	✓
480	I	✓	80	5700	C3	20°	-	49000	■	GWP3131AH857	✓
480	I	✓	80	5700	C2	30°	-	49000	■	GWP3131AG857	✓
480	I	✓	80	5700	C1	40°	-	46000	■	GWP3131AF857	✓
480	I	✓	80	5700	ELL	20°x80°	-	46000	■	GWP3131AA857	✓
480	I	✓	80	4000	C6	8°	-	46000	■	GWP3131AN840	✓
480	I	✓	80	4000	C5	10°	-	50500	■	GWP3131AM840	✓
480	I	✓	80	4000	C4	15°	-	50500	■	GWP3131AL840	✓
480	I	✓	80	4000	C3	20°	-	49000	■	GWP3131AH840	✓
480	I	✓	80	4000	C2	30°	-	49000	■	GWP3131AG840	✓
480	I	✓	80	4000	C1	40°	-	46000	■	GWP3131AF840	✓
480	I	✓	80	4000	ELL	20°x80°	-	46000	■	GWP3131AA840	✓
480	I	✓	70	5700	C6	8°	-	53500	■	GWP3131AN757	✓
480	I	✓	70	5700	C5	10°	-	58500	■	GWP3131AM757	✓
480	I	✓	70	5700	C4	15°	-	58500	■	GWP3131AL757	✓
480	I	✓	70	5700	C3	20°	-	56500	■	GWP3131AH757	✓
480	I	✓	70	5700	C2	30°	-	56500	■	GWP3131AG757	✓
480	I	✓	70	5700	C1	40°	-	53500	■	GWP3131AF757	✓
480	I	✓	70	5700	ELL	20°x80°	-	53500	■	GWP3131AA757	✓
480	I	✓	70	4000	C6	8°	-	53500	■	GWP3131AN740	✓
480	I	✓	70	4000	C5	10°	-	58500	■	GWP3131AM740	✓
480	I	✓	70	4000	C4	15°	-	58500	■	GWP3131AL740	✓
480	I	✓	70	4000	C3	20°	-	56500	■	GWP3131AH740	✓
480	I	✓	70	4000	C2	30°	-	56500	■	GWP3131AG740	✓
480	I	✓	70	4000	C1	40°	-	53500	■	GWP3131AF740	✓
480	I	✓	70	4000	ELL	20°x80°	-	53500	■	GWP3131AA740	✓



STADIUM PRO 1M RM ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
480	I	✓	90	5700	A1	45°	-	38000	■	GWP3131AB957	✓
480	I	✓	90	5700	A2	60°	-	37000	■	GWP3131AC957	✓
480	I	✓	80	5700	A1	45°	-	44500	■	GWP3131AB857	✓
480	I	✓	80	5700	A2	60°	-	43000	■	GWP3131AC857	✓
480	I	✓	80	4000	A1	45°	-	44500	■	GWP3131AB840	✓
480	I	✓	80	4000	A2	60°	-	43000	■	GWP3131AC840	✓
480	I	✓	70	5700	A1	45°	-	51000	■	GWP3131AB757	✓
480	I	✓	70	5700	A2	60°	-	49500	■	GWP3131AC757	✓
480	I	✓	70	4000	A1	45°	-	51000	■	GWP3131AB740	✓
480	I	✓	70	4000	A2	60°	-	49500	■	GWP3131AC740	✓



Control gear


DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 1M RM			
Single driver 0-10 V 220-240 V		GWP30017	✓
Single driver DALI 220-240 V		GWP30015	✓
Power supply unit DALI 220-240 V		GWP30040	✓
Power supply unit DMX 220-240 V		GWP30041	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 1M RM			
Red Dot pointer support		GWP30004	✓
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
Connection kit for 2 single drivers		GWP30027	✓
Connection kit for 3 single drivers		GWP30037	✓
STADIUM PRO 1M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓
STADIUM PRO 1M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓




GWP30004



GWP30002




GWP30003



Velodrome Maspes-Vigorelli - Milan - Italy


STADIUM PRO 2M




Scan the QR-code for the latest information

■ Graphite grey / Graphite grey /

- High-power LED floodlight, with a high-emittance LES (light emitting surface), suitable for lighting professional and semi-professional sporting facilities
- The floodlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated 'self-cleaning' heat dissipation system
 - The floodlight is available in the following colour temperatures 4,000K or 5,700K and colour rendering CRI>70, CRI>80 o CRI>90 (TLCI>80)
 - The range offers 6 types of circular optics, from 8° up to 40°, 1 symmetrical/elliptical optic and 2 asymmetric optics
 - The range requires a DALI2 or DMX-RDM power supply to permit the greatest flexibility in the creation of lighting scenarios, even of great complexity
 - The power supply box can be installed on the bracket or remote, and is protected from surges up to 10 kV, either in differential or common mode, with a single cable
 - The T.I.R.Ex.optic system developed by GEWISS with lenses in PMMA HT (high-transparency), gives complete control over the light beam, allowing for great flexibility in any project design, with high qualitative and quantitative performance
 - It consists of 2 modules, each with a bleed and anti-condensation valve, protected from accidental impact
 - The rotation system between the brackets and optic modules is of the truncated-conical aluminium type, with an integrated goniometer in the bracket for easy control of orientation, and screw and grub screw fastening, which guarantees the fastness of each individual module over time




Velodrome Maspes-Vigorelli - Milan - Italy



STADIUM PRO
2M

Identifying and classifying our optics



STADIUM PRO 2M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
960	I	✓	90	5700	C6	8°	-	79000	■	GWP3231AN957	✓
960	I	✓	90	5700	C5	10°	-	86000	■	GWP3231AM957	✓
960	I	✓	90	5700	C4	15°	-	86000	■	GWP3231AL957	✓
960	I	✓	90	5700	C3	20°	-	83000	■	GWP3231AH957	✓
960	I	✓	90	5700	C2	30°	-	83000	■	GWP3231AG957	✓
960	I	✓	90	5700	C1	40°	-	79000	■	GWP3231AF957	✓
960	I	✓	90	5700	ELL	20°x80°	-	79000	■	GWP3231AA957	✓
960	I	✓	80	5700	C6	8°	-	92000	■	GWP3231AN857	✓
960	I	✓	80	5700	C5	10°	-	101000	■	GWP3231AM857	✓
960	I	✓	80	5700	C4	15°	-	101000	■	GWP3231AL857	✓
960	I	✓	80	5700	C3	20°	-	98000	■	GWP3231AH857	✓
960	I	✓	80	5700	C2	30°	-	98000	■	GWP3231AG857	✓
960	I	✓	80	5700	C1	40°	-	92000	■	GWP3231AF857	✓
960	I	✓	80	5700	ELL	20°x80°	-	92000	■	GWP3231AA857	✓
960	I	✓	80	4000	C6	8°	-	92000	■	GWP3231AN840	✓
960	I	✓	80	4000	C5	10°	-	101000	■	GWP3231AM840	✓
960	I	✓	80	4000	C4	15°	-	101000	■	GWP3231AL840	✓
960	I	✓	80	4000	C3	20°	-	98000	■	GWP3231AH840	✓
960	I	✓	80	4000	C2	30°	-	98000	■	GWP3231AG840	✓
960	I	✓	80	4000	C1	40°	-	92000	■	GWP3231AF840	✓
960	I	✓	80	4000	ELL	20°x80°	-	92000	■	GWP3231AA840	✓
960	I	✓	70	5700	C6	8°	-	107000	■	GWP3231AN757	✓
960	I	✓	70	5700	C5	10°	-	117000	■	GWP3231AM757	✓
960	I	✓	70	5700	C4	15°	-	117000	■	GWP3231AL757	✓
960	I	✓	70	5700	C3	20°	-	113000	■	GWP3231AH757	✓
960	I	✓	70	5700	C2	30°	-	113000	■	GWP3231AG757	✓
960	I	✓	70	5700	C1	40°	-	107000	■	GWP3231AF757	✓
960	I	✓	70	5700	ELL	20°x80°	-	107000	■	GWP3231AA757	✓
960	I	✓	70	4000	C6	8°	-	107000	■	GWP3231AN740	✓
960	I	✓	70	4000	C5	10°	-	117000	■	GWP3231AM740	✓
960	I	✓	70	4000	C4	15°	-	117000	■	GWP3231AL740	✓
960	I	✓	70	4000	C3	20°	-	113000	■	GWP3231AH740	✓
960	I	✓	70	4000	C2	30°	-	113000	■	GWP3231AG740	✓
960	I	✓	70	4000	C1	40°	-	107000	■	GWP3231AF740	✓
960	I	✓	70	4000	ELL	20°x80°	-	107000	■	GWP3231AA740	✓



STADIUM PRO 2M ASYMMETRIC


IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
960	I	✓	90	5700	A1	45°	-	76000	■	GWP3231AB957	✓
960	I	✓	90	5700	A2	60°	-	73000	■	GWP3231AC957	✓
960	I	✓	80	5700	A1	45°	-	89000	■	GWP3231AB857	✓
960	I	✓	80	5700	A2	60°	-	86000	■	GWP3231AC857	✓
960	I	✓	80	4000	A1	45°	-	89000	■	GWP3231AB840	✓
960	I	✓	80	4000	A2	60°	-	86000	■	GWP3231AC840	✓
960	I	✓	70	5700	A1	45°	-	102000	■	GWP3231AB757	✓
960	I	✓	70	5700	A2	60°	-	99000	■	GWP3231AC757	✓
960	I	✓	70	4000	A1	45°	-	102000	■	GWP3231AB740	✓
960	I	✓	70	4000	A2	60°	-	99000	■	GWP3231AC740	✓



Control gear


DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 2M			
Single driver 0-10 V 220-240 V		GWP30017	✓
Single driver DALI 220-240 V		GWP30015	✓
Driver box 0-10 V 220-240 V		GWP30025	✓
Driver box DALI 220-240 V		GWP30023	✓
Power supply unit DALI 220-400 V		GWP30021	✓
Power supply unit DMX 220-400 V		GWP30022	✓
Power supply unit connection kit		GWP30020	✓




GWP30021
GWP30022

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 2M			
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
Red Dot pointer support		GWP30004	✓
Connector GW Connect 7 poles		GWP30008	✓
Connection kit for 2 single drivers		GWP30027	✓
STADIUM PRO 2M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓
STADIUM PRO 2M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓



GWP30002



GWP30003




GWP30004





Gewiss Stadium - Bergamo - Italy

STADIUM PRO 3M



Gewiss Stadium - Bergamo - Italy




Scan the QR-code for the latest information

■ Graphite grey / Graphite grey /


High-power LED floodlight, with an LES (light emitting surface) high emission, suitable for lighting sports facilities for professional competitive competitions

- Stadium Pro is for a professional use hence the photometric data are not disclosed. We invite you to take contact with our technical and commercial teams
- The spotlight has a graphite grey finish with trivalent treatment for maximum resistance to oxidation and is equipped with an integrated "self-cleaning" thermal dissipation system
- The spotlight is available in 4,000K or 5,700K colour temperatures and CRI>70, CRI>80 or CRI>90 (TLCI>80) colour rendering
- The range also includes 6 types of circular optics, from 8° to 40°, 1 symmetrical/ Elliptical optic and 2 asymmetric optics
- The range includes a DALI2 or DMX-RDM power supply, to allow maximum flexibility in the creation of even complex light sets
- The power supply box can be fixed on the edge-bracket, or remotely, it is immune to surges of up to 10 kV both in RCCB and common mode, with a single cable
- The T.I.R.Ex optical system developed by GEWISS, with high transparency PMMA HT lenses, permits total control over the light beam, allowing for wide flexibility in the design environment, with high qualitative and quantitative performance
- It consists of three modules, each with a venting and non-condensing valve, protected from accidental impacts
- The rotation system between the bracket and the optical modules is truncated-conical in aluminium with an integrated goniometer within the bracket for easy orientation control and fixing by means of a grub-screw, which ensure the tightness over time of each individual module



STADIUM PRO
3M

Identifying and classifying our optics



STADIUM PRO 3M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1450	I	✓	90	5700	C6	8°	-	118000	■	GWP3331AN957	✓
1450	I	✓	90	5700	C5	10°	-	129000	■	GWP3331AM957	✓
1450	I	✓	90	5700	C4	15°	-	129000	■	GWP3331AL957	✓
1450	I	✓	90	5700	C3	20°	-	125000	■	GWP3331AH957	✓
1450	I	✓	90	5700	C2	30°	-	125000	■	GWP3331AG957	✓
1450	I	✓	90	5700	C1	40°	-	118000	■	GWP3331AF957	✓
1450	I	✓	90	5700	ELL	20°x80°	-	118000	■	GWP3331AA957	✓
1450	I	✓	80	5700	C6	8°	-	138000	■	GWP3331AN857	✓
1450	I	✓	80	5700	C5	10°	-	151000	■	GWP3331AM857	✓
1450	I	✓	80	5700	C4	15°	-	151000	■	GWP3331AL857	✓
1450	I	✓	80	5700	C3	20°	-	147000	■	GWP3331AH857	✓
1450	I	✓	80	5700	C2	30°	-	147000	■	GWP3331AG857	✓
1450	I	✓	80	5700	C1	40°	-	138000	■	GWP3331AF857	✓
1450	I	✓	80	5700	ELL	20°x80°	-	138000	■	GWP3331AA857	✓
1450	I	✓	80	4000	C6	8°	-	138000	■	GWP3331AN840	✓
1450	I	✓	80	4000	C5	10°	-	151000	■	GWP3331AM840	✓
1450	I	✓	80	4000	C4	15°	-	151000	■	GWP3331AL840	✓
1450	I	✓	80	4000	C3	20°	-	147000	■	GWP3331AH840	✓
1450	I	✓	80	4000	C2	30°	-	147000	■	GWP3331AG840	✓
1450	I	✓	80	4000	C1	40°	-	138000	■	GWP3331AF840	✓
1450	I	✓	80	4000	ELL	20°x80°	-	138000	■	GWP3331AA840	✓
1450	I	✓	70	5700	C6	8°	-	160000	■	GWP3331AN757	✓
1450	I	✓	70	5700	C5	10°	-	175000	■	GWP3331AM757	✓
1450	I	✓	70	5700	C4	15°	-	175000	■	GWP3331AL757	✓
1450	I	✓	70	5700	C3	20°	-	170000	■	GWP3331AH757	✓
1450	I	✓	70	5700	C2	30°	-	170000	■	GWP3331AG757	✓
1450	I	✓	70	5700	C1	40°	-	160000	■	GWP3331AF757	✓
1450	I	✓	70	5700	ELL	20°x80°	-	160000	■	GWP3331AA757	✓
1450	I	✓	70	4000	C6	8°	-	160000	■	GWP3331AN740	✓
1450	I	✓	70	4000	C5	10°	-	175000	■	GWP3331AM740	✓
1450	I	✓	70	4000	C4	15°	-	175000	■	GWP3331AL740	✓
1450	I	✓	70	4000	C3	20°	-	170000	■	GWP3331AH740	✓
1450	I	✓	70	4000	C2	30°	-	170000	■	GWP3331AG740	✓
1450	I	✓	70	4000	C1	40°	-	160000	■	GWP3331AF740	✓
1450	I	✓	70	4000	ELL	20°x80°	-	160000	■	GWP3331AA740	✓



STADIUM PRO 3M ASYMMETRIC


IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1450	I	✓	90	5700	A1	45°	-	114000	■	GWP3331AB957	✓
1450	I	✓	90	5700	A2	60°	-	110000	■	GWP3331AC957	✓
1450	I	✓	80	5700	A1	45°	-	133000	■	GWP3331AB857	✓
1450	I	✓	80	5700	A2	60°	-	128700	■	GWP3331AC857	✓
1450	I	✓	80	4000	A1	45°	-	133000	■	GWP3331AB840	✓
1450	I	✓	80	4000	A2	60°	-	128700	■	GWP3331AC840	✓
1450	I	✓	70	5700	A1	45°	-	153000	■	GWP3331AB757	✓
1450	I	✓	70	5700	A2	60°	-	149000	■	GWP3331AC757	✓
1450	I	✓	70	4000	A1	45°	-	153000	■	GWP3331AB740	✓
1450	I	✓	70	4000	A2	60°	-	149000	■	GWP3331AC740	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 3M			
Single driver 0-10 V 220-240 V		GWP30017	✓
Single driver DALI 220-240 V		GWP30015	✓
Driver box 0-10 V 220-240 V		GWP30035	✓
Driver box DALI 220-240 V		GWP30033	✓
Power supply unit DALI 220-400 V		GWP30031	✓
Power supply unit DMX 220-400 V		GWP30032	✓
Power supply unit connection kit		GWP30030	✓




GWP30031
GWP30032

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STADIUM PRO 3M			
Red Dot pointer support		GWP30004	✓
Anti-glare louvre for circular optic versions		GWP30002	✓
Visor for symmetric or circular optic versions		GWP30003	✓
Connector GW Connect 12 poles		GWP20004	✓
Power supply unit mounting bracket		GWP30001	✓
H07RN-F 12x1,5 mm2 cable - skein 50 m		GWP20005	✓
Connection kit for 3 single drivers		GWP30037	✓
STADIUM PRO 3M - SYMM			
Replacement glass for symmetric optic versions		GWP30006	✓
STADIUM PRO 3M - ASYMM			
Replacement glass for asymmetric optic versions		GWP30009	✓



GWP30004



GWP30002




GWP30003



GWP30001

GUELL ZERO





Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- BK-RAL9005 / Black RAL9005 / Glossy

LED floodlight for indoor and outdoor, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- Extra pure polished aluminium reflector
- Stainless steel locking hardware
- Stainless steel locking springs for the glass
- Powder-coated steel tiltable bracket
- Complete with 1 m factory pre-wired cable H05RN-F 3G1 mm²
- Versions of GUPELL ZERO KIT are complete with 0.5 m arm with integrated connection box, suitable for through wiring
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI



GUPELL ZERO

GUPELL ZERO KIT

Identifying and classifying our optics



GUELL ZERO S/M

IP66 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28	I	-	80	4000	S/M	-	3461	3162	■	306514	✓
28	I	-	80	3000	S/M	-	3296	3014	■	306511	✓
28	I	-	80	4000	S/M	-	3461	3162	■	306512	✓
28	I	-	80	3000	S/M	-	3296	3014	■	306509	✓
15	I	-	80	4000	S/M	-	1888	1603	■	06115394	✓
15	I	-	80	3000	S/M	-	1888	1464	■	06151494	✓
15	I	-	80	4000	S/M	-	1888	1603	■	06149080	✓
15	I	-	80	3000	S/M	-	1840	1464	■	06152280	✓



GUELL ZERO A/W

IP66 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28	I	-	80	4000	A30/W	-	3461	3167	■	306523	✓
28	I	-	80	3000	A30/W	-	3296	3005	■	306520	✓
28	I	-	80	4000	A30/W	-	3461	3167	■	306521	✓
28	I	-	80	3000	A30/W	-	3296	3005	■	306518	✓
15	I	-	80	4000	A30/W	-	1888	1589	■	06115794	✓
15	I	-	80	3000	A30/W	-	1840	1488	■	06151294	✓
15	I	-	80	4000	A30/W	-	1888	1589	■	06148680	✓
15	I	-	80	3000	A30/W	-	1840	1488	■	06152080	✓



GUELL ZERO KIT S/M

IP66 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
28	I	-	80	4000	S/M	-	3461	3162	■	306541	✓
28	I	-	80	3000	S/M	-	3296	3014	■	306539	✓
15	I	-	80	4000	S/M	-	1888	1603	■	06124980	✓
15	I	-	80	3000	S/M	-	1840	1464	■	06150980	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL ZERO			
500 mm arm completes with connection base GUELL ZERO	■	14453380	✓
1000 mm arm completes with connection base GUELL ZERO	■	14453480	✓




14453380



14453480

GUELL 1+



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10-Ø14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) consult factory
- Design by GIORGIO LODI




Grotte di Frasassi - Genga - Italy



GUELL 1+

Identifying and classifying our optics



GUELL 1+ A/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
51	I	✓	80	5000	A40/W	-	8262	6635	■	LTF1123FA850	✓
51	I	✓	80	4000	A40/W	-	8262	6705	■	LTF1123FA840	✓
51	I	✓	80	3000	A40/W	-	7863	6440	■	LTF1123FA830	✓
36	I	✓	80	5000	A40/W	-	6196	5215	■	LTF1122FA850	✓
36	I	✓	80	4000	A40/W	-	6196	5270	■	LTF1122FA840	✓
36	I	✓	80	3000	A40/W	-	5897	5180	■	LTF1122FA830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
51	I	✓	80	5000	A40/W	-	8279	6635	■	LTF1123DA850	✓
51	I	✓	80	4000	A40/W	-	8262	6705	■	LTF1123DA840	✓
51	I	✓	80	3000	A40/W	-	7863	6440	■	LTF1123DA830	✓
36	I	✓	80	5000	A40/W	-	6196	5215	■	LTF1122DA850	✓
36	I	✓	80	4000	A40/W	-	6196	5270	■	LTF1122DA840	✓
36	I	✓	80	3000	A40/W	-	5897	5180	■	LTF1122DA830	✓



GUELL 1+ S/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
51	I	✓	80	5000	S/W	-	8262	6995	■	LTF1123FS850	✓
51	I	✓	80	4000	S/W	-	8262	7070	■	LTF1123FS840	✓
51	I	✓	80	3000	S/W	-	7863	6810	■	LTF1123FS830	✓
36	I	✓	80	5000	S/W	-	6196	5495	■	LTF1122FS850	✓
36	I	✓	80	4000	S/W	-	6196	5555	■	LTF1122FS840	✓
36	I	✓	80	3000	S/W	-	5897	5380	■	LTF1122FS830	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
51	I	✓	80	5000	S/W	-	8262	6995	■	LTF1123DS850	✓
51	I	✓	80	4000	S/W	-	8262	7070	■	LTF1123DS840	✓
51	I	✓	80	3000	S/W	-	7863	6810	■	LTF1123DS830	✓
36	I	✓	80	5000	S/W	-	6196	5495	■	LTF1122DS850	✓
36	I	✓	80	4000	S/W	-	6196	5555	■	LTF1122DS840	✓
36	I	✓	80	3000	S/W	-	5897	5380	■	LTF1122DS830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL 1+			
Louvre GUELL 1+	■	LTF1A3152	✓
Single pole top support GUELL 1+	■	LTF1A2112	✓
Double pole top support GUELL 1+	■	LTF1A2122	✓
Wall support 500 mm/19.69" GUELL 1/2	■	14173394	✓
Wall support 1000 mm/39.37" GUELL 1/2	■	14173494	✓




LTF1A2112




LTF1A2122



14173394




14173494



Padel Zenter - Jönköping - Sweden

GUELL 2+



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) consult factory
- Design by GIORGIO LODI




Church of St. George in Braida - Verona - Italy



GUELL 2+

Identifying and classifying our optics



GUELL 2+ A/W

IP66 - IK07 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
149	I	✓	80	5000	A40/W	-	24733	20975	■	LTF1225FA850	✓
149	I	✓	80	4000	A40/W	-	24733	21505	■	LTF1225FA840	✓
149	I	✓	80	3000	A40/W	-	23800	20645	■	LTF1225FA830	✓
128	I	✓	80	5000	A40/W	-	20310	17705	■	LTF1224FA850	✓
128	I	✓	80	4000	A40/W	-	20310	17705	■	LTF1224DA850	✓
128	I	✓	80	4000	A40/W	-	20310	17975	■	LTF1224FA840	✓
128	I	✓	80	3000	A40/W	-	19550	17060	■	LTF1224FA830	✓
103	I	✓	80	5000	A40/W	-	16522	13460	■	LTF1223FA850	✓
103	I	✓	80	4000	A40/W	-	16522	13665	■	LTF1223FA840	✓
103	I	✓	80	3000	A40/W	-	15725	13010	■	LTF1223FA830	✓
74	I	✓	80	5000	A40/W	-	12391	10475	■	LTF1222FA850	✓
74	I	✓	80	4000	A40/W	-	12391	10635	■	LTF1222FA840	✓
74	I	✓	80	3000	A40/W	-	11794	9990	■	LTF1222FA830	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

149	I	✓	80	5000	A40/W	-	24733	20975	■	LTF1225DA850	✓
149	I	✓	80	4000	A40/W	-	24733	21505	■	LTF1225DA840	✓
149	I	✓	80	3000	A40/W	-	23800	20645	■	LTF1225DA830	✓
128	I	✓	80	4000	A40/W	-	20310	17975	■	LTF1224DA840	✓
128	I	✓	80	3000	A40/W	-	19550	17060	■	LTF1224DA830	✓
103	I	✓	80	5000	A40/W	-	16522	13460	■	LTF1223DA850	✓
103	I	✓	80	4000	A40/W	-	16522	13665	■	LTF1223DA840	✓
103	I	✓	80	3000	A40/W	-	15725	13010	■	LTF1223DA830	✓
74	I	✓	80	5000	A40/W	-	12391	10475	■	LTF1222DA850	✓
74	I	✓	80	4000	A40/W	-	12391	10635	■	LTF1222DA840	✓
74	I	✓	80	3000	A40/W	-	11794	9990	■	LTF1222DA830	✓

GUELL 2+ S/W

IP66 - IK07 - 650 °C





LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
149	I	✓	80	5000	S/W	-	24733	21225	■	LTF1225FS850	✓
149	I	✓	80	4000	S/W	-	24733	21770	■	LTF1225FS840	✓
149	I	✓	80	3000	S/W	-	23800	20950	■	LTF1225FS830	✓
128	I	✓	80	5000	S/W	-	20310	18195	■	LTF1224FS850	✓
128	I	✓	80	4000	S/W	-	20310	18475	■	LTF1224FS840	✓
128	I	✓	80	3000	S/W	-	19550	17555	■	LTF1224FS830	✓
103	I	✓	80	5000	S/W	-	16522	13820	■	LTF1223FS850	✓
103	I	✓	80	4000	S/W	-	16522	14030	■	LTF1223FS840	✓
103	I	✓	80	3000	S/W	-	15725	13345	■	LTF1223FS830	✓
74	I	✓	80	5000	S/W	-	12391	10715	■	LTF1222FS850	✓
74	I	✓	80	4000	S/W	-	12391	10880	■	LTF1222FS840	✓
74	I	✓	80	3000	S/W	-	11794	10350	■	LTF1222FS830	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz


149	I	✓	80	5000	S/W	-	24733	21225	■	LTF1225DS850	✓
149	I	✓	80	4000	S/W	-	24733	21770	■	LTF1225DS840	✓
149	I	✓	80	3000	S/W	-	23800	20950	■	LTF1225DS830	✓
128	I	✓	80	5000	S/W	-	20310	18195	■	LTF1224DS850	✓
128	I	✓	80	4000	S/W	-	20310	18475	■	LTF1224DS840	✓
128	I	✓	80	3000	S/W	-	19550	17555	■	LTF1224DS830	✓
103	I	✓	80	5000	S/W	-	16522	13820	■	LTF1223DS850	✓
103	I	✓	80	4000	S/W	-	16522	14030	■	LTF1223DS840	✓
103	I	✓	80	3000	S/W	-	15725	13345	■	LTF1223DS830	✓
74	I	✓	80	5000	S/W	-	12391	10715	■	LTF1222DS850	✓
74	I	✓	80	4000	S/W	-	12391	10880	■	LTF1222DS840	✓
74	I	✓	80	3000	S/W	-	11794	10350	■	LTF1222DS830	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL 2+			
Louvre GUELL 2+		LTF1A3252	✓
Protective grid GUELL 2+		LTF1A5203	✓
Single pole top support GUELL 2+		LTF1A2212	✓
Double pole top support GUELL 2+		LTF1A2222	✓
Wall support 500 mm/19.69" GUELL 1/2		14173394	✓
Wall support 1000 mm/39.37" GUELL 1/2		14173494	✓




LTF1A3252




LTF1A2212



LTF1A2222



14173394




14173494



Timing sport center - Brescia - Italy

GUELL 2.5+



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Protected against power surges up to 10 kV
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI




Sports center Mario Rigamonti - Brescia - Italy



GUELL 2.5+

Identifying and classifying our optics



GUELL 2.5+ A/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
212	I	✓	80	5000	A40/W	-	32622	26655	■	LTF1625FA850	✓
212	I	✓	80	4000	A40/W	-	33288	27200	■	LTF1625FA840	✓
212	I	✓	80	3000	A40/W	-	30960	25295	■	LTF1625FA830	✓
193	I	✓	80	5000	A40/W	-	31002	25465	■	LTF1624FA850	✓
193	I	✓	80	4000	A40/W	-	31476	25855	■	LTF1624FA840	✓
193	I	✓	80	3000	A40/W	-	29292	24045	■	LTF1624FA830	✓
175	I	✓	80	5000	A40/W	-	28032	22905	■	LTF1623FA850	✓
175	I	✓	80	4000	A40/W	-	28602	23365	■	LTF1623FA840	✓
175	I	✓	80	3000	A40/W	-	26598	21730	■	LTF1623FA830	✓
153	I	✓	80	5000	A40/W	-	26388	21530	■	LTF1622FA850	✓
153	I	✓	80	4000	A40/W	-	26928	21970	■	LTF1622FA840	✓
153	I	✓	80	3000	A40/W	-	24906	20315	■	LTF1622FA830	✓

Power LED dimmable DALI - 220-240 V 50/60 Hz

212	I	✓	80	5000	A40/W	-	32622	26655	■	LTF1625DA850	✓
212	I	✓	80	4000	A40/W	-	33288	27200	■	LTF1625DA840	✓
212	I	✓	80	3000	A40/W	-	30960	25295	■	LTF1625DA830	✓
193	I	✓	80	5000	A40/W	-	31002	25465	■	LTF1624DA850	✓
193	I	✓	80	4000	A40/W	-	31476	25855	■	LTF1624DA840	✓
193	I	✓	80	3000	A40/W	-	29292	24045	■	LTF1624DA830	✓
175	I	✓	80	5000	A40/W	-	28032	22905	■	LTF1623DA850	✓
175	I	✓	80	4000	A40/W	-	28602	23365	■	LTF1623DA840	✓
175	I	✓	80	3000	A40/W	-	26598	21730	■	LTF1623DA830	✓
153	I	✓	80	5000	A40/W	-	26388	21530	■	LTF1622DA850	✓
153	I	✓	80	4000	A40/W	-	26928	21970	■	LTF1622DA840	✓
153	I	✓	80	3000	A40/W	-	24906	20315	■	LTF1622DA830	✓

GUELL 2.5+ S/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
212	I	✓	80	5000	S/W	-	32622	27185	■	LTF1625FS850	✓
212	I	✓	80	4000	S/W	-	33288	27740	■	LTF1625FS840	✓
212	I	✓	80	3000	S/W	-	30960	25800	■	LTF1625FS830	✓
193	I	✓	80	5000	S/W	-	31002	25835	■	LTF1624FS850	✓
193	I	✓	80	4000	S/W	-	31476	26230	■	LTF1624FS840	✓
193	I	✓	80	3000	S/W	-	29292	24410	■	LTF1624FS830	✓
175	I	✓	80	5000	S/W	-	28032	23360	■	LTF1623FS850	✓
175	I	✓	80	4000	S/W	-	28602	23835	■	LTF1623FS840	✓
175	I	✓	80	3000	S/W	-	26598	22165	■	LTF1623FS830	✓
153	I	✓	80	5000	S/W	-	26388	21990	■	LTF1622FS850	✓
153	I	✓	80	4000	S/W	-	26928	22440	■	LTF1622FS840	✓
153	I	✓	80	3000	S/W	-	24906	20755	■	LTF1622FS830	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

212	I	✓	80	5000	S/W	-	32622	27185	■	LTF1625DS850	✓
212	I	✓	80	4000	S/W	-	33288	27740	■	LTF1625DS840	✓
212	I	✓	80	3000	S/W	-	30960	25800	■	LTF1625DS830	✓
193	I	✓	80	5000	S/W	-	31002	25835	■	LTF1624DS850	✓
193	I	✓	80	4000	S/W	-	31476	26230	■	LTF1624DS840	✓
193	I	✓	80	3000	S/W	-	29292	24410	■	LTF1624DS830	✓
175	I	✓	80	5000	S/W	-	28032	23360	■	LTF1623DS850	✓
175	I	✓	80	4000	S/W	-	28602	23835	■	LTF1623DS840	✓
175	I	✓	80	3000	S/W	-	26598	22165	■	LTF1623DS830	✓
153	I	✓	80	5000	S/W	-	26388	21990	■	LTF1622DS850	✓
153	I	✓	80	4000	S/W	-	26928	22440	■	LTF1622DS840	✓
153	I	✓	80	3000	S/W	-	24906	20755	■	LTF1622DS830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL 2.5+			
Louvre GUELL 2.5+	■	LTF1A3652	✓
Protective grid GUELL 2.5+		LTF1A5603	✓
Steel 'U' bolt clamp for Ø 60-80 mm poles painted aluminium grey	■	14012294	✓
Single pole top support GUELL 2.5	■	310966	✓
Double pole top support GUELL 2.5	■	310967	✓




LTF1A3652



14012294



310966



310967

GUELL 3



■ GR-94 / Metallic grey / Textured



Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10-Ø14 mm
- High asymmetrical distributions low-glare optic options available (A50/W versions)
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Openable and maintainable luminaire (future-proof)
- Consult factory for dimmable DALI versions with remote supply unit, up to a 50-metre maximum distance (A50 / W models only)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI




Icerink De Meent - Alkmaar - Netherlands



GUELL 3

Identifying and classifying our optics



GUELL 3 S/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
291	I	-	80	4000	S/W	-	43015	38812	■	3116972	✓
291	I	-	80	3000	S/W	-	40972	37254	■	3116975	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
291	I	-	80	4000	S/W	-	43015	38812	■	3116974	✓
291	I	-	80	3000	S/W	-	40972	37254	■	3116977	✓



GUELL 3 A/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
291	I	-	80	4000	A40/W	-	43015	36328	■	3116963	✓
291	I	-	80	3000	A40/W	-	40972	34875	■	3116966	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
291	I	-	80	4000	A40/W	-	43015	36328	■	3116965	✓
291	I	-	80	3000	A40/W	-	40972	34875	■	3116968	✓



GUELL 3 A50/W


IP66 - IK07

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
305	I	✓	80	4000	A50/W	-	48341	35814	■	306114	✓
305	I	✓	80	3000	A50/W	-	43200	34346	■	3109685	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
305	I	-	80	4000	A50/W	-	48341	35814	■	306120	✓
305	I	✓	80	3000	A50/W	-	43200	34346	■	3103871	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL 3			
Protective grid		14452702	✓
Wall mount support 1000 mm	■	14453994	✓
Single pole top support GUELL 3 for poles Ø 60-76 mm/Ø 2.36"-2.99"	■	14453794	✓
Double pole top support GUELL 3 for poles Ø 60-76 mm/Ø 2.36"-2.99"	■	14453894	✓
GUELL 3 strengthening bracket. Suitable for one floodlight single point fixing M10 screw in centre of the bracket	■	14461104	✓
GUELL 3 S/W			
Louvre GUELL 3 Symmetrical		14454220	✓
GUELL 3 A/W			
Louvre A40/W	■	14452894	✓
Louvre GUELL 3-4 A50/W	■	3102585	✓
GUELL 3 A/W - S/W			
Frosted glass GUELL 3	■	14452994	✓




14452702




14453994




14453794




14453894



14461104



14454220



14452894
3102585



14452994

GUELL 4



■ GR-94 / Metallic grey / Textured



Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical connection box
- Cable gland for cables Ø 7 - Ø 17 mm
- High asymmetrical distributions low-glare optic options available (A50/W versions)
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Galvanised powder-coated steel bracket
- Polyester powder coat steel sheet gear housing
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Consult factory for dimmable DALI versions with remote supply unit, up to a 50-metre maximum distance (A50 / W models only)
- Design by GIORGIO LODI




Schierker Feuerstein arena - Wernigerode - Germany



GUELL 4

Identifying and classifying our optics



GUELL 4 A/W

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
428	I	-	80	4000	A40/W	-	62472	50539	■	3117452	✓
428	I	-	80	3000	A40/W	-	59100	47624	■	3117450	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
428	I	-	80	4000	A40/W	-	62472	50539	■	3117451	✓
428	I	-	80	3000	A40/W	-	59100	47624	■	3117449	✓

5000K versions are available on web



GUELL 4 S/W

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
428	I	-	80	4000	S/W	-	62472	55187	■	3117458	✓
428	I	-	80	3000	S/W	-	59100	50539	■	3117456	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
428	I	-	80	4000	S/W	-	62472	55187	■	3117457	✓
428	I	-	80	3000	S/W	-	59100	50539	■	3117455	✓

5000K versions are available on web



GUELL 4 A50/W

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
448	I	-	80	4000	A50/W	-	72511	52346	■	306128	✓

5000K versions are available on web




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
GUELL 4 A/W - S/W			
Vetro soft GUELL 4	■	14465794	✓
GUELL 4 A/W			
Louvre A40/W	■	14452894	✓
Louvre GUELL 3-4 A50/W	■	3102585	✓
GUELL 4			
Protective grid		14452702	✓



14465794




14452894
3102585



14452702

SMART [PRO]E 1M




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information


Medium-power outdoor and indoor LED floodlight, ideal for lighting small to medium-sized areas and sports facilities

- The main body is made in die cast aluminium EN AB 46100, with an integrated passive heat sink, and powder coated polyester frame with trivalent passivation
- Available with five different types of optics, three types of Correlated Colour Temperature (3000K/4000K/5700K) and two different types of Colour Rendering Index (CRI70, CRI80)
- COB LED technology for high efficacy
- Built-in 1-10V dimmable driver
- Designed to withstand surges up to 6 kV (differential mode) and 10 kV (common mode), temperature variations from -30°C to +40°C, water and dust penetration up to IP66, and impact up to IK08
- Insulation class I
- Electrical connection via 5x1mm² H07RN-F cable
- Reflector made of metallised PC-HT or anodised and polished aluminium
- 4mm thick toughened front glass, silkscreen printed for symmetrical versions or with anti-reflective nanocoating for asymmetrical versions
- Equipped with a venting and anti-condensation valve
- It can be installed on the wall, ceiling or ground thanks to the galvanised steel bracket which is powder coated in polyester with trivalent passivation and equipped with an adjustable goniometric scale and supplied in kit form
- Anti-ageing silicone gaskets and A2 stainless steel exterior screws



SMART [PRO]E 1M

Identifying and classifying our optics



SMART [PROJE 1M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
150	I	✓	80	5700	SM	Medium	-	21500	■	GWP2134CJ857	✓
150	I	✓	80	5700	SN	Narrow	-	21600	■	GWP2134CI857	✓
150	I	✓	80	5700	SW	Wide	-	21500	■	GWP2134CK857	✓
150	I	✓	80	4000	SM	Medium	-	21500	■	GWP2134CJ840	✓
150	I	✓	80	4000	SN	Narrow	-	21600	■	GWP2134CI840	✓
150	I	✓	80	4000	SW	Wide	-	21500	■	GWP2134CK840	✓
150	I	✓	80	3000	SM	Medium	-	20900	■	GWP2134CJ830	✓
150	I	✓	80	3000	SN	Narrow	-	21000	■	GWP2134CI830	✓
150	I	✓	80	3000	SW	Wide	-	20900	■	GWP2134CK830	✓
150	I	✓	70	5700	SM	Medium	-	22500	■	GWP2134CJ757	✓
150	I	✓	70	5700	SN	Narrow	-	22600	■	GWP2134CI757	✓
150	I	✓	70	5700	SW	Wide	-	22500	■	GWP2134CK757	✓
150	I	✓	70	4000	SM	Medium	-	22500	■	GWP2134CJ740	✓
150	I	✓	70	4000	SN	Narrow	-	22600	■	GWP2134CI740	✓
150	I	✓	70	4000	SW	Wide	-	22500	■	GWP2134CK740	✓
150	I	✓	70	3000	SM	Medium	-	21900	■	GWP2134CJ730	✓
150	I	✓	70	3000	SN	Narrow	-	22000	■	GWP2134CI730	✓
150	I	✓	70	3000	SW	Wide	-	21900	■	GWP2134CK730	✓

SMART [PROJE 1M ASYMMETRIC

IP66 - IK08




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
150	I	✓	80	5700	ALW	Medium	-	19500	■	GWP2134CX857	✓
150	I	✓	80	5700	ASW	Wide	-	21800	■	GWP2134CR857	✓
150	I	✓	80	4000	ALW	Medium	-	19500	■	GWP2134CX840	✓
150	I	✓	80	4000	ASW	Wide	-	21800	■	GWP2134CR840	✓
150	I	✓	80	3000	ALW	Medium	-	18900	■	GWP2134CX830	✓
150	I	✓	80	3000	ASW	Wide	-	21200	■	GWP2134CR830	✓
150	I	✓	70	5700	ALW	Medium	-	20400	■	GWP2134CX757	✓
150	I	✓	70	5700	ASW	Wide	-	22800	■	GWP2134CR757	✓
150	I	✓	70	4000	ALW	Medium	-	20400	■	GWP2134CX740	✓
150	I	✓	70	4000	ASW	Wide	-	22800	■	GWP2134CR740	✓
150	I	✓	70	3000	ALW	Medium	-	19800	■	GWP2134CX730	✓
150	I	✓	70	3000	ASW	Wide	-	22200	■	GWP2134CR730	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PROJE 1M			
Visor		GWP20300	✓
Connector GW Connect 3 poles (for indoor use only)		GWP20110	✓
Connector GW Connect 4 poles (for indoor use only)		GWP20111	✓
Connector GW Connect 5 poles (for indoor use only)		GWP20112	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
SMART [PROJE 1M - SYMM			
Replacement glass for symmetric optic versions		GWP20401	✓
SMART [PROJE 1M - ASYMM			
Replacement glass for asymmetric optic versions		GWP20403	✓

SMART [PRO]E 2M




■ Graphite grey / Graphite grey /

Scan the QR-code for the latest information

Medium-power outdoor and indoor LED floodlight, ideal for lighting small to medium-sized areas and sports facilities


- The main body is made in die cast aluminium EN AB 46100, with an integrated passive heat sink, and powder coated polyester frame with trivalent passivation
- Available with five different types of optics, three types of Correlated Colour Temperature (3000K/4000K/5700K) and two different types of Colour Rendering Index (CRI70, CRI80)
- COB LED technology for high efficacy
- Built-in 1-10 V dimmable driver (for RM versions to be ordered separately)
- Designed to withstand surges up to 6 kV (differential mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66, and impact up to IK08
- Insulation class I
- Electrical connection via 5x1mm² H07RN-F cable
- Reflector made of metallised PC-HT or anodised and polished aluminium
- 4mm thick toughened front glass, silkscreen printed for symmetrical versions or with anti-reflective nanocoating for asymmetrical versions
- Anti-ageing silicone gaskets and A2 stainless steel exterior screws
- Equipped with a venting and anti-condensation valve
- It can be installed on the wall, ceiling or ground thanks to the galvanised steel bracket which is powder coated in polyester with trivalent passivation and equipped with an adjustable goniometric scale and supplied in kit form



SMART [PRO]E 2M

SMART [PRO]E 2M RM

Identifying and classifying our optics



SMART IPROJE 2M RM SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
300	I	✓	80	5700	SM	Medium	-	43000	■	GWP2234AJ857	✓
300	I	✓	80	5700	SN	Narrow	-	43200	■	GWP2234AI857	✓
300	I	✓	80	5700	SW	Wide	-	43000	■	GWP2234AK857	✓
300	I	✓	80	4000	SM	Medium	-	43000	■	GWP2234AJ840	✓
300	I	✓	80	4000	SN	Narrow	-	43200	■	GWP2234AI840	✓
300	I	✓	80	4000	SW	Wide	-	43000	■	GWP2234AK840	✓
300	I	✓	80	3000	SM	Medium	-	41800	■	GWP2234AJ830	✓
300	I	✓	80	3000	SN	Narrow	-	42000	■	GWP2234AI830	✓
300	I	✓	80	3000	SW	Wide	-	41800	■	GWP2234AK830	✓
300	I	✓	70	5700	SM	Medium	-	45000	■	GWP2234AJ757	✓
300	I	✓	70	5700	SN	Narrow	-	45200	■	GWP2234AI757	✓
300	I	✓	70	5700	SW	Wide	-	45000	■	GWP2234AK757	✓
300	I	✓	70	4000	SM	Medium	-	45000	■	GWP2234AJ740	✓
300	I	✓	70	4000	SN	Narrow	-	45200	■	GWP2234AI740	✓
300	I	✓	70	4000	SW	Wide	-	45000	■	GWP2234AK740	✓
300	I	✓	70	3000	SM	Medium	-	43800	■	GWP2234AJ730	✓
300	I	✓	70	3000	SN	Narrow	-	44000	■	GWP2234AI730	✓
300	I	✓	70	3000	SW	Wide	-	43800	■	GWP2234AK730	✓

SMART IPROJE 2M RM ASYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 1CH											
300	I	✓	80	5700	ALW	Medium	-	39000	■	GWP2234AX857	✓
300	I	✓	80	5700	ASW	Wide	-	43600	■	GWP2234AR857	✓
300	I	✓	80	4000	ALW	Medium	-	39000	■	GWP2234AX840	✓
300	I	✓	80	4000	ASW	Wide	-	43600	■	GWP2234AR840	✓
300	I	✓	80	3000	ALW	Medium	-	37800	■	GWP2234AX830	✓
300	I	✓	80	3000	ASW	Wide	-	42400	■	GWP2234AR830	✓
300	I	✓	70	5700	ALW	Medium	-	40800	■	GWP2234AX757	✓
300	I	✓	70	5700	ASW	Wide	-	45600	■	GWP2234AR757	✓
300	I	✓	70	4000	ALW	Medium	-	40800	■	GWP2234AX740	✓
300	I	✓	70	4000	ASW	Wide	-	45600	■	GWP2234AR740	✓
300	I	✓	70	3000	ALW	Medium	-	39600	■	GWP2234AX730	✓
300	I	✓	70	3000	ASW	Wide	-	44400	■	GWP2234AR730	✓

SMART IPROJE 2M SYMMETRIC

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
300	I	✓	80	5700	SM	Medium	-	43000	■	GWP2234CJ857	✓
300	I	✓	80	5700	SN	Narrow	-	43200	■	GWP2234CI857	✓
300	I	✓	80	5700	SW	Wide	-	43000	■	GWP2234CK857	✓
300	I	✓	80	4000	SM	Medium	-	43000	■	GWP2234CJ840	✓
300	I	✓	80	4000	SN	Narrow	-	43200	■	GWP2234CI840	✓
300	I	✓	80	4000	SW	Wide	-	43000	■	GWP2234CK840	✓
300	I	✓	80	3000	SM	Medium	-	41800	■	GWP2234CJ830	✓
300	I	✓	80	3000	SN	Narrow	-	42000	■	GWP2234CI830	✓
300	I	✓	80	3000	SW	Wide	-	41800	■	GWP2234CK830	✓
300	I	✓	70	5700	SM	Medium	-	45000	■	GWP2234CJ757	✓
300	I	✓	70	5700	SN	Narrow	-	45200	■	GWP2234CI757	✓
300	I	✓	70	5700	SW	Wide	-	45000	■	GWP2234CK757	✓
300	I	✓	70	4000	SM	Medium	-	45000	■	GWP2234CJ740	✓
300	I	✓	70	4000	SN	Narrow	-	45200	■	GWP2234CI740	✓
300	I	✓	70	4000	SW	Wide	-	45000	■	GWP2234CK740	✓
300	I	✓	70	3000	SM	Medium	-	43800	■	GWP2234CJ730	✓
300	I	✓	70	3000	SN	Narrow	-	44000	■	GWP2234CI730	✓
300	I	✓	70	3000	SW	Wide	-	43800	■	GWP2234CK730	✓

SMART [PROJE 2M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
300	I	✓	80	5700	ALW	Medium	-	39000	■	GWP2234CX857	✓
300	I	✓	80	5700	ASW	Wide	-	43600	■	GWP2234CR857	✓
300	I	✓	80	4000	ALW	Medium	-	39000	■	GWP2234CX840	✓
300	I	✓	80	4000	ASW	Wide	-	43600	■	GWP2234CR840	✓
300	I	✓	80	3000	ALW	Medium	-	37800	■	GWP2234CX830	✓
300	I	✓	80	3000	ASW	Wide	-	42400	■	GWP2234CR830	✓
300	I	✓	70	5700	ALW	Medium	-	40800	■	GWP2234CX757	✓
300	I	✓	70	5700	ASW	Wide	-	45600	■	GWP2234CR757	✓
300	I	✓	70	4000	ALW	Medium	-	40800	■	GWP2234CX740	✓
300	I	✓	70	4000	ASW	Wide	-	45600	■	GWP2234CR740	✓
300	I	✓	70	3000	ALW	Medium	-	39600	■	GWP2234CX730	✓
300	I	✓	70	3000	ASW	Wide	-	44400	■	GWP2234CR730	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PROJE 2M RM			
Power supply unit 1-10 V 220-240 V		GWP20010	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PROJE 2M			
Visor		GWP20301	✓
Connector GW Connect 3 poles (for indoor use only)		GWP20110	✓
Connector GW Connect 4 poles (for indoor use only)		GWP20111	✓
Connector GW Connect 5 poles (for indoor use only)		GWP20112	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
SMART [PROJE 2M - SYMM			
Replacement glass for symmetric optic versions		GWP20402	✓
SMART [PROJE 2M - ASYMM			
Replacement glass for asymmetric optic versions		GWP20404	✓

SMART [PRO]E 4M




Scan the QR-code for the latest information

■ Graphite grey / Graphite grey /


High-power outdoor and indoor LED floodlight, ideal for lighting medium-sized areas and sports facilities

- The main body is made in die cast aluminium EN AB 46100, with an integrated passive heat sink, and powder coated polyester frame with trivalent passivation
- Available with five different types of optics, three types of Correlated Colour Temperature (3000K/4000K/5700K) and two different types of Colour Rendering Index (CRI70, CRI80)
- COB LED technology for high efficacy
- Power supply unit and IP68 connector kit supplied separately
- Designed to withstand surges up to 6 kV (differential mode) and 10 kV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66, and impact up to IK08
- Insulation class I
- Electrical connection via 5x1mm² H07RN-F cable
- Reflector made of metallised PC-HT or anodised and polished aluminium
- 4mm thick toughened front glass, silkscreen printed for symmetrical versions or with anti-reflective nanocoating for asymmetrical versions
- Anti-ageing silicone gaskets and A2 stainless steel exterior screws
- Plastic venting and anti-condensation device
- It can be installed on the wall, ceiling or ground thanks to the galvanised steel bracket which is powder coated in polyester with trivalent passivation and equipped with an adjustable goniometric scale and supplied in kit form



SMART [PRO]E
4M

Identifying and classifying our optics



SMART IPROJE 4M SYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
600	I	✓	80	5700	SM	Medium	-	86000	■	GWP2434AJ857	✓
600	I	✓	80	5700	SN	Narrow	-	86400	■	GWP2434AI857	✓
600	I	✓	80	5700	SW	Wide	-	86000	■	GWP2434AK857	✓
600	I	✓	80	4000	SM	Medium	-	86000	■	GWP2434AJ840	✓
600	I	✓	80	4000	SN	Narrow	-	86400	■	GWP2434AI840	✓
600	I	✓	80	4000	SW	Wide	-	86000	■	GWP2434AK840	✓
600	I	✓	80	3000	SM	Medium	-	83600	■	GWP2434AJ830	✓
600	I	✓	80	3000	SN	Narrow	-	84000	■	GWP2434AI830	✓
600	I	✓	80	3000	SW	Wide	-	83600	■	GWP2434AK830	✓
600	I	✓	70	5700	SM	Medium	-	90000	■	GWP2434AJ757	✓
600	I	✓	70	5700	SN	Narrow	-	90400	■	GWP2434AI757	✓
600	I	✓	70	5700	SW	Wide	-	90000	■	GWP2434AK757	✓
600	I	✓	70	4000	SM	Medium	-	90000	■	GWP2434AJ740	✓
600	I	✓	70	4000	SN	Narrow	-	90400	■	GWP2434AI740	✓
600	I	✓	70	4000	SW	Wide	-	90000	■	GWP2434AK740	✓
600	I	✓	70	3000	SM	Medium	-	87600	■	GWP2434AJ730	✓
600	I	✓	70	3000	SN	Narrow	-	88000	■	GWP2434AI730	✓
600	I	✓	70	3000	SW	Wide	-	87600	■	GWP2434AK730	✓



SMART IPROJE 4M ASYMMETRIC

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 2CH											
600	I	✓	80	5700	ALW	Medium	-	78000	■	GWP2434AX857	✓
600	I	✓	80	5700	ASW	Wide	-	87200	■	GWP2434AR857	✓
600	I	✓	80	4000	ALW	Medium	-	78000	■	GWP2434AX840	✓
600	I	✓	80	4000	ASW	Wide	-	87200	■	GWP2434AR840	✓
600	I	✓	80	3000	ALW	Medium	-	75600	■	GWP2434AX830	✓
600	I	✓	80	3000	ASW	Wide	-	84800	■	GWP2434AR830	✓
600	I	✓	70	5700	ALW	Medium	-	81600	■	GWP2434AX757	✓
600	I	✓	70	5700	ASW	Wide	-	91200	■	GWP2434AR757	✓
600	I	✓	70	4000	ALW	Medium	-	81600	■	GWP2434AX740	✓
600	I	✓	70	4000	ASW	Wide	-	91200	■	GWP2434AR740	✓
600	I	✓	70	3000	ALW	Medium	-	79200	■	GWP2434AX730	✓
600	I	✓	70	3000	ASW	Wide	-	88800	■	GWP2434AR730	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PROJE 4M			
Power supply unit 1-10 V 220-240 V		GWP20011	✓





GWP20011

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [PROJE 4M			
Visor		GWP20301	✓
Connector GW Connect 3 poles (for indoor use only)		GWP20110	✓
Connector GW Connect 4 poles (for indoor use only)		GWP20111	✓
Connector GW Connect 5 poles (for indoor use only)		GWP20112	✓
3-way connection kit		GWP20113	✓
4-way connection kit		GWP20114	✓
SMART [PROJE 4M - SYMM			
Replacement glass for symmetric optic versions		GWP20402	✓
SMART [PROJE 4M - ASYMM			
Replacement glass for asymmetric optic versions		GWP20404	✓

WIN PRO 20



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Fully integrated PA66 fiberglass reinforced technopolymer trim hinged to the housing
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Stainless steel locking hardware
- Powder-coated steel tiltable bracket
- Built-in driver
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Complete with integral, powder-coated, die-cast aluminium trim and 1 m factory pre-wired cable (WIN PRO+ versions)




Padel Center - Jönköping - Sweden



WIN PRO 20

Identifying and classifying our optics



WIN PRO 20 S/EW

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
68	I	-	70	4000	S/EW	-	13088	10644	■	3114511	✓
68	I	-	70	3000	S/EW	-	12856	10236	■	3114510	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
68	I	-	70	4000	S/EW	-	13088	10644	■	3114513	✓
68	I	-	70	3000	S/EW	-	12856	10236	■	3114512	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
68	I	-	70	4000	S/EW	-	13088	10644	■	3114515	✓
68	I	-	70	3000	S/EW	-	12856	10236	■	3114514	✓

5700 K and WIN PRO+ 20 (Aluminium Ring / 1 m cable) versions are available on web



WIN PRO 20 A/M

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
68	I	-	70	4000	A55/M	-	13088	9701	■	3114499	✓
68	I	-	70	3000	A55/M	-	12856	9330	■	3114498	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
68	I	-	70	4000	A55/M	-	13088	9701	■	3114501	✓
68	I	-	70	3000	A55/M	-	12856	9330	■	3114500	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
68	I	-	70	4000	A55/M	-	13088	9701	■	3114503	✓
68	I	-	70	3000	A55/M	-	12856	9330	■	3114502	✓

5700 K and WIN PRO+ 20 (Aluminium Ring / 1 m cable) versions are available on web



WIN PRO 20 A/W

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
68	I	-	70	4000	A35/W	-	13088	9356	■	3114505	✓
68	I	-	70	3000	A35/W	-	12856	8997	■	3114504	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
68	I	-	70	4000	A35/W	-	13088	9356	■	3114507	✓
68	I	-	70	3000	A35/W	-	12856	8997	■	3114506	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
68	I	-	70	4000	A35/W	-	13088	9356	■	3114509	✓
68	I	-	70	3000	A35/W	-	12856	8997	■	3114508	✓

5700 K and WIN PRO+ 20 (Aluminium Ring / 1 m cable) versions are available on web




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
WIN PRO 20			
Louvre WIN PRO 20 - 5°	■	3116934	✓
Louvre WIN PRO 20 - 10°	■	3116935	✓
External steel cowl painted aluminium grey	■	14043194	✓
External anti-glare louvre painted aluminium grey	■	14043294	✓
Connection Kit 5P Ø 8÷17 mm - IP68		3115887	✓
Wspornik montażowy ze stali nierdzewnej	■	14048104	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 1 luminaire	■	14029094	✓
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 2 opposed luminaires	■	14047194	✓
500 mm wall mounting extension arm in sheet steel painted aluminium grey	■	14043394	✓



WIN PRO 30



■ GR-94 / Metallic grey / Textured


Scan the QR-code for the latest information

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-transparent polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Fully integrated PA66 fiberglass reinforced technopolymer trim hinged to the housing
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Stainless steel locking hardware
- Powder-coated steel tiltable bracket
- Built-in driver
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Openable and maintainable luminaire (future-proof)
- Complete with ZHAGA socket positioned on the upper part of the luminaire (UP position) and D4i driver. Ready for "radio frequency node" smart, twilight and other compatible solutions (ZHAGA options). Consult factory for more options
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Complete with integral, powder-coated, die-cast aluminium trim and 1 m factory pre-wired cable (WIN PRO+ versions)




Timing sport center - Brescia - Italy



WIN PRO 30

Identifying and classifying our optics



WIN PRO 30 S/EW

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
252	I	-	70	5700	S/EW	-	41665	38822	■	3114614	✓
252	I	-	70	4000	S/EW	-	42232	39388	■	3114613	✓
252	I	-	70	3000	S/EW	-	40613	37879	■	3114612	✓
195	I	-	70	5700	S/EW	-	35073	30870	■	3114578	✓
195	I	-	70	4000	S/EW	-	35586	31320	■	3114577	✓
195	I	-	70	3000	S/EW	-	34221	30120	■	3114576	✓
130	I	-	70	5700	S/EW	-	23324	21064	■	3114542	✓
130	I	-	70	4000	S/EW	-	23712	21371	■	3114541	✓
130	I	-	70	3000	S/EW	-	22803	20552	■	3114540	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

252	I	-	70	5700	S/EW	-	41665	38822	■	3114617	✓
252	I	-	70	4000	S/EW	-	42232	39388	■	3114616	✓
252	I	-	70	3000	S/EW	-	40613	37879	■	3114615	✓
195	I	-	70	5700	S/EW	-	35073	30870	■	3114581	✓
195	I	-	70	4000	S/EW	-	35586	31320	■	3114580	✓
195	I	-	70	3000	S/EW	-	34221	30120	■	3114579	✓
130	I	-	70	5700	S/EW	-	23324	21064	■	3114545	✓
130	I	-	70	4000	S/EW	-	23712	21371	■	3114544	✓
130	I	-	70	3000	S/EW	-	22803	20552	■	3114543	✓

Power LED - with automatic power reduction 220-240 V 50/60 Hz

252	I	-	70	5700	S/EW	-	41665	38822	■	3114620	✓
252	I	-	70	4000	S/EW	-	42232	39388	■	3114619	✓
252	I	-	70	3000	S/EW	-	40613	37879	■	3114618	✓
195	I	-	70	5700	S/EW	-	35073	30870	■	3114584	✓
195	I	-	70	4000	S/EW	-	35586	31320	■	3114583	✓
195	I	-	70	3000	S/EW	-	34221	30120	■	3114582	✓
130	I	-	70	5700	S/EW	-	23324	21064	■	3114548	✓
130	I	-	70	4000	S/EW	-	23712	21371	■	3114547	✓
130	I	-	70	3000	S/EW	-	22803	20552	■	3114546	✓

WIN PRO 30 S/EW ZHAGA

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
252	I	-	70	5700	S/EW	-	41665	38822	■	3114623	✓
252	I	-	70	4000	S/EW	-	42232	39388	■	3114622	✓
252	I	-	70	3000	S/EW	-	40613	37879	■	3114621	✓
195	I	-	70	5700	S/EW	-	35073	30870	■	3114587	✓
195	I	-	70	4000	S/EW	-	35586	31320	■	3114586	✓
195	I	-	70	3000	S/EW	-	34221	30120	■	3114585	✓
130	I	-	70	5700	S/EW	-	23324	21064	■	3114551	✓
130	I	-	70	4000	S/EW	-	23712	21371	■	3114550	✓
130	I	-	70	3000	S/EW	-	22803	20552	■	3114549	✓



WIN PRO 30 A/M

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
252	I	-	70	5700	A55/M	-	41665	36726	■	3114590	✓
252	I	-	70	4000	A55/M	-	42232	37262	■	3114589	✓
252	I	-	70	3000	A55/M	-	40613	35834	■	3114588	✓
195	I	-	70	5700	A55/M	-	35073	29044	■	3114554	✓
195	I	-	70	4000	A55/M	-	35586	29468	■	3114553	✓
195	I	-	70	3000	A55/M	-	34221	28338	■	3114552	✓
130	I	-	70	5700	A55/M	-	23324	19844	■	3114518	✓
130	I	-	70	4000	A55/M	-	23712	20174	■	3114517	✓
130	I	-	70	3000	A55/M	-	22803	19401	■	3114516	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
252	I	-	70	5700	A55/M	-	41665	36726	■	3114593	✓
252	I	-	70	4000	A55/M	-	42232	37262	■	3114592	✓
252	I	-	70	3000	A55/M	-	40613	35834	■	3114591	✓
195	I	-	70	5700	A55/M	-	35073	29044	■	3114557	✓
195	I	-	70	4000	A55/M	-	35586	29468	■	3114556	✓
195	I	-	70	3000	A55/M	-	34221	28338	■	3114555	✓
130	I	-	70	5700	A55/M	-	23324	19844	■	3114521	✓
130	I	-	70	4000	A55/M	-	23712	20174	■	3114520	✓
130	I	-	70	3000	A55/M	-	22803	19401	■	3114519	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
252	I	-	70	5700	A55/M	-	41665	36726	■	3114596	✓
252	I	-	70	4000	A55/M	-	42232	37262	■	3114595	✓
252	I	-	70	3000	A55/M	-	40613	35834	■	3114594	✓
195	I	-	70	5700	A55/M	-	35073	29044	■	3114560	✓
195	I	-	70	4000	A55/M	-	35586	29468	■	3114559	✓
195	I	-	70	3000	A55/M	-	34221	28338	■	3114558	✓
130	I	-	70	5700	A55/M	-	23712	19844	■	3114524	✓
130	I	-	70	4000	A55/M	-	23712	20174	■	3114523	✓
130	I	-	70	3000	A55/M	-	22803	19401	■	3114522	✓



WIN PRO 30 A/M ZHAGA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
252	I	-	70	5700	A55/M	-	41665	36726	■	3114599	✓
252	I	-	70	4000	A55/M	-	42232	37262	■	3114598	✓
252	I	-	70	3000	A55/M	-	40613	35834	■	3114597	✓
195	I	-	70	5700	A55/M	-	35073	29044	■	3114563	✓
195	I	-	70	4000	A55/M	-	35586	29468	■	3114562	✓
195	I	-	70	3000	A55/M	-	34221	28338	■	3114561	✓
130	I	-	70	5700	A55/M	-	23324	19844	■	3114527	✓
130	I	-	70	4000	A55/M	-	23712	20174	■	3114526	✓
130	I	-	70	3000	A55/M	-	22803	19401	■	3114525	✓



WIN PRO 30 A/W

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
252	I	-	70	5700	A35/W	-	41665	35492	■	3114602	✓
252	I	-	70	4000	A35/W	-	42232	36010	■	3114601	✓
252	I	-	70	3000	A35/W	-	40613	34630	■	3114600	✓
195	I	-	70	5700	A35/W	-	35073	28723	■	3114566	✓
195	I	-	70	4000	A35/W	-	35586	28685	■	3114565	✓
195	I	-	70	3000	A35/W	-	34221	27856	■	3114564	✓
130	I	-	70	5700	A35/W	-	23324	19344	■	3114530	✓
130	I	-	70	4000	A35/W	-	23712	19626	■	3114529	✓
130	I	-	70	3000	A35/W	-	22803	18874	■	3114528	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

252	I	-	70	5700	A35/W	-	41665	35492	■	3114605	✓
252	I	-	70	4000	A35/W	-	42232	36010	■	3114604	✓
252	I	-	70	3000	A35/W	-	40613	34630	■	3114603	✓
195	I	-	70	5700	A35/W	-	35073	28723	■	3114569	✓
195	I	-	70	4000	A35/W	-	35586	28685	■	3114568	✓
195	I	-	70	3000	A35/W	-	34221	27856	■	3114567	✓
130	I	-	70	5700	A35/W	-	23324	19344	■	3114533	✓
130	I	-	70	4000	A35/W	-	23712	19626	■	3114532	✓
130	I	-	70	3000	A35/W	-	22803	18874	■	3114531	✓

Power LED - with automatic power reduction 220-240 V 50/60 Hz

252	I	-	70	5700	A35/W	-	41665	35492	■	3114608	✓
252	I	-	70	4000	A35/W	-	42232	36010	■	3114607	✓
252	I	-	70	3000	A35/W	-	40613	34630	■	3114606	✓
195	I	-	70	5700	A35/W	-	35073	28723	■	3114572	✓
195	I	-	70	4000	A35/W	-	35586	28685	■	3114571	✓
195	I	-	70	3000	A35/W	-	34221	27856	■	3114570	✓
130	I	-	70	5700	A35/W	-	23324	19344	■	3114536	✓
130	I	-	70	4000	A35/W	-	23712	19626	■	3114535	✓
130	I	-	70	3000	A35/W	-	22803	18874	■	3114534	✓

WIN PRO 30 A/W ZHAGA


IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
252	I	-	70	5700	A35/W	-	41665	35492	■	3114611	✓
252	I	-	70	4000	A35/W	-	42232	36010	■	3114610	✓
252	I	-	70	3000	A35/W	-	40613	34630	■	3114609	✓
195	I	-	70	5700	A35/W	-	35073	28723	■	3114575	✓
195	I	-	70	4000	A35/W	-	35586	28685	■	3114574	✓
195	I	-	70	3000	A35/W	-	34221	27856	■	3114573	✓
130	I	-	70	5700	A35/W	-	23324	19344	■	3114539	✓
130	I	-	70	4000	A35/W	-	23712	19626	■	3114538	✓
130	I	-	70	3000	A35/W	-	22803	18874	■	3114537	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
WIN PRO 30			
Louvre WIN PRO 30 - 5°	■	3116517	✓
Louvre WIN PRO 30 - 10°	■	3116518	✓
External steel cowl painted aluminium grey	■	14045794	✓
External anti-glare louvre painted aluminium grey	■	14045694	✓
Strengthening bracket. Suitable for one floodlight single point fixing M12 screw in centre of the bracket	■	14046120	✓
Single pole top mounting, for Ø 60-76 mm poles, painted aluminium grey	■	14051294	✓
1000 mm extension arm in heavy gauge steel, painted aluminium grey	■	14048694	✓
Double pole top mounting, Ø 60-76 mm poles, painted aluminium grey	■	14051394	✓
Long bracket for ceiling mounting, painted aluminium grey	■	14057394	✓
Connection Kit 5P Ø 8÷17 mm - IP68		3115887	✓



3116517

3116518

14045794



14045694

14046120

14051294



14048694

14051394

14057394




3115887



Icerink De Meent - Alkmaar - Netherlands

WIN PRO 40





■ GR-94 / Metallic grey / Textured

Scan the QR-code for the latest information




- High-powered LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Extra clear, toughened, flat glass diffuser
 - High-transparency polycarbonate optics
 - Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
 - Tempered glass hinged to the housing by polyester powder coat finish die-cast aluminium brackets ISO 9227/12944 - ISO 9223 (C5)
 - Cable gland M20x1.5 for cables Ø 6 - Ø 13 mm
 - Supplied with 0,5 m pre-wired H07RN-F 3G2,5 mm² cable
 - Stainless steel locking hardware
 - Powder-coated steel tiltable bracket
 - All WIN PRO 40 power consumption includes power unit losses
 - Integral graduated goniometer for aiming purposes
 - Openable and maintainable luminaire (future-proof)
 - For WIN PRO 40, use only the power supply units available as accessories (ordered separately)
 - IP66-rated power control gears are available in RPA, DALI and DMX-RDM. Maximum distance of 100 m cable length between control gear and luminaire (1CH)
 - Standard supplied with two stainless steel brackets allowing the control gear to be fixed directly to the back of the luminaire
 - The power supply groups are made up of drivers with protection against mains power surges of up to 10 kV (CM/DM)
 - Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
 - For up lighting installation, consult factory



WIN PRO 40

Identifying and classifying our optics



WIN PRO 40 S/EW

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED											
575	I	-	70	5700	S/EW	-	94568	86052	■	3118174	✓
575	I	-	70	4000	S/EW	-	97382	85140	■	3118173	✓
575	I	-	70	3000	S/EW	-	92264	81981	■	3118172	✓
392	I	-	70	5700	S/EW	-	62982	57825	■	3118165	✓
392	I	-	70	4000	S/EW	-	64856	57195	■	3118164	✓
392	I	-	70	3000	S/EW	-	61447	55073	■	3118163	✓



WIN PRO 40 A/M

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED											
575	I	-	70	5700	A55/M	-	94568	84112	■	3118168	✓
575	I	-	70	4000	A55/M	-	97382	83322	■	3118167	✓
575	I	-	70	3000	A55/M	-	92264	80133	■	3118166	✓
392	I	-	70	5700	A55/M	-	62982	54848	■	3118159	✓
392	I	-	70	4000	A55/M	-	64856	54251	■	3118158	✓
392	I	-	70	3000	A55/M	-	61447	52238	■	3118157	✓



WIN PRO 40 A/W

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED											
575	I	-	70	5700	A35/W	-	94568	80318	■	3118171	✓
575	I	-	70	4000	A35/W	-	97382	79472	■	3118170	✓
575	I	-	70	3000	A35/W	-	92264	76511	■	3118169	✓
392	I	-	70	5700	A35/W	-	62982	53586	■	3118162	✓
392	I	-	70	4000	A35/W	-	64856	53006	■	3118161	✓
392	I	-	70	3000	A35/W	-	61447	51039	■	3118160	✓



Control gear


DESCRIPTION	COLOR	PART NUMBER	UKCA
WIN PRO 40			
DRIVER BOX 600 W - 2 A - 1 CH - RPA		3118130	✓
DRIVER BOX 600 W - 2 A - 1 CH - DALI		3118131	✓
DRIVER BOX 600 W - 2 A - 1 CH - DMX		3118132	✓




3118130
3118131
3118132

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
WIN PRO 40			
Louvre WIN PRO 40 - 5°	■	3118121	✓
Louvre WIN PRO 40 - 10°	■	3118182	✓
Connection Kit 5P Ø 8÷17 mm - IP68		3115887	✓
Strengthening bracket. Suitable for one floodlight single point fixing M20 screw in centre of the bracket	■	3118332	✓



3118121



3118182




3115887



3118332

WIN PRO L3




Scan the QR-code for the latest information

■ GR-94 / Metallic grey / Textured


High-powered LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- High-efficiency die-cast aluminium heat sink
- Extra clear, toughened, flat glass diffuser
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Tempered glass hinged to the housing by polyester powder coat finish die-cast aluminium brackets ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium electrical connection box polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5)
- Waterproof M25x1.5 cable gland for cables Ø 13 - Ø 18 mm
- Stainless steel locking hardware
- Die-cast aluminium bracket, polyester powder coat prior surface chemical conversion
- Integral graduated goniometer for aiming purposes
- Openable and maintainable luminaire (future-proof)
- All WIN PRO L power consumption includes power unit losses
- For WIN PRO L, use only the power supply units available as accessories (ordered separately)
- Sono disponibili gruppi di alimentazione dimmerabili DALI e DMX-RDM IP66. Il collegamento elettrico tra essi ed i relativi proiettori deve essere fatto con una lunghezza massima di cavo di 200 m
- The power supply groups are made up of drivers with protection against mains power surges of up to 10 kV (CM/DM)
- Are available as accessories two stainless steel brackets allowing the control gear to be fixed directly to the luminaire bracket
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For up lighting installation, consult factory



WIN PRO L3 A

Identifying and classifying our optics



WIN PRO L3 A/M

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1625	I	-	80	5700	A32/M	32°	280332	-	■	LTF6324RA857	✓
1625	I	-	80	5700	A55/M	55°	280332	-	■	LTF6324RC857	✓
1625	I	-	70	5700	A32/M	32°	306540	-	■	LTF6324RA757	✓
1625	I	-	70	5700	A55/M	55°	306540	-	■	LTF6324RC757	✓
1625	I	-	70	4000	A32/M	32°	310284	-	■	LTF6324RA740	✓
1625	I	-	70	4000	A55/M	55°	310284	-	■	LTF6324RC740	✓
1625	I	-	70	3000	A32/M	32°	296712	-	■	LTF6324RA730	✓
1625	I	-	70	3000	A55/M	55°	296712	-	■	LTF6324RC730	✓
1450	I	-	80	5700	A32/M	32°	247104	-	■	LTF6323RA857	✓
1450	I	-	80	5700	A55/M	55°	247104	-	■	LTF6323RC857	✓
1450	I	-	70	5700	A32/M	32°	270036	-	■	LTF6323RA757	✓
1450	I	-	70	5700	A55/M	55°	270036	-	■	LTF6323RC757	✓
1450	I	-	70	4000	A32/M	32°	273312	-	■	LTF6323RA740	✓
1450	I	-	70	4000	A55/M	55°	276312	-	■	LTF6323RC740	✓
1450	I	-	70	3000	A32/M	32°	261612	-	■	LTF6323RA730	✓
1450	I	-	70	3000	A55/M	55°	261612	-	■	LTF6323RC730	✓



WIN PRO L3 A/W

IP66 - IK08 - 960 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - 3CH											
1625	I	-	80	5700	A35/W	35°	280332	-	■	LTF6324RB857	✓
1625	I	-	70	5700	A35/W	35°	306540	-	■	LTF6324RB757	✓
1625	I	-	70	4000	A35/W	35°	310284	-	■	LTF6324RB740	✓
1625	I	-	70	3000	A35/W	35°	296712	-	■	LTF6324RB730	✓
1450	I	-	80	5700	A35/W	35°	247104	-	■	LTF6323RB857	✓
1450	I	-	70	5700	A35/W	35°	270036	-	■	LTF6323RB757	✓
1450	I	-	70	4000	A35/W	35°	276312	-	■	LTF6323RB740	✓
1450	I	-	70	3000	A35/W	35°	261612	-	■	LTF6323RB730	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
WIN PRO L3			
WIN PRO L3 Driver box 1500 3CH DALI 1,05 A		LTF6A0305	✓
Driver box 1500 3CH DMX 1,05 A		LTF6A0306	✓
WIN PRO L3 Driver box 1500 3CH DALI 1,2 A		LTF6A0307	✓
Driver box 1500 3CH DMX 1,2 A		LTF6A0308	✓
Brackets supports for driver		LTF6A2043	✓
Louvre 5°		LTF6A3312	✓
Louvre 10°		LTF6A3322	✓
Pointer support		LTF6A6033	✓

ELIA FL S3




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information


LED floodlight, available in medium and high-power versions for outdoor and indoor applications in industrial, tertiary and sports contexts, such as façades, warehouses, car parks and sports fields

- Thanks to its black powder-coated die-cast aluminium body and its front glass, the fixture is tough, durable (IP66 and IK08) and is able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- Available in 4 different sizes and power steps (50 W, 100 W, 150 W and 200 W), the range allows for great flexibility with its multiple possible combinations: 3 colour temperature options (3,000 K warm white, 4,000 K neutral white and 5,700 K cool white) with a colour rendering index of more than 80; 2 integrated power supply options (On/Off and DALI); and 2 optics options (60° and asymmetrical)
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket with a protractor, or pole-mounted (in poles with diameter up to 61 mm) through a dedicated accessory (to be ordered separately)



ELIA FL S3 50W

Identifying and classifying our optics



ELIA FL S3 50W 60°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	I	✓	80	5700	SYMM	60°	-	6800	■	GWF1100HH857	✓
50	I	✓	80	4000	SYMM	60°	-	6800	■	GWF1100HH840	✓
50	I	✓	80	3000	SYMM	60°	-	6600	■	GWF1100HH830	✓



ELIA FL S3 50W ASYMMETRIC

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	I	✓	80	5700	ASYMM	-	-	6400	■	GWF1100HC857	✓
50	I	✓	80	4000	ASYMM	-	-	6400	■	GWF1100HC840	✓
50	I	✓	80	3000	ASYMM	-	-	6200	■	GWF1100HC830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA FL S3			
Headpole - black		GWF1901	✓



GWF1901

ELIA FL M3




Scan the QR-code for the latest information

■ Black RAL 9017 / Black RAL9017 /


LED floodlight, available in medium and high-power versions for outdoor and indoor applications in industrial, tertiary and sports contexts, such as façades, warehouses, car parks and sports fields

- Thanks to its black powder-coated die-cast aluminium body and its front glass, the fixture is tough, durable (IP66 and IK08) and is able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- Available in 4 different sizes and power steps (50 W, 100 W, 150 W and 200 W), the range allows for great flexibility with its multiple possible combinations: 3 colour temperature options (3,000 K warm white, 4,000 K neutral white and 5,700 K cool white) with a colour rendering index of more than 80; 2 integrated power supply options (On/Off and DALI); and 2 optics options (60° and asymmetrical)
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket with a protractor, or pole-mounted (in poles with diameter up to 61 mm) through a dedicated accessory (to be ordered separately)



ELIA FL M3 100W

Identifying and classifying our optics



ELIA FL M3 100W 60°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
100	I	✓	80	5700	SYMM	60°	-	13800	■	GWF1100NH857	✓
100	I	✓	80	4000	SYMM	60°	-	13800	■	GWF1100NH840	✓
100	I	✓	80	3000	SYMM	60°	-	13300	■	GWF1100NH830	✓



ELIA FL M3 100W ASYMMETRIC

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
100	I	✓	80	5700	ASYMM	-	-	13400	■	GWF1100NC857	✓
100	I	✓	80	4000	ASYMM	-	-	13400	■	GWF1100NC840	✓
100	I	✓	80	3000	ASYMM	-	-	12900	■	GWF1100NC830	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA FL M3			
Headpole - black		GWF1901	✓



GWF1901

ELIA FL L3




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information


LED floodlight, available in medium and high-power versions for outdoor and indoor applications in industrial, tertiary and sports contexts, such as façades, warehouses, car parks and sports fields

- Thanks to its black powder-coated die-cast aluminium body and its front glass, the fixture is tough, durable (IP66 and IK08) and is able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- Available in 4 different sizes and power steps (50 W, 100 W, 150 W and 200 W), the range allows for great flexibility with its multiple possible combinations: 3 colour temperature options (3,000 K warm white, 4,000 K neutral white and 5,700 K cool white) with a colour rendering index of more than 80; 2 integrated power supply options (On/Off and DALI); and 2 optics options (60° and asymmetrical)
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket with a protractor, or pole-mounted (in poles with diameter up to 61 mm) through a dedicated accessory (to be ordered separately)



ELIA FL L3 150W

Identifying and classifying our optics



ELIA FL L3 150W ASYMMETRIC

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
150	I	✓	80	5700	ASYMM	-	-	20600	■	GWF1100RC857	✓
150	I	✓	80	4000	ASYMM	-	-	20600	■	GWF1100RC840	✓
150	I	✓	80	3000	ASYMM	-	-	19900	■	GWF1100RC830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
150	I	✓	80	4000	ASYMM	-	-	20600	■	GWF1101RC840	✓



ELIA FL L3 150W 60°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
150	I	✓	80	5700	SYMM	60°	-	21200	■	GWF1100RH857	✓
150	I	✓	80	4000	SYMM	60°	-	21200	■	GWF1100RH840	✓
150	I	✓	80	3000	SYMM	60°	-	20400	■	GWF1100RH830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
150	I	✓	80	4000	SYMM	60°	-	21200	■	GWF1101RH840	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA FL L3			
Headpole - black		GWF1901	✓



GWF1901

ELIA FL XL3




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information


LED floodlight, available in medium and high-power versions for outdoor and indoor applications in industrial, tertiary and sports contexts, such as façades, warehouses, car parks and sports fields

- Thanks to its black powder-coated die-cast aluminium body and its front glass, the fixture is tough, durable (IP66 and IK08) and is able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- Available in 4 different sizes and power steps (50 W, 100 W, 150 W and 200 W), the range allows for great flexibility with its multiple possible combinations: 3 colour temperature options (3,000 K warm white, 4,000 K neutral white and 5,700 K cool white) with a colour rendering index of more than 80; 2 integrated power supply options (On/Off and DALI); and 2 optics options (60° and asymmetrical)
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket with a protractor, or pole-mounted (in poles with diameter up to 61 mm) through a dedicated accessory (to be ordered separately)



ELIA FL XL3 200W

Identifying and classifying our optics



ELIA FL XL3 200W 60°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
200	I	✓	80	5700	SYMM	60°	-	27900	■	GWF1100ZH857	✓
200	I	✓	80	4000	SYMM	60°	-	27900	■	GWF1100ZH840	✓
200	I	✓	80	3000	SYMM	60°	-	26900	■	GWF1100ZH830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
200	I	✓	80	4000	SYMM	60°	-	27900	■	GWF1101ZH840	✓



ELIA FL XL3 200W ASYMMETRIC

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
200	I	✓	80	5700	ASYMM	-	-	27600	■	GWF1100ZC857	✓
200	I	✓	80	4000	ASYMM	-	-	27600	■	GWF1100ZC840	✓
200	I	✓	80	3000	ASYMM	-	-	26600	■	GWF1100ZC830	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
200	I	✓	80	4000	ASYMM	-	-	27600	■	GWF1101ZC840	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ELIA FL XL3			
Headpole - black		GWF1901	✓



GWF1901

ELIA FL MINI XS1




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information

Low-power LED floodlight for indoor and outdoor architectural lighting for both residential and professional applications, such as façades, gardens, green areas and walkways


- Thanks to its black powder-coated die-cast aluminium body and its front glass, it is tough, durable and able to withstand harsh environmental conditions
- Available in 2 sizes and 3 power steps (10 W, 20 W and 30 W), the range allows for great flexibility with its multiple possible combinations: 2 colour temperature options (3,000 K warm white and 4,000 K neutral white) with a colour rendering index of more than 80, and 2 optics options (100° or asymmetrical)
- The fixture is equipped with an integrated On/Off electronic power supply, and it is also available with an integrated motion and luminosity sensor
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket



ELIA FL MINI XS1 10W*

ELIA FL MINI XS1 10W
PIR

Identifying and classifying our optics



ELIA FL MINI XS1 10W 100°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10	I	✓	80	4000	SYMM	100°	-	1500	■	GWF1100AL840	✓
10	I	✓	80	3000	SYMM	100°	-	1400	■	GWF1100AL830	✓





ELIA FL MINI XS1 10W 100° PIR

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + PIR sensor											
10	I	✓	80	4000	SYMM	100°	-	1500	■	GWF1105AL840	✓
10	I	✓	80	3000	SYMM	100°	-	1400	■	GWF1105AL830	✓



ELIA FL MINI XS2




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information

Low-power LED floodlight for indoor and outdoor architectural lighting for both residential and professional applications, such as façades, gardens, green areas and walkways


- Thanks to its black powder-coated die-cast aluminium body and its front glass, it is tough, durable and able to withstand harsh environmental conditions
- Available in 2 sizes and 3 power steps (10 W, 20 W and 30 W), the range allows for great flexibility with its multiple possible combinations: 2 colour temperature options (3,000 K warm white and 4,000 K neutral white) with a colour rendering index of more than 80, and 2 optics options (100° or asymmetrical)
- The fixture is equipped with an integrated On/Off electronic power supply, and it is also available with an integrated motion and luminosity sensor
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket



ELIA FL MINI XS2 20W

ELIA FL MINI XS2 20W
PIR

Identifying and classifying our optics



ELIA FL MINI XS2 20W 100°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	I	✓	80	4000	SYMM	100°	-	2400	■	GWF1100BL840	✓
20	I	✓	80	3000	SYMM	100°	-	2300	■	GWF1100BL830	✓




ELIA FL MINI XS2 20W 100° PIR

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + PIR sensor											
20	I	✓	80	4000	SYMM	100°	-	2400	■	GWF1105BL840	✓
20	I	✓	80	3000	SYMM	100°	-	2300	■	GWF1105BL830	✓



ELIA FL MINI XS3




■ Black RAL 9017 / Black RAL9017 /

Scan the QR-code for the latest information

Low-power LED floodlight for indoor and outdoor architectural lighting for both residential and professional applications, such as façades, gardens, green areas and walkways


- Thanks to its black powder-coated die-cast aluminium body and its front glass, it is tough, durable and able to withstand harsh environmental conditions
- Available in 2 sizes and 3 power steps (10 W, 20 W and 30 W), the range allows for great flexibility with its multiple possible combinations: 2 colour temperature options (3,000 K warm white and 4,000 K neutral white) with a colour rendering index of more than 80, and 2 optics options (100° or asymmetrical)
- The fixture is equipped with an integrated On/Off electronic power supply, and it is also available with an integrated motion and luminosity sensor
- The luminaire can be ceiling, wall or floor-mounted through the integrated adjustable steel bracket



ELIA FL MINI XS3 30W

ELIA FL MINI XS3 30W
PIR

Identifying and classifying our optics



ELIA FL MINI XS3 30W 100°

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	✓	80	4000	SYMM	100°	-	4000	■	GWF1100CL840	✓
30	I	✓	80	3000	SYMM	100°	-	3900	■	GWF1100CL830	✓



ELIA FL MINI XS3 30W 100° PIR

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + PIR sensor											
30	I	✓	80	4000	SYMM	100°	-	4000	■	GWF1105CL840	✓
30	I	✓	80	3000	SYMM	100°	-	3900	■	GWF1105CL830	✓



ELIA FL MINI XS3 30W ASYMMETRIC

IP66 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	✓	80	4000	ASYMM	-	-	3700	■	GWF1100CC840	✓
30	I	✓	80	3000	ASYMM	-	-	3600	■	GWF1100CC830	✓



ELIA FL MINI XS3 30W ASYMMETRIC PIR

IP65 - IK08 - 750 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz + PIR sensor											
30	I	✓	80	4000	ASYMM	-	-	3700	■	GWF1105CC840	✓
30	I	✓	80	3000	ASYMM	-	-	3600	■	GWF1105CC830	✓



SPIDER+ 10



Private Villa - Verona - Italy





Scan the QR-code for the latest information


■ BK-81 / Black / Textured

LED floodlight for indoor and outdoor, comprising:

- Polyester powder coat finish, die-cast aluminium housing, in compact size
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Waterproof cable gland M16x1.5 for cables Ø 5- Ø 10 mm
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Stainless steel locking hardware
- Painted steel bracket
- Complete with 1 m factory pre-wired cable H05RN-F 3G1 mm²
- SPIDER+ 10 KIT models are equipped with a technopolymer ground spike and 3 metres cable H05RN-F 3G1 mm²
- Design by GIORGIO LODI



SPIDER+ 10



SPIDER+ 10
KIT

SPIDER+ 10 S/EW

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	S/EW	-	1485	1060	■	3108610	✓
9.5	I	-	80	3000	S/EW	-	1350	977	■	3108608	✓



SPIDER+ 10 KIT S/EW

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9.5	I	-	80	4000	S/EW	-	1485	1060	■	3108613	✓
9.5	I	-	80	3000	S/EW	-	1350	977	■	3108612	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPIDER+ 10 - SPIDER+ 10 KIT			
Connection Kit Y 3-way Ø 7-10.5 mm IP68		310496	✓
Connection Kit Y 3-way Ø 14-17 mm IP68		310495	✓



310495
310496

SPIDER+ 20




Scan the QR-code for the latest information

■ BK-81 / Black / Textured


LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel fasteners for glass
- Extra pure polished aluminium reflector
- Stainless steel locking hardware
- Polyester powder-coated steel bracket with simplified mounting system
- Complete with 0,7 m factory pre-wired cable H05RN-F 3G1 mm²
- The luminous flux data shown refer to the maximum power operating level
- Design by GIORGIO LODI



SPIDER+ 20

Identifying and classifying our optics



SPIDER+ 20 S/W

IP66 - IK05 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
51	I	-	80	4000	S/W	-	6965	6179	■	3118358	✓
51	I	-	80	3000	S/W	-	6675	5921	■	3118357	✓




SPIDER+ 20 A/EW

IP66 - IK05 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
51	I	-	80	4000	A35/EW	-	6965	6005	■	3118356	✓
51	I	-	80	3000	A35/EW	-	6675	5754	■	3118355	✓



SPIDER+ 30




■ BK-81 / Black / Textured

Scan the QR-code for the latest information


LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel fasteners for glass
- Extra pure polished aluminium reflector
- Stainless steel locking hardware
- Polyester powder-coated steel bracket with simplified mounting system
- Complete with 0,7 m factory pre-wired cable H05RN-F 3G1 mm²
- The luminous flux data shown refer to the maximum power operating level
- Design by GIORGIO LODI



SPIDER+ 30

Identifying and classifying our optics



SPIDER+ 30 S/W

IP66 - IK06 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	S/W	-	13930	11987	■	3118366	✓
101	I	-	80	3000	S/W	-	13350	11486	■	3118365	✓





SPIDER+ 30 A/EW

IP66 - IK06 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	A35/EW	-	13930	11649	■	3118364	✓
101	I	-	80	3000	A35/EW	-	13350	11162	■	3118363	✓



SPIDER+ POST




■ BK-81 / Black / Textured


Scan the QR-code for the latest information

Pole-top mounted outdoor luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium pole clamp with polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5), for Ø 60 mm poles
- Extra pure polished aluminium reflector
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Glazing diffuser permanently sealed to the housing trough high-temperature resistant silicone
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP66-rated, PA66 polyamide, socket-plug fast connector, complete with factory pre-wired cable for mains connection without opening the luminaire, for cables Ø 6,5 - Ø 10 mm
- Luminaire designed to operate with two predetermined power levels that can be selected by the user acting on the specific cable in the fast connector
- Built-in driver
- Stainless steel locking hardware
- The luminous flux data shown refer to the maximum power operating level
- Pole clamp for Ø 76 mm poles is available as accessory
- The DLS+DETEK versions are supplied with an electronic device complete with a High Frequency sensor and a daylight sensor (DLS). This is programmed to switch the device on automatically when natural light is low, ensuring constant secure lighting at 30% of the luminous flow and reaching 100% of the flow when any presence is detected
- Design by GIORGIO LODI



SPIDER+ POST



SPIDER+
DLS+DETEK

SPIDER+ POST A/EW MULTIPOWER

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
37	II	-	80	4000	A35/EW	-	6967	6005	■	3109057	✓
51							5525	4762			
37	II	-	80	3000	A35/EW	-	6677	5754	■	3109056	✓
51							5295	4563			



SPIDER+ POST A/EW DLS+DETEK

IP66 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	80	4000	A35/EW	-	5525	4763	■	3115352	✓
40	II	-	80	3000	A35/EW	-	5291	4560	■	3115351	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPIDER+ POST			
Painted die-cast aluminium pole-mounting joint for pole Ø 76 mm	■	3109437	✓
Wall angled bracket in hot dipped galvanized steel, cataphoresis and finished polyester - Ø 60 mm	■	1407779690100	✓




3109437



1407779690100

KREOS




■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

LED street luminaire, comprising:


- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Coated die-cast aluminium pole-top adaptor for pole Ø 60 / 76 mm
- High-performance polished, oxidised, PVD 99.99% silver treated, pure aluminium reflectors. This treatment creates an iridescence-free surface with a greater than 97% reflectance
- StReet optic options: SR/075 usually for narrow roads ($0.5 \geq L/H \geq 0.75$), SR/100 for two-lane roads ($L/H = 1$), SR/125 for wide streets and ($L/H = 1.25$), SR/150 for wide roads/parking lots ($L/H = 1.5$) schemes. L/H ratio (L-road width/H-pole height)
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- The integral switch splitter automatically disconnects the driver from mains when opened
- Die-cast aluminium retaining clip with stainless steel spring allows quick and tool-free access to the luminaire for extraordinary maintenance
- Removable galvanized sheet metal gear tray
- Built-in driver
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Complete with 1 m H07RN-F 2x1.5 mm² or H07RN-F 4x1.5 mm² (dimmable options) cable, for mains connection without opening the luminaire
- Stainless steel locking hardware
- Complete with NEMA socket connected to DALI driver and waterproof short-circuit cap for On/Off operation mode and SMART-compatible mounting solutions (NEMA options)
- Complete with ZHAGA socket positioned on the upper part of the luminaire (UP position) and D4i driver. Ready for "radio frequency node" smart, twilight and other compatible solutions (ZHAGA options). Consult factory for more options
- Upon request, luminaires can be provided with ZHAGA socket positioned in the lower part of the luminaire (DOWN position) or mixed (UP position + DOWN position) to be able to connect presence and/or motion detectors or combined solutions
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- DALI-2 (IEC 62386) dimmable ballast available. Consult factory
- CLO (Constant Light Output) options available. Consult factory




KREOS



KREOS
NEMA




KREOS
ZHAGA



KREOS
ZHAGA (up+down)

Identifying and classifying our optics



KREOS SR/075

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
82	II	-	70	4000	SR/075	-	12707	9851	■	3106228	✓
82	II	-	70	3000	SR/075	-	12125	9400	■	3106237	✓
63	II	-	70	4000	SR/075	-	10611	8302	■	3106227	✓
63	II	-	70	3000	SR/075	-	10125	7922	■	3106236	✓
53	II	-	70	4000	SR/075	-	9039	7293	■	3106226	✓
53	II	-	70	3000	SR/075	-	8625	6959	■	3106235	✓
44	II	-	70	4000	SR/075	-	7729	6323	■	3106225	✓
44	II	-	70	3000	SR/075	-	7375	6033	■	3106234	✓
35	II	-	70	4000	SR/075	-	6288	5117	■	3106224	✓
35	II	-	70	3000	SR/075	-	6000	4883	■	3106233	✓
34	II	-	70	4000	SR/075	-	5305	4240	■	3106223	✓
34	II	-	70	3000	SR/075	-	5062	4046	■	3106232	✓
24	II	-	70	4000	SR/075	-	3930	3163	■	3106222	✓
24	II	-	70	3000	SR/075	-	3750	3018	■	3106231	✓
16	II	-	70	4000	SR/075	-	2685	2155	■	3106221	✓
16	II	-	70	3000	SR/075	-	2562	2056	■	3106230	✓
12	II	-	70	4000	SR/075	-	1965	1567	■	3106220	✓
12	II	-	70	3000	SR/075	-	1875	1495	■	3106229	✓



KREOS SR/100

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
82	II	-	70	4000	SR/100	-	12707	9862	■	3106112	✓
82	II	-	70	3000	SR/100	-	12125	9410	■	3106170	✓
63	II	-	70	4000	SR/100	-	10611	8311	■	3106111	✓
63	II	-	70	3000	SR/100	-	10125	7930	■	3106169	✓
53	II	-	70	4000	SR/100	-	9039	7302	■	3106110	✓
53	II	-	70	3000	SR/100	-	8625	6968	■	3106168	✓
44	II	-	70	4000	SR/100	-	7729	6330	■	3106109	✓
44	II	-	70	3000	SR/100	-	7375	6040	■	3106167	✓
35	II	-	70	4000	SR/100	-	6288	5122	■	3106108	✓
35	II	-	70	3000	SR/100	-	6000	4887	■	3106166	✓
34	II	-	70	4000	SR/100	-	5305	4247	■	3106107	✓
34	II	-	70	3000	SR/100	-	5062	4053	■	3106165	✓
24	II	-	70	4000	SR/100	-	3930	3210	■	3106106	✓
24	II	-	70	3000	SR/100	-	3750	3063	■	3106164	✓
16	II	-	70	4000	SR/100	-	2685	2190	■	3106105	✓
16	II	-	70	3000	SR/100	-	2562	2090	■	3106163	✓
12	II	-	70	4000	SR/100	-	1965	1575	■	3106104	✓
12	II	-	70	3000	SR/100	-	1875	1503	■	3106162	✓

Power LED - with automatic power reduction 220-240 V 50/60 Hz

82	II	-	70	4000	SR/100	-	12707	9862	■	3106121	✓
82	II	-	70	3000	SR/100	-	12125	9410	■	3106179	✓
63	II	-	70	4000	SR/100	-	10611	8311	■	3106120	✓
63	II	-	70	3000	SR/100	-	10125	7930	■	3106178	✓
53	II	-	70	4000	SR/100	-	9039	7302	■	3106119	✓
53	II	-	70	3000	SR/100	-	8625	6968	■	3106177	✓
44	II	-	70	4000	SR/100	-	7729	6330	■	3106118	✓
44	II	-	70	3000	SR/100	-	7375	6040	■	3106176	✓
35	II	-	70	4000	SR/100	-	6288	5122	■	3106117	✓
35	II	-	70	3000	SR/100	-	6000	4887	■	3106175	✓
34	II	-	70	4000	SR/100	-	5305	4247	■	3106116	✓
34	II	-	70	3000	SR/100	-	5062	4053	■	3106174	✓
24	II	-	70	4000	SR/100	-	3930	3210	■	3106115	✓
24	II	-	70	3000	SR/100	-	3750	3063	■	3106173	✓
16	II	-	70	4000	SR/100	-	2685	2190	■	3106114	✓
16	II	-	70	3000	SR/100	-	2562	2090	■	3106172	✓
12	II	-	70	4000	SR/100	-	1965	1575	■	3106113	✓
12	II	-	70	3000	SR/100	-	1875	1503	■	3106171	✓



KREOS SR/100 NEMA

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI with NEMA socket - 220-240 V 50/50 Hz											
82	II	-	70	4000	SR/100	-	12707	9862	■	3105696	✓
82	II	-	70	3000	SR/100	-	12125	9410	■	3106161	✓
63	II	-	70	4000	SR/100	-	10611	8311	■	3105695	✓
63	II	-	70	3000	SR/100	-	10125	7930	■	3106160	✓
53	II	-	70	4000	SR/100	-	9039	7302	■	3105694	✓
53	II	-	70	3000	SR/100	-	8625	6968	■	3106159	✓
44	II	-	70	4000	SR/100	-	7729	6330	■	3105693	✓
44	II	-	70	3000	SR/100	-	7375	6040	■	3106158	✓
35	II	-	70	4000	SR/100	-	6288	5122	■	3105692	✓
35	II	-	70	3000	SR/100	-	6000	4887	■	3106157	✓
34	II	-	70	4000	SR/100	-	5305	4247	■	3105691	✓
34	II	-	70	3000	SR/100	-	5062	4053	■	3106156	✓
24	II	-	70	4000	SR/100	-	3930	3210	■	3105690	✓
24	II	-	70	3000	SR/100	-	3750	3063	■	3106155	✓
16	II	-	70	4000	SR/100	-	2685	2190	■	3105689	✓
16	II	-	70	3000	SR/100	-	2562	2090	■	3106154	✓
12	II	-	70	4000	SR/100	-	1965	1575	■	3105688	✓
12	II	-	70	3000	SR/100	-	1875	1503	■	3106153	✓



KREOS SR/100 ZHAGA

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
63	II	-	70	4000	SR/100	-	10611	8311	■	3112204	✓
63	II	-	70	3000	SR/100	-	10125	7930	■	3112307	✓
53	II	-	70	4000	SR/100	-	9039	7302	■	3112308	✓
53	II	-	70	3000	SR/100	-	8625	6968	■	3112309	✓
44	II	-	70	4000	SR/100	-	7729	6330	■	3112310	✓
44	II	-	70	3000	SR/100	-	7375	6040	■	3112311	✓
35	II	-	70	4000	SR/100	-	6288	5122	■	3112312	✓
35	II	-	70	3000	SR/100	-	6000	4887	■	3112313	✓
34	II	-	70	4000	SR/100	-	5305	4247	■	3112314	✓
34	II	-	70	3000	SR/100	-	5062	4053	■	3112315	✓
24	II	-	70	4000	SR/100	-	3930	3210	■	3112316	✓
24	II	-	70	3000	SR/100	-	3750	3063	■	3112317	✓
16	II	-	70	4000	SR/100	-	2685	2190	■	3112318	✓
16	II	-	70	3000	SR/100	-	2562	2090	■	3112319	✓
12	II	-	70	4000	SR/100	-	1965	1575	■	3112320	✓
12	II	-	70	3000	SR/100	-	1875	1503	■	3112321	✓



Power LED - dimmable D4i with ZHAGA socket UP and DOWN - 220-240 V 50/60 Hz											
63	II	-	70	4000	SR/100	-	10611	8311	■	3118632	✓
63	II	-	70	3000	SR/100	-	10125	7930	■	3118633	✓
53	II	-	70	4000	SR/100	-	9039	7302	■	3118634	✓
53	II	-	70	3000	SR/100	-	8625	6968	■	3118635	✓
44	II	-	70	4000	SR/100	-	7729	6330	■	3118636	✓
44	II	-	70	3000	SR/100	-	7375	6040	■	3118637	✓
35	II	-	70	4000	SR/100	-	6288	5122	■	3118638	✓
35	II	-	70	3000	SR/100	-	6000	4887	■	3118639	✓
34	II	-	70	4000	SR/100	-	5305	4247	■	3118640	✓
34	II	-	70	3000	SR/100	-	5062	4053	■	3118641	✓
24	II	-	70	4000	SR/100	-	3930	3210	■	3118642	✓
24	II	-	70	3000	SR/100	-	3750	3063	■	3118643	✓
16	II	-	70	4000	SR/100	-	2685	2190	■	3118644	✓
16	II	-	70	3000	SR/100	-	2562	2090	■	3118645	✓
12	II	-	70	4000	SR/100	-	1965	1575	■	3118646	✓
12	II	-	70	3000	SR/100	-	1875	1503	■	3118647	✓

KREOS SR/125

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
82	II	-	70	4000	SR/125	-	12707	9779	■	3106246	✓
82	II	-	70	3000	SR/125	-	12125	9331	■	3106255	✓
63	II	-	70	4000	SR/125	-	10611	8241	■	3106245	✓
63	II	-	70	3000	SR/125	-	10125	7864	■	3106254	✓
53	II	-	70	4000	SR/125	-	9039	7240	■	3106244	✓
53	II	-	70	3000	SR/125	-	8625	6908	■	3106253	✓
44	II	-	70	4000	SR/125	-	7729	6277	■	3106243	✓
44	II	-	70	3000	SR/125	-	7375	5990	■	3106252	✓
35	II	-	70	4000	SR/125	-	6288	5079	■	3106242	✓
35	II	-	70	3000	SR/125	-	6000	4846	■	3106251	✓
34	II	-	70	4000	SR/125	-	5305	4204	■	3106241	✓
34	II	-	70	3000	SR/125	-	5062	4011	■	3106250	✓
24	II	-	70	4000	SR/125	-	3930	3144	■	3106240	✓
24	II	-	70	3000	SR/125	-	3750	3000	■	3106249	✓
16	II	-	70	4000	SR/125	-	2865	2142	■	3106239	✓
16	II	-	70	3000	SR/125	-	2562	2044	■	3106248	✓
12	II	-	70	4000	SR/125	-	1965	1558	■	3106238	✓
12	II	-	70	3000	SR/125	-	1875	1487	■	3106247	✓



KREOS SR/150

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
82	II	-	70	4000	SR/150	-	12707	9156	■	3106264	✓
82	II	-	70	3000	SR/150	-	12125	8737	■	3106273	✓
63	II	-	70	4000	SR/150	-	10611	7743	■	3106263	✓
63	II	-	70	3000	SR/150	-	10125	7388	■	3106272	✓
53	II	-	70	4000	SR/150	-	9039	6725	■	3106262	✓
53	II	-	70	3000	SR/150	-	8625	6417	■	3106271	✓
44	II	-	70	4000	SR/150	-	7729	5838	■	3106261	✓
44	II	-	70	3000	SR/150	-	7375	5571	■	3106270	✓
35	II	-	70	4000	SR/150	-	6288	4710	■	3106260	✓
35	II	-	70	3000	SR/150	-	6000	4494	■	3106269	✓
34	II	-	70	4000	SR/150	-	5305	3937	■	3106259	✓
34	II	-	70	3000	SR/150	-	5062	3757	■	3106268	✓
24	II	-	70	4000	SR/150	-	3930	2927	■	3106258	✓
24	II	-	70	3000	SR/150	-	3750	2793	■	3106267	✓
16	II	-	70	4000	SR/150	-	2685	1995	■	3106257	✓
16	II	-	70	3000	SR/150	-	2562	1904	■	3106266	✓
12	II	-	70	4000	SR/150	-	1965	1485	■	3106256	✓
12	II	-	70	3000	SR/150	-	1875	1417	■	3106265	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KREOS			
Reducer pole Ø 42÷46 mm	■	3106386	✓
Hot-dipped galvanized wall angled steel bracket, cataphoresis and polyester powder	■	1407796	✓




3106386



1407796

ROAD [5] MINI



Scan the QR-code for the latest information


■ GR-RAL9006 / Grey RAL9006 /

Street lighting device with cover, frame, and pole attachment in EN AB 46100 die-cast aluminium with low copper content:

- Polyester powder coated
- High-power LED
- Printed Circuit Board (PCB) in metal core
- Common mode surge protection up to 10kV
- With safety switch
- Cable plate in PA6.6 + glass fiber
- Cable input via PG13.5 cable gland
- High reflective aluminium optical system
- Tempered flat glass with 4 mm thickness
- Opening and closing system with integrated front handle
- It can be used up to 50°C of ambient temperature but with reduced currents as indicated in the instruction manual
- Suitable for installation both on top of the pole and offset with 5° pitch adjustment




Urban street - Giubiasco - Italy



ROAD [5]
MINI

Identifying and classifying our optics



ROAD [5] MINI 1X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
37	II	✓	70	4000	WIDE	-	-	5000	■	GWR5211	✓
37	II	✓	70	3000	WIDE	-	-	4300	■	GWR521130K	✓
26	II	✓	70	4000	WIDE	-	-	3700	■	GWR5271	✓
26	II	✓	70	3000	WIDE	-	-	3200	■	GWR527130K	✓
13	II	✓	70	4000	WIDE	-	-	2000	■	GWR5231	✓
13	II	✓	70	3000	WIDE	-	-	1700	■	GWR523130K	✓
37	I	✓	70	4000	WIDE	-	-	5000	■	GWR5711	✓
37	I	✓	70	3000	WIDE	-	-	4300	■	GWR571130K	✓
26	I	✓	70	4000	WIDE	-	-	3700	■	GWR5771	✓
26	I	✓	70	3000	WIDE	-	-	3200	■	GWR577130K	✓
13	I	✓	70	4000	WIDE	-	-	2000	■	GWR5731	✓
13	I	✓	70	3000	WIDE	-	-	1700	■	GWR573130K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
37	II	✓	70	4000	WIDE	-	-	5000	■	GWR5211M	✓
37	II	✓	70	3000	WIDE	-	-	4300	■	GWR5211M30K	✓
26	II	✓	70	4000	WIDE	-	-	3700	■	GWR5271M	✓
26	II	✓	70	3000	WIDE	-	-	3200	■	GWR5271M30K	✓
19	II	✓	70	4000	WIDE	-	-	2700	■	GWR5251M	✓
37	I	✓	70	4000	WIDE	-	-	5000	■	GWR5711M	✓
37	I	✓	70	3000	WIDE	-	-	4300	■	GWR5711M30K	✓
26	I	✓	70	4000	WIDE	-	-	3700	■	GWR5771M	✓
26	I	✓	70	3000	WIDE	-	-	3200	■	GWR5771M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
37	II	✓	70	4000	WIDE	-	-	5000	■	GWR5211B	✓
37	II	✓	70	3000	WIDE	-	-	4300	■	GWR5211B30K	✓
26	II	✓	70	4000	WIDE	-	-	3700	■	GWR5271B	✓
26	II	✓	70	3000	WIDE	-	-	3200	■	GWR5271B30K	✓
19	II	✓	70	4000	WIDE	-	-	2700	■	GWR5251B	✓
19	II	-	70	3000	WIDE	-	-	2400	■	GWR5251B30K	✓
37	I	✓	70	4000	WIDE	-	-	5000	■	GWR5711B	✓
37	I	✓	70	3000	WIDE	-	-	4300	■	GWR5711B30K	✓
26	I	✓	70	4000	WIDE	-	-	3700	■	GWR5771B	✓
26	I	✓	70	3000	WIDE	-	-	3200	■	GWR5771B30K	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
37	I	✓	70	4000	WIDE	-	-	5000	■	GWR5711V	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
37	II	✓	70	4000	WIDE	-	-	5000	■	GWR5211V	✓
26	II	✓	70	4000	WIDE	-	-	3700	■	GWR5271V	✓
13	II	✓	70	4000	WIDE	-	-	2000	■	GWR5231V	✓

ROAD [5] MINI 1X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
37	II	✓	70	4000	HUGE	-	-	4700	■	GWR5111	✓
37	II	✓	70	3000	HUGE	-	-	4100	■	GWR511130K	✓
26	II	✓	70	4000	HUGE	-	-	3500	■	GWR5171	✓
26	II	✓	70	3000	HUGE	-	-	3000	■	GWR517130K	✓
13	II	✓	70	4000	HUGE	-	-	1900	■	GWR5131	✓
13	II	✓	70	3000	HUGE	-	-	1600	■	GWR513130K	✓
37	I	✓	70	4000	HUGE	-	-	4700	■	GWR5611	✓
37	I	✓	70	3000	HUGE	-	-	4100	■	GWR561130K	✓
26	I	✓	70	4000	HUGE	-	-	3500	■	GWR5671	✓
26	I	✓	70	3000	HUGE	-	-	3000	■	GWR567130K	✓
13	I	✓	70	4000	HUGE	-	-	1900	■	GWR5631	✓
13	I	✓	70	3000	HUGE	-	-	1600	■	GWR563130K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
37	II	✓	70	4000	HUGE	-	-	4700	■	GWR5111M	✓
37	II	✓	70	3000	HUGE	-	-	4100	■	GWR5111M30K	✓
26	II	✓	70	4000	HUGE	-	-	3500	■	GWR5171M	✓
26	II	✓	70	3000	HUGE	-	-	3000	■	GWR5171M30K	✓
19	II	✓	70	4000	HUGE	-	-	2600	■	GWR5151M	✓
37	I	✓	70	4000	HUGE	-	-	4700	■	GWR5611M	✓
37	I	✓	70	3000	HUGE	-	-	4100	■	GWR5611M30K	✓
26	I	✓	70	4000	HUGE	-	-	3500	■	GWR5671M	✓
26	I	✓	70	3000	HUGE	-	-	3000	■	GWR5671M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
37	II	✓	70	4000	HUGE	-	-	4700	■	GWR5111B	✓
37	II	✓	70	3000	HUGE	-	-	4100	■	GWR5111B30K	✓
26	II	✓	70	4000	HUGE	-	-	3500	■	GWR5171B	✓
26	II	✓	70	3000	HUGE	-	-	3000	■	GWR5171B30K	✓
19	II	✓	70	4000	HUGE	-	-	2600	■	GWR5151B	✓
37	I	✓	70	4000	HUGE	-	-	4700	■	GWR5611B	✓
37	I	✓	70	3000	HUGE	-	-	4100	■	GWR5611B30K	✓
26	I	✓	70	4000	HUGE	-	-	3500	■	GWR5671B	✓
26	I	✓	70	3000	HUGE	-	-	3000	■	GWR5671B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
37	II	✓	70	4000	HUGE	-	-	4700	■	GWR5111V	✓
26	II	✓	70	4000	HUGE	-	-	3500	■	GWR5171V	✓
13	II	✓	70	4000	HUGE	-	-	1900	■	GWR5131V	✓



ROAD [5] MINI 1X3 LED CYCLE

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
27	II	✓	70	4000	CYCLE	-	-	1900	■	GWR5371M	✓
27	II	✓	70	3000	CYCLE	-	-	1900	■	GWR5371M30K	✓
27	I	✓	70	4000	CYCLE	-	-	1900	■	GWR5871M	✓
27	I	✓	70	3000	CYCLE	-	-	1900	■	GWR5871M30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
27	II	✓	70	4000	CYCLE	-	-	1900	■	GWR5371MV	✓



ROAD [5] MINI 2X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
66	II	✓	70	4000	WIDE	-	-	9100	■	GWR5212	✓
66	II	✓	70	3000	WIDE	-	-	7900	■	GWR521230K	✓
51	II	✓	70	4000	WIDE	-	-	7300	■	GWR5272	✓
51	II	✓	70	3000	WIDE	-	-	6400	■	GWR527230K	✓
66	I	✓	70	4000	WIDE	-	-	9100	■	GWR5712	✓
66	I	✓	70	3000	WIDE	-	-	7900	■	GWR571230K	✓
51	I	✓	70	4000	WIDE	-	-	7300	■	GWR5772	✓
51	I	✓	70	3000	WIDE	-	-	6400	■	GWR577230K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
74	II	✓	70	4000	WIDE	-	-	9900	■	GWR5212M	✓
74	II	✓	70	3000	WIDE	-	-	8600	■	GWR5212M30K	✓
51	II	✓	70	4000	WIDE	-	-	7300	■	GWR5272M	✓
51	II	✓	70	3000	WIDE	-	-	6400	■	GWR5272M30K	✓
37	II	✓	70	4000	WIDE	-	-	5400	■	GWR5252M	✓
37	II	-	70	3000	WIDE	-	-	4700	■	GWR5252M30K	✓
74	I	✓	70	4000	WIDE	-	-	9900	■	GWR5712M	✓
74	I	✓	70	3000	WIDE	-	-	8600	■	GWR5712M30K	✓
51	I	✓	70	4000	WIDE	-	-	7300	■	GWR5772M	✓
51	I	✓	70	3000	WIDE	-	-	6400	■	GWR5772M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
74	II	✓	70	4000	WIDE	-	-	9900	■	GWR5212B	✓
74	II	✓	70	3000	WIDE	-	-	8600	■	GWR5212B30K	✓
51	II	✓	70	4000	WIDE	-	-	7300	■	GWR5272B	✓
51	II	✓	70	3000	WIDE	-	-	6400	■	GWR5272B30K	✓
37	II	✓	70	4000	WIDE	-	-	5400	■	GWR5252B	✓
74	I	✓	70	4000	WIDE	-	-	9900	■	GWR5712B	✓
74	I	✓	70	3000	WIDE	-	-	8600	■	GWR5712B30K	✓
51	I	✓	70	4000	WIDE	-	-	7300	■	GWR5772B	✓
51	I	✓	70	3000	WIDE	-	-	6400	■	GWR5772B30K	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
37	II	✓	70	4000	WIDE	-	-	5400	■	GWR5252D	✓
37	II	✓	70	3000	WIDE	-	-	4700	■	GWR5252D30K	✓
74	I	✓	70	4000	WIDE	-	-	9900	■	GWR5712V	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
74	II	✓	70	4000	WIDE	-	-	9900	■	GWR5212V	✓
74	II	-	70	3000	WIDE	-	-	8600	■	GWR5212V30K	✓
51	II	✓	70	4000	WIDE	-	-	7300	■	GWR5272V	✓

ROAD [5] MINI 2X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
66	II	✓	70	4000	HUGE	-	-	8600	■	GWR5112	✓
66	II	✓	70	3000	HUGE	-	-	7400	■	GWR511230K	✓
51	II	✓	70	4000	HUGE	-	-	6900	■	GWR5172	✓
51	II	✓	70	3000	HUGE	-	-	6000	■	GWR517230K	✓
66	I	✓	70	4000	HUGE	-	-	8600	■	GWR5612	✓
66	I	✓	70	3000	HUGE	-	-	7400	■	GWR561230K	✓
51	I	✓	70	4000	HUGE	-	-	6900	■	GWR5672	✓
51	I	✓	70	3000	HUGE	-	-	6000	■	GWR567230K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
74	II	✓	70	4000	HUGE	-	-	9300	■	GWR5112M	✓
74	II	✓	70	3000	HUGE	-	-	8100	■	GWR5112M30K	✓
51	II	✓	70	4000	HUGE	-	-	6900	■	GWR5172M	✓
51	II	✓	70	3000	HUGE	-	-	6000	■	GWR5172M30K	✓
37	II	✓	70	4000	HUGE	-	-	5100	■	GWR5152M	✓
74	I	✓	70	4000	HUGE	-	-	9300	■	GWR5612M	✓
74	I	✓	70	3000	HUGE	-	-	8100	■	GWR5612M30K	✓
51	I	✓	70	4000	HUGE	-	-	6900	■	GWR5672M	✓
51	I	✓	70	3000	HUGE	-	-	6000	■	GWR5672M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
74	II	✓	70	4000	HUGE	-	-	9300	■	GWR5112B	✓
74	II	✓	70	3000	HUGE	-	-	8100	■	GWR5112B30K	✓
51	II	✓	70	4000	HUGE	-	-	6900	■	GWR5172B	✓
51	II	✓	70	3000	HUGE	-	-	6000	■	GWR5172B30K	✓
37	II	✓	70	4000	HUGE	-	-	5100	■	GWR5152B	✓
74	I	✓	70	4000	HUGE	-	-	9300	■	GWR5612B	✓
74	I	✓	70	3000	HUGE	-	-	8100	■	GWR5612B30K	✓
51	I	✓	70	4000	HUGE	-	-	6900	■	GWR5672B	✓
51	I	✓	70	3000	HUGE	-	-	6000	■	GWR5672B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
74	II	✓	70	4000	HUGE	-	-	9300	■	GWR5112V	✓
51	II	✓	70	4000	HUGE	-	-	6900	■	GWR5172V	✓



ROAD [5] MINI 2X3 LED CYCLE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
53	II	✓	70	4000	CYCLE	-	-	3800	■	GWR5372M	✓
53	II	✓	70	3000	CYCLE	-	-	3800	■	GWR5372M30K	✓
53	I	✓	70	4000	CYCLE	-	-	3800	■	GWR5872M	✓
53	I	✓	70	3000	CYCLE	-	-	3800	■	GWR5872M30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
53	II	✓	70	4000	CYCLE	-	-	3800	■	GWR5372MV	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ROAD [5] MINI			
Visor - graphite grey		GWR5191	✓
Wall-mounting bracket 150x160x290 mm - graphite grey		GW86167	✓
Single pole head bracket 1 m - graphite grey		GW87581	✓
Double pole head bracket 1+1 m - graphite grey		GW87582	✓
Short bracket 0.5 m - graphite grey		GW87587	✓
Long bracket 1 m - graphite grey		GW87586	✓
Conical pole painted h = 5.5 m - graphite grey		GW84096	✓
Conical pole painted h = 6.8 m - graphite grey		GW87591	✓
Conical pole painted h = 7.8 m - graphite grey		GW84097	✓
Conical pole painted h = 8.8 m - graphite grey		GW87592	✓
Conical pole painted h = 9.8 m - graphite grey		GW87593	✓




GWR5191



GW86167



GW87581



GW87582



GW87587




GW87586



GW84096

ROAD [5] MEDIUM



■ GR-RAL9006 / Grey RAL9006 /


Scan the QR-code for the latest information

Street lighting device with cover, frame, and pole attachment in EN AB 46100 die-cast aluminium with low copper content:

- Polyester powder coated
- High-power LED
- Printed Circuit Board (PCB) in metal core
- Common mode surge protection up to 10kV
- With safety switch
- Cable plate in PA6.6 + glass fiber
- Cable input via PG13.5 cable gland
- High reflective aluminium optical system
- Tempered flat glass with 4 mm thickness
- Opening and closing system with integrated front handle
- It can be used up to 50°C of ambient temperature but with reduced currents as indicated in the instruction manual
- Suitable for installation both on top of the pole and offset with 5° pitch adjustment




Urban street - Giubiasco - Italy




ROAD [5]
MEDIUM

Identifying and classifying our optics



WIDE - 186 W - 4000 K
180° — 0° | 90° — 270°



HURGE - 186 W - 4000 K
180° — 0° | 90° — 270°

ROAD [5] MEDIUM 3X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
111	II	✓	70	4000	WIDE	-	-	14800	■	GWR5213	✓
111	II	✓	70	3000	WIDE	-	-	12800	■	GWR521330K	✓
77	II	✓	70	4000	WIDE	-	-	11000	■	GWR5273	✓
77	II	✓	70	3000	WIDE	-	-	9500	■	GWR527330K	✓
111	I	✓	70	4000	WIDE	-	-	14800	■	GWR5713	✓
111	I	✓	70	3000	WIDE	-	-	12800	■	GWR571330K	✓
77	I	✓	70	4000	WIDE	-	-	11000	■	GWR5773	✓
77	I	✓	70	3000	WIDE	-	-	9500	■	GWR577330K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
111	II	✓	70	4000	WIDE	-	-	14800	■	GWR5213M	✓
111	II	✓	70	3000	WIDE	-	-	12800	■	GWR5213M30K	✓
77	II	✓	70	4000	WIDE	-	-	11000	■	GWR5273M	✓
77	II	✓	70	3000	WIDE	-	-	9500	■	GWR5273M30K	✓
55	II	✓	70	4000	WIDE	-	-	8100	■	GWR5253M	✓
111	I	✓	70	4000	WIDE	-	-	14800	■	GWR5713M	✓
111	I	✓	70	3000	WIDE	-	-	12800	■	GWR5713M30K	✓
77	I	✓	70	4000	WIDE	-	-	11000	■	GWR5773M	✓
77	I	✓	70	3000	WIDE	-	-	9500	■	GWR5773M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
111	II	✓	70	4000	WIDE	-	-	14800	■	GWR5213B	✓
111	II	✓	70	3000	WIDE	-	-	12800	■	GWR5213B30K	✓
77	II	✓	70	4000	WIDE	-	-	11000	■	GWR5273B	✓
77	II	✓	70	3000	WIDE	-	-	9500	■	GWR5273B30K	✓
55	II	✓	70	4000	WIDE	-	-	8100	■	GWR5253B	✓
111	I	✓	70	4000	WIDE	-	-	14800	■	GWR5713B	✓
111	I	✓	70	3000	WIDE	-	-	12800	■	GWR5713B30K	✓
77	I	✓	70	4000	WIDE	-	-	11000	■	GWR5773B	✓
77	I	✓	70	3000	WIDE	-	-	9500	■	GWR5773B30K	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
55	II	✓	70	4000	WIDE	-	-	8100	■	GWR5253D	✓
55	II	✓	70	3000	WIDE	-	-	7000	■	GWR5253D30K	✓
111	I	✓	70	4000	WIDE	-	-	14800	■	GWR5713V	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
111	II	✓	70	4000	WIDE	-	-	14800	■	GWR5213V	✓
77	II	✓	70	4000	WIDE	-	-	11000	■	GWR5273V	✓

ROAD [5] MEDIUM 3X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
111	II	✓	70	4000	HUGE	-	-	13900	■	GWR5113	✓
111	II	✓	70	3000	HUGE	-	-	12100	■	GWR511330K	✓
77	II	✓	70	4000	HUGE	-	-	10400	■	GWR5173	✓
77	II	✓	70	3000	HUGE	-	-	9000	■	GWR517330K	✓
111	I	✓	70	4000	HUGE	-	-	13900	■	GWR5613	✓
111	I	✓	70	3000	HUGE	-	-	12100	■	GWR561330K	✓
77	I	✓	70	4000	HUGE	-	-	10400	■	GWR5673	✓
77	I	✓	70	3000	HUGE	-	-	9000	■	GWR567330K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
111	II	✓	70	4000	HUGE	-	-	13900	■	GWR5113M	✓
111	II	✓	70	3000	HUGE	-	-	12100	■	GWR5113M30K	✓
77	II	✓	70	4000	HUGE	-	-	10400	■	GWR5173M	✓
77	II	✓	70	3000	HUGE	-	-	9000	■	GWR5173M30K	✓
55	II	✓	70	4000	HUGE	-	-	7700	■	GWR5153M	✓
111	I	✓	70	4000	HUGE	-	-	13900	■	GWR5613M	✓
111	I	✓	70	3000	HUGE	-	-	12100	■	GWR5613M30K	✓
77	I	✓	70	4000	HUGE	-	-	10400	■	GWR5673M	✓
77	I	✓	70	3000	HUGE	-	-	9000	■	GWR5673M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
111	II	✓	70	4000	HUGE	-	-	13900	■	GWR5113B	✓
111	II	✓	70	3000	HUGE	-	-	12100	■	GWR5113B30K	✓
77	II	✓	70	4000	HUGE	-	-	10400	■	GWR5173B	✓
77	II	✓	70	3000	HUGE	-	-	9000	■	GWR5173B30K	✓
55	II	✓	70	4000	HUGE	-	-	7700	■	GWR5153B	✓
111	I	✓	70	4000	HUGE	-	-	13900	■	GWR5613B	✓
111	I	✓	70	3000	HUGE	-	-	12100	■	GWR5613B30K	✓
77	I	✓	70	4000	HUGE	-	-	10400	■	GWR5673B	✓
77	I	✓	70	3000	HUGE	-	-	9000	■	GWR5673B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
111	II	✓	70	4000	HUGE	-	-	13900	■	GWR5113V	✓
77	II	✓	70	4000	HUGE	-	-	10400	■	GWR5173V	✓



ROAD [5] MEDIUM 4X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
148	II	✓	70	4000	WIDE	-	-	19700	■	GWR5214	✓
148	II	✓	70	3000	WIDE	-	-	17100	■	GWR521430K	✓
102	II	✓	70	4000	WIDE	-	-	14600	■	GWR5274	✓
102	II	✓	70	3000	WIDE	-	-	12700	■	GWR527430K	✓
148	I	✓	70	4000	WIDE	-	-	19700	■	GWR5714	✓
148	I	✓	70	3000	WIDE	-	-	17100	■	GWR571430K	✓
102	I	✓	70	4000	WIDE	-	-	14600	■	GWR5774	✓
102	I	✓	70	3000	WIDE	-	-	12700	■	GWR577430K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
148	II	✓	70	4000	WIDE	-	-	19700	■	GWR5214M	✓
148	II	✓	70	3000	WIDE	-	-	17100	■	GWR5214M30K	✓
102	II	✓	70	4000	WIDE	-	-	14600	■	GWR5274M	✓
102	II	✓	70	3000	WIDE	-	-	12700	■	GWR5274M30K	✓
73	II	✓	70	4000	WIDE	-	-	10800	■	GWR5254M	✓
148	I	✓	70	4000	WIDE	-	-	19700	■	GWR5714M	✓
148	I	✓	70	3000	WIDE	-	-	17100	■	GWR5714M30K	✓
102	I	✓	70	4000	WIDE	-	-	14600	■	GWR5774M	✓
102	I	✓	70	3000	WIDE	-	-	12700	■	GWR5774M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
148	II	✓	70	4000	WIDE	-	-	19700	■	GWR5214B	✓
148	II	✓	70	3000	WIDE	-	-	17100	■	GWR5214B30K	✓
102	II	✓	70	4000	WIDE	-	-	14600	■	GWR5274B	✓
102	II	✓	70	3000	WIDE	-	-	12700	■	GWR5274B30K	✓
73	II	✓	70	4000	WIDE	-	-	10800	■	GWR5254B	✓
148	I	✓	70	4000	WIDE	-	-	19700	■	GWR5714B	✓
148	I	✓	70	3000	WIDE	-	-	17100	■	GWR5714B30K	✓
102	I	✓	70	4000	WIDE	-	-	14600	■	GWR5774B	✓
102	I	✓	70	3000	WIDE	-	-	12700	■	GWR5774B30K	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
73	II	✓	70	4000	WIDE	-	-	10800	■	GWR5254D	✓
73	II	✓	70	3000	WIDE	-	-	9400	■	GWR5254D30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
148	II	✓	70	4000	WIDE	-	-	19700	■	GWR5214V	✓
102	II	✓	70	4000	WIDE	-	-	14600	■	GWR5274V	✓

ROAD [5] MEDIUM 4X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
148	II	✓	70	4000	HUGE	-	-	18600	■	GWR5114	✓
148	II	✓	70	3000	HUGE	-	-	16100	■	GWR511430K	✓
131	II	✓	70	3000	HUGE	-	-	14800	■	GWR517430K	✓
102	II	✓	70	4000	HUGE	-	-	13800	■	GWR5174	✓
148	I	✓	70	4000	HUGE	-	-	18600	■	GWR5614	✓
148	I	✓	70	3000	HUGE	-	-	16100	■	GWR561430K	✓
131	I	✓	70	3000	HUGE	-	-	14800	■	GWR567430K	✓
102	I	✓	70	4000	HUGE	-	-	13800	■	GWR5674	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
148	II	✓	70	4000	HUGE	-	-	18600	■	GWR5114M	✓
148	II	✓	70	3000	HUGE	-	-	16100	■	GWR5114M30K	✓
131	II	✓	70	3000	HUGE	-	-	14800	■	GWR5174M30K	✓
102	II	✓	70	4000	HUGE	-	-	13800	■	GWR5174M	✓
73	II	✓	70	4000	HUGE	-	-	10200	■	GWR5154M	✓
148	I	✓	70	4000	HUGE	-	-	18600	■	GWR5614M	✓
148	I	✓	70	3000	HUGE	-	-	16100	■	GWR5614M30K	✓
131	I	✓	70	3000	HUGE	-	-	14800	■	GWR5674M30K	✓
102	I	✓	70	4000	HUGE	-	-	13800	■	GWR5674M	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
148	II	✓	70	4000	HUGE	-	-	18600	■	GWR5114B	✓
148	II	✓	70	3000	HUGE	-	-	16100	■	GWR5114B30K	✓
131	II	✓	70	3000	HUGE	-	-	14800	■	GWR5174B30K	✓
102	II	✓	70	4000	HUGE	-	-	13800	■	GWR5174B	✓
73	II	✓	70	4000	HUGE	-	-	10200	■	GWR5154B	✓
148	I	✓	70	4000	HUGE	-	-	18600	■	GWR5614B	✓
148	I	✓	70	3000	HUGE	-	-	16100	■	GWR5614B30K	✓
131	I	✓	70	3000	HUGE	-	-	14800	■	GWR5674B30K	✓
102	I	✓	70	4000	HUGE	-	-	13800	■	GWR5674B	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
148	II	✓	70	4000	HUGE	-	-	18600	■	GWR5114V	✓
102	II	✓	70	4000	HUGE	-	-	13800	■	GWR5174V	✓



ROAD [5] MEDIUM 5X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
155	II	✓	70	4000	WIDE	-	-	21500	■	GWR5215	✓
155	II	✓	70	3000	WIDE	-	-	18700	■	GWR521530K	✓
127	II	✓	70	4000	WIDE	-	-	18300	■	GWR5275	✓
127	II	✓	70	3000	WIDE	-	-	15900	■	GWR527530K	✓
155	I	✓	70	4000	WIDE	-	-	21500	■	GWR5715	✓
155	I	✓	70	3000	WIDE	-	-	18700	■	GWR571530K	✓
127	I	✓	70	4000	WIDE	-	-	18300	■	GWR5775	✓
127	I	✓	70	3000	WIDE	-	-	15900	■	GWR577530K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
155	II	✓	70	4000	WIDE	-	-	21500	■	GWR5215M	✓
155	II	✓	70	3000	WIDE	-	-	18700	■	GWR5215M30K	✓
127	II	✓	70	4000	WIDE	-	-	18300	■	GWR5275M	✓
127	II	✓	70	3000	WIDE	-	-	15900	■	GWR5275M30K	✓
91	II	✓	70	4000	WIDE	-	-	13500	■	GWR5255M	✓
155	I	✓	70	4000	WIDE	-	-	21500	■	GWR5715M	✓
155	I	✓	70	3000	WIDE	-	-	18700	■	GWR5715M30K	✓
127	I	✓	70	4000	WIDE	-	-	18300	■	GWR5775M	✓
127	I	✓	70	3000	WIDE	-	-	15900	■	GWR5775M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
155	II	✓	70	4000	WIDE	-	-	21500	■	GWR5215B	✓
155	II	✓	70	3000	WIDE	-	-	18700	■	GWR5215B30K	✓
127	II	✓	70	4000	WIDE	-	-	18300	■	GWR5275B	✓
127	II	✓	70	3000	WIDE	-	-	15900	■	GWR5275B30K	✓
91	II	✓	70	4000	WIDE	-	-	13500	■	GWR5255B	✓
155	I	✓	70	4000	WIDE	-	-	21500	■	GWR5715B	✓
155	I	✓	70	3000	WIDE	-	-	18700	■	GWR5715B30K	✓
127	I	✓	70	4000	WIDE	-	-	18300	■	GWR5775B	✓
127	I	✓	70	3000	WIDE	-	-	15900	■	GWR5775B30K	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
91	II	✓	70	4000	WIDE	-	-	13500	■	GWR5255D	✓
91	II	✓	70	3000	WIDE	-	-	11700	■	GWR5255D30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
155	II	✓	70	4000	WIDE	-	-	21500	■	GWR5215V	✓
127	II	✓	70	4000	WIDE	-	-	18300	■	GWR5275V	✓

ROAD [5] MEDIUM 5X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
155	II	✓	70	4000	HUGE	-	-	20300	■	GWR5115	✓
155	II	✓	70	3000	HUGE	-	-	17700	■	GWR511530K	✓
127	II	✓	70	4000	HUGE	-	-	17200	■	GWR5175	✓
127	II	✓	70	3000	HUGE	-	-	15000	■	GWR517530K	✓
155	I	✓	70	4000	HUGE	-	-	20300	■	GWR5615	✓
155	I	✓	70	3000	HUGE	-	-	17700	■	GWR561530K	✓
127	I	✓	70	4000	HUGE	-	-	17200	■	GWR5675	✓
127	I	✓	70	3000	HUGE	-	-	15000	■	GWR567530K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
155	II	✓	70	4000	HUGE	-	-	20300	■	GWR5115M	✓
155	II	✓	70	3000	HUGE	-	-	17700	■	GWR5115M30K	✓
127	II	✓	70	4000	HUGE	-	-	17200	■	GWR5175M	✓
127	II	✓	70	3000	HUGE	-	-	15000	■	GWR5175M30K	✓
91	II	✓	70	4000	HUGE	-	-	12700	■	GWR5155M	✓
155	I	✓	70	4000	HUGE	-	-	20300	■	GWR5615M	✓
155	I	✓	70	3000	HUGE	-	-	17700	■	GWR5615M30K	✓
127	I	✓	70	4000	HUGE	-	-	17200	■	GWR5675M	✓
127	I	✓	70	3000	HUGE	-	-	15000	■	GWR5675M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
155	II	✓	70	4000	HUGE	-	-	20300	■	GWR5115B	✓
155	II	✓	70	3000	HUGE	-	-	17700	■	GWR5115B30K	✓
127	II	✓	70	4000	HUGE	-	-	17200	■	GWR5175B	✓
127	II	✓	70	3000	HUGE	-	-	15000	■	GWR5175B30K	✓
91	II	✓	70	4000	HUGE	-	-	12700	■	GWR5155B	✓
155	I	✓	70	4000	HUGE	-	-	20300	■	GWR5615B	✓
155	I	✓	70	3000	HUGE	-	-	17700	■	GWR5615B30K	✓
127	I	✓	70	4000	HUGE	-	-	17200	■	GWR5675B	✓
127	I	✓	70	3000	HUGE	-	-	15000	■	GWR5675B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
155	II	✓	70	4000	HUGE	-	-	20300	■	GWR5115V	✓
127	II	✓	70	4000	HUGE	-	-	17200	■	GWR5175V	✓



ROAD [5] MEDIUM 6X3 LED WIDE

IP66 - IK08



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
186	II	✓	70	4000	WIDE	-	-	25800	■	GWR5216	✓
186	II	✓	70	3000	WIDE	-	-	22400	■	GWR521630K	✓
153	II	✓	70	4000	WIDE	-	-	21900	■	GWR5276	✓
153	II	✓	70	3000	WIDE	-	-	19000	■	GWR527630K	✓
186	I	✓	70	4000	WIDE	-	-	25800	■	GWR5716	✓
186	I	✓	70	3000	WIDE	-	-	22400	■	GWR571630K	✓
153	I	✓	70	4000	WIDE	-	-	21900	■	GWR5776	✓
153	I	✓	70	3000	WIDE	-	-	19000	■	GWR577630K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
186	II	✓	70	4000	WIDE	-	-	25800	■	GWR5216M	✓
186	II	✓	70	3000	WIDE	-	-	22400	■	GWR5216M30K	✓
153	II	✓	70	4000	WIDE	-	-	21900	■	GWR5276M	✓
153	II	✓	70	3000	WIDE	-	-	19000	■	GWR5276M30K	✓
109	II	✓	70	4000	WIDE	-	-	16200	■	GWR5256M	✓
186	I	✓	70	4000	WIDE	-	-	25800	■	GWR5716M	✓
186	I	✓	70	3000	WIDE	-	-	22400	■	GWR5716M30K	✓
153	I	✓	70	4000	WIDE	-	-	21900	■	GWR5776M	✓
153	I	✓	70	3000	WIDE	-	-	19000	■	GWR5776M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
186	II	✓	70	4000	WIDE	-	-	25800	■	GWR5216B	✓
186	II	✓	70	3000	WIDE	-	-	22400	■	GWR5216B30K	✓
153	II	✓	70	4000	WIDE	-	-	21900	■	GWR5276B	✓
153	II	✓	70	3000	WIDE	-	-	19000	■	GWR5276B30K	✓
109	II	✓	70	4000	WIDE	-	-	16200	■	GWR5256B	✓
186	I	✓	70	4000	WIDE	-	-	25800	■	GWR5716B	✓
186	I	✓	70	3000	WIDE	-	-	22400	■	GWR5716B30K	✓
153	I	✓	70	4000	WIDE	-	-	21900	■	GWR5776B	✓
153	I	✓	70	3000	WIDE	-	-	19000	■	GWR5776B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
186	II	✓	70	4000	WIDE	-	-	25800	■	GWR5216V	✓
153	II	✓	70	4000	WIDE	-	-	21900	■	GWR5276V	✓

ROAD [5] MEDIUM 6X3 LED HUGE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
186	II	✓	70	4000	HUGE	-	-	24400	■	GWR5116	✓
186	II	✓	70	3000	HUGE	-	-	21200	■	GWR511630K	✓
153	II	✓	70	4000	HUGE	-	-	20700	■	GWR5176	✓
153	II	✓	70	3000	HUGE	-	-	18000	■	GWR517630K	✓
186	I	✓	70	4000	HUGE	-	-	24400	■	GWR5616	✓
186	I	✓	70	3000	HUGE	-	-	21200	■	GWR561630K	✓
153	I	✓	70	4000	HUGE	-	-	20700	■	GWR5676	✓
153	I	✓	70	3000	HUGE	-	-	18000	■	GWR567630K	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
186	II	✓	70	4000	HUGE	-	-	24400	■	GWR5116M	✓
186	II	✓	70	3000	HUGE	-	-	21200	■	GWR5116M30K	✓
153	II	✓	70	4000	HUGE	-	-	20700	■	GWR5176M	✓
153	II	✓	70	3000	HUGE	-	-	18000	■	GWR5176M30K	✓
109	II	✓	70	4000	HUGE	-	-	15300	■	GWR5156M	✓
186	I	✓	70	4000	HUGE	-	-	24400	■	GWR5616M	✓
186	I	✓	70	3000	HUGE	-	-	21200	■	GWR5616M30K	✓
153	I	✓	70	4000	HUGE	-	-	20700	■	GWR5676M	✓
153	I	✓	70	3000	HUGE	-	-	18000	■	GWR5676M30K	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
186	II	✓	70	4000	HUGE	-	-	24400	■	GWR5116B	✓
186	II	✓	70	3000	HUGE	-	-	21200	■	GWR5116B30K	✓
153	II	✓	70	4000	HUGE	-	-	20700	■	GWR5176B	✓
153	II	✓	70	3000	HUGE	-	-	18000	■	GWR5176B30K	✓
109	II	✓	70	4000	HUGE	-	-	15300	■	GWR5156B	✓
186	I	✓	70	4000	HUGE	-	-	24400	■	GWR5616B	✓
186	I	✓	70	3000	HUGE	-	-	21200	■	GWR5616B30K	✓
153	I	✓	70	4000	HUGE	-	-	20700	■	GWR5676B	✓
153	I	✓	70	3000	HUGE	-	-	18000	■	GWR5676B30K	✓
Power LED dimmable DALI (5 Step) - 220-240 V 50/60 Hz											
186	II	✓	70	4000	HUGE	-	-	24400	■	GWR5116V	✓
153	II	✓	70	4000	HUGE	-	-	20700	■	GWR5176V	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
ROAD [5] MEDIUM			
Wall-mounting bracket 150x160x290 mm - graphite grey		GW86167	✓
Single pole head bracket 1 m - graphite grey		GW87581	✓
Double pole head bracket 1+1 m - graphite grey		GW87582	✓
Short bracket 0.5 m - graphite grey		GW87587	✓
Long bracket 1 m - graphite grey		GW87586	✓
Conical pole painted h = 5.5 m - graphite grey		GW84096	✓
Conical pole painted h = 6.8 m - graphite grey		GW87591	✓
Conical pole painted h = 7.8 m - graphite grey		GW84097	✓
Conical pole painted h = 8.8 m - graphite grey		GW87592	✓
Conical pole painted h = 9.8 m - graphite grey		GW87593	✓






Showroom and garage K. Van Oudenaren - Zaandam - Netherlands

KYRO+



Urban street - Saarlouis - Germany





Scan the QR-code for the latest information

■ AN-96 / Anthracite gray / Textured

Series of LED street lighting luminaires, comprising:


- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Polyester powder coat finish die-cast aluminium pole clamp
- Extra clear, toughened, flat glass diffuser
- High-transparency polycarbonate optics
- StReet optic options: SR/075 usually for narrow roads ($0.5 \geq L/H \geq 0.75$), SR/100 for two-lane roads ($L/H = 1$), SR/125 for wide streets and ($L/H = 1.25$), SR/150 for wide roads/parking lots ($L/H = 1.5$) schemes. L/H ratio (L-road width/H-pole height)
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- The integral switch splitter automatically disconnects the driver from mains when opened
- Anti-tear cable gland M25x1.5 for cables $\varnothing 9 - \varnothing 14$ mm
- Built-in driver
- Stainless steel locking hardware
- Fibreglass technopolymer components plate holder
- Toolless removable and upgradable gear tray
- Fully integrated stainless steel aluminium spring clips
- Suitable for pole installations $\varnothing 42 - \varnothing 60/62$ mm (KYRO+ 1 models), $\varnothing 76$ mm (KYRO+ 1-D76), and $\varnothing 60/62 - \varnothing 76$ mm (KYRO+ 2)
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Supplied with 1 m H07RN-F 4x 1.5 mm² cable and IP66-rated socket-plug polyamide fast connector, with silver-coated brass contacts, for cables $\varnothing 9 - \varnothing 14$ mm, for mains connection without opening the luminaire (DALI options)
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Automatic power reduction (RPA) options available. Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- CLO (Constant Light Output) options available. Consult factory
- Design by SILVIA PAOLA PENNACCHIO



KYRO+
1

KYRO+
2

Identifying and classifying our optics



KYRO+1 SR/075

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/075	-	10863	9528	■	306593	✓
70	II	-	70	3000	SR/075	-	10182	9280	■	3105305	✓
36	II	-	70	4000	SR/075	-	5431	4928	■	306594	✓
36	II	-	70	3000	SR/075	-	5291	4799	■	3105293	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/075	-	10863	9528	■	306613	✓
70	II	✓	70	3000	SR/075	-	10182	9280	■	3105306	✓
36	II	✓	70	4000	SR/075	-	5431	4928	■	306614	✓
36	II	✓	70	3000	SR/075	-	5291	4799	■	3105294	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/075	-	10863	9528	■	306601	✓
70	II	-	70	3000	SR/075	-	10182	9280	■	3105307	✓
36	II	-	70	4000	SR/075	-	5431	4928	■	306602	✓
36	II	-	70	3000	SR/075	-	5291	4799	■	3105295	✓



KYRO+1 SR/100

IP66 - IK09 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/100	-	10863	9536	■	306597	✓
70	II	-	70	3000	SR/100	-	10182	8914	■	3105308	✓
36	II	-	70	4000	SR/100	-	5431	4919	■	306598	✓
36	II	-	70	3000	SR/100	-	5291	4791	■	3105296	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/100	-	10863	9152	■	306615	✓
70	II	✓	70	3000	SR/100	-	10182	8914	■	3105309	✓
36	II	✓	70	4000	SR/100	-	5431	4919	■	306616	✓
36	II	✓	70	3000	SR/100	-	5291	4791	■	3105297	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/100	-	10863	9152	■	306605	✓
70	II	-	70	3000	SR/100	-	10182	8914	■	3105310	✓
36	II	-	70	4000	SR/100	-	5431	4919	■	306606	✓
36	II	-	70	3000	SR/100	-	5291	4791	■	3105298	✓



KYRO+1 SR/125

IP66 - IK09 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/125	-	10863	9516	■	306609	✓
70	II	-	70	3000	SR/125	-	10182	9268	■	3105311	✓
36	II	-	70	4000	SR/125	-	5431	4909	■	306610	✓
36	II	-	70	3000	SR/125	-	5291	4781	■	3105299	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/125	-	10863	9516	■	306599	✓
70	II	✓	70	3000	SR/125	-	10182	9268	■	3105312	✓
36	II	✓	70	4000	SR/125	-	5431	4909	■	306600	✓
36	II	✓	70	3000	SR/125	-	5291	4781	■	3105300	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/125	-	10863	9516	■	306596	✓
70	II	-	70	3000	SR/125	-	10182	9268	■	3105313	✓
36	II	-	70	4000	SR/125	-	5431	4909	■	306595	✓
36	II	-	70	3000	SR/125	-	5291	4781	■	3105301	✓



KYRO+1 SR/150

IP66 - IK09 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/150	-	10863	9450	■	306611	✓
70	II	-	70	3000	SR/150	-	10182	9205	■	3105314	✓
36	II	-	70	4000	SR/150	-	5431	4898	■	306612	✓
36	II	-	70	3000	SR/150	-	5291	4770	■	3105302	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/150	-	10863	9450	■	306607	✓
70	II	✓	70	3000	SR/150	-	10182	9205	■	3105315	✓
36	II	✓	70	4000	SR/150	-	5431	4898	■	306608	✓
36	II	✓	70	3000	SR/150	-	5291	4770	■	3105303	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/150	-	10863	9450	■	306603	✓
70	II	-	70	3000	SR/150	-	10182	9205	■	3105316	✓
36	II	-	70	4000	SR/150	-	5431	4898	■	306604	✓
36	II	-	70	3000	SR/150	-	5291	4770	■	3105304	✓



KYRO+1-D76 SR/075

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/075	-	10863	9528	■	306672	✓
70	II	-	70	3000	SR/075	-	10182	9280	■	3105329	✓
36	II	-	70	4000	SR/075	-	5431	4928	■	306673	✓
36	II	-	70	3000	SR/075	-	5291	4799	■	3105317	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/075	-	10863	9528	■	306692	✓
70	II	✓	70	3000	SR/075	-	10182	9280	■	3105330	✓
36	II	✓	70	4000	SR/075	-	5431	4928	■	306693	✓
36	II	✓	70	3000	SR/075	-	5291	4799	■	3105318	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/075	-	10863	9528	■	306680	✓
70	II	-	70	3000	SR/075	-	10182	9280	■	3105331	✓
36	II	-	70	4000	SR/075	-	5431	4928	■	306681	✓
36	II	-	70	3000	SR/075	-	5291	4799	■	3105319	✓



KYRO+1-D76 SR/100

IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/100	-	10863	9152	■	306676	✓
70	II	-	70	3000	SR/100	-	10182	8914	■	3105332	✓
36	II	-	70	4000	SR/100	-	5431	4919	■	306677	✓
36	II	-	70	3000	SR/100	-	5291	4791	■	3105320	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/100	-	10863	9152	■	306694	✓
70	II	✓	70	3000	SR/100	-	10182	8914	■	3105333	✓
36	II	✓	70	4000	SR/100	-	5431	4919	■	306695	✓
36	II	✓	70	3000	SR/100	-	5291	4791	■	3105321	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/100	-	10863	9152	■	306684	✓
70	II	-	70	3000	SR/100	-	10182	8914	■	3105334	✓
36	II	-	70	4000	SR/100	-	5431	4919	■	306685	✓
36	II	-	70	3000	SR/100	-	5291	4791	■	3105322	✓



KYRO+1-D76 SR/125

IP66 - IK09 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/125	-	10863	9516	■	306688	✓
70	II	-	70	3000	SR/125	-	10182	9268	■	3105335	✓
36	II	-	70	4000	SR/125	-	5431	4909	■	306689	✓
36	II	-	70	3000	SR/125	-	5291	4781	■	3105323	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/125	-	10863	9516	■	306678	✓
70	II	✓	70	3000	SR/125	-	10182	9268	■	3105336	✓
36	II	✓	70	4000	SR/125	-	5431	4909	■	306679	✓
36	II	✓	70	3000	SR/125	-	5291	4781	■	3105324	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/125	-	10863	9516	■	306674	✓
70	II	-	70	3000	SR/125	-	10182	9268	■	3105337	✓
36	II	-	70	4000	SR/125	-	5431	4909	■	306675	✓
36	II	-	70	3000	SR/125	-	5291	4781	■	3105325	✓



KYRO+1-D76 SR/150

IP66 - IK09 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/150	-	10863	9450	■	306690	✓
70	II	-	70	3000	SR/150	-	10182	9205	■	3105338	✓
36	II	-	70	4000	SR/150	-	5431	4898	■	306691	✓
36	II	-	70	3000	SR/150	-	5291	4770	■	3105326	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
70	II	✓	70	4000	SR/150	-	10863	9450	■	306686	✓
70	II	✓	70	3000	SR/150	-	10182	9205	■	3105339	✓
36	II	✓	70	4000	SR/150	-	5431	4898	■	306687	✓
36	II	✓	70	3000	SR/150	-	5291	4770	■	3105327	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
70	II	-	70	4000	SR/150	-	10863	9450	■	306682	✓
70	II	-	70	3000	SR/150	-	10182	9205	■	3105340	✓
36	II	-	70	4000	SR/150	-	5431	4898	■	306683	✓
36	II	-	70	3000	SR/150	-	5291	4770	■	3105328	✓



KYRO+2 SR/075

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/075	-	21726	18877	■	306645	✓
136	II	-	70	3000	SR/075	-	20364	18386	■	3105353	✓
103	II	-	70	4000	SR/075	-	16294	14299	■	306646	✓
103	II	-	70	3000	SR/075	-	15273	13928	■	3105341	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/075	-	21726	18877	■	306643	✓
136	II	✓	70	3000	SR/075	-	20364	18386	■	3105354	✓
103	II	✓	70	4000	SR/075	-	16294	14299	■	306644	✓
103	II	✓	70	3000	SR/075	-	15273	13928	■	3105342	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/075	-	21726	18877	■	306641	✓
136	II	-	70	3000	SR/075	-	20364	18386	■	3105355	✓
103	II	-	70	4000	SR/075	-	16294	14299	■	306642	✓
103	II	-	70	3000	SR/075	-	15273	13928	■	3105343	✓



KYRO+2 SR/100

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/100	-	21726	19257	■	306625	✓
136	II	-	70	3000	SR/100	-	20364	18757	■	3105356	✓
103	II	-	70	4000	SR/100	-	16294	14801	■	306626	✓
103	II	-	70	3000	SR/100	-	15273	14416	■	3105344	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/100	-	21726	19257	■	306651	✓
136	II	✓	70	3000	SR/100	-	20364	18757	■	3105357	✓
103	II	✓	70	4000	SR/100	-	16294	14801	■	306652	✓
103	II	✓	70	3000	SR/100	-	15273	14416	■	3105345	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/100	-	21726	19257	■	306637	✓
136	II	-	70	3000	SR/100	-	20364	18757	■	3105358	✓
103	II	-	70	4000	SR/100	-	16294	14801	■	306638	✓
103	II	-	70	3000	SR/100	-	15273	14416	■	3105346	✓



KYRO+2 SR/125

IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/125	-	21726	18508	■	306617	✓
136	II	-	70	3000	SR/125	-	20364	18027	■	3105359	✓
103	II	-	70	4000	SR/125	-	16294	14178	■	306618	✓
103	II	-	70	3000	SR/125	-	15273	13810	■	3105347	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/125	-	21726	18508	■	306647	✓
136	II	✓	70	3000	SR/125	-	20364	18027	■	3105360	✓
103	II	✓	70	4000	SR/125	-	16294	14178	■	306648	✓
103	II	✓	70	3000	SR/125	-	15273	13810	■	3105348	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/125	-	21726	18508	■	306629	✓
136	II	-	70	3000	SR/125	-	20364	18027	■	3105361	✓
103	II	-	70	4000	SR/125	-	16294	14178	■	306630	✓
103	II	-	70	3000	SR/125	-	15273	13810	■	3105349	✓



KYRO+2 SR/150


IP66 - IK08 - 850 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/150	-	21726	18486	■	306621	✓
136	II	-	70	3000	SR/150	-	20364	18006	■	3105362	✓
103	II	-	70	4000	SR/150	-	16294	14035	■	306622	✓
103	II	-	70	3000	SR/150	-	15273	13670	■	3105350	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/150	-	21726	18486	■	306649	✓
136	II	✓	70	3000	SR/150	-	20364	18006	■	3105363	✓
103	II	✓	70	4000	SR/150	-	16294	14035	■	306650	✓
103	II	✓	70	3000	SR/150	-	15273	13670	■	3105351	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/150	-	21726	18486	■	306633	✓
136	II	-	70	3000	SR/150	-	20364	18006	■	3105406	✓
103	II	-	70	4000	SR/150	-	16294	14035	■	306634	✓
103	II	-	70	3000	SR/150	-	15273	13670	■	3105352	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KYRO+			
Kit of 10 rubber sealing gaskets for up to 2 no. Ø 8 mm cables		14077820	✓
1 m cable H07RN-F 4x1,5 + connector		3102823	✓
1 m Wire H07RN-F 2x1,5 + connector		3102824	✓
Single 1200 mm extension arms, hot dipped galvanised steel, suitable for installation on Ø 60 mm pole top		14077102	✓
Hot dipped galvanised steel brackets suitable for installing single fittings (back to Back) on Ø80-120mm poles. Complete with fixing rods and nuts, requires poles to be drilled		14081902	✓
Hot dipped galvanised steel brackets suitable for installing single or twin fittings (back to Back) on Ø80-120mm poles. Complete with fixing rods and nuts, requires poles to be drilled		14084202	✓
KYRO+ SOLUTION / KYRO+1			
Wall mounting bracket L=310 mm (KYRO+1), in phospho-chromate and cataphoresispre-treated steel finished polyester painted	■	14077596	✓
KYRO+ SOLUTION / KYRO+2			
Wall mounting bracket 370 mm (KYRO+2), in phospho-chromate and cataphoresispre-treated steel finished polyester painted	■	14077696	✓




14077820




3102823




3102824




14077102



14081902




14084202



14077596

14077696

STREET [O3]



■ Graphite grey / Graphite grey /


Scan the QR-code for the latest information

Street lighting device consisting of cover, frame and pole attachment in aluminium with low copper content die-casting:

- PA6 side ventilation grills
- Powder polyester coated after pre-treatment for increased corrosion resistance
- Common mode surge protection up to 12kV according to IEC EN 61000-4-5 (issued by a third party) without the aid of additional protective devices
- Optical system made with methacrylate lens, consisting of several different lenses that, with a single photometric distribution, and varying the installation parameters and the number of motors installed, allows the achievement of the obligatory road requirements
- It can be used up to 50°C of ambient temperature but with reduced currents as indicated in the instruction manual




Municipality - Bellinzona - Switzerland




STREET [O3]

Identifying and classifying our optics



ST1-131 W-4000 K
180° — 0° | 90° — 270°



CYCLE-99 W-4000 K
180° — 0° | 90° — 270°

STREET [O3] ST1

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
131	II	✓	70	4000	ST1	-	-	12900	■	GW87413	✓
127	II	✓	70	4000	ST1	-	-	13740	■	GW87414	✓
99	II	✓	70	4000	ST1	-	-	9860	■	GW87412	✓
68	II	✓	70	4000	ST1	-	-	6760	■	GW87411	✓
37	II	✓	70	4000	ST1	-	-	3470	■	GW87410	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
129	II	✓	70	4000	ST1	-	-	13870	■	GW87534	✓
105	II	✓	70	4000	ST1	-	-	11240	■	GW87533	✓
81	II	✓	70	4000	ST1	-	-	8590	■	GW87532	✓
54	II	✓	70	4000	ST1	-	-	5890	■	GW87531	✓
31	II	✓	70	4000	ST1	-	-	3030	■	GW87530	✓



STREET [O3] CYCLE

IP66 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
99	II	✓	70	4000	CYCLE	-	-	9250	■	GWS7112	✓
68	II	✓	70	4000	CYCLE	-	-	6330	■	GWS7111	✓
37	II	✓	70	4000	CYCLE	-	-	3260	■	GWS7110	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STREET [O3]			
Wall-mounting bracket 150x160x290 mm - graphite grey		GW86167	✓
Single pole head bracket 1 m - graphite grey		GW87581	✓
Double pole head bracket 1+1 m - graphite grey		GW87582	✓
Short bracket 0.5 m - graphite grey		GW87587	✓
Long bracket 1 m - graphite grey		GW87586	✓
Conical pole painted h = 5.5 m - graphite grey		GW84096	✓
Conical pole painted h = 6.8 m - graphite grey		GW87591	✓
Conical pole painted h = 7.8 m - graphite grey		GW84097	✓
Conical pole painted h = 8.8 m - graphite grey		GW87592	✓
Conical pole painted h = 9.8 m - graphite grey		GW87593	✓




THEOS GLASS



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information



Tank Storage Standic B.V. - Dordrecht - Nederland

Series of LED street lighting luminaires, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Coated die-cast aluminium captive trim, hinged to the housing
- Coated die-cast aluminium pole-top adaptor for pole Ø 60 / 76 mm
- High-transparency polycarbonate optics
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- The integral switch splitter automatically disconnects the driver from mains when opened
- Built-in driver
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Stainless steel locking hardware
- Complete with 1 m H07RN-F 2x1.5 mm² or H07RN-F 4x1.5 mm² (dimnable options) cable, for mains connection without opening the luminaire
- SitReet optic options: SR/075 usually for narrow roads (0.5 ≥ L/H ≥ 0.75), SR/100 for two-lane roads (L/H = 1), SR/125 for wide streets and (L/H = 1.25), SR/150 for wide roads/parking lots (L/H = 1.5) schemes. L/H ratio (L-road width/H-pole height)
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Complete with NEMA socket connected to DALI driver and waterproof short-circuit cap for On/Off operation mode and SMART-compatible mounting solutions (NEMA options)
- The ZHAGA versions are complete with a ZHAGA SOCKET located on the upper part of the appliance (ZHU - position UP) or positioned both in the upper and lower part of the appliance (ZHUD - Position UP + position DOWN) and D4i driver. They are installation-ready for "Radio Frequency node" solutions, twilight sensors, and other types of compatible sensors
- The versions of ZHAGA with ZHAGA SOCKET positioned in both the upper and lower part of the appliance can work with either a pair of devices or with only one device positioned in one of the two sockets
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Third-party controls NEMA 7-pin socket options available. Consult factory
- CLO (Constant Light Output) options available. Consult factory
- Design by SILVIA PAOLA PENNACCHIO



THEOS GLASS
MINI

THEOS GLASS

Identifying and classifying our optics



THEOS GLASS SR/075

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/075	-	23898	20423	■	306443	✓
136	II	✓	70	3000	SR/075	-	22400	19771	■	3105159	✓
104	II	✓	70	4000	SR/075	-	17923	15427	■	306430	✓
104	II	✓	70	3000	SR/075	-	17105	14935	■	3105147	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/075	-	23898	20423	■	306442	✓
136	II	✓	70	3000	SR/075	-	22400	19771	■	3105160	✓
104	II	✓	70	4000	SR/075	-	17923	15427	■	306435	✓
104	II	✓	70	3000	SR/075	-	17105	14935	■	3105148	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/075	-	23898	20423	■	306434	✓
136	II	✓	70	3000	SR/075	-	22400	19771	■	3105161	✓
104	II	✓	70	4000	SR/075	-	17923	15427	■	306438	✓
104	II	✓	70	3000	SR/075	-	17105	14935	■	3105149	✓



THEOS GLASS SR/100

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/100	-	23898	20559	■	306460	✓
136	II	✓	70	3000	SR/100	-	22400	19903	■	3105162	✓
104	II	✓	70	4000	SR/100	-	17923	15483	■	306461	✓
104	II	✓	70	3000	SR/100	-	17105	14989	■	3105150	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/100	-	23898	20559	■	306486	✓
136	II	✓	70	3000	SR/100	-	22400	19903	■	3105163	✓
104	II	✓	70	4000	SR/100	-	17923	15483	■	306487	✓
104	II	✓	70	3000	SR/100	-	17105	14989	■	3105151	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/100	-	23898	20559	■	306472	✓
136	II	✓	70	3000	SR/100	-	22400	19903	■	3105164	✓
104	II	✓	70	4000	SR/100	-	17923	15483	■	306473	✓
104	II	✓	70	3000	SR/100	-	17105	14989	■	3105152	✓



THEOS GLASS SR/100 NEMA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI with NEMA socket - 220-240 V 50/50 Hz											
136	II	-	70	4000	SR/100	-	23898	20559	■	3111937	✓
136	II	-	70	3000	SR/100	-	22400	19903	■	3112211	✓
104	II	-	70	4000	SR/100	-	17923	15483	■	3112201	✓
104	II	-	70	3000	SR/100	-	17105	14989	■	3112210	✓



THEOS GLASS SR/100 ZHAGA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
136	II	-	70	4000	SR/100	-	23898	20559	■	3112849	✓
136	II	-	70	3000	SR/100	-	22400	19903	■	3112848	✓
104	II	-	70	4000	SR/100	-	17923	15483	■	3112847	✓
104	II	-	70	3000	SR/100	-	17105	14989	■	3112846	✓
Power LED - dimmable D4i with ZHAGA socket UP and DOWN - 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/100	-	17923	15483	■	3117727	✓
136	II	-	70	4000	SR/100	-	23898	20559	■	3117729	✓
104	II	-	70	3000	SR/100	-	17105	14989	■	3117726	✓
136	II	-	70	3000	SR/100	-	22400	19903	■	3117728	✓



THEOS GLASS SR/125

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/125	-	23898	20250	■	306452	✓
136	II	✓	70	3000	SR/125	-	22400	19604	■	3105165	✓
104	II	✓	70	4000	SR/125	-	17923	15282	■	306453	✓
104	II	✓	70	3000	SR/125	-	17105	16800	■	3105153	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/125	-	23898	20250	■	306482	✓
136	II	✓	70	3000	SR/125	-	22400	19604	■	3105166	✓
104	II	✓	70	4000	SR/125	-	17923	15282	■	306483	✓
104	II	✓	70	3000	SR/125	-	17105	16800	■	3105154	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/125	-	23898	20250	■	306464	✓
136	II	✓	70	3000	SR/125	-	22400	19604	■	3105167	✓
104	II	✓	70	4000	SR/125	-	17923	15282	■	306465	✓
104	II	✓	70	3000	SR/125	-	17105	16800	■	3105155	✓



THEOS GLASS SR/150

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/150	-	23898	20028	■	306456	✓
136	II	✓	70	3000	SR/150	-	22400	19389	■	3105168	✓
104	II	✓	70	4000	SR/150	-	17923	14957	■	306457	✓
104	II	✓	70	3000	SR/150	-	17105	14480	■	3105156	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/150	-	23898	20028	■	306484	✓
136	II	✓	70	3000	SR/150	-	22400	19389	■	3105169	✓
104	II	✓	70	4000	SR/150	-	17923	14957	■	306485	✓
104	II	✓	70	3000	SR/150	-	17105	14480	■	3105157	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
136	II	✓	70	4000	SR/150	-	23898	20028	■	306468	✓
136	II	✓	70	3000	SR/150	-	22400	19389	■	3105170	✓
104	II	✓	70	4000	SR/150	-	17923	14957	■	306469	✓
104	II	✓	70	3000	SR/150	-	17105	14480	■	3105158	✓



THEOS GLASS MINI SR/075

IP66 - IK08 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/075	-	11949	10149	■	306428	✓
71	II	✓	70	3000	SR/075	-	11200	9665	■	3105216	✓
58	II	✓	70	4000	SR/075	-	9923	8495	■	3101903	✓
58	II	✓	70	3000	SR/075	-	9633	8089	■	3105206	✓
46	II	✓	70	4000	SR/075	-	7870	6896	■	3101891	✓
46	II	✓	70	3000	SR/075	-	7748	6567	■	3105194	✓
35	II	✓	70	4000	SR/075	-	5974	5121	■	306429	✓
35	II	✓	70	3000	SR/075	-	5600	5073	■	3105183	✓
19	II	✓	70	4000	SR/075	-	3234	2864	■	306454	✓
19	II	✓	70	3000	SR/075	-	3086	2728	■	3105171	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/075	-	11949	10149	■	306448	✓
71	II	✓	70	3000	SR/075	-	11200	9665	■	3105217	✓
58	II	✓	70	4000	SR/075	-	9923	8495	■	3101911	✓
58	II	✓	70	3000	SR/075	-	9633	8089	■	3105207	✓
46	II	✓	70	4000	SR/075	-	7870	6896	■	3101899	✓
46	II	✓	70	3000	SR/075	-	7748	6567	■	3105195	✓
35	II	✓	70	4000	SR/075	-	5974	5121	■	306449	✓
35	II	✓	70	3000	SR/075	-	5600	5073	■	3105184	✓
19	II	✓	70	4000	SR/075	-	3234	2864	■	306462	✓
19	II	✓	70	3000	SR/075	-	3086	2728	■	3105172	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/075	-	11949	10149	■	306436	✓
71	II	✓	70	3000	SR/075	-	11200	9665	■	3105218	✓
58	II	✓	70	4000	SR/075	-	9923	8495	■	3101907	✓
58	II	✓	70	3000	SR/075	-	9633	8089	■	3105208	✓
46	II	✓	70	4000	SR/075	-	7870	6896	■	3101895	✓
46	II	✓	70	3000	SR/075	-	7748	6567	■	3105196	✓
35	II	✓	70	4000	SR/075	-	5974	5121	■	306437	✓
35	II	✓	70	3000	SR/075	-	5600	5073	■	3105185	✓
19	II	✓	70	4000	SR/075	-	3234	2864	■	306458	✓
19	II	✓	70	3000	SR/075	-	3086	2728	■	3105173	✓

THEOS GLASS MINI SR/100

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

71	II	✓	70	4000	SR/100	-	11949	10427	■	306432	✓
71	II	✓	70	3000	SR/100	-	11200	9886	■	3102749	✓
58	II	✓	70	4000	SR/100	-	9923	9010	■	3101904	✓
58	II	✓	70	3000	SR/100	-	9633	8543	■	3102750	✓
46	II	✓	70	4000	SR/100	-	7870	7149	■	3101892	✓
46	II	✓	70	3000	SR/100	-	7748	7061	■	3105197	✓
35	II	✓	70	4000	SR/100	-	5974	5503	■	306433	✓
35	II	✓	70	3000	SR/100	-	5600	5327	■	3105186	✓
19	II	✓	70	4000	SR/100	-	3234	2903	■	306455	✓
19	II	✓	70	3000	SR/100	-	3086	2810	■	3105174	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

71	II	✓	70	4000	SR/100	-	11949	10427	■	306450	✓
71	II	✓	70	3000	SR/100	-	11200	9886	■	3105219	✓
58	II	✓	70	4000	SR/100	-	9923	9010	■	3101912	✓
58	II	✓	70	3000	SR/100	-	9633	8543	■	3105209	✓
46	II	✓	70	4000	SR/100	-	7870	7149	■	3101900	✓
46	II	✓	70	3000	SR/100	-	7748	7061	■	3105198	✓
35	II	✓	70	4000	SR/100	-	5974	5503	■	306451	✓
35	II	✓	70	3000	SR/100	-	5600	5327	■	3105187	✓
19	II	✓	70	4000	SR/100	-	3234	2903	■	306463	✓
19	II	✓	70	3000	SR/100	-	3086	2810	■	3105175	✓

Power LED - with automatic power reduction 220-240 V 50/60 Hz

71	II	✓	70	4000	SR/100	-	11949	10427	■	306440	✓
71	II	✓	70	3000	SR/100	-	11200	9886	■	3105220	✓
58	II	✓	70	4000	SR/100	-	9923	9010	■	3101908	✓
58	II	✓	70	3000	SR/100	-	9633	8543	■	3105210	✓
46	II	✓	70	4000	SR/100	-	7870	7149	■	3101896	✓
46	II	✓	70	3000	SR/100	-	7748	7061	■	3105199	✓
35	II	✓	70	4000	SR/100	-	5974	5503	■	306441	✓
35	II	✓	70	3000	SR/100	-	5600	5327	■	3105188	✓
19	II	✓	70	4000	SR/100	-	3234	2903	■	306459	✓
19	II	✓	70	3000	SR/100	-	3086	2810	■	3105176	✓

THEOS GLASS MINI SR/100 NEMA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	-----	--------	-------	------------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED - dimmable DALI with NEMA socket - 220-240 V 50/50 Hz

71	II	-	70	4000	SR/100	-	11949	10427	■	3108905	✓
71	II	-	70	3000	SR/100	-	11200	9886	■	3112209	✓
58	II	-	70	4000	SR/100	-	9923	9010	■	3112203	✓
58	II	-	70	3000	SR/100	-	9633	8543	■	3112208	✓
46	II	-	70	4000	SR/100	-	7870	7149	■	3108904	✓
46	II	-	70	3000	SR/100	-	7748	7061	■	3112207	✓
35	II	-	70	4000	SR/100	-	5974	5503	■	3108903	✓
35	II	-	70	3000	SR/100	-	5600	5327	■	3112206	✓
19	II	-	70	4000	SR/100	-	3234	2903	■	3112202	✓
19	II	-	70	3000	SR/100	-	3086	2810	■	3112205	✓



THEOS GLASS MINI SR/100 ZHAGA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
71	II	-	70	4000	SR/100	-	11949	10427	■	3112859	✓
71	II	-	70	3000	SR/100	-	11200	9886	■	3112858	✓
58	II	-	70	4000	SR/100	-	9923	9010	■	3112857	✓
58	II	-	70	3000	SR/100	-	9633	8543	■	3112856	✓
46	II	-	70	4000	SR/100	-	7870	7149	■	3112855	✓
46	II	-	70	3000	SR/100	-	7748	7061	■	3112854	✓
35	II	-	70	4000	SR/100	-	5974	5503	■	3112853	✓
35	II	-	70	3000	SR/100	-	5600	5327	■	3112852	✓
19	II	-	70	4000	SR/100	-	3234	2903	■	3112851	✓
19	II	-	70	3000	SR/100	-	3086	2810	■	3112850	✓
Power LED - dimmable D4i with ZHAGA socket UP and DOWN - 220-240 V 50/60 Hz											
71	II	-	70	4000	SR/100	-	11949	10427	■	3117739	✓
71	II	-	70	3000	SR/100	-	11200	9886	■	3117738	✓
58	II	-	70	4000	SR/100	-	9923	9010	■	3117737	✓
58	II	-	70	3000	SR/100	-	9633	8543	■	3117736	✓
46	II	-	70	4000	SR/100	-	7870	7149	■	3117735	✓
46	II	-	70	3000	SR/100	-	7748	7061	■	3117734	✓
35	II	-	70	4000	SR/100	-	5974	5503	■	3117733	✓
35	II	-	70	3000	SR/100	-	5600	5327	■	3117732	✓
19	II	-	70	4000	SR/100	-	3234	2903	■	3117731	✓
19	II	-	70	3000	SR/100	-	3086	2810	■	3117730	✓



THEOS GLASS MINI SR/125

IP66 - IK08 - 960 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/125	-	11949	9722	■	306444	✓
71	II	✓	70	3000	SR/125	-	11200	9341	■	3105221	✓
58	II	✓	70	4000	SR/125	-	9923	8255	■	3101905	✓
58	II	✓	70	3000	SR/125	-	9633	7932	■	3105211	✓
46	II	✓	70	4000	SR/125	-	7870	6701	■	3101893	✓
46	II	✓	70	3000	SR/125	-	7748	6439	■	3105200	✓
35	II	✓	70	4000	SR/125	-	5974	4966	■	306445	✓
35	II	✓	70	3000	SR/125	-	5600	4772	■	3105189	✓
19	II	✓	70	4000	SR/125	-	3234	2783	■	306466	✓
19	II	✓	70	3000	SR/125	-	3086	2674	■	3105177	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/125	-	11949	9722	■	306431	✓
71	II	✓	70	3000	SR/125	-	11200	9341	■	3105222	✓
58	II	✓	70	4000	SR/125	-	9923	8255	■	3101913	✓
58	II	✓	70	3000	SR/125	-	9633	7932	■	3105212	✓
46	II	✓	70	4000	SR/125	-	7870	6701	■	3101901	✓
46	II	✓	70	3000	SR/125	-	7748	6439	■	3105201	✓
35	II	✓	70	4000	SR/125	-	5974	4966	■	306476	✓
35	II	✓	70	3000	SR/125	-	5600	4772	■	3105190	✓
19	II	✓	70	4000	SR/125	-	3234	2783	■	306474	✓
19	II	✓	70	3000	SR/125	-	3086	2674	■	3105178	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/125	-	11949	9722	■	306480	✓
71	II	✓	70	3000	SR/125	-	11200	9341	■	3105223	✓
58	II	✓	70	4000	SR/125	-	9923	8255	■	3101909	✓
58	II	✓	70	3000	SR/125	-	9633	7932	■	3105213	✓
46	II	✓	70	4000	SR/125	-	7870	6701	■	3101897	✓
46	II	✓	70	3000	SR/125	-	7748	6439	■	3105202	✓
35	II	✓	70	4000	SR/125	-	5974	4966	■	306477	✓
35	II	✓	70	3000	SR/125	-	5600	4772	■	3105191	✓
19	II	✓	70	4000	SR/125	-	3234	2783	■	306470	✓
19	II	✓	70	3000	SR/125	-	3086	2674	■	3105179	✓



THEOS GLASS MINI SR/150


IP66 - IK08 - 960 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/150	-	11949	9395	■	306446	✓
71	II	✓	70	3000	SR/150	-	11200	8912	■	3105224	✓
58	II	✓	70	4000	SR/150	-	9923	8089	■	3101906	✓
58	II	✓	70	3000	SR/150	-	9633	7013	■	3102751	✓
46	II	✓	70	4000	SR/150	-	7870	6567	■	3101894	✓
46	II	✓	70	3000	SR/150	-	7748	6229	■	3105203	✓
35	II	✓	70	4000	SR/150	-	5974	4862	■	306447	✓
35	II	✓	70	3000	SR/150	-	5600	4612	■	3105192	✓
19	II	✓	70	4000	SR/150	-	3234	2728	■	306467	✓
19	II	✓	70	3000	SR/150	-	3086	2587	■	3105180	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/150	-	11949	9395	■	306439	✓
71	II	✓	70	3000	SR/150	-	11200	8912	■	3105225	✓
58	II	✓	70	4000	SR/150	-	9923	8089	■	3101914	✓
58	II	✓	70	3000	SR/150	-	9633	7013	■	3105214	✓
46	II	✓	70	4000	SR/150	-	7870	6567	■	3101902	✓
46	II	✓	70	3000	SR/150	-	7748	6229	■	3105204	✓
35	II	✓	70	4000	SR/150	-	5974	4862	■	306478	✓
35	II	✓	70	3000	SR/150	-	5600	4612	■	3105193	✓
19	II	✓	70	4000	SR/150	-	3234	2728	■	306475	✓
19	II	✓	70	3000	SR/150	-	3086	2587	■	3105181	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
71	II	✓	70	4000	SR/150	-	11949	9395	■	306481	✓
71	II	✓	70	3000	SR/150	-	11200	8912	■	3105226	✓
58	II	✓	70	4000	SR/150	-	9923	8089	■	3101910	✓
58	II	✓	70	3000	SR/150	-	9633	7013	■	3105215	✓
46	II	✓	70	4000	SR/150	-	7870	6567	■	3101898	✓
46	II	✓	70	3000	SR/150	-	7748	6229	■	3105205	✓
35	II	✓	70	4000	SR/150	-	5974	4862	■	306479	✓
35	II	✓	70	3000	SR/150	-	5600	4863	■	3105241	✓
19	II	✓	70	4000	SR/150	-	3234	2728	■	306471	✓
19	II	✓	70	3000	SR/150	-	3086	2587	■	3105182	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
THEOS GLASS			
Wall mount bracket THEOS	■	14174796	✓
Hot-dipped galvanized wall angled steel bracket, cataphoresis and polyester powder	■	14077796	✓




14174796



14077796



THEOS LUM GLASS




■ AN-96 / Anthracite gray / Matt

Scan the QR-code for the latest information


LED catenary lighting luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Powder-polyester coated die-cast aluminium trim
- High-transparency polycarbonate optics
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Complete with supplementary surge protection device (SPD) against mains overvoltages up to 10 kV and electrostatic charges (ESD)
- Connection to mains through technopolymer box, for cables Ø 7 - 17 mm. Complete with factory pre-wired 0.5 m H07RN-F cable
- Stainless steel locking hardware
- Ultra-thick galvanised sheet steel rope fixing device
- Wire mount, whose special geometrical design is studied for easy installation and firm locking with strong metal clamps
- Optimised light emission dual-adjustment design: the angle adjustment allows for direction when the wire is not perpendicular to the road, and the transversal adjustment allows levelling when the wire is not parallel to the ground
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- CLO (Constant Light Output) options available. Consult factory
- Design by SILVIA PAOLA PENNACCHIO



THEOS LUM GLASS

Identifying and classifying our optics



THEOS LUM GLASS SR/075

IP66 - IK09 - 960 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/075	-	14650	14515	■	3113471	✓
104	II	-	70	3000	SR/075	-	14120	14055	■	3113472	✓
90	II	-	70	4000	SR/075	-	13090	12689	■	3113459	✓
90	II	-	70	3000	SR/075	-	12630	12284	■	3113460	✓
70	II	-	70	4000	SR/075	-	10700	9654	■	3113447	✓
70	II	-	70	3000	SR/075	-	10300	9348	■	3113448	✓
52	II	-	70	4000	SR/075	-	7980	7244	■	3113435	✓
52	II	-	70	3000	SR/075	-	7700	7012	■	3113436	✓
35	II	-	70	4000	SR/075	-	5431	4870	■	3113423	✓
35	II	-	70	3000	SR/075	-	5091	4712	■	3113424	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/075	-	14650	14515	■	3113475	✓
104	II	-	70	3000	SR/075	-	14120	14055	■	3113476	✓
90	II	-	70	4000	SR/075	-	13090	12689	■	3113463	✓
90	II	-	70	3000	SR/075	-	12630	12284	■	3113464	✓
70	II	-	70	4000	SR/075	-	10700	9654	■	3113451	✓
70	II	-	70	3000	SR/075	-	10300	9348	■	3113452	✓
52	II	-	70	4000	SR/075	-	7980	7244	■	3113439	✓
52	II	-	70	3000	SR/075	-	7700	7012	■	3113440	✓
35	II	-	70	4000	SR/075	-	5431	4870	■	3113427	✓
35	II	-	70	3000	SR/075	-	5091	4712	■	3113428	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/075	-	14650	14515	■	3113479	✓
104	II	-	70	3000	SR/075	-	14120	14055	■	3113480	✓
90	II	-	70	4000	SR/075	-	13090	12689	■	3113467	✓
90	II	-	70	3000	SR/075	-	12630	12284	■	3113468	✓
70	II	-	70	4000	SR/075	-	10700	9654	■	3113455	✓
70	II	-	70	3000	SR/075	-	10300	9348	■	3113456	✓
52	II	-	70	4000	SR/075	-	7980	7244	■	3113443	✓
52	II	-	70	3000	SR/075	-	7700	7012	■	3113444	✓
35	II	-	70	4000	SR/075	-	5431	4870	■	3113431	✓
35	II	-	70	3000	SR/075	-	5091	4712	■	3113432	✓

THEOS LUM GLASS SR/125

IP66 - IK09 - 960 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/125	-	14650	14346	■	3113473	✓
104	II	-	70	3000	SR/125	-	14120	13888	■	3113474	✓
90	II	-	70	4000	SR/125	-	13090	12538	■	3113461	✓
90	II	-	70	3000	SR/125	-	12630	12138	■	3113462	✓
70	II	-	70	4000	SR/125	-	10700	9540	■	3113449	✓
70	II	-	70	3000	SR/125	-	10300	9236	■	3113450	✓
52	II	-	70	4000	SR/125	-	7980	7160	■	3113437	✓
52	II	-	70	3000	SR/125	-	7700	6930	■	3113438	✓
35	II	-	70	4000	SR/125	-	5431	4840	■	3113425	✓
35	II	-	70	3000	SR/125	-	5091	4687	■	3113426	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/125	-	14650	14346	■	3113477	✓
104	II	-	70	3000	SR/125	-	14120	13888	■	3113478	✓
90	II	-	70	4000	SR/125	-	13090	12538	■	3113465	✓
90	II	-	70	3000	SR/125	-	12630	12138	■	3113466	✓
70	II	-	70	4000	SR/125	-	10700	9540	■	3113453	✓
70	II	-	70	3000	SR/125	-	10300	9236	■	3113454	✓
52	II	-	70	4000	SR/125	-	7980	7160	■	3113441	✓
52	II	-	70	3000	SR/125	-	7700	6930	■	3113442	✓
35	II	-	70	4000	SR/125	-	5431	4840	■	3113429	✓
35	II	-	70	3000	SR/125	-	5091	4687	■	3113430	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
104	II	-	70	4000	SR/125	-	14650	14346	■	3113481	✓
104	II	-	70	3000	SR/125	-	14120	13888	■	3113482	✓
90	II	-	70	4000	SR/125	-	13100	12538	■	3113469	✓
90	II	-	70	3000	SR/125	-	12630	12138	■	3113470	✓
70	II	-	70	4000	SR/125	-	10700	9540	■	3113457	✓
70	II	-	70	3000	SR/125	-	10300	9236	■	3113458	✓
52	II	-	70	4000	SR/125	-	7980	7160	■	3113445	✓
52	II	-	70	3000	SR/125	-	7700	6930	■	3113446	✓
35	II	-	70	4000	SR/125	-	5431	4840	■	3113433	✓
35	II	-	70	3000	SR/125	-	5091	4687	■	3113434	✓



Urbanization university district - Granada - Spain

LYRA+




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information


LED street luminaire, comprising:

- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium pole clamp with polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5) , for Ø 60 mm poles
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Stainless steel fasteners for glass
- Built-in driver
- Supplementary device for protection against network surges of up to 10 kV (DM) included
- Stainless steel locking hardware
- Complete with 1 m factory pre-wired cable H07RN-F 2x1.5 mm²
- Pole clamp for Ø 76 mm poles is available as accessory
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- The QUICK versions are complete with IP66 waterproof connector
- On request, the appliances can be supplied with SR/075 optics for narrow roads and with W/H ratio (road width/pole height) up to 0.75, SR/125 for wide roads and with W/H ratio of 1.25 and SR/150 wide roads and with W/H ratio of 1.5
- Contact the company for DALI dimming versions or with ZHAGA socket and D4i driver
- CLO (Constant Light Output) options available. Consult factory
- Design by GIORGIO LODI



LYRA+

Identifying and classifying our optics



LYRA+ SR/100

IP66 - IK06 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
65	II	-	70	4000	SR/100	-	9800	9365	■	3115301	✓
65	II	-	70	3000	SR/100	-	9320	8513	■	3115300	✓
54	II	-	70	4000	SR/100	-	8680	7669	■	3115299	✓
54	II	-	70	3000	SR/100	-	7200	6970	■	3115298	✓
30	II	-	70	4000	SR/100	-	4480	3939	■	3115297	✓
30	II	-	70	3000	SR/100	-	4120	3580	■	3115296	✓
20	II	-	70	4000	SR/100	-	3740	2820	■	3116039	✓
20	II	-	70	3000	SR/100	-	3560	2560	■	3116038	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
LYRA+			
Painted die-cast aluminium pole-mounting joint for pole Ø 76 mm	■	3117338	✓
Hot-dipped galvanized wall angled steel bracket, cataphoresis and polyester powder	■	1407796	✓




3117338



1407796

INDEX+




- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured

Scan the QR-code for the latest information

Series of bollards, comprising:

- Die-cast aluminium cover painted prior chemical preparation of the surface
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer cable compartment cover
- Stainless steel locking hardware
- Each luminaire is supplied with two IP 68 cable gland allowing a single or a through power connection
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- AISI 304 stainless steel sheet metal sturdy bases for floor mounting are available as accessories. For purpose illumination: promoting safe navigation through campuses, car parks and public spaces
- Concrete installation fixing rods are available as accessories. Compatible with standard die-cast aluminium and optional stainless steel heavy use (HU) baseplates



INDEX+
46

INDEX+
86

INDEX+ 46 C/EW

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
13	II	-	80	4000	C/EW	-	2250	1605	■	3121557	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121556	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121559	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121558	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
13	II	-	80	4000	C/EW	-	2250	1605	■	3121561	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121560	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121563	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121562	✓



INDEX+ 86 C/EW

IP65 - IK10 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
17	II	-	80	4000	C/EW	-	3120	2120	■	3121549	✓
17	II	-	80	3000	C/EW	-	2870	2049	■	3121548	✓
17	II	-	80	4000	C/EW	-	3120	2120	■	3121551	✓
17	II	-	80	3000	C/EW	-	2870	2049	■	3121550	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121748	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121747	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121750	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121749	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
17	II	-	80	4000	C/EW	-	3120	2120	■	3121553	✓
17	II	-	80	3000	C/EW	-	2870	2049	■	3121552	✓
17	II	-	80	4000	C/EW	-	3120	2120	■	3121555	✓
17	II	-	80	3000	C/EW	-	2870	2049	■	3121554	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121752	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121751	✓
13	II	-	80	4000	C/EW	-	2250	1605	■	3121754	✓
13	II	-	80	3000	C/EW	-	2130	1547	■	3121753	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
INDEX+			
AISI 316 stainless steel floor installation base		3114401	✓
AISI 316 stainless steel floor installation base		3114402	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓



3114401





3114402



14049320

KHA TECH





Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- INOX / Stainless steel / Matt

Series of bollards, comprising:

- Electropolished AISI 316 stainless steel or aluminium body and top-cap polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5) depending on versions
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- IP68-rated, loop-through, technopolymer box (WATER-STOP), connected with factory pre-wired H07RN-F cable to the luminaire, for cables Ø 7 - 13.5 mm
- Stainless steel locking hardware
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- AISI 304 stainless steel sheet metal sturdy bases for floor mounting are available as accessories. For purpose illumination: promoting safe navigation through campuses, car parks and public spaces
- Concrete installation fixing rods are available as accessories. Compatible with standard die-cast aluminium and optional stainless steel heavy use (HU) baseplates
- Design by SILVIA PAOLA PENNACCHIO



KHA TECH
5

KHA TECH
9

KHA TECH 5 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
15	II	-	80	4000	C/EW	-	2172	1587	■	3114016	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3114011	✓
15	II	-	80	4000	C/EW	-	2172	1587	■	3114014	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3114009	✓
15	II	-	80	4000	C/EW	-	2172	1587	■	3114018	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3114013	✓

KHA TECH 9 C/EW

IP66 - IK10 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
15	II	-	80	4000	C/EW	-	2172	1587	■	3114006	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3114001	✓
15	II	-	80	4000	C/EW	-	2172	1587	■	3114004	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3113999	✓
15	II	-	80	4000	C/EW	-	2172	1587	■	3114008	✓
15	II	-	80	3000	C/EW	-	2100	1508	■	3114003	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA TECH			
AISI 316 stainless steel floor installation base		3114401	✓
AISI 316 stainless steel floor installation base		3114402	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓



3114401



3114402



14049320

KHA



Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- INOX / Stainless steel / Matt

Series of bollards, comprising:


- Electropolished AISI 316 stainless steel or aluminium body and top-cap polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5) depending on versions
- UV stabilised transparent polycarbonate diffuser
- Extra pure polished aluminium reflector
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- Technopolymer connection box with automatic fuse holder to facilitate power connection
- Anti-tear cable gland for through-wiring available as accessory
- Stainless steel locking hardware
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- AISI 304 stainless steel sheet metal sturdy bases for floor mounting are available as accessories. For purpose illumination: promoting safe navigation through campuses, car parks and public spaces
- Concrete installation fixing rods are available as accessories. Compatible with standard die-cast aluminium and optional stainless steel heavy use (HU) baseplates
- Design by SILVIA PAOLA PENNACCHIO




AN-96

BK-81

INOX



KHA
5 LED



KHA
9 LED

KHA 5 LED C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	II	-	80	4000	C/EW	-	2448	1357	■	06061096	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06060796	✓
19	II	-	80	4000	C/EW	-	2448	1357	■	06060981	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06060681	✓
19	II	-	80	4000	C/EW	-	2448	1357	■	06061104	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06060804	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06060196	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06059896	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06060081	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06059781	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06060204	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06059904	✓



KHA 9 LED C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	II	-	80	4000	C/EW	-	2448	1357	■	06063896	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06063596	✓
19	II	-	80	4000	C/EW	-	2448	1357	■	06063781	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06063481	✓
19	II	-	80	4000	C/EW	-	2448	1357	■	06063904	✓
19	II	-	80	3000	C/EW	-	2370	1182	■	06063604	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06062996	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06062696	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06062881	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06062581	✓
19	I	-	80	4000	C/EW	-	2448	1357	■	06063004	✓
19	I	-	80	3000	C/EW	-	2370	1182	■	06062704	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA			
Internal aluminium cowl limits horizontal light output to 200°		14049720	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓
PG 13.5 anti-tearing cable gland for through wiring connection		14002384	✓



14049720



14049320



14002384

KHA SLIM



Seafront Muelle 1 - Málaga - Spain



Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- INOX / Stainless steel / Matt

Series of bollards, comprising:


- Electropolished AISI 316 stainless steel or aluminium body and top-cap polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5) depending on versions
- Clear UV-stabilised and impact-resistant technopolymer diffuser
- Extra pure polished aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Electrical connection with quick disconnect connector in PA66 without halogens and phosphorus with silver-plated copper contacts, for cables $\varnothing 9 - \varnothing 14$ mm
- Inner aluminium extruded LED heat sink
- Stainless steel locking hardware
- Technopolymer electrical gearbox
- Concrete installation fixing rods are available as accessories (ordered separately)
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- KHA SLIM 220 floor installation can be done through a galvanised steel plinth to be directly buried in concrete or with a stainless steel base to be fastened to the floor with anchor bolts (included)
- Design by SILVIA PAOLA PENNACCHIO




AN-96

BK-81

INOX









KHA SLIM
93



KHA SLIM
220

KHA SLIM 93 LED C/EW







IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
13	II	-	80	4000	C/EW	-	1733	546		06083796	✓
13	II	-	80	3000	C/EW	-	1677	483		06083496	✓
13	II	-	80	4000	C/EW	-	1733	546		06083681	✓
13	II	-	80	3000	C/EW	-	1677	483		06083381	✓
13	II	-	80	4000	C/EW	-	1733	546		06083804	✓
13	II	-	80	3000	C/EW	-	1677	483		06083504	✓



KHA SLIM 220 LED C/EW


IP66 - IK09 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
13	II	-	80	4000	C/EW	-	1733	546		06081396	✓
13	II	-	80	3000	C/EW	-	1677	483		06081096	✓
13	II	-	80	4000	C/EW	-	1733	546		06081281	✓
13	II	-	80	3000	C/EW	-	1677	483		06080981	✓
13	II	-	80	4000	C/EW	-	1733	546		06081404	✓
13	II	-	80	3000	C/EW	-	1677	483		06081104	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA SLIM			
Anchor rods for in-ground concrete mounting stainless steel plate with galvanised steel rods (KHA SLIM H max 93 cm/36.61" only)		14071320	✓
Hot dipped galvanised fixing base for recessing into concrete (suitable only for models 220/250 cm height)		14071220	✓
AISI 316 stainless steel floor installation base (suitable only for models 220/250 cm height)		14071120	✓



14071320




14071220




14071120

KHA CITY



Adigeo shopping centre - Verona - Italy




Scan the QR-code for the latest information


- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured

Series of lighting columns, comprising:

- Extruded aluminium profile housing, powder-coated ISO 9227/12944 - ISO 9223 (C5)
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- The COMFORT options are designed to optimise visual comfort and reduce glare
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- IP68-rated, loop-through, technopolymer box (WATER-STOP), connected with factory pre-wired H07RN-F cable to the luminaire, for cables Ø 7 - 13.5 mm
- Stainless steel locking hardware
- Floor mounting AISI 304 stainless steel flange plate
- Concrete installation fixing rods are available as accessories (ordered separately)
- Floor mounting stainless steel flange plate to match prefabricated plinths (Base FR) available as accessory for KHA CITY 12 and KHA CITY 12 COMFORT (ordered separately)
- Bolt-on root galvanised steel plinth or stainless steel flange plate (anchor plugs not included) floor mounting options available as accessories for KHA CITY 26 e KHA CITY COMFORT 26 (ordered separately)



Identifying and classifying our optics



KHA CITY 12 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1538	■	3113976	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3113971	✓
20	II	-	80	4000	A55/M	51	2900	1538	■	3113974	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3113969	✓

KHA CITY COMFORT 12 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1345	■	3113977	✓
20	II	-	80	3000	A55/M	51	2800	1290	■	3113972	✓
20	II	-	80	4000	A55/M	51	2900	1345	■	3113975	✓
20	II	-	80	3000	A55/M	51	2800	1290	■	3113970	✓

KHA CITY 12 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3113991	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113981	✓
23	II	-	80	4000	C/EW	-	3335	2434	■	3113989	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113979	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3113996	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113986	✓
23	II	-	80	4000	C/EW	-	3335	2434	■	3113994	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113984	✓

KHA CITY COMFORT 12 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2056	■	3113992	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3113982	✓
23	II	-	80	4000	C/EW	-	3335	2056	■	3113990	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3113980	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2056	■	3113997	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3113987	✓
23	II	-	80	4000	C/EW	-	3335	2056	■	3113995	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3113985	✓

KHA CITY 26 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1538	■	3114931	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3114928	✓
20	II	-	80	4000	A55/M	51	2900	1538	■	3114932	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3114929	✓

KHA CITY COMFORT 26 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1345	■	3114926	✓
20	II	-	80	3000	A55/M	51	2800	1290	■	3114924	✓
20	II	-	80	4000	A55/M	51	2900	1345	■	3114927	✓
20	II	-	80	3000	A55/M	51	2800	1290	■	3114925	✓



KHA CITY 26 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3114916	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114912	✓
23	II	-	80	4000	C/EW	-	3335	2434	■	3114918	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114914	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3114917	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114913	✓
23	II	-	80	4000	C/EW	-	3335	2434	■	3114919	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114915	✓



KHA CITY COMFORT 26 C/EW


IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2056	■	3114908	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3114904	✓
23	II	-	80	4000	C/EW	-	3335	2056	■	3114910	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3114906	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2056	■	3114909	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3114905	✓
23	II	-	80	4000	C/EW	-	3335	2056	■	3114911	✓
23	II	-	80	3000	C/EW	-	3220	1955	■	3114907	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA CITY 26			
Hot dipped galvanised fixing base for recessing into concrete.		3114957	✓
AISI 316 stainless steel floor installation base		3114960	✓




3114957



3114960

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA CITY 12			
AISI 316 stainless steel floor installation base		3114402	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓
KHA CITY 26			
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		3115347	✓



3114402



14049320




3115347



Restaurant Burg Landshut - Bernkastel-Kues - Germany

KHA CITY MARINE



■ INOX / Stainless steel / Matt

Scan the QR-code for the latest information

Series of lighting columns, comprising:

- Electropolished AISI 316 stainless steel body and top-cap ISO 9223 (CX)
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- IP68-rated, loop-through, technopolymer box (WATER-STOP), connected with factory pre-wired H07RN-F cable to the luminaire, for cables Ø 7 - 13.5 mm
- Stainless steel locking hardware
- Floor mounting AISI 304 stainless steel flange plate
- Floor mounting stainless steel flange plate to match prefabricated plinths (Base FR) available as accessory for KHA CITY 12 MARINE (ordered separately)
- Concrete installation fixing rods are available as accessories (ordered separately)
- Bolt-on root galvanised steel plinth or stainless steel flange plate (anchor plugs not included) floor mounting options available as accessories for KHA CITY 26 MARINE (ordered separately)




Sydney - Australia



KHA CITY MARINE
A/M





KHA CITY MARINE
C/EW



KHA CITY MARINE
12

KHA CITY MARINE
26

Identifying and classifying our optics



KHA CITY MARINE 12 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1538	■	3113978	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3113973	✓



KHA CITY MARINE 12 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3113993	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113983	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3113998	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3113988	✓



KHA CITY MARINE 26 A/M

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
20	II	-	80	4000	A55/M	51	2900	1538	■	3114933	✓
20	II	-	80	3000	A55/M	51	2800	1474	■	3114930	✓



KHA CITY MARINE 26 C/EW


IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3114922	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114920	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
23	II	-	80	4000	C/EW	-	3335	2434	■	3114923	✓
23	II	-	80	3000	C/EW	-	3220	2313	■	3114921	✓




Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA CITY MARINE 26			
Hot dipped galvanised fixing base for recessing into concrete.		3114957	✓
AISI 316 stainless steel floor installation base		3114960	✓




3114957




3114960

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA CITY MARINE 12			
AISI 316 stainless steel floor installation base		3114402	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓
KHA CITY MARINE 26			
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		3115347	✓



3114402




14049320



3115347

AMON MINI



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

Series of bollards, comprising:


- Extruded aluminium profile housing, powder-coated ISO 9227/12944 - ISO 9223 (C5)
- UV stabilised polycarbonate satin diffuser (SOFT versions)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- Coated die-cast aluminium optical compartment
- Extra pure polished aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Electrical connection via junction box
- Built-in driver
- Stainless steel locking hardware
- Coated die-cast aluminium cabling compartment
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Floor mounting steel base plate included
- Heavy-duty die-cast aluminium base cover available as accessory (ordered separately)
- Stainless steel bolt-on root for concrete anchoring available as accessory (ordered separately)
- Dimmable DALI options available. Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory




AMON WALL



AMON MAXI




AMON MINI




AMON MINI SOFT

Identifying and classifying our optics



SW - 41W - 4000 K
180° — 0° | 90° — 270°



SEW - 41W - 4000 K
180° — 0° | 90° — 270°

AMON MINI S/W

IP65 - IK09 - 650 °C


LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
40	I	-	80	4000	S/W	-	5046	2021	■	306059	✓



AMON MINI SOFT S/EW


IP65 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
40	I	-	80	4000	S/EW	-	5046	1359	■	306061	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
AMON MINI			
AMON groundplate cover	■	310921	✓
Flange plate with fixing rod		310922	✓
Steel bolt-on root		310923	✓



310921




310922



310923

AMON MAXI



■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Series of lighting columns, comprising:

- Extruded aluminium column, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra-clear, toughened, flat glass diffuser, silk-screened on the inside
- UV stabilised polycarbonate opal diffuser (SOFT versions)
- Coated die-cast aluminium optical compartment
- Optical unit made of high transmittance technopolymer optics or polished and oxidised pure aluminium according to models
- Anti-ageing custom moulded silicone sealing gasket(s)
- Electrical connection via junction box
- Die-cast aluminium inspection access door included
- Built-in driver
- Stainless steel locking hardware
- Coated die-cast aluminium cabling compartment
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Floor mounting steel base plate included
- Heavy-duty die-cast aluminium base cover available as accessory (ordered separately)
- Stainless steel bolt-on root for concrete anchoring available as accessory (ordered separately)
- Dimmable DALI options available. Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory




New building electrical wholesaler Robri - Wekerom - Netherlands



AMON WALL




AMON MINI



AMON MAXI

AMON MAXI
SOFT

Identifying and classifying our optics



AMON MAXI S/W

IP65 - IK08 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
76	I	-	80	4000	S/W	-	10092	3707	■	306063	✓
76	I	-	80	3000	S/W	-	9770	3596	■	306072	✓



AMON MAXI A/M

IP65 - IK08 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
29	I	-	80	3000	A30/M	-	2850	1396	■	306074	✓
27	I	-	80	4000	A17/M	-	3120	1527	■	306064	✓
27	I	-	80	4000	A30/M	-	3120	1518	■	306065	✓
27	I	-	80	3000	A17/M	-	2850	1405	■	306073	✓



AMON MAXI S/EW

IP65 - IK08 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
44	I	-	80	4000	S/EW	-	4992	2096	■	306066	✓
44	I	-	80	3000	S/EW	-	4512	1894	■	306075	✓



AMON MAXI SOFT S/EW


IP65 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
88	I	-	80	4000	S/EW	-	7046	4145	■	306067	✓
88	I	-	80	3000	S/EW	-	5885	3938	■	306076	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
AMON MAXI			
AMON groundplate cover	■	310921	✓
Flange plate with fixing rod		310922	✓
Steel bolt-on root		310923	✓



310921



310922




310923

URBAN [O3]



Municipality - Bellinzona - Switzerland




Scan the QR-code for the latest information

■ Graphite grey / Graphite grey /


Urban lighting device in die-cast aluminum EN AB 46100:

- Equipped with lateral ventilation system made in technopolymer
- Powder poliester coated after epoxy surface treatment and phosphochromating process
- Modular LED engines (2-4) with extruded aluminum heat sink
- Holding plate in PC
- Double 2-pole safety switch for 2.5 mm² wires
- Internal wiring with UG4G4 1 mm² wires
- Equipped with PMMA lenses
- Anti-aging silicone gasket
- External screws in stainless steel AISI 316
- Recessed handle closing system and steel holding cable
- It can be used up to 50°C of ambient temperature but with reduced currents as indicated in the instruction manual
- Side fixing for Ø60mm bracket in die-cast aluminum with possibility of ±15° inclination adjustment



URBAN [O3]

Identifying and classifying our optics



URBAN [O3] ST1

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
105	II	-	70	4000	ST1	-	-	11240	■	GW87608	✓
81	II	-	70	4000	ST1	-	-	8590	■	GW87607	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
105	II	-	70	4000	ST1	-	-	11240	■	GW87628	✓
81	II	-	70	4000	ST1	-	-	8590	■	GW87627	✓



URBAN [O3] ELLIPTICAL

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
105	II	-	70	4000	ELL	-	-	11240	■	GWS7258	✓
81	II	-	70	4000	ELL	-	-	8590	■	GWS7257	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
105	II	-	70	4000	ELL	-	-	11240	■	GWS7278	✓
81	II	-	70	4000	ELL	-	-	8590	■	GWS7277	✓



URBAN [O3] CYCLE

IP66 - IK08

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
105	II	-	70	4000	CYCLE	-	-	10560	■	GWS7208	✓
81	II	-	70	4000	CYCLE	-	-	8060	■	GWS7207	✓
Power LED automatic power reduction, bipower with self-learning - 220-240 V 50/60 Hz											
105	II	-	70	4000	CYCLE	-	-	10560	■	GWS7228	✓
81	II	-	70	4000	CYCLE	-	-	8060	■	GWS7227	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
URBAN [O3]			
Single pole head bracket 0.4 m - graphite grey		GW87881	✓
Double pole head bracket 0.8 m - graphite grey		GW87882	✓
Single intermediate bracket 0.4 m - graphite grey		GW87883	✓
Painted cylindrical pole h = 4 m - graphite grey		GW87691	✓
Painted cylindrical pole h = 4 m - BlueGreen		GW87691B	✓
Painted cylindrical pole h = 4.5 m - graphite grey		GW87692	✓
Painted cylindrical pole h = 4.5 m - BlueGreen		GW87692B	✓




GW87881



GW87882



GW87883




GW87691
GW87692

HEDO+ FT



Jumeirah lakes towers - Dubai - UAE




Scan the QR-code for the latest information


■ AN-96 / Anthracite gray / Textured

Pole-top mounted outdoor luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Coated die-cast aluminium pole-top adaptor for pole Ø 60 / 76 mm
- Extra clear, toughened, flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- The IP66-rated socket-plug fast connector for mains connection without opening the luminaire. Made in PA66 with silver-plated brass contacts for cables Ø 9 - Ø 12 mm
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Stainless steel locking hardware
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Complete with NEMA socket connected to DALI driver and waterproof short-circuit cap for On/Off operation mode and SMART-compatible mounting solutions (NEMA options)
- Complete with ZHAGA socket positioned on the upper part of the luminaire (UP position) and D4i driver. Ready for "radio frequency node" smart, twilight and other compatible solutions (ZHAGA options). Consult factory for more options
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by ROBERTO FIORATO



Identifying and classifying our optics



HEDO+ FT C/EW

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
43	II	-	70	4000	C/EW	-	7181	5189	■	3104726	✓
43	II	-	70	3000	C/EW	-	6837	4924	■	3104723	✓
36	II	-	70	4000	C/EW	-	6012	4349	■	3104717	✓
36	II	-	70	3000	C/EW	-	5724	4132	■	3104714	✓
25	II	-	70	4000	C/EW	-	4175	3024	■	3104708	✓
25	II	-	70	3000	C/EW	-	3975	2879	■	3104705	✓
18	II	-	70	4000	C/EW	-	3006	2185	■	3104699	✓
18	II	-	70	3000	C/EW	-	2862	2077	■	3104696	✓

Power LED - with automatic power reduction 220-240 V 50/60 Hz

43	II	-	70	4000	C/EW	-	7181	5189	■	3104728	✓
43	II	-	70	3000	C/EW	-	6837	4924	■	3104725	✓
36	II	-	70	4000	C/EW	-	6012	4349	■	3104719	✓
36	II	-	70	3000	C/EW	-	5724	4132	■	3104716	✓
25	II	-	70	4000	C/EW	-	4175	3024	■	3104710	✓
25	II	-	70	3000	C/EW	-	3975	2879	■	3104707	✓
18	II	-	70	4000	C/EW	-	3006	2185	■	3104701	✓
18	II	-	70	3000	C/EW	-	2862	2077	■	3104698	✓

HEDO+ FT C/EW NEMA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI with NEMA socket - 220-240 V 50/50 Hz											
43	II	-	70	4000	C/EW	-	7181	5189	■	3106065	✓
36	II	-	70	4000	C/EW	-	6012	4349	■	3106064	✓
25	II	-	70	4000	C/EW	-	4175	3024	■	3106063	✓
18	II	-	70	4000	C/EW	-	3006	2185	■	3106062	✓

HEDO+ FT C/EW ZHAGA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
43	II	-	70	4000	C/EW	-	7181	5189	■	3113882	✓
43	II	-	70	3000	C/EW	-	6837	4924	■	3116033	✓
36	II	-	70	4000	C/EW	-	6012	4349	■	3113881	✓
36	II	-	70	3000	C/EW	-	5724	4132	■	3116032	✓
25	II	-	70	4000	C/EW	-	4175	3024	■	3113880	✓
25	II	-	70	3000	C/EW	-	3975	2879	■	3116031	✓
18	II	-	70	4000	C/EW	-	3006	2185	■	3113879	✓
18	II	-	70	3000	C/EW	-	2862	2077	■	3116030	✓



HEDO+ FT SR/075

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	-	70	4000	SR/075	-	6021	4653	■	3104771	✓
40	II	-	70	3000	SR/075	-	5719	4291	■	3104768	✓
34	II	-	70	4000	SR/075	-	5143	3971	■	3104762	✓
34	II	-	70	3000	SR/075	-	4886	3690	■	3104759	✓
27	II	-	70	4000	SR/075	-	3942	3176	■	3104753	✓
27	II	-	70	3000	SR/075	-	3813	2945	■	3104750	✓
19	II	-	70	4000	SR/075	-	2833	2258	■	3104744	✓
19	II	-	70	3000	SR/075	-	2740	2109	■	3104741	✓
14	II	-	70	4000	SR/075	-	2094	1697	■	3104735	✓
14	II	-	70	3000	SR/075	-	2026	1591	■	3104732	✓
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
40	II	-	70	4000	SR/075	-	6021	4653	■	3104773	✓
40	II	-	70	3000	SR/075	-	5719	4291	■	3104770	✓
34	II	-	70	4000	SR/075	-	5143	3971	■	3104764	✓
34	II	-	70	3000	SR/075	-	4886	3690	■	3104761	✓
27	II	-	70	4000	SR/075	-	3942	3176	■	3104755	✓
27	II	-	70	3000	SR/075	-	3813	2945	■	3104752	✓
19	II	-	70	4000	SR/075	-	2833	2258	■	3104746	✓
19	II	-	70	3000	SR/075	-	2740	2109	■	3104743	✓
14	II	-	70	4000	SR/075	-	2094	1697	■	3104737	✓
14	II	-	70	3000	SR/075	-	2026	1591	■	3104734	✓



HEDO+ FT SR/075 NEMA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI with NEMA socket - 220-240 V 50/50 Hz											
40	II	-	70	4000	SR/075	-	6021	4653	■	3106070	✓
34	II	-	70	4000	SR/075	-	5143	3971	■	3106069	✓
27	II	-	70	4000	SR/075	-	3942	3176	■	3106068	✓
19	II	-	70	4000	SR/075	-	2833	2258	■	3106067	✓
14	II	-	70	4000	SR/075	-	2094	1697	■	3106066	✓




HEDO+ FT SR/075 ZHAGA

IP66 - IK08 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable D4i with ZHAGA socket UP - 220-240 V 50/60 Hz											
40	II	-	70	4000	SR/075	-	6021	4653	■	3113877	✓
40	II	-	70	3000	SR/075	-	5719	4291	■	3116028	✓
34	II	-	70	4000	SR/075	-	5143	3971	■	3114024	✓
34	II	-	70	3000	SR/075	-	4886	3690	■	3113837	✓
27	II	-	70	4000	SR/075	-	3942	3176	■	3113876	✓
27	II	-	70	3000	SR/075	-	3813	2945	■	3116027	✓
19	II	-	70	4000	SR/075	-	2833	2258	■	3113875	✓
19	II	-	70	3000	SR/075	-	2740	2109	■	3116026	✓
14	II	-	70	4000	SR/075	-	2094	1697	■	3113874	✓
14	II	-	70	3000	SR/075	-	2026	1591	■	3116025	✓





K-FARM - Malo - Italy

SPILLO MINI



■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Series of LED landscaping outdoor bollard and pole-top luminaires, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Anti-tear cable gland M25x1.5 for cables \varnothing 9 - \varnothing 14 mm
- Stainless steel locking hardware
- Each LED can by-passed in case of failure thanks to a coupled electronic safety device (NUD)
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- Supplied with 1m factory pre-wired HORN-5 cable
- Built-in driver
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- Design by ALESSANDRO PEDRETTI




K-FARM - Malo - Italy



SPILLO



SPILLO MINI
POST



SPILLO MINI

SPIILLO MINI POST

IP65 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
16	II	-	70	4000	C/EW	-	2240	1237	■	303496	✓
16	II	-	70	3000	C/EW	-	2056	1237	■	303739	✓
11	II	-	70	4000	C/EW	-	1450	867	■	303494	✓
11	II	-	70	3000	C/EW	-	1330	796	■	303737	✓



SPIILLO MINI

IP65 - IK10


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
16	II	-	70	4000	C/EW	-	2240	1237	■	303497	✓
16	II	-	70	3000	C/EW	-	2056	1237	■	30349790101	✓
11	II	-	70	4000	C/EW	-	1500	867	■	303528	✓
11	II	-	70	3000	C/EW	-	1377	867	■	3116213	✓

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPIILLO MINI			
Pole too adaptor Ø 48 mm	■	310404	✓
Pole top adaptor Ø 60 mm	■	310416	✓
Baseplate Spillo Mini		310414	✓




310404
310416



310414

SPILLO



■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Series of LED landscaping outdoor bollard and pole-top luminaires, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Anti-tear cable gland M25x1.5 for cables Ø 9 - Ø 14 mm
- Stainless steel locking hardware
- Each LED can by-passed in case of failure thanks to a coupled electronic safety device (NUD)
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- Supplied with 1m factory pre-wired HORN-F-5 cable
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Built-in driver
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- Design by ALESSANDRO PEDRETTI



Mitsui Outlet Park - Taichung - Taiwan




SPILLO MINI POST



SPILLO

Identifying and classifying our optics



SPILLO



IP65 - IK10

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
44	II	-	70	4000	C/EW	-	6970	3733	■	304024	✓
44	II	-	70	3000	C/EW	-	6448	3733	■	30402490102	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
44	II	-	70	4000	C/EW	-	6970	3733	■	303501	✓
44	II	-	70	4000	CP	-	6970	3998	■	303814	✓
44	II	-	70	3000	C/EW	-	6448	3733	■	303738	✓
44	II	-	70	3000	CP	-	6483	3998	■	30381490100	✓
24	II	-	70	4000	C/EW	-	3485	1767	■	303499	✓
24	II	-	70	3000	C/EW	-	3382	1767	■	304009	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SPILLO			
Pole top adaptor Ø 60 mm	■	310403	✓
Pole top adaptor Ø 76 mm	■	310405	✓
Pole Spillo INT. 3.3 m	■	315023	✓
Pole Spillo F.T. 2.8 m with flange	■	315024	✓
Baseplate Spillo		310415	✓



HEDO+




Scan the QR-code for the latest information

■ AN-96 / Anthracite gray / Textured


Pole-top mounted outdoor luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Coated die-cast aluminium pole-top adaptor for pole Ø 60 / 76 mm
- Microprismatic, flat glass diffuser, silk-screened on the inside
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- The IP66-rated socket-plug fast connector for mains connection without opening the luminaire. Made in PA66 with silver-plated brass contacts for cables Ø 9 - Ø 12 mm
- Built-in driver
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Stainless steel locking hardware
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by ROBERTO FIORATO



HEDO+

Identifying and classifying our optics



HEDO+ C/EW

IP65 - IK09

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
42	I	-	80	4000	C/EW	-	6140	3865	■	3104691	✓
42	I	-	80	3000	C/EW	-	5894	3710	■	3104689	✓
23	I	-	80	4000	C/EW	-	3247	2145	■	3104685	✓
23	I	-	80	3000	C/EW	-	3150	2080	■	3104683	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
42	I	-	80	4000	C/EW	-	6140	3865	■	3104692	✓
42	I	-	80	3000	C/EW	-	5894	3710	■	3104690	✓
23	I	-	80	4000	C/EW	-	3247	2145	■	3104686	✓
23	I	-	80	3000	C/EW	-	3150	2080	■	3104684	✓



PERFORMANCE IN LIGHTING S.p.A.

Viale del Lavoro 9/11

37030 Colognola ai Colli (VR) - Italy

T +39 045 61 59 211

E info.it@pil.lighting

www.performanceinlighting.com

PERFORMANCE
 LIGHTING

powered by
