

Chevron Oak



Chevron Oak porcelain pavers are a sophisticated outdoor decking option characterized by delicate brown and tan zig-zag graining. These pavers showcase an elegant and classic chevron design, offering a timeless aesthetic that adds a touch of luxury to outdoor spaces.

Tile Tech® hardscape systems provide architects and design professionals with a complete solution to transform any roof deck, walkway, driveway, courtyard, or patio into beautiful, useful spaces. Embracing USGBC LEED standards, our paving products boast a composition that includes 35% pre-consumer recycled materials. With no traces of Volatile Organic Compounds (VOC) and a Solar Reflectance Index (SRI) of ≥32, porcelain pavers emerge as an eco-friendly choice that goes beyond conventional paving solutions.





SAND & GRAVEL BASE INSTALLATION







Specifications

Available Sizes (Rectified)



15-1/2" x 47-1/2" 394 x 1207 mm

Color and Shade Variation



Moderate variation

LEED Opportunities

Recycled Content:

MR Credit 4.1 and 4.2 (2 LEED pts.)

Regional Materials (500 mi) EQ Credit 4.2 (1 LEED pt.)

Low Emmitting Materials EQ Credit 4.2 (1 LEED pt.)

Innovation in Design

ID Credit 1.1 - 1.4 (1-4 LEED pts.)

Heat Island Effect (Non-roof) SS Credit 7.1 (1 LEED pt.)

Shipping Details

Packaging (24" x 24") 72 pcs. | 279 Sq.Ft. | 2,700 lbs./pallet Packaging (24" x 48") 32 pcs. | 256 Sq.Ft. | 2,350 lbs./pallet





Thickness:	3/4" 19 mm	
Weight:	9 lbs./Sq.Ft.	
Water Absorption:	Max. 0.05%	ISO10543-3
Static Load (Center)	≥1,840 lbf.	ASTM N/A, EN 12825
Bending Strength	3,300 lbs.	ASTM C-648, ISO 10545-4
Distribution Load	2,500 lbs.	ASTM N/A, EN 12825
Slip Resistant	R11	DIN51130
COF (Wet, Dry)	>0.60	ASTM C-1028-7, ISO N/A
Abrasion Resistant	Yes (Class 5)	ASTM C-1027, ISO 10545-6
Stain Resistant	Yes (Class 5)	ASTM C-1378, ISO 10545-14
Frost Resistant	Yes	ASTM C-1026, ISO 10545-12
Chemical Resistance	Yes	ASTM C-650, ISO 10545-13
Solar Reflectance (SRI)	50	
Rectified	Yes	

Full test reports and specification details available on our website.

