



**COLORTEK®**

**VENATTA®  
MARBLE FINISH**

Wall to Floor  
Marble Decorative Finish



# VENATTA® MARBLE SPLENDOR

Venatta is a decorative coating used to create, wall to floor, multi-layered and textured stone finishes.

Combined with our decorative paints, metallic glazes and protective top coats, Venatta provides limitless possibilities when it comes to designing sophisticated and stunning interiors.

Disclaimer: Due to printing technologies specifications, actual colors may vary from those displayed in this catalog.

[www.colortek.eu](http://www.colortek.eu)


Venatta, Colortek, Wall & Floor Fashion and the Colortek Drop Symbol are registered trademarks.

© 2018





**ONYX VOLCANO**



**APPLICATION STEPS**

C1A R10  
Metallo Roman Silver  
Deco Additive 7


**ONYX TERRACOTA**



**APPLICATION STEPS**

C1A R10  
Deco Additive 7  
Metallo Copper  
Metallo Roman Silver  
Scumble + Dark Crack Medium

**ONYX GOLD**



**APPLICATION STEPS**

Baca 510/69  
Deco Additive 7  
Dark Crack Medium


**ONYX BLACK**



**APPLICATION STEPS**

C1A R10  
Deco Additive 6

**ONYX SILVER**



**APPLICATION STEPS**

C1A R10  
Metallo Roman Silver (NT=2 / Quart)  
Deco Additive 6

**ONYX CLOUDY RED**



**APPLICATION STEPS**

C1A R10  
Metallo Roman Silver (NT=25 / Quart)  
Deco Additive 6  
Deco Additive 8

**FOREST VERDE**



**APPLICATION STEPS**

C1A R10  
Fusion Green (GF=3/KG)


**FOREST AMETISTA**



**APPLICATION STEPS**

C1A R10  
Metallo Violet  
Deco Additive 6


**FOREST JADE**



**APPLICATION STEPS**

C1A R10  
Fusion Green  
Deco Additive 7

**FOREST LAKE**



**APPLICATION STEPS**

C1A R10  
Metallo Roman Silver\*  
Deco Additive 6

\* BC 90 ; VB 40 ; NT 1 ; RD 2 / Quart



### SAFARI HUESO



#### APPLICATION STEPS

Coacryl 275  
Deco Additive 6  
Scumble (NT = 25)

### SAFARI SAMBA



#### APPLICATION STEPS

Coacryl 275  
Deco Additive 6  
Metallo Roman Silver  
Metallo Copper  
Scumble + Dark Crack Medium

### SAFARI NATAL



#### APPLICATION STEPS

Coacryl 275  
Deco Additive 6  
Dark Crack Medium

### SAFARI ARENA



#### APPLICATION STEPS

Metallo Flash Gold

### SAFARI MOSTAZA



#### APPLICATION STEPS

Coacryl 37.1  
Deco Additive 7  
Scumble + Dark Crack Medium

### SAFARI NARANJA



#### APPLICATION STEPS

Metallo Roman Silver  
Deco Additive 7  
Scumble + Walnut


**BOTTEGA MARFIL**



**APPLICATION STEPS**

Metallo Roman Silver  
Metallo Copper + Classic Color  
Deco Additive 6  
Dark Crack Medium

**BOTTEGA CÁLIDO**



**APPLICATION STEPS**

Metallo Roman Silver  
Metallo Copper  
Dark Crack Medium

**BOTTEGA CALIZA**



**APPLICATION STEPS**


Metallo Roman Silver  
Metallo Copper  
Scumble (NT = 25)


**BOTTEGA TOPO**



**APPLICATION STEPS**

Metallo Roman Silver  
Metallo Copper  
Deco Additive 7  
Dark Crack Medium





**DAKOTA RIO BLANCO**



**APPLICATION STEPS**

C1A White  
Metallo Roman Silver  
Deco Additive 6

**DAKOTA KASHMIR**



**APPLICATION STEPS**

Metallo Roman Silver  
Deco Additive 6  
Dark Crack Medium


**DAKOTA SOMBRA**



**APPLICATION STEPS**

C1A White  
Deco Additive 8

**DAKOTA ROSSO**



**APPLICATION STEPS**

C1A White  
Metallo Copper  
Metallo Roman Silver  
Dark Crack Medium

**DAKOTA SOMBRA BLANCA**



**APPLICATION STEPS**

C1A White  
Metallo Roman Silver  
Scumble (NT = 25)  
Coacryl White

**DAKOTA TUNDRA**



**APPLICATION STEPS**

C1A R96  
C1C White  
Coacryl IT 169-2

# VENATTA® TECHNICAL INFORMATION

Technical information and application instructions.

For a visual reference on the application steps , please refer to our application video available on YouTube

<https://youtu.be/PlhVSxRVqXY>

[www.colortek.eu](http://www.colortek.eu)





# VENATTA® WALL APPLICATION



Yield: 2kg / m<sup>2</sup>



5 kg



25 kg

## 1. PRIMING

On absorbent substrates, apply Colortek Fondo F on the properly primed and clean substrate.

On blocked or non-absorbent substrates such as glazed tiles, use Colortek Neogrip after slightly sanding the surface. Large tile joints should be removed and treated with our epoxy joint filler and surface repair putty, Colortek SX2 FillWell.

## 2. VENATTA APPLICATION

Apply the first coat of Venatta with an inox trowel and leave the surface to dry.

Apply a second coat of Venatta and while the coat is still wet, create the Marble stone veins in the surface using tool REF. 793 – 49503.

Once the pattern is created, leave the surface to dry to approximately 60% before going over it with an inox trowel used to press and smoothen the marble pattern.

If you feel the surface has dried while ironing the surface, you can spray water mist to dampen the substrate.

Once this step has concluded, leave the surface to dry.

## 3. STAINING



Choose your main marble stone color and tint either Colortek C1A or C1C to paint over the Venatta surface. This will set the main tone of the final effect. For dark marble finishes, you can use Colortek C1A R10. You can also opt to use some of our decorative paints as the effect's main base. For instance, you can use Colortek Fusion, Baca, etc.

For a more dramatic metallic effect, apply Colortek Metallo over the surface and leave surface to dry.

For richer marble veins, use one of the Colortek metallic additives and paint with a brush, going over the marble veins to create a duo tone effect. Clean any excess material with a wet sponge and Leave the surface to dry.

## 4. PROTECTIVE TOP COAT

When a reflective finish is desired or when Venatta is used in wet areas such as bathrooms, you can apply Colortek Carrolux on the surface as a final protective coat.



# VENATTA<sup>®</sup> FLOOR SYSTEM



## 1. SURFACE PREPARATION

- On concrete, apply SX0 PrimeWell, or SX9 HumiGuard.
- On Glazed floor tiles, apply Neogrip.

## 2. NEOFILLER BASE COAT APPLICATION

- Apply Neofiller in 2 coats and sand with a 40 grid once the surface has hardened.

## 3. VENATTA APPLICATION

- Apply in two coats. While the second coat is still wet, create the marble stone veins in the surface.

## 4. PROTECTIVE COAT APPLICATION

- Apply Carrolux liquid or gel to protect the floor and to obtain a sophisticated reflective finish.



# CARROLUX<sup>®</sup> PROTECTIVE TOP COATS

Venatta can be top coated with Carrolux, a transparent top coat specifically engineered for performance in wet areas and to achieve glass-like layered glossy finishes. Carrolux is available in two versions:

Carrolux Gel — best for trowel application and thick coats application leaving a “glass” layer effect.

Carrolux Liquid — for spray application that will respect the stone rugged texture and tactile feel.

## IMPORTANT NOTICE

The application of Carrolux will cause a shift in color tonality and intensity, most notably when applied on light colors finishes.

## 1. WITHOUT CARROLUX



## 2. WITH CARROLUX





**COLORTEK**<sup>®</sup>

Product designed in the EU

[www.colortek.eu](http://www.colortek.eu)  
[info@colortek.eu](mailto:info@colortek.eu)



**Synergy, Added Value, Continuous Improvement,  
Diversity, Integrity, Social Responsibility.**

